



FCC Test Report

APPLICANT : Lenovo(Shanghai) Electronics Technology Co., Ltd.
EQUIPMENT : Portable Tablet Computer
BRAND NAME : Lenovo
MODEL NAME : Lenovo TB-J616F
FCC ID : O57TBJ616F
STANDARD : 47 CFR Part 15 Subpart B
CLASSIFICATION : Certification
TEST DATE(S) : May 07, 2021 ~ May 09, 2021

We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

Reviewed by: Jason Jia / Supervisor

Approved by: Alex Wang / Manager



Sporton International (Kunshan) Inc.

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY.....3

SUMMARY OF TEST RESULT4

1. GENERAL DESCRIPTION5

 1.1. Applicant.....5

 1.2. Manufacturer5

 1.3. Product Feature of Equipment Under Test5

 1.4. Product Specification of Equipment Under Test6

 1.5. Modification of EUT6

 1.6. Test Location7

 1.7. Test Software7

 1.8. Applicable Standards7

2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....8

 2.1. Test Mode8

 2.2. Connection Diagram of Test System 10

 2.3. Support Unit used in test configuration and system.....11

 2.4. EUT Operation Test Setup 11

3. TEST RESULT.....12

 3.1. Test of AC Conducted Emission Measurement12

 3.2. Test of Radiated Emission Measurement 16

4. LIST OF MEASURING EQUIPMENT20

5. UNCERTAINTY OF EVALUATION21

APPENDIX A. SETUP PHOTOGRAPHS



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FC141907	Rev. 01	Initial issue of report	May 28, 2021



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.107	AC Conducted Emission	< 15.107 limits	PASS	Under limit 7.69 dB at 0.162 MHz
3.2	15.109	Radiated Emission	< 15.109 limits	PASS	Under limit 3.28 dB at 73.650 MHz for Quasi-Peak

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



1. General Description

1.1. Applicant

Lenovo(Shanghai) Electronics Technology Co., Ltd.
Section 304-305, Building No. 4, # 222, Meiyue Road, China (Shanghai) Pilot Free Trade Zone

1.2. Manufacturer

Lenovo PC HK Limited
23/F, Lincoln House, Taikoo Place 979 King's Road, Quarry Bay, Hong Kong, P.R.China

1.3. Product Feature of Equipment Under Test

Product Feature	
Equipment	Portable Tablet Computer
Brand Name	Lenovo
Model Name	Lenovo TB-J616F
FCC ID	O57TBJ616F
EUT supports Radios application	WLAN 2.4GHz 802.11b/g/n HT20/HT40 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE FM Receiver and GNSS
HW Version	Lenovo Tablet TB-J616F
SW Version	Lenovo Tablet TB-J616F_RF01_210429
EUT Stage	Identical Prototype

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are five types of EUT. The difference could be referred to the Product Equality Declaration exhibit submitted. According to the differences, we choose sample 1 to perform full test and sample 2/3/4/5 to verify the difference.

1.4. Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	802.11b/g/n: 2400 MHz ~ 2483.5 MHz 802.11a/n/ac: 5150 MHz ~ 5250 MHz; 5250 MHz ~ 5350 MHz; 5470 MHz ~ 5725 MHz 5725 MHz ~ 5850 MHz Bluetooth: 2400 MHz ~ 2483.5 MHz
Rx Frequency	802.11b/g/n: 2400 MHz ~ 2483.5 MHz 802.11a/n/ac: 5150 MHz ~ 5250 MHz; 5250 MHz ~ 5350 MHz; 5470 MHz ~ 5725 MHz 5725 MHz ~ 5850 MHz Bluetooth: 2400 MHz ~ 2483.5 MHz GNSS : 1559 MHz ~ 1610 MHz FM : 88 MHz ~ 108 MHz
Antenna Type	WLAN : IFA Antenna Bluetooth : IFA Antenna GNSS: IFA Antenna FM : External Earphone Antenna
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11a/g/n/ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM) Bluetooth LE : GFSK Bluetooth (1Mbps) : GFSK Bluetooth (2Mbps) : $\pi/4$ -DQPSK Bluetooth (3Mbps) : 8-DPSK GNSS : BPSK FM

1.5. Modification of EUT

No modifications are made to the EUT during all test items.



1.6. Test Location

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International (Kunshan) Inc.		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-KS 03CH02-KS	CN1257	314309

1.7. Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH02-KS	AUDIX	E3	6.2009-8-24a
2.	CO01-KS	AUDIX	E3	6.2009-8-24

1.8. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart B
- ANSI C63.4-2014

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.



2. Test Configuration of Equipment Under Test

2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.


Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

Test Items	Function Type
AC Conducted Emission	Mode 1: Bluetooth Idle + WLAN (2.4G) Idle + Camera(Rear) + USB Cable 1(Charging from Adapter 1) + Battery 1 + Keyboard + Pen 1 + Pen 2 for Sample 1
	Mode 2: Bluetooth Idle + WLAN (5G) Idle + Camera(Front) + USB Cable 2(Charging from Adapter 2) + Battery 1 + Keyboard + Pen 1 + Pen 2 for Sample 1
	Mode 3: Bluetooth Idle + WLAN (2.4G) Idle + MPEG4(Run Color Bar) + USB Cable 2(Charging from Adapter 3) + Battery 1 + Keyboard + Pen 1 + Pen 2 for Sample 1
	Mode 4: Bluetooth Idle + WLAN (5G) Idle + FM Rx(98MHz) + USB Cable 2(Charging from Adapter 2) With Cradle + Battery 1 + Pen 1 + Pen 2 for Sample 1
	Mode 5: Bluetooth Idle + WLAN (2.4G) Idle + GNSS Rx + USB Cable 1(Data Link with Notebook) + Battery 1 + Keyboard + Pen 1 + Pen 2 for Sample 1
	Mode 6: Bluetooth Idle + WLAN (5G) Idle + GNSS Rx + USB Cable 2(Data Link with Notebook) + Battery 1 + Keyboard + Pen 1 + Pen 2 for Sample 1
	Mode 7: Bluetooth Idle + WLAN (2.4G) Idle + GNSS Rx + USB Cable 1(Data Link with Notebook) + Battery 1 + Keyboard + Pen 1 + Pen 2 for Sample 2
	Mode 8: Bluetooth Idle + WLAN (2.4G) Idle + GNSS Rx + USB Cable 1(Data Link with Notebook) + Battery 1 + Keyboard + Pen 1 + Pen 2 for Sample 3
	Mode 9: Bluetooth Idle + WLAN (2.4G) Idle + Camera(Front) + USB Cable 2(Charging from Adapter 3) + Battery 2 + Keyboard + Pen 1 + Pen 2 for Sample 4
	Mode 10 : Bluetooth Idle + WLAN (5G) Idle + GNSS Rx + USB Cable 2(Data Link with Notebook) + Battery 2 + Keyboard + Pen 1 + Pen 2 for Sample 4
	Mode 11 : Bluetooth Idle + WLAN (5G) Idle + GNSS Rx + USB Cable 2(Data Link with Notebook) + Battery 2 + Keyboard + Pen 1 + Pen 2 for Sample 5



Radiated Emissions	<p>Mode 1: Bluetooth Idle + WLAN (2.4G) Idle + Camera(Rear) + USB Cable 1(Charging from Adapter 1) + Battery 1 + Keyboard + Pen 1 + Pen 2 for Sample 1</p> <p>Mode 2: Bluetooth Idle + WLAN (5G) Idle + Camera(Front) + USB Cable 2(Charging from Adapter 2) + Battery 1 + Keyboard + Pen 1 + Pen 2 for Sample 1</p> <p>Mode 3: Bluetooth Idle + WLAN (2.4G) Idle + MPEG4(Run Color Bar) + USB Cable 1(Charging from Adapter 3) + Battery 1 + Keyboard + Pen 1 + Pen 2 for Sample 1</p> <p>Mode 4: Bluetooth Idle + WLAN (5G) Idle + FM Rx(98MHz) + Battery 1 + Earphone + Keyboard + Pen 1 + Pen 2 for Sample 1</p> <p>Mode 5: Bluetooth Idle + WLAN (2.4G) Idle + GNSS Rx + USB Cable 1(Charging from Adapter 3)With Cradle + Battery 1 + Earphone + Pen 1 + Pen 2 for Sample 1</p> <p>Mode 6: Bluetooth Idle + WLAN (5G) Idle + GNSS Rx + USB Cable 1(Data Link with Notebook) + Battery 1 + Keyboard + Pen 1 + Pen 2 for Sample 1</p> <p>Mode 7: Bluetooth Idle + WLAN (2.4G) Idle + GNSS Rx + USB Cable 2(Data Link with Notebook) + Battery 1 + Keyboard + Pen 1 + Pen 2 for Sample 1</p> <p>Mode 8: Bluetooth Idle + WLAN (2.4G) Idle + MPEG4(Run Color Bar) + PAD Charging to Pen 1 + Keyboard + Pen 2 for Sample 1</p> <p>Mode 9: Bluetooth Idle + WLAN (2.4G) Idle + GNSS Rx + USB Cable 2(Data Link with Notebook) + Battery 1 + Keyboard + Pen 1 + Pen 2 for Sample 2</p> <p>Mode 10 : Bluetooth Idle + WLAN (2.4G) Idle + GNSS Rx + USB Cable 2(Data Link with Notebook) + Battery 1 + Keyboard + Pen 1 + Pen 2 for Sample 3</p> <p>Mode 11 : Bluetooth Idle + WLAN (2.4G) Idle + Camera(Rear) + PAD Charging to Pen 1 + Keyboard + Pen 2 for Sample 4</p> <p>Mode 12 : Bluetooth Idle + WLAN (2.4G) Idle + GNSS Rx + USB Cable 2(Data Link with Notebook) + Battery 2 + Keyboard + Pen 1 + Pen 2 for Sample 4</p> <p>Mode 13 : Bluetooth Idle + WLAN (2.4G) Idle + GNSS Rx + USB Cable 2(Data Link with Notebook) + Battery 2 + Keyboard + Pen 1 + Pen 2 for Sample 5</p>
Remark:	
<ol style="list-style-type: none"> 1. The worst case of AC is mode 3; only the test data of this mode is reported. 2. The worst case of RE is mode 8; only the test data of this mode is reported. 3. Data Link with Notebook means data application transferred mode between EUT and Notebook. 	

2.2.Connection Diagram of Test System



The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application

2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Vector Signal Generator	R&S	SMBV100A	258305	N/A	N/A
2.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded, 1.8m
3.	WLAN AP	TP-Link	TL-WDR5600	N/A	N/A	Unshielded, 1.8m
4.	Bluetooth Earphone	Nokia	BH-102	PYAHS-107W	N/A	N/A
5.	Notebook	Lenovo	G480	QDS-BRCM1050I	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
6.	Notebook	Dell	Latitude3440	N/A	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
7.	Bluetooth Earphone	Lenovo	LBH308	N/A	N/A	N/A
8.	Bluetooth Earphone	Xiaomi	LYEJ02LM	N/A	N/A	N/A
9.	Hard Disk	Lenovo	F310	DoC	Shielded, 1.2m	N/A
10.	Hard disk	KINGSHARE	KSP6120G	Fcc DoC	Shielded, 1.2m	N/A
11.	Earphone	Lenovo	SH100	N/A	Unshielded, 1.2m	N/A
12.	SD Card	Kingston	8GB	N/A	N/A	N/A

2.4. EUT Operation Test Setup

At the same time, the EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test.

1. Data application is transferred between notebook and EUT via USB cable.
2. Turn on GNSS function to make the EUT receive continuous signals from GNSS station.
3. Turn on MPEG4 function.
4. Turn on camera to capture images.
5. Turn on FM function to make the EUT receive continuous signals from FM station.



3. Test Result

3.1. Test of AC Conducted Emission Measurement

3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

<Class B Limit>

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.1.4 Test Setup




AMN = Artificial mains network (LISN)
AE = Associated equipment
EUT = Equipment under test
ISN = Impedance stabilization network



3.1.5 Test Result of AC Conducted Emission

Test Engineer :	Amos Zhang	Temperature :	25.3~26.2°C
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		




Site : CO01-KS
 Condition : FCC CLASS-B TWO-LISN-CN02-L LINE

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1 *	0.162	57.69	-7.69	65.38	37.60	9.64	10.45	QP
2	0.162	38.29	-17.09	55.38	18.20	9.64	10.45	Average
3	0.176	50.26	-14.42	64.68	30.20	9.64	10.42	QP
4	0.176	31.66	-23.02	54.68	11.60	9.64	10.42	Average
5	0.219	53.19	-9.69	62.88	33.20	9.64	10.35	QP
6	0.219	34.79	-18.09	52.88	14.80	9.64	10.35	Average
7	0.246	46.18	-15.73	61.91	26.20	9.64	10.34	QP
8	0.246	28.18	-23.73	51.91	8.20	9.64	10.34	Average
9	0.300	43.75	-16.49	60.24	23.80	9.64	10.31	QP
10	0.300	25.85	-24.39	50.24	5.90	9.64	10.31	Average
11	0.387	42.52	-15.60	58.12	22.60	9.65	10.27	QP
12	0.387	25.52	-22.60	48.12	5.60	9.65	10.27	Average
13	12.253	44.57	-15.43	60.00	23.50	10.70	10.37	QP
14	12.253	36.27	-13.73	50.00	15.20	10.70	10.37	Average
15	14.364	45.44	-14.56	60.00	24.20	10.85	10.39	QP
16	14.364	37.14	-12.86	50.00	15.90	10.85	10.39	Average
17	15.718	45.85	-14.15	60.00	24.50	10.94	10.41	QP
18	15.718	36.55	-13.45	50.00	15.20	10.94	10.41	Average



Test Engineer :	Amos Zhang	Temperature :	25.3~26.2°C
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-KS
 Condition : FCC CLASS-B TWO-LISN-CN02-N NEUTRAL

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1 *	0.162	57.17	-8.21	65.38	36.90	9.82	10.45	QP
2	0.162	38.77	-16.61	55.38	18.50	9.82	10.45	Average
3	0.187	49.16	-14.99	64.15	28.90	9.87	10.39	QP
4	0.187	33.86	-20.29	54.15	13.60	9.87	10.39	Average
5	0.208	51.74	-11.53	63.27	31.50	9.88	10.36	QP
6	0.208	32.44	-20.83	53.27	12.20	9.88	10.36	Average
7	0.232	47.80	-14.59	62.39	27.60	9.86	10.34	QP
8	0.232	30.80	-21.59	52.39	10.60	9.86	10.34	Average
9	0.262	44.75	-16.63	61.38	24.59	9.83	10.33	QP
10	0.262	28.35	-23.03	51.38	8.19	9.83	10.33	Average
11	0.317	45.58	-14.22	59.80	25.50	9.78	10.30	QP
12	0.317	26.68	-23.12	49.80	6.60	9.78	10.30	Average
13	12.253	43.37	-16.63	60.00	22.20	10.80	10.37	QP
14	12.253	34.77	-15.23	50.00	13.60	10.80	10.37	Average
15	13.337	44.58	-15.42	60.00	23.30	10.90	10.38	QP
16	13.337	35.78	-14.22	50.00	14.50	10.90	10.38	Average
17	15.066	44.75	-15.25	60.00	23.30	11.05	10.40	QP
18	15.066	35.65	-14.35	50.00	14.20	11.05	10.40	Average

Note:

- Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
- Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)



3.2. Test of Radiated Emission Measurement

3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

<Class B Limit>

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.2.2. Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dBµV/m) = 20 log Emission level (µV/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz





3.2.5. Test Result of Radiated Emission

Test Engineer :	Yoke Li	Temperature :	21~22°C
		Relative Humidity :	41~42%
Test Distance :	3m	Polarization :	Horizontal




Site : 03CH02-KS
 Condition : FCC CLASS-B 3m LF 6111D SN44483 HORIZONTAL

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	73.65	36.33	-3.67	40.00	54.16	12.90	1.47	32.20	100	120	Peak
2	148.34	27.07	-16.43	43.50	39.88	17.17	2.12	32.10	---	---	Peak
3	191.99	27.16	-16.34	43.50	41.98	14.86	2.42	32.10	---	---	Peak
4	320.03	28.60	-17.40	46.00	38.02	19.60	3.12	32.14	---	---	Peak
5	608.12	24.25	-21.75	46.00	26.33	25.91	4.29	32.28	---	---	Peak
6	851.59	27.44	-18.56	46.00	25.47	29.29	5.07	32.39	---	---	Peak
7	3528.00	44.44	-29.56	74.00	61.39	34.28	10.45	61.68	---	---	Peak
8	5704.00	44.98	-29.02	74.00	57.52	35.83	13.25	61.62	---	---	Peak
9	7512.00	45.55	-28.45	74.00	53.88	38.17	15.35	61.85	---	---	Peak
10	10062.00	47.11	-26.89	74.00	51.72	39.39	18.04	62.04	---	---	Peak
11	12078.00	47.12	-26.88	74.00	48.56	40.22	19.73	61.39	---	---	Peak
12	15111.00	46.83	-27.17	74.00	45.57	41.26	22.24	62.24	---	---	Peak



Test Engineer :	Yoke Li	Temperature :	21~22°C
		Relative Humidity :	41~42%
Test Distance :	3m	Polarization :	Vertical



Site : 03CH02-KS
 Condition : FCC CLASS-B 3m LF 6111D SN44483 VERTICAL

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	73.65	36.72	-3.28	40.00	54.55	12.90	1.47	32.20	100	280 QP
2	224.00	23.98	-22.02	46.00	37.78	15.74	2.61	32.15	---	---
3	352.04	23.71	-22.29	46.00	32.08	20.56	3.27	32.20	---	---
4	607.15	24.78	-21.22	46.00	26.89	25.90	4.28	32.29	---	---
5	741.01	26.18	-19.82	46.00	25.79	27.94	4.73	32.28	---	---
6	861.29	27.33	-18.67	46.00	25.34	29.25	5.10	32.36	---	---
7	2888.00	40.92	-33.08	74.00	59.64	33.42	9.44	61.58	---	---
8	5552.00	44.99	-29.01	74.00	57.92	35.58	13.11	61.62	---	---
9	8792.00	46.15	-27.85	74.00	53.38	38.29	16.81	62.33	---	---
10	11430.00	47.59	-26.41	74.00	50.68	39.59	19.14	61.82	---	---
11	14049.00	47.75	-26.25	74.00	47.05	41.05	21.28	61.63	---	---
12	15822.00	47.33	-26.67	74.00	44.79	42.02	22.89	62.37	---	---

Note:

- Level(dBμV/m) = Read Level(dBμV) + Antenna Factor(dB/m) + Cable Loss(dB) - Preamp Factor(dB)
- Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)



4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Receiver	R&S	ESC17	100768	9kHz~7GHz;	Apr. 21, 2021	May 07, 2021	Apr. 20, 2022	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Oct. 17, 2020	May 07, 2021	Oct. 16, 2021	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060105	9kHz~30MHz	Oct. 27, 2020	May 07, 2021	Oct. 26, 2021	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP0000008 11	AC 0V~300V, 45Hz~1000Hz	Oct. 17, 2020	May 07, 2021	Oct. 16, 2021	Conduction (CO01-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz;Ma x 30dBm	Oct. 17, 2020	May 09, 2021	Oct. 16, 2021	Radiation (03CH02-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55370528	10Hz-44G,MAX 30dB	Oct. 17, 2020	May 09, 2021	Oct. 16, 2021	Radiation (03CH02-KS)
Bilog Antenna	TeseQ	CBL6111D	44483	30MHz-1GHz	Dec. 29, 2020	May 09, 2021	Dec. 28, 2021	Radiation (03CH02-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Nov. 09, 2020	May 09, 2021	Nov. 08, 2021	Radiation (03CH02-KS)
SHF-EHF Horn	Com-power	AH-840	101115	18GHz~40GHz	Nov. 09, 2020	May 09, 2021	Nov. 08, 2021	Radiation (03CH02-KS)
Amplifier	MITEQ	EM18G40GGA	060728	18~40GHz	Jan. 06, 2021	May 09, 2021	Jan. 05, 2022	Radiation (03CH02-KS)
Amplifier	SONOMA	310N	187289	9KHz-1GHz	Jan. 06, 2021	May 09, 2021	Jan. 05, 2022	Radiation (03CH02-KS)
Amplifier	Keysight	83017A	MY53270316	500MHz~26.5G Hz	Oct. 17, 2020	May 09, 2021	Oct. 16, 2021	Radiation (03CH02-KS)
AC Power Source	Chroma	61601	61601000247 3	N/A	NCR	May 09, 2021	NCR	Radiation (03CH02-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	May 09, 2021	NCR	Radiation (03CH02-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	May 09, 2021	NCR	Radiation (03CH02-KS)

NCR: No Calibration Required



5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.9dB
---	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.9dB
---	-------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0dB
---	-------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.1 dB
---	--------