

## EMC TEST REPORT



Applicant:	Lenovo(Shanghai) Electronics Technology Co., Ltd.
Address:	Section 304-305, Building No. 4, # 222, Meiyue Road, China (Shanghai) Pilot Free Trade Zone

Manufacturer or Supplier:	Lenovo PC HK Limited
Address:	23/F, Lincoln House, Taikoo Place 979 King's Road, Quarry Bay, Hong Kong
Product:	ThinkReality A6 Compute Box
Brand Name:	ThinkReality
Model Name:	ThinkReality A6 Compute Pack
FCC ID:	O57TRA6CP
Date of tests:	Jun. 11, 2019 ~ Jul. 11, 2019

The submitted sample of the above equipment has been tested for according to the requirements of the following standards:

- FCC Part 15, Subpart B, Class B**
- ANSI C63.4:2014**

**CONCLUSION: The submitted sample was found to COMPLY with the test requirement**

Prepared by Alex Chen Engineer / Mobile Department	Approved by Luke Lu Manager / Mobile Department
	
Date: Jul. 16, 2019	Date: Jul. 16, 2019

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute you unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



# TABLE OF CONTENTS

<b>RELEASE CONTROL RECORD .....</b>	<b>3</b>
<b>1 GENERAL INFORMATION .....</b>	<b>4</b>
1.1 GENERAL DESCRIPTION OF EUT.....	4
1.2 SUMMARY OF TEST RESULTS.....	6
1.3 MEASUREMENT UNCERTAINTY.....	6
1.4 DESCRIPTION OF TEST MODES.....	7
1.5 DESCRIPTION OF SUPPORT UNITS.....	8
<b>2 EMISSION TEST .....</b>	<b>9</b>
2.1 CONDUCTED EMISSION MEASUREMENT .....	9
2.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT .....	9
2.1.2 TEST INSTRUMENTS.....	9
2.1.3 TEST PROCEDURES .....	10
2.1.4 DEVIATION FROM TEST STANDARD .....	10
2.1.5 TEST SETUP.....	11
2.1.6 EUT OPERATING CONDITIONS .....	11
2.1.7 TEST RESULTS .....	12
2.2 RADIATED EMISSION MEASUREMENT.....	14
2.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT .....	14
2.2.2 TEST INSTRUMENTS.....	16
2.2.3 TEST PROCEDURE.....	17
2.2.4 DEVIATION FROM TEST STANDARD .....	18
2.2.5 TEST SETUP.....	19
2.2.6 EUT OPERATING CONDITIONS .....	19
2.2.7 TEST RESULTS .....	20
<b>3 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB .....</b>	<b>24</b>



**BUREAU**  
**VERITAS**

Test Report No.: FV190610W002

## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FV190610W002	Original release	Jul. 16, 2019



# 1 GENERAL INFORMATION

## 1.1 GENERAL DESCRIPTION OF EUT

<b>PRODUCT</b>	ThinkReality A6 Compute Box	
<b>BRAND NAME</b>	ThinkReality	
<b>MODEL NAME</b>	ThinkReality A6 Compute Pack	
<b>NOMINAL VOLTAGE</b>	5.0/9Vdc (adapter) 3.85Vdc (Li-ion, battery)	
<b>BATTERY</b>	Brand Name: Lenovo Model Name: L19D2P31 Power Rating: DC 3.85Vdc, 6800mAh, Li-ion, battery	
<b>MODULATION TYPE</b>	<b>WLAN</b>	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
	<b>BT_LE</b>	GFSK
	<b>Bluetooth</b>	GFSK, $\pi/4$ -DQPSK, 8DPSK
<b>OPERATING FREQUENCY</b>	<b>WLAN</b>	2412 ~ 2462MHz for 11b/g/n(HT20) 2422 ~ 2452MHz for 11n(HT40) 5180 ~ 5240MHz, 5260 ~ 5320 MHz, 5470 ~ 5700MHz, 5745 ~ 5825 MHz for 11a/ n(HT20)/ n(HT40) / ac(VHT80)
	<b>Bluetooth/BT_LE</b>	2402MHz ~ 2480MHz
<b>HW VERSION</b>	SKY_BLUE_BOX V04	
<b>SW VERSION</b>	A6_user_S760001_2019051604343_sdm845_4G_ROW_US	
<b>I/O PORTS</b>	Refer to user's manual	
<b>CABLE</b>	USB cable1: non-shielded, detachable, 1.0m USB cable2: non-shielded, detachable, 1.0m	
<b>ACCESSORY DEVICES</b>	Refer to note as below	

### NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

3. List of Accessory:

ACCESSORIES	BRAND	MODEL	SPECIFICATION
CPU	Qualcomm	SDA-845-A-914BMPSP-TR-02-0-AA	914NPSP
LPDDR4x	SAMSUNG	K3UH5H50MM-AGCJ	4G
UFS	SAMSUNG	KLUCG2K1EA-B0C1	64G
BT/WLAN Module	Qualcomm	WCN-3990-0-116WLPSP-SR-0K-0	-
Battery	Lenovo	L19D2P31	Rating: 3.85Vdc, 6800mAh
AC Adapter	Lenovo	SC-31	I/P: 100-240Vac, 0.8A O/P: 5Vdc, 3A/9Vdc, 3A
USB Cable 1	Lenovo	LGBUC001-CS-H	(red) 1.0m shielded cable w/o core
USB Cable 2	Lenovo	LGBUC004-CS-H	(black) 1.0m shielded cable w/o core
Glass	ThinkReality	ThinkReality A6 Headset	-
Controller	ThinkReality	ThinkReality A6 Controller	-

## 1.2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart B			
Standard Section	Test Item	Result	Remark
FCC Part 15, Subpart B, Class B ANSI C63.4:2014	Conducted Test	PASS	Meets limits minimum passing margin is -14.55dB at 21.716000MHz.
	Radiated Emission Test (30MHz ~ 1GHz)	PASS	Meets Class B Limit Minimum passing margin is -3.31dB at 120.21MHz
	Radiated Emission Test (Above 1GHz)	PASS	Meets Class B Limit Minimum passing margin is -29.3dB at 10418MHz

## 1.3 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	150kHz ~ 30MHz	+/-2.66dB
Radiated emissions	30MHz ~ 1GHz	+/-3.26dB
	1GHz ~ 18GHz	+/-4.48dB



## 1.4 DESCRIPTION OF TEST MODES

Test Mode	Test Condition
<b>Radiated emission test</b>	
1	Adapter+ USB Cable+ Control+ BOX+ AR/VR G+ Earphone+ WIFI 2.4g Idle + BT Idle+ NFC
2	Adapter+ USB Cable+ Control+ BOX+ AR/VR G+ Earphone+ WIFI 5g Idle+ BT Idle+ NFC
<b>Conducted emission test</b>	
1	Adapter+ USB Cable+ Control+ BOX+ AR/VR G+ Earphone+ WIFI 2.4g Idle + BT Idle+ NFC
2	Adapter+ USB Cable+ Control+ BOX+ AR/VR G+ Earphone+ WIFI 5g Idle+ BT Idle+ NFC

**NOTE:**

1. For conducted emission test, test mode 1 was the worst case and only this mode was presented in this report.
2. For radiated emission test, test mode 1 was the worst case and only this mode was presented in this report



## 1.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

### FOR ALL TESTS

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Wireless AP	ABOCOM	WR224GR	060500749P	N/A
2	Earphone	N/A	N/A	N/A	N/A
3	IC Card	N/A	N/A	N/A	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	N/A
2	Shielded, Detachable 1.5m;
3	N/A



## 2 EMISSION TEST

### 2.1 CONDUCTED EMISSION MEASUREMENT

#### 2.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

TEST STANDARD: FCC Part 15, Subpart B (Section: 15.107)

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB $\mu$ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
  2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
  3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

#### 2.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR3	101900	Feb. 26,19	Feb. 25, 20
EMC32 test software	Rohde&Schwarz	EMC32	NA	NA	NA
LISN network	Rohde&Schwarz	ENV216	101922	Feb. 26,19	Feb. 25, 20

- NOTE:**
1. The test was performed in CE shielded room.
  2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

### 2.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.


**NOTE:** All modes of operation were investigated and the worst-case emissions are reported.

### 2.1.4 DEVIATION FROM TEST STANDARD

No deviation.



## 2.1.5 TEST SETUP



- Note:**
- 1.Support units were connected to second LISN.
  - 2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

## 2.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power and connected of all equipment.
- b. EUT was operated according to the use type described in the manufacturer's specifications or the user's manual.



## 2.1.7 TEST RESULTS

<b>TEST VOLTAGE</b>	DC 5.0V From Adapter Input 120 Vac, 60 Hz	<b>Detector Function &amp; Resolution Bandwidth</b>	Quasi-Peak (QP) / Average (AV), 9 kHz
<b>ENVIRONMENTAL CONDITIONS</b>	25deg. C, 52RH	<b>TESTED BY</b>	John Wen

Frequency (MHz)	QuasiPeak (dB $\mu$ V)	CAverage (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)	Line	Filter	Corr. (dB)
0.372000	---	27.54	48.46	-20.92	L1	ON	10.1
0.372000	35.78	---	58.46	-22.68	L1	ON	10.1
0.496000	---	20.95	46.07	-25.12	L1	ON	10.1
0.496000	33.50	---	56.07	-22.57	L1	ON	10.1
4.888000	---	27.28	46.00	-18.72	L1	ON	10.4
4.888000	32.77	---	56.00	-23.23	L1	ON	10.4
9.824000	---	33.68	50.00	-16.32	L1	ON	10.6
9.824000	39.97	---	60.00	-20.03	L1	ON	10.6
11.572000	---	33.24	50.00	-16.76	L1	ON	10.7
11.572000	39.06	---	60.00	-20.94	L1	ON	10.7
<b>21.716000</b>	---	<b>35.45</b>	<b>50.00</b>	<b>-14.55</b>	<b>L1</b>	<b>ON</b>	<b>11.1</b>
21.716000	41.20	---	60.00	-18.80	L1	ON	11.1

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.






BUREAU VERITAS

Test Report No.: FV190610W002

<b>TEST VOLTAGE</b>	DC 5.0V From Adapter Input 120 Vac, 60 Hz	<b>Detector Function &amp; Resolution Bandwidth</b>	Quasi-Peak (QP) / Average (AV), 9 kHz
<b>ENVIRONMENTAL CONDITIONS</b>	25deg. C, 52RH	<b>TESTED BY</b>	John Wen

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.512000	---	25.38	46.00	-20.62	N	ON	9.9
0.512000	36.61	---	56.00	-19.39	N	ON	9.9
1.026000	---	19.25	46.00	-26.75	N	ON	10.0
1.026000	31.83	---	56.00	-24.17	N	ON	10.0
1.464000	---	17.57	46.00	-28.43	N	ON	10.0
1.464000	30.86	---	56.00	-25.14	N	ON	10.0
10.060000	---	28.22	50.00	-21.78	N	ON	10.3
10.060000	35.90	---	60.00	-24.10	N	ON	10.3
10.498000	---	27.94	50.00	-22.06	N	ON	10.3
10.498000	35.45	---	60.00	-24.55	N	ON	10.3
22.512000	---	26.12	50.00	-23.88	N	ON	10.6
22.512000	32.67	---	60.00	-27.33	N	ON	10.6

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.





## 2.2 RADIATED EMISSION MEASUREMENT

### 2.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

**TEST STANDARD: FCC Part 15, Subpart B (Section: 15.109)**

Emissions radiated outside of the specified bands, shall be according to the general radiated limits as following:

Radiated Emissions Limits at 10 meters (dBµV/m)				
Frequencies (MHz)	FCC 15B/ ICES-003, Class A	FCC 15B / ICES-003, Class B	CISPR 22, Class A	CISPR 22, Class B
30-88	39	29.5	40	30
88-216	43.5	33.1		
216-230	46.4	35.6		
230-960			47	37
960-1000	49.5	43.5	Not defined	Not defined
1000-3000	Avg: 49.5	Avg: 43.5		
3000+	Peak: 69.5	Peak: 63.5	Not defined	Not defined

Radiated Emissions Limits at 3 meters (dBµV/m)				
Frequencies (MHz)	FCC 15B / ICES-003, Class A	FCC 15B / ICES-003, Class B	CISPR 22, Class A	CISPR 22, Class B
30-88	49.5	40	50.5	40.5
88-216	54	43.5		
216-230	56.9	46		
230-960			57.5	47.5
960-1000	60	54	Avg: 56 Peak: 76	Avg: 50 Peak: 70
1000-3000	Avg: 60	Avg: 54		
3000+	Peak: 80	Peak: 74	Avg: 60 Peak: 80	Avg: 54 Peak: 74



**Frequency Range (For unintentional radiators)**

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705-108	1000
108-500	2000
500-1000	5000
Above 1000	5 <sup>th</sup> harmonic of the highest frequency or 40GHz, whichever is lower

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
  2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
  3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
  4. QP detector shall be applied if not specified.

## 2.2.2 TEST INSTRUMENTS

### Frequency range below 1GHz

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldpn-CT0001143-1216	Feb. 26,19	Feb. 25,20
Bilog Antenna	ETS-LINDGREN	3143B	00161965	Feb. 26,19	Feb. 25,20
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Feb. 26,19	Feb. 25,20
Signal Pre-Amplifier	EMSI	EMC 9135	980249	Jun. 24,19	Jun. 23,20

### Frequency range above 1GHz

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldpn-CT0001143-1216	Feb. 26,19	Feb. 25,20
Horn Antenna	ETS-LINDGREN	3117	00168728	Feb. 26,19	Feb. 25,20
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Feb. 26,19	Feb. 25,20
Signal Pre-Amplifier	EMSI	EMC 012645B	980257	Jun. 24,19	Jun. 23,20

- NOTE:**
1. The test was performed in 3m chamber.
  2. The calibration interval of the above test instruments is 12 months or 24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
  3. The FCC Site Registration No. is 525120; The Designation No. is CN1171.





## 2.2.3 TEST PROCEDURE

### <Frequency Range below 1GHz>

The basic test procedure was in accordance with ANSI C63.4:2014 (section 12).

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from 1 meter to 4 meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1GHz.

#### NOTE:

1. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
3. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) (if the raw value not contains the amplifier);
4. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain(dB) (if the raw value contains the amplifier).
5. Margin value = Emission level – Limit value.

### <Frequency Range above 1GHz>

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter fully-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. The bore sight should be used during the test above 1GHz.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz

#### NOTE:

1. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth is 1MHz and video bandwidth of test receiver/spectrum analyzer is 3MHz for Peak detection at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth of test receiver/spectrum analyzer is 1Hz for Average detection (AV) at frequency above 1GHz.
3. For measurement of frequency above 1000 MHz, the EUT was set 3 meters away from the receiver antenna.
4. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
5. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) (if the raw value not contains the amplifier);
6. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain(dB) (if the raw value contains the amplifier)
7. Margin value = Emission level – Limit value.


## 2.2.4 DEVIATION FROM TEST STANDARD

No deviation.




### 2.2.5 TEST SETUP

<Frequency Range below 1GHz>



<Frequency Range above 1GHz>



\* : depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

### 2.2.6 EUT OPERATING CONDITIONS

Same as item 2.1.6.




### 2.2.7 TEST RESULTS

<b>TEST VOLTAGE</b>	DC 5.0V From Adapter Input 120 Vac, 60 Hz	<b>FREQUENCY RANGE</b>	30-1000 MHz
<b>ENVIRONMENTAL CONDITIONS</b>	23deg. C, 70 %RH	<b>DETECTOR FUNCTION &amp; RESOLUTION BANDWIDTH</b>	Quasi-Peak, 120 kHz
<b>TESTED BY</b>	Tony		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M											
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK	
120.21	34.25	61.37	43.5	-9.25	8.51	1.45	37.08	100	64	QP	
216.24	37.99	61.19	46	-8.01	11.51	1.87	36.58	165	255	QP	
239.52	39.87	61.97	46	-6.13	12.54	1.99	36.63	110	288	QP	
301.6	38.07	58.45	46	-7.93	14.15	2.22	36.75	100	146	QP	
312.27	37.44	57.46	46	-8.56	14.48	2.26	36.76	120	100	QP	
361.74	36.01	54.34	46	-9.99	16.01	2.46	36.8	100	310	QP	

- REMARKS:**
1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
  2. Negative sign (-) in the margin column signify levels below the limit.
  3. Frequency range scanned: 30MHz to 1000MHz.
  4. Only emissions significantly above equipment noise floor are reported.






<b>TEST VOLTAGE</b>	DC 5.0V From Adapter Input 120 Vac, 60 Hz	<b>FREQUENCY RANGE</b>	30-1000 MHz
<b>ENVIRONMENTAL CONDITIONS</b>	23deg. C, 70 %RH	<b>DETECTOR FUNCTION &amp; RESOLUTION BANDWIDTH</b>	Quasi-Peak, 120 kHz
<b>TESTED BY</b>	Tony		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
120.21	40.19	67.12	43.5	-3.31	8.7	1.45	37.08	100	166	QP
142.52	30.7	57	43.5	-12.8	9.03	1.56	36.89	100	40	QP
216.24	39.37	62.5	46	-6.63	11.58	1.87	36.58	110	23	QP
239.52	39.29	61.23	46	-6.71	12.7	1.99	36.63	100	233	QP
312.27	34	53.92	46	-12	14.58	2.26	36.76	195	131	QP
361.74	30.5	48.73	46	-15.5	16.11	2.46	36.8	155	211	QP

- REMARKS:**
1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
  2. Negative sign (-) in the margin column signify levels below the limit.
  3. Frequency range scanned: 30MHz to 1000MHz.
  4. Only emissions significantly above equipment noise floor are reported.






**BUREAU  
VERITAS**

**Test Report No.: FV190610W002**

<b>TEST VOLTAGE</b>	DC 5.0V From Adapter Input 120 Vac, 60 Hz	<b>FREQUENCY RANGE</b>	1-18 GHz
<b>ENVIRONMENTAL CONDITIONS</b>	23deg. C, 70 %RH	<b>DETECTOR FUNCTION &amp; RESOLUTION BANDWIDTH</b>	Peak/Average, 1 MHz
<b>TESTED BY</b>	Tony		

<b>ANTENNA POLARITY &amp; TEST DISTANCE: HORIZONTAL AT 3 M</b>										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
3975	30.43	29.05	74	-43.57	37.75	5.51	41.88	100	0	Peak
3975	20.45	19.07	54	-33.55	37.75	5.51	41.88	100	0	Average
7171	31.54	28.73	74	-42.46	37.27	8.54	43	100	0	Peak
7171	21.77	18.96	54	-32.23	37.27	8.54	43	100	0	Average
10418	34.66	28.91	74	-39.34	39.47	10.74	44.46	100	0	Peak
<b>10418</b>	<b>24.7</b>	<b>18.95</b>	<b>54</b>	<b>-29.3</b>	<b>39.47</b>	<b>10.74</b>	<b>44.46</b>	<b>100</b>	<b>0</b>	<b>Average</b>

- REMARKS:**
1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
  2. Negative sign (-) in the margin column signify levels below the limit.
  3. Frequency range scanned: 1GHz to 18GHz.
  4. Only emissions significantly above equipment noise floor are reported.






**BUREAU  
VERITAS**

**Test Report No.: FV190610W002**

<b>TEST VOLTAGE</b>	DC 5.0V From Adapter Input 120 Vac, 60 Hz	<b>FREQUENCY RANGE</b>	1-18 GHz
<b>ENVIRONMENTAL CONDITIONS</b>	23deg. C, 70 %RH	<b>DETECTOR FUNCTION &amp; RESOLUTION BANDWIDTH</b>	Peak/Average, 1 MHz
<b>TESTED BY</b>	Tony		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
3924	28.52	29	74	-45.48	35.86	5.52	41.86	100	360	Peak
3924	18.87	19.35	54	-35.13	35.86	5.52	41.86	100	360	Average
6015	30.11	27.53	74	-43.89	36.81	7.99	42.22	100	360	Peak
6015	22.51	19.93	54	-31.49	36.81	7.99	42.22	100	360	Average
9177	33.49	28.78	74	-40.51	38.77	10.26	44.32	100	360	Peak
9177	23.75	19.04	54	-30.25	38.77	10.26	44.32	100	360	Average

- REMARKS:**
1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
  2. Negative sign (-) in the margin column signify levels below the limit.
  3. Frequency range scanned: 1GHz to 18GHz.
  4. Only emissions significantly above equipment noise floor are reported.





**BUREAU  
VERITAS**

Test Report No.: FV190610W002

### **3 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB**

No any modifications were made to the EUT by the lab during the test.

**---END---**