



Test Report No.: SA150414N009



RF EXPOSURE REPORT

Product: LENOVO CAST
Model Name: WD200
FCC ID: O57WD200
Applicant: Lenovo (Shanghai) Electronics Technology Co., Ltd.
Address: No. 68 Building, 199 Fenju Road, Wai Gao Qiao FTZ ,
Shanghai , China
Manufacturer: Lenovo PC HK Limited
Address: 23/F, Lincoln House, Taikoo Place 979 King's Road,
Quarry Bay, Hong Kong
Prepared by: Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch
Lab Location: No. 34, Chenwulu Section, Guantai Rd., Houjie Town,
Dongguan City, Guangdong 523942, China
TEL: +86 769 8593 5656
FAX: +86 769 8593 1080
E-MAIL: customerservice.dg@cn.bureauveritas.com
Report No.: SA150414N009
Received Date: Apr. 14, 2015
Test Date: Apr. 15, 2015 ~ May 05, 2015
Issued Date: May 06, 2015

This report should not be used by the client to claim product certification, approval, or endorsement by A2LA or any government agencies.

Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com



TABLE OF CONTENTS

RF EXPOSURE REPORT.....	1
RELEASE CONTROL RECORD	3
1 CERTIFICATION	4
2 GENERAL INFORMATI	5
2.1 GENERAL DESCRIPTION OF EUT	5
3 RF EXPOSURE	6
3.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)	6
3.2 MPE CALCULATION FORMULA.....	6
3.3 CLASSIFICATION	6
3.4 CONDUCTED POWER	7



BUREAU
VERITAS

Test Report No.: SA150414N009

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA150414N009	Original release	May 06, 2015

Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com



1 CERTIFICATION

PRODUCT: LENOVO CAST
BRAND NAME: Lenovo
MODEL NAME: WD200
APPLICANT: Lenovo (Shanghai) Electronics Technology Co., Ltd.
TESTED: Apr. 15, 2015 ~ May 05, 2015
TEST SAMPLE: Production Unit
STANDARDS: **FCC Part 2 (Section 2.1091)**
FCC OET Bulletin 65, Supplement C (01-01)
IEEE C95.1

The above equipment has been tested by **Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch** and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Yuqiang Yin , **DATE:** May 06, 2015
(Yuqiang Yin / Engineer)

APPROVED BY : Glyn He , **DATE:** May 06, 2015
(Glyn He / Supervisor)



2 GENERAL INFORMATI

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	LENOVO CAST	
MODEL NAME	WD200	
FCC ID	O57WD200	
NOMINAL VOLTAGE	5.0Vdc (adapter or host equipment)	
OPERATING TEMPERATURE RANGE	-10 ~ 45°C	
MODULATION TECHNOLOGY	DSSS, OFDM	
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM	
OPERATING FREQUENCY	WIFI 2.4G	2412~ 2462MHz for 11b/g/n(HT20) 2422~ 2452MHz for 11b/g/n(HT40)
	WIFI 5G	5180 ~ 5240MHz, 5260 ~ 5320MHz 5500 ~ 5700MHz, 5745 ~ 5825MHz
ANTENNA TYPE	PCB Antenna with 2dBi gain	
HW VERSION	V2.0	
SW VERSION	V1.1	
I/O PORTS	Refer to user's manual	
CABLE SUPPLIED	USB Cable: Shielded, Detachable, 1.0m HDMI Cable: Shielded, Detachable, 1.0m	

NOTE:

- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- The EUT provides completed transmitters and receivers.

MODULATION MODE	TX FUNCTION
802.11a	1TX/1RX
802.11b	1TX/1RX
802.11g	1TX/1RX
802.11n (HT20)	2TX/2RX
802.11n (HT40)	2TX/2RX

- For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.



3 RF EXPOSURE

3.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

3.2 MPE CALCULATION FORMULA

$$Pd = (Pout * G) / (4 * pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

3.3 CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Module Approval**.



3.4 CONDUCTED POWER

CALCULATION FOR MAXIMUM E.I.R.P.

WIFI 2.4G

OPERATING BAND(MHz)	Output Power E.I.R.P. (dBm)	Output Power E.I.R.P. (mW)	Power Density (mW/cm ²)	limit (mW/cm ²)	PASS / FAIL
2412~2472	23.03	200.909	0.040	1.00	PASS

WIFI 5G

OPERATING BAND(MHz)	Output Power E.I.R.P. (dBm)	Output Power E.I.R.P. (mW)	Power Density (mW/cm ²)	limit (mW/cm ²)	PASS / FAIL
5180 ~ 5240	14.64	29.107	0.006	1.00	PASS
5260 ~ 5320	14.50	28.184	0.006	1.00	PASS
5500 ~ 5700	14.89	30.832	0.006	1.00	PASS
5745 ~ 5825	14.51	28.249	0.006	1.00	PASS