

**ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT
INTENTIONAL RADIATOR CERTIFICATION TO
FCC PART 15 SUBPART C REQUIREMENT**

OF

150M Wireless Broadband AP/Router

MODEL No.: SP916NL

FCC ID: O5BSP916NL

REPORT NO: ES110530148F-2

ISSUE DATE: June 02, 2012

Prepared for

**Micronet Communication Inc
12F-1, No.100, Min-Chuan Road, Hsin-Tien Dist., New Taipei City 231, Taiwan**

Prepared by
SHENZHEN EMTEK CO., LTD.

**Bldg 69, Majialong Industry Zone, Nanshan District,
Shenzhen, Guangdong, China
TEL: 86-755-26954280
FAX: 86-755-26954282**

VERIFICATION OF COMPLIANCE

Applicant:	Micronet Communication Inc 12F-1, No.100, Min-Chuan Road, Hsin-Tien Dist., New Taipei City 231, Taiwan
Manufacturer:	Micronet Communication Inc 12F-1, No.100, Min-Chuan Road, Hsin-Tien Dist., New Taipei City 231, Taiwan
Trademark:	N/A
Product Description:	150M Wireless Broadband AP/Router
Model Number:	SP916NL
File Number:	ES110530148F-2
Date of Test:	May 30, 2012 to June 01, 2012

We hereby certify that:

The above equipment was tested by SHENZHEN EMTEK CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2009) and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.247.

The test results of this report relate only to the tested sample identified in this report.

Date of Test : May 30, 2012 to June 01, 2012

Prepared by : Aaron Lai/Editor

Reviewer : King Wang/Supervisor

Approve & Authorized Signer : Lisa Wang/Manager

Table of Contents

1. GENERAL INFORMATION	5
1.1 PRODUCT DESCRIPTION	5
1.2 RELATED SUBMITTAL(S) / GRANT(S).....	5
1.3 TEST METHODOLOGY	6
1.4 SPECIAL ACCESSORIES.....	6
1.5 EQUIPMENT MODIFICATIONS	6
1.6 TEST FACILITY	6
2. SYSTEM TEST CONFIGURATION.....	7
2.1 EUT CONFIGURATION.....	7
2.2 EUT EXERCISE	7
2.3 TEST PROCEDURE	7
2.4 CONFIGURATION OF TESTED SYSTEM	7
3. DESCRIPTION OF TEST MODES	9
4. SUMMARY OF TEST RESULTS.....	10
5. CONDUCTED EMISSIONS TEST	11
5.1 MEASUREMENT PROCEDURE	11
5.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	11
5.3 MEASUREMENT EQUIPMENT USED	11
5.4 CONDUCTED EMISSION LIMIT	12
5.5 MEASUREMENT RESULT.....	12
5.6 CONDUCTED MEASUREMENT PHOTO	13
6. RADIATED EMISSION TEST	14
6.1 MEASUREMENT PROCEDURE	14
6.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	14
6.3 MEASUREMENT EQUIPMENT USED	15
6.4 RADIATED EMISSION LIMIT.....	15
6.5 MEASUREMENT RESULT.....	16
6.6 RADIATED MEASUREMENT PHOTOS	34
7. OCCUPIED BANDWIDTH TEST	36
7.1 MEASUREMENT PROCEDURE	36
7.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	36
7.3 MEASUREMENT EQUIPMENT USED	36
7.4 MEASUREMENT RESULTS.....	36
8. MAXIMUM PEAK OUTPUT POWER TEST	45
8.1 MEASUREMENT PROCEDURE	45
8.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	45
8.3 MEASUREMENT EQUIPMENT USED	45
8.4 PEAK POWER OUTPUT LIMIT	45
8.5 MEASUREMENT RESULTS.....	45
9. BAND EDGE TEST	54
9.1 MEASUREMENT PROCEDURE	54
9.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	54
9.3 MEASUREMENT EQUIPMENT USED	54
9.4 MEASUREMENT RESULTS.....	54
10. POWER DENSITY	57

10.1	TEST EQUIPMENT	57
10.2	MEASURING INSTRUMENTS AND SETTING.....	57
10.3	TEST PROCEDURES	57
10.4	BLOCK DIAGRAM OF TEST SETUP	57
10.5	LIMIT	58
10.6	TEST RESULT	58
11.	ANTENNA PORT EMISSION.....	66
11.1	TEST EQUIPMENT.....	66
11.2	MEASURING INSTRUMENTS AND SETTING.....	66
11.3	TEST PROCEDURES	66
11.4	BLOCK DIAGRAM OF TEST SETUP	66
11.5	TEST RESULT	66
12.	ANTENNA APPLICATION.....	79
12.1	ANTENNA REQUIREMENT.....	79
12.2	RESULT	79

1. General Information

1.1 Product Description

A major technical descriptions of EUT is described as following:

- A). Standards: IEEE802.11b/g/n
- B). Operation Frequency: 802.11b/g/n(HT20): 2412-2462MHz;
802.11n(HT40):2422-2452MHz
- C). Modulation: OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n,
DSSS with DBPSK/DQPSK/CCK for 802.11b
- D). Number of Channel: 802.11b/g/n(HT20): 11Channels; 802.11n(HT40): 7 Channels
- E). Data Rate (Max): 802.11b: 11 Mbps
802.11g: 54 Mbps
802.11n: 150Mbps
- F). Conducted Power: 12.17dBm(802.11b), 11.26dBm(802.11g),
10.52dBm(802.11n, HT20) 9.45dBm(802.11n, HT40)
- G) Antenna Gain: 5dBi
- H). Antenna Type: Welding Antenna
- I). Power Supply: DC 9V with AC Adapter
- J). Adapter: Model:TEA09U-09060
 - Input: AC 100-240V, 50/60Hz, 0.3A
 - Output: DC 9V, 0.6A

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447		

Note:

1. This device is a 150M Wireless Broadband AP/Router included 802.11b, 802.11g and 802.11n 2.4GHz transceiver function.
2. Test of channel was included the lowest middle and highest frequency in highest data rate and to perform the test, then record on this report.

1.2 Related Submittal(s) / Grant(s)

This submittal(s) (test report) is intended for FCC ID: O5BSP916NL filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules. The composite system (receiver) is compliance with Subpart B is authorized under a DOC procedure.

1.3 Test Methodology

All the test program has follow FCC new test procedure KDB558074

1.4 Special Accessories

Not available for this EUT intended for grant.

1.5 Equipment Modifications

Not available for this EUT intended for grant.

1.6 Test Facility

Site Description

EMC Lab. : Accredited by CNAS, 2010.10.29
The certificate is valid until 2013.10.28
The Laboratory has been assessed and proved to be in compliance
with CNAS/CL01: 2006(identical to ISO/IEC17025: 2005)
The Certificate Registration Number is L2291

Accredited by TUV Rheinland Shenzhen 2010.5.25
The Laboratory has been assessed according to the requirements
ISO/IEC 17025

Accredited by FCC, October 28, 2010
The Certificate Registration Number is 406365.

Accredited by Industry Canada, March 05, 2010
The Certificate Registration Number is 46405-4480.

Name of Firm

: SHENZHEN EMTEK CO., LTD.

Site Location

: Bldg 69, Majialong Industry Zone,
Nanshan District, Shenzhen, Guangdong, China

2. System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The Transmitter was operated in the normal operating mode. the Tx frequency was fixed which was for the purpose of the measurements.

2.3 Test Procedure

2.3.1 Conducted Emissions

The EUT is placed on a turn table which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4-2009 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

2.3.2 Radiated Emissions

The EUT is placed on a turn table which is 0.8 m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter(EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.4-2009.

2.4 Configuration of Tested System




Table 2-1 Equipment Used in Tested System

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.	Note
1.	150M Wireless Broadband AP/Router	N/A	ER-5840n	O5BSP916NL	N/A	EUT
2.	PC	LENOVO	9702	N/A	L3C4410	
3.	LCD Monitor	LENOVO	9227-AE6	N/A	4M0293084302824	
4.	Keyboard	LENOVO	KU-0225	N/A	0585494	
5.	Mouse	LENOVO	MO28UOL	N/A	44G7862 068	
6	Printer	HP	C89520	N/A	CN25S182N6	

Note:

- (1) Unless otherwise denoted as EUT in 『Remark』 column, device(s) used in tested system is a support equipment.

3. Description of Test Modes

The Transmitter of EUT is a 150M Wireless Broadband AP/Router and powered by host equipment. The max data rates of this Digital Transmission system (DTS) are 11Mbps (802.11b), 54Mbps(802.11g) & 72.2Mbps(802.11n, HT20) 150Mbps(802.11n, HT40).

The equipment enables high-speed access without wires to network assets. This EUT uses the IEEE 802.11b/g/n protocol.

For 802.11b/g/n(HT20):

1. For lowest channel : 2412MHz (Channel 1)
2. For middle channel : 2437MHz (Channel 6)
3. For highest channel: 2462MHz (Channel 11)

For 802.11 n(HT40):

1. For lowest channel : 2422MHz (Channel 3)
2. For middle channel : 2437MHz (Channel 6)
3. For highest channel: 2452MHz (Channel 9)

EUT operating conditions:

The EUT exercise program used during conducted testing was designed to exercise the EUT in a manner similar to typical use, The exercise sequence is listed as below:

1. Setup the EUT and simulators as shown on 2.4.
2. Turn on the power of all equipments.
3. The EUT Ping with the wireless router.
4. Repeat the above steps.

4. Summary of Test Results


FCC Rules	Description Of Test	Result
§15.247(a)(2)	6dB bandwidth	Compliant
§15.247(b)(3)	Max Peak output Power test	Compliant
§15.247(e)	Power density	Compliant
§15.247(d)	Band edge test	Compliant
§15.207	AC Power Conducted Emission	Compliant
§15.247(d), §15.209	Radiated Emission	Compliant
§15.203	Antenna Port Emission	Compliant
§15.109	Antenna Application	Compliant

5. Conducted Emissions Test

5.1 Measurement Procedure

1. The EUT was placed on a table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

5.2 Test SET-UP (Block Diagram of Configuration)



5.3 Measurement Equipment Used

Conducted Emission Test Site					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Test Receiver	Rohde & Schwarz	ESCS30	828985/018	05/29/2012	05/29/2013
L.I.S.N.	Schwarzbeck	NNLK8129	8129203	05/29/2012	05/29/2013
50Ω Coaxial Switch	Anritsu	MP59B	M20531	N/A	N/A
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100006	05/29/2012	05/29/2013
Voltage Probe	Rohde & Schwarz	TK9416	N/A	05/29/2012	05/29/2013
I.S.N	Rohde & Schwarz	ENY22	1109.9508.02	05/29/2012	05/29/2013

5.4 Conducted Emission Limit

Conducted Emission

Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

5.5 Measurement Result

Date of Test:	June 01, 2012	Temperature:	22°C
Frequency Detector:	0.15~30MHz	Humidity:	50%
Test Result:	PASS	Test Mode:	WIFI Mode

Test Line	Frequency MHz	Emission Level QP dB(μV)	Emission Level AV dB(μV)	Limits QP dB(μV)	Limits AV dB(μV)	Over QP dB(μV)	Over AV dB(μV)
Neutral	0.19	49.60	35.77	64.26	54.26	-14.66	-18.49
	0.57	42.30	30.93	56.00	46.00	-13.70	-15.07
	0.67	43.70	28.99	56.00	46.00	-12.30	-17.01
	0.87	44.60	25.49	56.00	46.00	-11.40	-20.51
	1.58	42.30	25.87	56.00	46.00	-13.70	-20.13
	2.38	45.80	29.73	56.00	46.00	-10.20	-16.27
Line	0.19	53.40	34.31	64.26	54.26	-10.86	-19.95
	0.41	46.70	25.76	57.75	47.75	-11.05	-21.99
	0.56	43.80	25.87	56.00	46.00	-12.20	-20.13
	1.20	45.70	22.56	56.00	46.00	-10.30	-23.44
	1.61	44.60	22.75	56.00	46.00	-11.40	-23.25
	6.73	49.31	24.23	60.00	50.00	-10.69	-25.77

5.6 Conducted Measurement Photo




6. Radiated Emission Test

6.1 Measurement Procedure


1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measured were complete.

6.2 Test SET-UP (Block Diagram of Configuration)


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



6.3 Measurement Equipment Used

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Pre-Amplifier	HP	8447D	2944A07999	05/29/2012	05/29/2013
Bilog Antenna	Schwarzbeck	VULB9163	142	05/29/2012	05/29/2013
Loop Antenna	ARA	PLA-1030/B	1029	05/29/2012	05/29/2013
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170399	05/29/2012	05/29/2013
Horn Antenna	Schwarzbeck	BBHA 9120	D143	05/29/2012	05/29/2013
Cable	Schwarzbeck	AK9513	ACRX1	05/29/2012	05/29/2013
Cable	Rosenberger	N/A	FP2RX2	05/29/2012	05/29/2013
Cable	Schwarzbeck	AK9513	CRPX1	05/29/2012	05/29/2013
Cable	Schwarzbeck	AK9513	CRRX2	05/29/2012	05/29/2013
Pre-Amplifier	HP	8447D	2944A07999	05/29/2012	05/29/2013

6.4 Radiated Emission Limit

FCC Class B Limit at 3m:

Frequency MHz	Distance Meter	Field Strength uV/m	Field Strength dBuV/m
30~88	3	100	40.0
88~216	3	150	43.5
216~960	3	200	46.0
Above 960	3	500	54.0

Note: The frequencies above 1000MHz, as measured using instrumentation with a peak detector function was corresponding to 20dB above maximum permitted average limit.

6.5 Measurement Result

Operation Mode: 802.11b TX Channel 1 Test Date : June 01, 2012
 Frequency Range: 30~1000MHz Temperature : 28°C
 Test Result: PASS Humidity : 65 %
 Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Over (dB)	Note
31.00	V	36.95	40	-3.05	PK
37.77	V	36.17	40	-3.83	PK
98.40	V	41.94	43.5	-1.56	PK
124.82	V	37.49	43.5	-6.01	PK
191.67	V	36.51	43.5	-6.99	PK
499.46	V	39.19	46	-6.81	PK
73.53	H	32.62	40	-7.38	PK
98.40	H	40.54	43.5	-2.96	PK
124.82	H	35.24	43.5	-8.26	PK
191.67	H	37.68	43.5	-5.82	PK
249.18	H	39.98	46	-6.02	PK
499.46	H	41.7	46	-4.3	PK

Note: (1) All Readings are Peak Value.
 (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 (3) The average measurement was not performed when the peak measured data under the limit of average detection.
 (4) EUT lying on the table position is the worst case result in the report.

Operation Mode: 802.11b TX Channel 6 Test Date : June 01, 2012
Frequency Range: 30~1000MHz Temperature : 28°C
Test Result: PASS Humidity : 65 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Over (dB)	Note
32.62	V	35.58	40	-4.42	PK
37.37	V	35.63	40	-4.37	PK
101.97	V	41.70	43.5	-1.80	PK
120.82	V	36.85	43.5	-6.65	PK
188.71	V	37.04	43.5	-6.46	PK
497.98	V	38.92	46	-7.08	PK
71.26	H	32.09	40	-7.91	PK
95.46	H	41.32	43.5	-2.18	PK
127.22	H	35.74	43.5	-7.76	PK
190.60	H	37.17	43.5	-6.33	PK
245.21	H	40.15	46	-5.85	PK
495.77	H	41.43	46	-4.57	PK

Note: (1) All Readings are Peak Value.
(2) Emission Level= Reading Level+Probe Factor +Cable Loss.
(3) The average measurement was not performed when the peak measured data under the limit of average detection.
(4) EUT lying on the table position is the worst case result in the report.

Operation Mode: 802.11b TX Channel 11 Test Date : June 01, 2012
 Frequency Range: 30~1000MHz Temperature : 28°C
 Test Result: PASS Humidity : 65 %
 Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Over (dB)	Note
33.30	V	36.93	40	-3.07	PK
36.30	V	35.61	40	-4.39	PK
97.15	V	40.97	43.5	-2.53	PK
127.28	V	35.81	43.5	-7.69	PK
191.62	V	32.67	43.5	-10.83	PK
499.44	V	35.48	46	-10.52	PK
70.10	H	29.96	40	-10.04	PK
99.43	H	41.57	43.5	-1.93	PK
121.19	H	32.63	43.5	-10.87	PK
194.91	H	40.16	43.5	-3.34	PK
250.60	H	38.36	46	-7.64	PK
501.34	H	41.84	46	-4.16	PK

- Note:**
- (1) All Readings are Peak Value.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.
 - (4) EUT lying on the table position is the worst case result in the report.

Operation Mode: 802.11g TX Channel 1 Test Date : June 01, 2012
Frequency Range: 30~1000MHz Temperature : 28°C
Test Result: PASS Humidity : 65 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Over (dB)	Note
30.64	V	36.37	40	-3.63	PK
37.77	V	36.77	40	-3.23	PK
98.40	V	40.24	43.5	-3.26	PK
124.82	V	37.98	43.5	-5.52	PK
191.67	V	38.34	43.5	-5.16	PK
499.46	V	39.69	46	-6.31	PK
81.30	H	33.26	40	-6.74	PK
98.40	H	40.64	43.5	-2.86	PK
124.82	H	36.01	43.5	-7.49	PK
193.22	H	38.62	43.5	-4.88	PK
249.18	H	41.62	46	-4.38	PK
499.46	H	40.91	46	-5.09	PK

Note: (1) All Readings are Peak Value.
(2) Emission Level= Reading Level+Probe Factor +Cable Loss.
(3) The average measurement was not performed when the peak measured data under the limit of average detection.
(4) EUT lying on the table position is the worst case result in the report.

Operation Mode: 802.11g TX Channel 6 Test Date : June 01, 2012
 Frequency Range: 30~1000MHz Temperature : 28°C
 Test Result: PASS Humidity : 65%
 Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Over (dB)	Note
31.68	V	36.81	40	-3.19	PK
37.67	V	36.23	40	-3.77	PK
101.97	V	40.00	43.5	-3.50	PK
120.82	V	37.34	43.5	-6.16	PK
188.71	V	38.87	43.5	-4.63	PK
498.41	V	39.42	46	-6.58	PK
79.03	H	32.73	40	-7.27	PK
95.46	H	41.42	43.5	-2.08	PK
127.22	H	36.51	43.5	-6.99	PK
192.15	H	38.11	43.5	-5.39	PK
245.21	H	41.79	46	-4.21	PK
496.42	H	40.64	46	-5.36	PK

- Note:**
- (1) All Readings are Peak Value.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.
 - (4) EUT lying on the table position is the worst case result in the report.

Operation Mode: 802.11g TX Channel 11 Test Date : June 01, 2012
Frequency Range: 30~1000MHz Temperature : 28°C
Test Result: PASS Humidity : 65 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Over (dB)	Note
32.74	V	36.81	40	-3.19	PK
36.70	V	35.74	40	-4.26	PK
97.15	V	39.19	43.5	-4.31	PK
127.27	V	36.3	43.5	-7.20	PK
191.62	V	34.5	43.5	-9.00	PK
499.44	V	35.98	46	-10.02	PK
77.87	H	30.6	40	-9.40	PK
99.61	H	41.67	43.5	-1.83	PK
121.19	H	33.4	43.5	-10.10	PK
196.46	H	41.1	43.5	-2.40	PK
250.60	H	39.74	46	-6.26	PK
522.51	H	40.57	46	-5.43	PK

Note: (1) All Readings are Peak Value.
(2) Emission Level= Reading Level+Probe Factor +Cable Loss.
(3) The average measurement was not performed when the peak measured data under the limit of average detection.
(4) EUT lying on the table position is the worst case result in the report.

**We took 802.11n HT20, HT 40 to test, and the worst operation mode is 802.11n HT20.
Test data as the next pages and all modulation methods do not exceed the above mentioned limits.**

Operation Mode:	802.11n TX Channel 1	Test Date :	June 01, 2012
Frequency Range:	30~1000MHz	Temperature :	28°C
Test Result:	PASS	Humidity :	65 %
Measured Distance:	3m	Test By:	WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Over (dB)	Note
30.64	V	36.67	40	-3.33	PK
37.77	V	36.57	40	-3.43	PK
98.40	V	41.34	43.5	-2.16	PK
124.82	V	37.57	43.5	-5.93	PK
191.67	V	38.62	43.5	-4.88	PK
499.46	V	39.66	46	-6.34	PK
73.53	H	33.6	40	-6.4	PK
98.40	H	40.44	43.5	-3.06	PK
124.82	H	36.61	43.5	-6.89	PK
191.67	H	38.8	43.5	-4.7	PK
249.18	H	40.04	46	-5.96	PK
499.46	H	41.13	46	-4.87	PK

Note: (1) All Readings are Peak Value.
(2) Emission Level= Reading Level+Probe Factor +Cable Loss.
(3) The average measurement was not performed when the peak measured data under the limit of average detection.
(4) EUT lying on the table position is the worst case result in the report.

Operation Mode: 802.11n TX Channel 6 Test Date : June 01, 2012
Frequency Range: 30~1000MHz Temperature : 28°C
Test Result: PASS Humidity : 65 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Over (dB)	Note
33.00	V	35.20	40	-4.80	PK
36.72	V	35.34	40	-4.66	PK
100.43	V	41.16	43.5	-2.34	PK
121.37	V	37.01	43.5	-6.49	PK
189.56	V	38.26	43.5	-5.24	PK
497.43	V	39.44	46	-6.56	PK
71.08	H	32.86	40	-7.14	PK
95.77	H	41.06	43.5	-2.44	PK
126.26	H	37.62	43.5	-5.88	PK
189.66	H	37.36	43.5	-6.14	PK
245.93	H	40.40	46	-5.60	PK
498.41	H	40.72	46	-5.28	PK

Note: (1) All Readings are Peak Value.
(2) Emission Level= Reading Level+Probe Factor +Cable Loss.
(3) The average measurement was not performed when the peak measured data under the limit of average detection.
(4) EUT lying on the table position is the worst case result in the report.

Operation Mode: 802.11n TX Channel 11 Test Date : June 01, 2012
Frequency Range: 30~1000MHz Temperature : 28°C
Test Result: PASS Humidity : 65 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Over (dB)	Note
34.25	V	36.31	40	-3.69	PK
36.72	V	35.32	40	-4.68	PK
96.04	V	39.65	43.5	-3.85	PK
127.17	V	35.35	43.5	-8.15	PK
191.55	V	34.85	43.5	-8.65	PK
499.02	V	36.45	46	-9.55	PK
74.89	H	31.15	40	-8.85	PK
99.88	H	40.22	43.5	-3.28	PK
121.09	H	34.48	43.5	-9.02	PK
193.73	H	37.02	43.5	-6.48	PK
249.93	H	38.5	46	-7.50	PK
515.09	H	40.08	46	-5.92	PK

Note: (1) All Readings are Peak Value.
(2) Emission Level= Reading Level+Probe Factor +Cable Loss.
(3) The average measurement was not performed when the peak measured data under the limit of average detection.
(4) EUT lying on the table position is the worst case result in the report.

Operation Mode: 802.11b TX Channel 1 Test Date : June 01, 2012
Frequency Range: Above 1GHz Temperature : 28°C
Test Result: PASS Humidity : 65 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4923.07	V	51.41	37.55	74	54	-22.59	-16.45
6596.15	V	49.01	36.7	74	54	-24.99	-17.3
7403.84	V	51.41	39.31	74	54	-22.59	-14.69
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
4923.07	H	51.24	38	74	54	-22.76	-16
7326.92	H	51.61	39.76	74	54	-22.39	-14.24
7423.07	H	52.96	39.81	74	54	-21.04	-14.19

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown “--” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
 - (4) EUT lying on the table position is the worst case result in the report.

Operation Mode: 802.11b TX (Channel 6) Test Date : June 01, 2012
Frequency Range: Above 1GHz Temperature : 28°C
Test Result: PASS Humidity : 65 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4943.07	V	49.61	36.35	74	54	-24.39	-17.65
6606.5	V	51.46	37.37	74	54	-22.54	-16.63
7382.69	V	54.64	41.11	74	54	-19.36	-12.89
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
4933.74	H	54.74	38.86	74	54	-19.26	-15.14
7342.6	H	52.39	37.11	74	54	-21.61	-16.89
7411.84	H	54.19	40.05	74	54	-19.81	-13.95

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown “--” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
 - (4) EUT lying on the table position is the worst case result in the report.

Operation Mode: 802.11b TX (Channel 11) Test Date : June 01, 2012
Frequency Range: Above 1GHz Temperature : 28°C
Test Result: PASS Humidity : 65 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4935.42	V	49.91	35.15	74	54	-24.09	-18.85
6605.15	V	48.56	34.8	74	54	-25.44	-19.2
7392.5	V	53.75	39.87	74	54	-20.25	-14.13
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
4931.52	H	55.8	39.46	74	54	-18.2	-14.54
7337.7	H	53.95	40.34	74	54	-20.05	-13.66
7401.73	H	49.93	37.83	74	54	-24.07	-16.17

No others harmonics emissions are higher than 20dB below the limits of 47 CFR Part 15.247.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown “--” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
 - (4) EUT lying on the table position is the worst case result in the report.

Operation Mode: 802.11g TX Channel 1 Test Date : June 01, 2012
Frequency Range: Above 1GHz Temperature : 28°C
Test Result: PASS Humidity : 65 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4250	V	43.27	30.75	74	54	-30.73	-23.25
4557.69	V	44.98	32.55	74	54	-29.02	-21.45
7384.61	V	50.98	39.17	74	54	-23.02	-14.83
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
4923.07	H	51.01	37.52	74	54	-22.99	-16.48
6038.46	H	46.74	34.82	74	54	-27.26	-19.18
8057.69	H	52.02	39.42	74	54	-21.98	-14.58

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown “--” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
 - (4) EUT lying on the table position is the worst case result in the report.

Operation Mode: 802.11g TX (Channel 6) Test Date : June 01, 2012
Frequency Range: Above 1GHz Temperature : 28°C
Test Result: PASS Humidity : 65 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4260.5	V	41.82	29.73	74	54	-32.18	-24.27
4567.74	V	47.1	33.22	74	54	-26.9	-20.78
7364.4	V	54.44	40.62	74	54	-19.56	-13.38
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
4933.12	H	53.11	38.36	74	54	-20.89	-15.64
6053.92	H	47.49	32.19	74	54	-26.51	-21.81
8046.51	H	53.23	39.54	74	54	-20.77	-14.46

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Note: (1) All Readings are Peak Value and AV.
(2) Emission Level= Reading Level+Probe Factor +Cable Loss.
(3) Data of measurement within this frequency range shown “--” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
(4) EUT lying on the table position is the worst case result in the report.

Operation Mode: 802.11g TX (Channel 11) Test Date : June 01, 2012
Frequency Range: Above 1GHz Temperature : 28°C
Test Result: PASS Humidity : 65 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4260.05	V	41.62	28.6	74	54	-32.38	-25.4
4563.05	V	44.57	30.71	74	54	-29.43	-23.29
7374.25	V	53.31	39.74	74	54	-20.69	-14.26
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
4931.12	H	55.54	38.95	74	54	-18.46	-15.05
6048.09	H	49.05	34.87	74	54	-24.95	-19.13
8047.46	H	48.97	37.95	74	54	-25.03	-16.05

No others harmonics emissions are higher than 20dB below the limits of 47 CFR Part 15.247.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown “--” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
 - (4) EUT lying on the table position is the worst case result in the report.

We took 802.11n HT20, HT 40 to test, and the worst operation mode is 802.11n HT20. Test data as the next pages, and all modulation methods do not exceed the mentioned limits.

Operation Mode:	802.11n TX Channel 1	Test Date :	June 01, 2012
Frequency Range:	Above 1GHz	Temperature :	28°C
Test Result:	PASS	Humidity :	65 %
Measured Distance:	3m	Test By:	WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
5250	V	49.31	35.5	74	54	-24.69	-18.5
7250	0	51.75	39.21	74	54	-22.25	-14.79
8942.3	V	53.82	40.79	74	54	-20.18	-13.21
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
5250	H	50.68	35.45	74	54	-23.32	-18.55
6480.76	H	49.11	37.21	74	54	-24.89	-16.79
8038.46	H	52.97	39.8	74	54	-21.03	-14.2

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown “--” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
 - (4) EUT lying on the table position is the worst case result in the report.

Operation Mode: 802.11n TX (Channel 6) Test Date : June 01, 2012
Frequency Range: Above 1GHz Temperature : 28°C
Test Result: PASS Humidity : 65 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
5265.36	V	47.57	34.15	74	54	-26.43	-19.85
7267.26	V	52.77	39.57	74	54	-21.23	-14.43
8922.05	V	55.87	42.56	74	54	-18.13	-11.44
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
5262.03	H	53.7	36.19	74	54	-20.3	-17.81
6484.78	H	49.82	36.18	74	54	-24.18	-17.82
8037.41	H	54.29	40.25	74	54	-19.71	-13.75

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown “--” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
 - (4) EUT lying on the table position is the worst case result in the report.


Operation Mode: 802.11n TX (Channel 11) Test Date : June 01, 2012
Frequency Range: Above 1GHz Temperature : 28°C
Test Result: PASS Humidity : 65 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
5265.02	V	47.9	34.48	74	54	-26.1	-19.52
7253.05	V	51.39	36.81	74	54	-22.61	-17.19
8932.23	V	55.92	41.24	74	54	-18.08	-12.76
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
5258.11	H	53.73	36.7	74	54	-20.27	-17.3
6490.12	H	50.23	37.72	74	54	-23.77	-16.28
8030.11	H	51.95	38.35	74	54	-22.05	-15.65

No others harmonics emissions are higher than 20dB below the limits of 47 CFR Part 15.247.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown “--” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
 - (4) EUT lying on the table position is the worst case result in the report.

6.6 Radiated Measurement Photos




SHENZHEN EMTEK CO., LTD.

REPORT NO: ES110530148F-2

FCC ID: O5BSP916NL

DATE: 02/06/2012




7. Occupied Bandwidth Test

7.1 Measurement Procedure

The EUT was operating in IEEE 802.11b/g/n mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

7.2 Test SET-UP (Block Diagram of Configuration)



7.3 Measurement Equipment Used

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Agilent	E4407B	88156318	05/29/2012	05/29/2013

The following table is the setting of spectrum analyzer.

Spectrum analyzer	Setting
Attenuation	Auto
Span Frequency	50MHz
RB	300kHz
VB	1MHz
Detector	Peak
Trace	Max hold
Sweep Time	Auto

Test Procedures

1. Set resolution bandwidth (RBW) = 1-5 % of the emission bandwidth (EBW).
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission. Compare the resultant bandwidth with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is 1-5 %.


7.4 Measurement Results



6 Bandwidth Test Data Chart:
Refer to attached data chart.

Spectrum Detector: PK
Test By: Andy
Test Result: PASS
Operation Mode: 802.11b

Test Date : June 01, 2012
Temperature : 28°C
Humidity : 65 %


Channel number	Channel frequency (MHz)	Measurement level (MHz)	Required Limit (kHz)
1	2412	10.454	>500
6	2437	10.437	>500
11	2462	10.439	>500







Spectrum Detector: PK Test Date : June 01, 2012
Test By: Andy Temperature : 28°C
Test Result: PASS Humidity : 65 %
Operation Mode: 802.11 g


Channel number	Channel frequency (MHz)	Measurement level (MHz)	Required Limit (kHz)
1	2412	16.601	>500
6	2437	16.520	>500
11	2462	16.607	>500







Spectrum Detector: PK Test Date : June 01, 2012
 Test By: Andy Temperature : 28°C
 Test Result: PASS Humidity : 65 %
 Operation Mode: 802.11 n (H20)


Channel number	Channel frequency (MHz)	Measurement level (MHz)	Required Limit (kHz)
1	2412	17.657	>500
6	2437	17.804	>500
11	2462	17.813	>500







Spectrum Detector: PK Test Date : June 01, 2012
Test By: Andy Temperature : 28°C
Test Result: PASS Humidity : 65 %
Operation Mode: 802.11 n (H40)

Channel number	Channel frequency (MHz)	Measurement level (MHz)	Required Limit (kHz)
3	2422	36.344	>500
6	2437	36.294	>500
7	2452	36.282	>500






8. Maximum Peak Output Power Test

8.1 Measurement Procedure

- a. The Transmitter output (antenna port) was connected to the Spectrum Analyzer.
- b. Turn on the EUT and Spectrum Analyzer and then record the peak power value.
- c. Repeat above procedures on all channels needed to be tested.

8.2 Test SET-UP (Block Diagram of Configuration)



8.3 Measurement Equipment Used

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Agilent	E4407B	88156318	05/29/2012	05/29/2013



8.4 Peak Power output limit


The maximum peak power shall be less 1Watt.

8.5 Measurement Results

Spectrum Detector:	PK	Test Date :	June 01, 2012
Test By:	Andy	Temperature :	28°C
Test Result:	PASS	Humidity :	65 %
Operation Mode:	802.11b		



Channel number	Channel Frequency(MHz)	Peak Power output(dBm)	Peak Power Limit(W)	Pass/Fail
1	2412.00	12.17	1W(30dBm)	PASS
6	2437.00	11.87	1W(30dBm)	PASS
11	2462.00	11.51	1W(30dBm)	PASS






Spectrum Detector: PK Test Date : June 01, 2012
Test By: Andy Temperature : 28°C
Test Result: PASS Humidity : 65 %
Operation Mode: 802.11g



Channel number	Channel Frequency(MHz)	Peak Power output(dBm)	Peak Power Limit(W)	Pass/Fail
1	2412.00	11.26	1W(30dBm)	PASS
6	2437.00	11.03	1W(30dBm)	PASS
11	2462.00	10.66	1W(30dBm)	PASS






Spectrum Detector: PK Test Date : June 01, 2012
Test By: Andy Temperature : 28°C
Test Result: PASS Humidity : 65 %
Operation Mode: 802.11n(HT20)



Channel number	Channel Frequency(MHz)	Peak Power output(dBm)	Peak Power Limit(W)	Pass/Fail
1	2412.00	10.52	1W(30dBm)	PASS
6	2437.00	10.44	1W(30dBm)	PASS
11	2462.00	9.96	1W(30dBm)	PASS






Spectrum Detector: PK Test Date : June 01, 2012
Test By: Andy Temperature : 28°C
Test Result: PASS Humidity : 65 %
Operation Mode: 802.11n(HT40)

Channel number	Channel Frequency(MHz)	Peak Power output(dBm)	Peak Power Limit(W)	Pass/Fail
1	2422.00	9.45	1W(30dBm)	PASS
6	2447.00	9.36	1W(30dBm)	PASS
11	2452.00	9.00	1W(30dBm)	PASS





9. Band Edge Test

9.1 Measurement Procedure

1. The EUT was Operating in hopping mode or could be controlled its channel. Printed out test result from the spectrum by hard copy function.
2. The EUT was placed on a turn table which is 0.8m above ground plane.
3. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
4. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
5. Repeat above procedures until all frequency measured were complete.

9.2 Test SET-UP (Block Diagram of Configuration)

As 6.2 Test set up (B) and (C)

9.3 Measurement Equipment Used

Same as 6.3 Radiated Emission Measurement.

9.4 Measurement Results

Test mode: 802.11b

Spectrum Detector:	PK/AV	Test Date :	June 01, 2012
Test By:	Andy	Temperature :	28 °C
Test channel:	01	Humidity :	65 %

Frequency (MHz)	Polarity	Level (dBuV/m)		Limited (dBuV/m)	
		PK	AV	PK	AV
2390.00	H	45.02	33.67	74	54
2390.00	V	45.14	33.73	74	54

Spectrum Detector:	PK/AV	Test Date :	June 01, 2012
Test By:	Andy	Temperature :	28 °C
Test channel:	11	Humidity :	65 %

Frequency (MHz)	Polarity	Level (dBuV/m)		Limited (dBuV/m)	
		PK	AV	PK	AV
2483.50	H	44.76	33.64	74	54
2483.50	V	43.91	32.83	74	54

Test mode: 802.11g

Spectrum Detector:	PK/AV	Test Date :	June 01, 2012
Test By:	Andy	Temperature :	28 °C
Test channel:	01	Humidity :	65 %

Frequency (MHz)	Polarity	Level (dBuV/m)		Limited (dBuV/m)	
		PK	AV	PK	AV
2390.00	H	45.37	34.02	74	54
2390.00	V	44.88	33.09	74	54

Spectrum Detector:	PK/AV	Test Date :	June 01, 2012
Test By:	Andy	Temperature :	28 °C
Test channel:	11	Humidity :	65 %

Frequency (MHz)	Polarity	Level (dBuV/m)		Limited (dBuV/m)	
		PK	AV	PK	AV
2483.50	H	45.41	33.88	74	54
2483.50	V	42.98	31.98	74	54

Test mode: 802.11n HT 20

Spectrum Detector:	PK/AV	Test Date :	June 01, 2012
Test By:	Andy	Temperature :	28 °C
Test channel:	01	Humidity :	65 %

Frequency (MHz)	Polarity	Level (dBuV/m)		Limited (dBuV/m)	
		PK	AV	PK	AV
2390.00	H	45.27	33.79	74	54
2390.00	V	45.00	34.17	74	54

Spectrum Detector:	PK/AV	Test Date :	June 01, 2012
Test By:	Andy	Temperature :	28 °C
Test channel:	11	Humidity :	65 %

Frequency (MHz)	Polarity	Level (dBuV/m)		Limited (dBuV/m)	
		PK	AV	PK	AV
2483.50	H	45.74	34.39	74	54
2483.50	V	42.93	32.51	74	54

Test mode: 802.11n HT40

Spectrum Detector:	PK/AV	Test Date :	June 01, 2012
Test By:	Andy	Temperature :	28 °C
Test channel:	03	Humidity :	65 %

Frequency (MHz)	Polarity	Level (dBuV/m)		Limited (dBuV/m)	
		PK	AV	PK	AV
2390.00	H	46.20	33.22	74	54
2390.00	V	45.13	32.47	74	54

Spectrum Detector:	PK/AV	Test Date :	June 01, 2012
Test By:	Andy	Temperature :	28 °C
Test channel:	09	Humidity :	65 %

Frequency (MHz)	Polarity	Level (dBuV/m)		Limited (dBuV/m)	
		PK	AV	PK	AV
2483.50	H	45.23	35.47	74	54
2483.50	V	43.98	32.59	74	54

10. Power Density

10.1 Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Agilent	E4407B	88156318	05/29/2012	05/29/2013

10.2 Measuring Instruments and Setting


The following table is the setting of spectrum analyzer.

Spectrum analyzer	Setting
Attenuation	Auto
Span Frequency	Set the span to 5-30 % greater than the EBW.
RB	100kHz
VB	300kHz
Detector	Peak
Trace	Max hold
Sweep Time	Auto
offset	BWCF = $10\log(3 \text{ kHz}/100\text{kHz}) = -15.2 \text{ dB}$.

10.3 Test Procedures

- a: Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
- b: Set the RBW = 100 kHz. Set the VBW \geq 300 kHz.
- c: Set the span to 5-30 % greater than the EBW.
- d: Detector = peak Sweep time = auto couple. Trace mode = max hold. Allow trace to fully stabilize.
- e: Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.
- f: Scale the observed power level to an equivalent value in 3 kHz by adjusting (reducing) the measured power by a bandwidth correction factor (BWCF) where $BWCF = 10\log(3 \text{ kHz}/100\text{kHz}) = -15.2 \text{ dB}$.
- g: The resulting peak PSD level must be $\leq 8 \text{ dBm}$.

10.4 Block Diagram of Test Setup




10.5 Limit



The transmitted power density averaged over any 1 second interval shall not be greater +8dBm in any 3 kHz bandwidth.

10.6 Test Result

Spectrum Detector: PK Test Date : June 01, 2012
Test By: Andy Temperature : 28°C
Test Result: PASS Humidity : 65 %
Operation Mode: 802.11 b


Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
2415.12	-19.88	<8dBm	PASS
2439.76	-20.48	<8dBm	PASS
2462.00	-21.18	<8dBm	PASS







Spectrum Detector: PK Test Date : June 01, 2012
Test By: Andy Temperature : 28°C
Test Result: PASS Humidity : 65 %
Operation Mode: 802.11 g


Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
2413.50	-27.43	<8dBm	PASS
2430.30	-27.89	<8dBm	PASS
2463.37	-28.44	<8dBm	PASS







Spectrum Detector: PK Test Date : June 01, 2012
Test By: Andy Temperature : 28°C
Test Result: PASS Humidity : 65 %
Operation Mode: 802.11 n (HT20)


Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
2413.60	-28.09	<8dBm	PASS
2438.20	-28.60	<8dBm	PASS
2463.20	-29.22	<8dBm	PASS







Spectrum Detector: PK Test Date : June 01, 2012
Test By: Andy Temperature : 28°C
Test Result: PASS Humidity : 65 %
Operation Mode: 802.11 n(HT40)

Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
2426.0	-30.65	<8dBm	PASS
2450.0	-30.97	<8dBm	PASS
2455.0	-31.11	<8dBm	PASS





11. Antenna Port Emission

11.1 Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Agilent	E4407B	88156318	05/29/2012	05/29/2013

11.2 Measuring Instruments and Setting


The following table is the setting of spectrum analyzer.

Spectrum analyzer	Setting
Attenuation	Auto
RB	100kHz
VB	1MHz
Detector	Peak
Trace	Max hold

11.3 Test Procedures

The conducted spurious emissions were measured conducted using a spectrum analyzer at low, mid, and hi channels, The limit was determined by attenuation 20dB of the RF peak power output.



11.4 Block Diagram of Test setup





11.5 Test Result

PASS.



802.11b Low Channel 1





802.11b Mid Channel 6





802.11b High Channel 11





802.11g Low Channel 1





802.11g Mid Channel 6





802.11g Mid Channel 11





802.11n HT 20 Low Channel 1





802.11n HT 20 Mid Channel 6





802.11n HT 20 High Channel 11





802.11n HT 40 Low Channel 3



802.11n HT 40 Mid Channel 6



802.11n HT 40 Mid Channel 9



12. Antenna Application

12.1 Antenna Requirement

The EUT'S antenna is met the requirement of FCC part 15C section 15.203.

12.2 Result

The EUT'S antenna is welding Antenna. If user remove the antenna, can cause damage to the EUT! The antenna's gain is 5dBi and meets the requirement.

