

ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT

INTENTIONAL RADIATOR CERTIFICATION TO FCC PART 15 SUBPART C REQUIREMENT

	OF
Product Name:	Dongle
Brand Name:	HP
Model No.:	DHN1
Model Difference:	N/A
FCC ID:	O62-DHN1
Report No.:	E2/2015/80053
Issue Date:	Sep. 15, 2015
FCC Rule Part:	§15.249
Prepared for:	Darfon Electronics Corp. 167, Shanying Road, Gueishan, Taoyuan 33341, Taiwan, R.O.C.
Prepared by:	SGS Taiwan Ltd. Electronics & Communication Laboratory No.2, Keji 1st Rd., Guishan District, Taoyuan City, Taiwan 333



Note: This report shall not be reproduced except in full, without the written approval of SGS Taiwan Ltd. This document may be altered or revised by SGS Taiwan Ltd. personnel only, and shall be noted in the revision section of the document.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exenerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is unawful and offenders may be prosecuted to the fullest extent of the law.

```
        SGS Taiwan Ltd.
        No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號

        台灣檢驗科技股份有限公司
        t (886-2) 2299-3279
        f (886-2) 2298-0488
        www.tw.sgs.com
```



Report No: E2/2015/80053 Issue Date: Oct. 06, 2015 Page: 2 of 45

VERIFICATION OF COMPLIANCE

Applicant:	Darfon Electronics Corp. 167, Shanying Road, Gueishan, Taoyuan 33341, Taiwan, R.O.C.
Product Name:	Dongle
Brand Name:	HP
Model No.:	DHN1
Model Difference:	N/A
FCC ID:	O62-DHN1
File Number:	E2/2015/80053
Date of test:	Aug. 20, 2015 ~ Oct. 06, 2015
Date of EUT Received:	Aug. 20, 2015

We hereby certify that:

The above equipment was tested by SGS Taiwan Ltd., Electronics & Communication Laboratory.

The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 2013 and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits.

The test results of this report relate only to the tested sample identified in this report.

Test By:	Aken Huang	Date:	Oct. 06, 2015
Prepared By:	Aken Huang/Engineer Vroletta Tang	Date:	Oct. 06, 2015
Approved By: _	Violetta Tang / Clerk Jim Chang Jim Chang / Asst. Manager	Date:	Oct. 06, 2015
	0 0		

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms edocument.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is and/subject to the fullest extent of the law. By persecuted to the fullest extent of the law. SGS Taiwan Ltd. No.134, WuKungRoad, NewTaipeiIndustrialPark, WukuDistrict, NewTaipeiCity, Taiwan 24803/新北市五股區新北產業園區五工路 134 號



Revision History

Report Number	Revision	Description	Issue Date
E2/2015/80052	Rev.00	Initial creation of document	Oct. 06, 2015

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本概告未經本公司書面許可,不可帮份積裂。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sqs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sqs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號 Taiwan Ltd.



Table of Contents

1.	GENERAL INFORMATION	5
1.1	PRODUCT DESCRIPTION	5
1.2	TEST METHODOLOGY OF APPLIED STANDARDS	6
1.3	TEST FACILITY	6
1.4	SPECIAL ACCESSORIES	6
1.5	EQUIPMENT MODIFICATIONS	6
2.	SYSTEM TEST CONFIGURATION	7
2.1	EUT CONFIGURATION	
2.2	EUT EXERCISE	
2.3	Test Procedure	7
2.4	MEASUREMENT RESULTS EXPLANATION EXAMPLE	
2.5	LIMITATION	8
2.6	CONFIGURATION OF TESTED SYSTEM	
3.	SUMMARY OF TEST RESULTS	
4.	DESCRIPTION OF TEST MODES	
4.1	OPERATED IN 2400 ~ 2483.5MHz BAND	
4.2	THE WORST TEST MODES AND CHANNEL DETAILS	
5.	MEASUREMENT UNCERTAINTY	
6.	CONDUCTED EMISSIONS TEST.	
6 .1	Measurement Procedure:	
6.2	TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	
6.3	MEASUREMENT EQUIPMENT USED:	
6.4	MEASUREMENT EQUIT MENT USED	
7.	RADIATED EMISSION TEST	
7.1	MEASUREMENT PROCEDURE	
7.1	TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	
7.3	MEASUREMENT EQUIPMENT USED:	
7.5	FIELD STRENGTH CALCULATION	
7.6	MEASUREMENT RESULT	
8.	20 DB BANDWIDTH MEASUREMENT	
o. 8.1	MEASUREMENT PROCEDURE	-
8.2	TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	
8.3	MEASUREMENT EQUIPMENT USED:	
8.4	MEASUREMENT EQUIPMENT USED.	
0.4		

Taiwan Ltd.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sqs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sqs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. SGS Taiwan Ltd. No.134. WuKunQRoad.NewTaipelindustrialPark.WukuDIstrict.NewTaipel/Clty.Taiwan24803/新北市五股區新北產業間區五工路 134 號 No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134號



1. GENERAL INFORMATION

1.1 Product Description

Product Name:	Dongle
Brand Name:	HP
Model No.:	DHN1
Model Difference:	N/A
Transmit Power	93.00dBuV/m
Operation Frequency:	2403MHz - 2475MHz
Channel number:	73 Channels
Channel space:	1MHz
Modulation Type:	GFSK
Hardware Version:	Rev01
Software Version:	V3310
Power Supply:	5V from USB port
Antenna Designation:	PCB Antenna, Gain: -1.54dBi

This report complies with FCC 15.249

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



1.2 Test Methodology of Applied Standards

FCC Part 15, Subpart C §15.249

ANSI C63.10:2013

Note:

- 1. All test items have been performed and record as per the above standards.
- 2. The EUT is compliance with FCC Subpart B is authorized under the certification procedure.

1.3 Test Facility

SGS Taiwan Ltd. Electronics & Communication Laboratory No.2, Keji 1st Rd., Guishan District, Taoyuan City, Taiwan 333. (TAF code 0513)

FCC Registration Numbers are: 628985 (Hwaya)

Canada Registration Number: 4620A-5.

1.4 Special Accessories

There are no special accessories used while test was conducted.

1.5 Equipment Modifications

There was no modification incorporated into the EUT.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sqs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sqs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the ransaction documents. This document is unlawful and offenders may be prosecuted to the fullest extent of the law.



2. SYSTEM TEST CONFIGURATION

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

An engineering test mode (software/firmware) that applicant provided was utilized to manipulate the EUT into transmit, selection of the test channel, and modulation scheme.

2.3 Test Procedure

2.3.1 Conducted Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz,. The CISPR Quasi-Peak and Average detector mode is employed according to §15.207. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.

2.3.2 Radiated Emissions

The EUT is a placed on as turn table. For emissions testing at or below 1 GHz, the table height shall be 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height shall be 1.5 m. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes and measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made "while keeping the antenna in the 'cone of radiation' from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response." is still within the 3dB illumination BW of the measurement antenna.

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuation factor between EUT conducted port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly EUT RF output level.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms_and_conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms_edocument.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, WuKungRoad, NewTaipelIndustrialPark, WukuDistrict, NewTaipeiCity, Taiwan24803/新北市 五股區新北產業園區五工路 134 號



2.5 Limitation

(1) Conducted Emission

According to section 15.207(a) Conducted Emission Limits is as following.

Frequency (MHz)	Conducted Limit (dBuV)		
	Quasi-Peak	Average	
0.15 – 0.5	66 - 56	56 - 46	
0.5 – 5	56	46	
5 - 30	60	50	

(2) Radiated Emission 15.249(a)

The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following.

Frequency	Field strength of	Field strength of	Distance (m)
(MHz)	Fundamental	Harmonics	
902 – 928	50 mV/m	500 uV/m	3
	(94dBuV/m)	(54dBuV/m)	
2400 – 2483.5	50 mV/m	500 uV/m	3
	(94dBuV/m)	(54dBuV/m)	
5725 – 5875	50 mV/m	500 uV/m	3
	(94dBuV/m)	(54dBuV/m)	
24.0 – 24.25 GHz	250 mV/m	2500 uV/m	3
	(107.95dBuV/m)	(67.95dBuV/m)	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



(3) Radiated Emission15.249 (d)

Emission Radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50dB below the level of the fundamental or to the general radiated emission limits in Section 15.209 as below. whichever is the lesser attenuation.

Frequency	Field strength	Distance (m)	Field strength at
(MHz)	μ V/m		3m dBμV/m
1.705-30	30	30	69.54
30-88	100	3	40
88-216	150	3	43.5
216-960	200	3	46
Above 960	500	3	54

(4) Radiated Emission 15.249(e)

For frequencies above 1000MHz, the above field strength limits are based on average limits. The peak filed strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20dB under any condition of modulation.

- Remark 1. Emission level in dBuV/m=20 log (uV/m)
 - Measurement was performed at an antenna to the closed point of EUT distance of meters.
 - 3. Only spurious frequency is permitted to locate within the Restricted Bands specified in provision of ξ 15.205
 - 4. Emission spurious frequency which appearing within the Restricted Bands specified in provision of £15.205, then the general radiated emission limits in ξ 15.209 apply.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sqs.com/terms_e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



2.6 Configuration of Tested System




Table 2-2 Equipment Used in Tested System

lte m	Equipment	Mfr/Brand	Model/ Type No.	Series No.	Data Cable	Power Cord
1.	2.4G Test Software	N/A	N/A	N/A	N/A	N/A

Note: All the above equipment/cables were placed in worse case positions to maximize emission signals during emission test.

Grounding: Grounding was in accordance with the manufacturer's requirements and conditions for the intended use.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

Taiwan Ltd.



Summary of Test Results 3.

FCC Rules	Description Of Test	Result
§15.207(a)	AC Power Line Conducted Emission	N/A
§15.249(a) (d) (e)	Radiated Emission	Compliant
§15.215(c)	20dB Bandwidth Measurement	Compliant

4. **Description of test modes**

Operated in 2400 ~ 2483.5MHz Band 4.1

73 channels are provided.

CHANNEL	FREQUENCY		FREQUENCY	CHANNEL	FREQUENCY
1	2403MHz	26	2428MHz	51	2453MHz
2	2414MHz	27	2429MHz	52	2454MHz
3	2405MHz	28	2430MHz	53	2455MHz
4	2406MHz	29	2431MHz	54	2456MHz
5	2407MHz	30	2432MHz	55	2457MHz
6	2408MHz	31	2433MHz	56	2458MHz
7	2409MHz	32	2434MHz	57	2459MHz
8	2410MHz	33	2435MHz	58	2460MHz
9	2411MHz	34	2436MHz	59	2461MHz
10	2412MHz	35	2437MHz	60	2462MHz
11	2413MHz	36	2438MHz	61	2463MHz
12	2414MHz	37	2439MHz	62	2464MHz
13	2415MHz	38	2440MHz	63	2465MHz
14	2416MHz	39	2441MHz	64	2466MHz
15	2417MHz	40	2442MHz	65	2467MHz
16	2418MHz	41	2443MHz	66	2468MHz
17	2419MHz	42	2444MHz	67	2469MHz
18	2420MHz	43	2445MHz	68	2470MHz
19	2421MHz	44	2446MHz	69	2471MHz
20	2422MHz	45	2447MHz	70	2472MHz
21	2423MHz	46	2448MHz	71	2473MHz
22	2424MHz	47	2449MHz	72	2474MHz
23	2425MHz	48	2450MHz	73	2475MHz
24	2426MHz	49	2451MHz		
25	2427MHz	50	2452MHz		

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



4.2 The Worst Test Modes and Channel Details

- 1. The EUT has been tested under operating condition.
- 2. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

RADIATED EMISSION TEST:

RADIATED EMISSION TEST (BELOW 1 GHz)						
MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	PACKET TYPE	ANTENNA PORT	
2.4G	1 to 73	1,38,73	GFSK		MAIN	
	RADIATED	EMISSION TES	ST (ABOVE 1 GH	z)		
MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	PACKET TYPE	ANTENNA PORT	
2.4G	1 to 73	1,38,73	GFSK		MAIN	

Note:

The field strength of radiation emission was measured as EUT stand-up position (H mode) and lie down position (E1, E2 mode) for General Wireless 2.4GHz Transmitter for channel Low, Mid and High, the worst case E2 position was reported.

ANTENNA PORT CONDUCTED MEASUREMENT:

CONDUCTED TEST					
MODE	AVAILABLE	TESTED	MODULATION	PACKET	ANTENNA
INIODE	CHANNEL	CHANNEL	MODULATION	TYPE	PORT
2.4G	1 to 73	1,38,73	GFSK		MAIN

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



5. MEASUREMENT UNCERTAINTY

Test Items	Uncertainty
AC Power Line Conducted Emission	+/- 2.586 dB
20dB Bandwidth	+/- 123.36 Hz
100 KHz Bandwidth Of Frequency Band Edges	+/- 1.55 dB
Temperature	+/- 0.8 °C
Humidity	+/- 4.7 %
DC / AC Power Source	DC= +/- 1%, AC= +/- 0.2%

Radiated Spurious Emission:

	30MHz - 180MHz: +/- 3.37dB
Measurement uncertainty (Polarization : Vertical)	180MHz -417MHz: +/- 3.19dB
	0.417GHz-1GHz: +/- 3.19dB
	1GHz - 18GHz: +/- 4.04dB
	18GHz - 40GHz: +/- 4.04dB

	30MHz - 167MHz: +/- 4.22dB
Measurement uncertainty	167MHz -500MHz: +/- 3.44dB
(Polarization : Horizontal)	0.5GHz-1GHz: +/- 3.39dB
	1GHz - 18GHz: +/- 4.08dB
	18GHz - 40GHz: +/- 4.08dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2


Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

6. Conducted Emissions Test

6.1 Measurement Procedure:

- 1. The EUT was placed on a table which is 0.8m above ground plane.
- 2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 3. Repeat above procedures until all frequency measured were complete.

6.2 Test SET-UP (Block Diagram of Configuration)



6.3 <u>Measurement Equipment Used:</u>

Conducted Emission Test Site								
EQUIPMENT	EQUIPMENT MFR MODEL SERIAL							
TYPE		NUMBER	NUMBER	CAL.				
EMI Test Receiver	R&S	ESCI 7	100950	12/12/2014	12/11/2015			
Coaxial Cables	N/A	N30N30-1042-15 0cm	N/A	01/06/2015	01/07/2016			
LISN	Schwarzbeck	NSLK 8127	8127-648	06/09/2015	06/08/2016			
LISN	Rolf-Heine	NNB-2/16Z	99012	03/04/2015	03/03/2016			
Test Software	Farad	EZ-EMC	Ver. SGS-03A2	N.C.R.	N.C.R.			

6.4 Measurement Result:

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



2

3

4

5

6

0.1980

0.2500

0.3380

3.2340

17.7380

51.17

45 12

41.39

42.94

41.06

0.07

0.09

0.14

0.60

0.58

51.24

45 21

41.53

43.54

41.64

63.69

61 76

59.25

56.00

60.00

-12.45

-1655

-17.72

-12.46

-18.36

peak


peak

peak

peak

peak

AC POWER LINE CONDUCTED EMISSION TEST DATA



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。


This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is unawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號



FCC ID: 062-DHN1

Temperature: 24 °C Site : Conduction Room Phase: N AC 120V/60Hz Humidity: 71 % Limit: CISPR 13 / CISPR 22 Conduction(QP) Power: Mode: Note:



No.	Mk.	Freq.	Level	Factor	ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1900	50.65	0.13	50.78	64.04	-13.26	peak	
2		0.2140	48.22	0.14	48.36	63.05	-14.69	peak	
3		0.2620	44.86	0.16	45.02	61.37	-16.35	peak	
4		0.2860	41.62	0.17	41.79	60.64	-18.85	peak	
5	•	3.2460	44.59	0.65	45.24	56.00	-10.76	peak	
6		17.1940	40.66	0.63	41.29	60.00	-18.71	peak	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sqs.com/terms and conditions.htm and, for electronic format documents, subject to this document is ubject to this document is observed printed overlear, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is unlawful and offenders may be prosecuted to the fullest extent of the law.




7. Radiated Emission Test

7.1 Measurement Procedure

- 1. The EUT was placed on a turntable that is 0.8m (below 1GHz) / 1.5m (above 1GHz) above ground plane.
- 2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 4. Repeat above procedures until all frequency measured were complete.

7.2 Test SET-UP (Block Diagram of Configuration)

(A) Radiated Emission Test Set-UP Frequency Below 30MHz.




Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



(B) Radiated Emission Test Set-Up, Frequency form 30MHz to 1000MHz



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms_e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

y. No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號



7.3 Measurement Equipment Used:

966 Chamber								
EQUIPMENT	MFR	MODEL	SERIAL	LAST	CAL DUE.			
TYPE		NUMBER	NUMBER	CAL.				
EMI Test Receiver	R&S	ESU 40	100363	04/09/2015	04/08/2016			
Loop Antenna	ETS-Lindgren	6502	00143303	12/09/2014	12/08/2015			
Broadband Antenna	TESEQ	CBL 6112D	35240	12/05/2014	12/04/2015			
Horn Antenna	ETS-Lindgren	3117	00143272	12/08/2014	12/07/2015			
Horn Antenna	ETS-Lindgren	3160-09	00117911	11/13/2014	11/12/2015			
Horn Antenna	ETS-Lindgren	3160-10	00117783	11/13/2014	11/12/2015			
Pre Amplifier	EMC Instruments	EMC330	980096	12/19/2014	12/18/2015			
Pre Amplifier	EMC Instruments	EMC0011830	980199	12/19/2014	12/18/2015			
Pre Amplifier	R&S	SCU-18	10204	12/19/2014	12/18/2015			
Pre Amplifier	R&S	SCU-26	100780	12/19/2014	12/18/2015			
Coaxial Cable	Huber+Suhner	RG 214/U	966Rx 9K-30M	12/19/2014	12/18/2015			
Coaxial Cable	Huber+Suhner	RG 214/U SUCOFLEX 104	966Rx 30M-3G	12/19/2014	12/18/2015			
Coaxial Cable	Huber+Suhner	SUCOFLEX 104	966Rx 1G-18G	12/19/2014	12/18/2015			
Coaxial Cable	Huber+Suhner	mini 141-12 SUCOFLEX 104	966Rx 18G-40G	12/19/2014	12/18/2015			
Coaxial Cable	Huber+Suhner	SUCOFLEX 104	966Tx 30M-18G	12/19/2014	12/18/2015			
Coaxial Cable	Huber+Suhner	SUCOFLEX 102	966Tx 18G-40G	12/19/2014	12/18/2015			
Attenuator	WOKEN	218FS-10	RF27	12/19/2014	12/18/2015			
Site NSA	SGS	966 Chamber C	SAC-C	03/04/2015	03/03/2016			
Site VSWR	SGS	966 Chamber C	SAC-C	03/04/2015	03/03/2016			
DC Power Supply	HOLA	DP-3003	D7070035	05/04/2015	05/03/2016			
Controller	MF	MF-7802	N/A	N.C.R.	N.C.R.			
Antenna Master	MF	N/A	N/A	N.C.R.	N.C.R.			

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



7.5 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CL - AG

Where	•	CL = Cable Attenuation Factor (Cable Loss)
	RA = Reading Amplitude	AG = Amplifier Gain
	AF = Antenna Factor	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。


This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sqs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sqs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134號 Taiwan Ltd.



7.6 Measurement Result **Radiated Spurious Emission Measurement Result (MAIN)**

Operation Mode :	2.4G	Test Date :	2015/8/28
Fundamental Frequency :	2403 MHz	Temp. / Humi. :	26.4deg_C/47RH
Operation Band :	Main	Test Engineer :	Vito
EUT Pol. :	E2	Measurement Antenna Pol. :	Vertical




Freq.	Note	Detector	Spectum	Factor	Actual	Limit	Margin
		Mode	Reading Level		FS	@3m	
MHz	F/H/E/S	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
2402.98	F	Peak	86.35	6.65	93.00	114	-21.01
2402.98	F	Average	51.12	6.65	57.77	94	-36.23

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Report No: E2/2015/80053 Issue Date: Oct. 06, 2015 Page: 22 of 45

Operation Mode :	2.4G	Test Date :	2015/8/28
Fundamental Frequency :	2403 MHz	Temp. / Humi. :	26.4deg_C/47RH
Operation Band :	Main	Test Engineer :	Vito
EUT Pol. :	E2	Measurement Antenna Pol. :	Horizontal




Freq.	Note	Detector	Spectum	Factor	Actual	Limit	Margin
		Mode	Reading Level		FS	@3m	
MHz	F/H/E/S	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
2403.09	F	Peak	86.17	6.65	92.82	114	-21.18
2403.09	F	Average	51.64	6.65	58.29	94	-35.71

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Report No: E2/2015/80053 Issue Date: Oct. 06, 2015 Page: 23 of 45

Operation Mode :	2.4G	Test Date :	2015/8/28
Fundamental Frequency :	2440 MHz	Temp. / Humi. :	26.4deg_C/47RH
Operation Band :	Main	Test Engineer :	Vito
EUT Pol. :	E2	Measurement Antenna Pol. :	Vertical




Freq.	Note	Detector	Spectum	Factor	Actual	Limit	Margin
		Mode	Reading Level		FS	@3m	
MHz	F/H/E/S	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
2439.99	F	Peak	83.42	6.83	90.24	114	-23.76
2439.99	F	Average	50.68	6.83	57.51	94	-36.49

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Report No: E2/2015/80053 Issue Date: Oct. 06, 2015 Page: 24 of 45

Operation Mode :	2.4G	Test Date :	2015/8/28
Fundamental Frequency :	2440 MHz	Temp. / Humi. :	26.4deg_C/47RH
Operation Band :	Main	Test Engineer :	Vito
EUT Pol. :	E2	Measurement Antenna Pol.:	Horizontal




Freq.	Note	Detector	Spectum	Factor	Actual	Limit	Margin
		Mode	Reading Level		FS	@3m	
MHz	F/H/E/S	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
2440.04	F	Peak	83.41	6.83	90.24	114	-23.76
2440.04	F	Average	53.10	6.83	59.93	94	-34.07

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Report No: E2/2015/80053 Issue Date: Oct. 06, 2015 Page: 25 of 45

Operation Mode :	2.4G	Test Date :	2015/8/28
Fundamental Frequency :	2475 MHz	Temp. / Humi. :	26.4deg_C/47RH
Operation Band :	Main	Test Engineer :	Vito
EUT Pol. :	E2	Measurement Antenna Pol. :	Vertical




Freq.	Note	Detector	Spectum	Factor	Actual	Limit	Margin
		Mode	Reading Level		FS	@3m	
MHz	F/H/E/S	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
2475.03	F	Peak	81.57	6.94	88.51	114	-25.49
2475.03	F	Average	49.97	6.94	56.91	94	-37.09

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Report No: E2/2015/80053 Issue Date: Oct. 06, 2015 Page: 26 of 45

Operation Mode:	2.4G	Test Date :	2015/8/28
Fundamental Frequency:	2475 MHz	Temp. / Humi. :	26.4deg_C/47RH
Operation Band :	Main	Test Engineer :	Vito
EUT Pol. :	E2	Measurement Antenna Pol. :	Horizontal




lote Detector	Spectum	Factor	Actual	Limit	Margin
Mode	Reading Level		FS	@3m	
I/E/S PK/QP/AV	′ dBµV	dB	dBµV/m	dBµV/m	dB
F Peak	82.21	6.94	89.15	114	-24.85
F Average	49.38	6.94	56.32	94	-37.68
	Mode I/E/S PK/QP/AV F Peak	Mode Reading Level I/E/S PK/QP/AV dBμV F Peak 82.21	Mode Reading Level I/E/S PK/QP/AV dBµV dB F Peak 82.21 6.94	Mode Reading Level FS I/E/S PK/QP/AV dBμV dB dBμV/m F Peak 82.21 6.94 89.15	ModeReading LevelFS@3mI/E/SPK/QP/AVdBμVdBdBμV/mdBμV/mFPeak82.216.9489.15114

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Radiated Spurious Emission Measurement Result

Operation Mode :	2.4G	Test Date :	2015/8/28
Fundamental Frequency :	2403 MHz	Temp. / Humi. :	26.4deg_C/47RH
Operation Band :	BE CH LOW	Test Engineer :	Vito
EUT Pol. :	E2	Measurement Antenna Pol.:	Vertical



Actual FS(dB μ V/m) = SPA. Reading level(dB μ V) + Factor(dB)

Factor(dB) = Antenna Factor(dBµV/m) + Cable Loss(dB) – Pre_Amplifier Gain(dB)

Note : "F" : denotes Fundamental Frequency. ; "H" : denotes Harmonic Frequency.

"E" : denotes Band Edge Frequency. ; "S" : denotes Spurious Frequency.

"---" : denotes Noise Floor.

The trace on RE (radiation emission) plot is as colored blue, and the detection manner we've employed is peak detector.


Freq.	Note	Detector	Spectum	Factor	Actual	Limit	Margin
		Mode	Reading Level		FS	@3m	
MHz	F/H/E/S	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
2390.00	Е	Peak	53.58	6.62	60.19	74	-13.81
2390.00	E	Average	33.02	6.62	39.64	54	-14.36

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Report No: E2/2015/80053 Issue Date: Oct. 06, 2015 Page: 28 of 45



Actual FS(dB μ V/m) = SPA. Reading level(dB μ V) + Factor(dB)

Factor(dB) = Antenna Factor(dBµV/m) + Cable Loss(dB) – Pre_Amplifier Gain(dB)

Note : "F" : denotes Fundamental Frequency. ; "H" : denotes Harmonic Frequency.

"E" : denotes Band Edge Frequency. ; "S" : denotes Spurious Frequency.

"---" : denotes Noise Floor.

The trace on RE (radiation emission) plot is as colored blue, and the detection manner we've employed is peak detector.


Freq.	Note	Detector	Spectum	Factor	Actual	Limit	Margin
		Mode	Reading Level		FS	@3m	
MHz	F/H/E/S	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
2390.00	Е	Peak	53.87	6.62	60.49	74	-13.51
2390.00	Е	Average	33.00	6.62	39.62	54	-14.38

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Report No: E2/2015/80053 Issue Date: Oct. 06, 2015 Page: 29 of 45



Actual FS(dB μ V/m) = SPA. Reading level(dB μ V) + Factor(dB)

Factor(dB) = Antenna Factor(dB μ V/m) + Cable Loss(dB) – Pre Amplifier Gain(dB)

Note : "F" : denotes Fundamental Frequency. ; "H" : denotes Harmonic Frequency.

"E" : denotes Band Edge Frequency. ; "S" : denotes Spurious Frequency.

"---": denotes Noise Floor.

The trace on RE (radiation emission) plot is as colored blue, and the detection manner we've employed is peak detector.

Freq.	Note	Detector	Spectum	Factor	Actual	Limit	Margin
		Mode	Reading Level		FS	@3m	
MHz	F/H/E/S	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
2483.50	Е	Peak	51.02	6.96	57.99	74	-16.01
2483.50	Е	Average	33.06	6.96	40.02	54	-13.98


Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

Taiwan Ltd



Report No: E2/2015/80053 Issue Date: Oct. 06, 2015 Page: 30 of 45



Actual FS(dBµV/m) = SPA. Reading level(dBµV) + Factor(dB)

Factor(dB) = Antenna Factor(dBµV/m) + Cable Loss(dB) – Pre_Amplifier Gain(dB)

Note : "F" : denotes Fundamental Frequency. ; "H" : denotes Harmonic Frequency.

"E" : denotes Band Edge Frequency. ; "S" : denotes Spurious Frequency.

"---" : denotes Noise Floor.

The trace on RE (radiation emission) plot is as colored blue, and the detection manner we've employed is peak detector.

Freq.	Note	Detector Mode	Spectum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	F/H/E/S	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
2483.50	Е	Peak	50.77	6.96	57.73	74	-16.27
2483.50	Е	Average	33.04	6.96	40.00	54	-14.00


Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Radiated Spurious Emission Measurement Result For Frequency form 30MHz to 1000MHz

I of Trequency form out									
Operation Mode :	2.4G	Test Date :	2015/8/28						
Fundamental Frequency:	2403 MHz	Temp. / Humi. :	26.4deg_C/47RH						
Operation Band :	TX CH LOW	Test Engineer :	Vito						
EUT Pol. :	E2	Measurement Antenna Pol. :	Vertical						



Freq.	Note	Detector Mode	Spectum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	F/H/E/S	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
37.76	S	Peak	50.38	-17.57	32.81	40	-7.20
128.94	S	Peak	46.27	-21.34	24.93	43.5	-18.57
322.94	S	Peak	40.00	-18.55	21.44	46	-24.56
453.89	S	Peak	38.08	-14.80	23.27	46	-22.73
560.59	S	Peak	41.17	-12.86	28.31	46	-17.69
664.38	S	Peak	44.45	-11.66	32.78	46	-13.22

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sqs.com/terms and conditions.htm and, for electronic format documents, subject to this document is ubject to this document is observed printed overlear, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is unlawful and offenders may be prosecuted to the fullest extent of the law.




Report No: E2/2015/80053 Issue Date: Oct. 06, 2015 Page: 32 of 45

Operation Mode : Fundamental Frequency: **Operation Band :** EUT Pol.:

2.4G 2403 MHz TX CH LOW E2

Test Date : Temp. / Humi. : Test Engineer : Measurement Antenna Pol. : 2015/8/28 26.4deg_C/47RH Vito Horizontal



Freq.	Note	Detector Mode	Spectum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	F/H/E/S	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
225.94	S	Peak	48.81	-22.60	26.21	46	-19.79
290.93	S	Peak	49.39	-19.38	30.00	46	-16.00
355.92	S	Peak	47.71	-17.29	30.41	46	-15.59
666.32	S	Peak	37.07	-11.65	25.41	46	-20.59
767.20	S	Peak	37.26	-10.01	27.25	46	-18.75
869.05	S	Peak	38.83	-8.28	30.55	46	-15.45

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。




Report No: E2/2015/80053 Issue Date: Oct. 06, 2015 Page: 33 of 45

Operation Mode : Fundamental Frequency: **Operation Band :** EUT Pol.:

2.4G 2440 MHz TX CH MID E2

Test Date : Temp. / Humi. : Test Engineer : Measurement Antenna Pol. : 2015/8/28 26.4deg_C/47RH Vito Vertical



Freq.	Note	Detector Mode	Spectum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	F/H/E/S	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
37.76	S	Peak	39.31	-17.57	21.74	40	-18.26
128.94	S	Peak	45.90	-21.34	24.56	43.5	-18.94
387.93	S	Peak	39.64	-16.28	23.37	46	-22.63
550.89	S	Peak	43.36	-13.24	30.12	46	-15.88
664.38	S	Peak	43.84	-11.66	32.18	46	-13.82
923.37	S	Peak	39.10	-7.56	31.54	46	-14.46

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sqs.com/terms</u> e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. y. No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號

Member of SGS Group




Report No: E2/2015/80053 Issue Date: Oct. 06, 2015 Page: 34 of 45

Operation Mode : Fundamental Frequency: **Operation Band :** EUT Pol.:

2.4G 2440 MHz TX CH MID E2

Test Date : Temp. / Humi. : Test Engineer : Measurement Antenna Pol. : 2015/8/28 26.4deg_C/47RH Vito Horizontal



Freq.	Note	Detector Mode	Spectum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	F/H/E/S	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
31.94	S	Peak	32.85	-14.17	18.69	40	-21.31
225.94	S	Peak	48.42	-22.60	25.82	46	-20.18
290.93	S	Peak	48.97	-19.38	29.58	46	-16.42
355.92	S	Peak	47.69	-17.29	30.40	46	-15.60
420.91	S	Peak	42.90	-15.39	27.51	46	-18.49
772.05	S	Peak	46.01	-10.23	35.77	46	-10.23

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。




Report No: E2/2015/80053 Issue Date: Oct. 06, 2015 Page: 35 of 45

Operation Mode : Fundamental Frequency : **Operation Band :** EUT Pol.:

2.4G 2475 MHz **TX CH HIGH** E2

Test Date : Temp. / Humi. : Test Engineer : Measurement Antenna Pol. : 2015/8/28 26.4deg_C/47RH Vito Vertical



Freq.	Note	Detector Mode	Spectum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	F/H/E/S	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
36.79	S	Peak	35.85	-16.96	18.89	40	-21.11
128.94	S	Peak	46.46	-21.34	25.12	43.5	-18.38
322.94	S	Peak	40.37	-18.55	21.82	46	-24.18
517.91	S	Peak	36.68	-13.60	23.07	46	-22.93
582.90	S	Peak	40.37	-12.45	27.92	46	-18.08
664.38	S	Peak	43.12	-11.66	31.45	46	-14.55

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。




Report No: E2/2015/80053 Issue Date: Oct. 06, 2015 Page: 36 of 45

Operation Mode : Fundamental Frequency : **Operation Band :** EUT Pol.:

2.4G 2475 MHz **TX CH HIGH** E2

Test Date : Temp. / Humi. : Test Engineer : Measurement Antenna Pol. : 2015/8/28 26.4deg_C/47RH Vito Horizontal



Freq.	Note	Detector Mode	Spectum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	F/H/E/S	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
193.93	S	Peak	45.96	-23.82	22.14	43.5	-21.36
291.90	S	Peak	48.71	-19.38	29.33	46	-16.67
355.92	S	Peak	47.69	-17.29	30.40	46	-15.60
387.93	S	Peak	45.14	-16.28	28.86	46	-17.14
420.91	S	Peak	43.58	-15.39	28.19	46	-17.81
805.03	S	Peak	39.43	-9.13	30.29	46	-15.71


Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Radiated Spurious Emission Measurement Result

For Frequency above 1GHz

Operation Mode :	2.4G	Test Date :	201 5/8/28
Fundamental Frequency:	2403 MHz	Temp. / Humi. :	26.4deg_C/47RH
Operation Band :	TX CH LOW	Test Engineer :	Vito
EUT Pol. :	E2	Measurement Antenna Pol. :	Vertical



Freq.	Note	Detector	Spectum	Factor	Actual	Limit	Margin
		Mode	Reading Level		FS	@3m	
MHz	F/H/E/S	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
4806.00	Н	Peak	33.17	10.98	44.16	74	-29.84
4806.00	Н	Average	23.35	10.98	34.33	54	-19.67

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。




Report No: E2/2015/80053 Issue Date: Oct. 06, 2015 Page: 38 of 45

Operation Mode : Fundamental Frequency: **Operation Band :** EUT Pol.:

2.4G 2403 MHz TX CH LOW E2

Test Date : Temp. / Humi. : Test Engineer : Measurement Antenna Pol. : 2015/8/28 26.4deg_C/47RH Vito Horizontal




Note	Detector	Spectum	Factor	Actual	Limit	Margin
	Mode	Reading Level		FS	@3m	
F/H/E/S	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
Н	Peak	33.14	10.98	44.13	74	-29.87
Н	Average	23.72	10.98	34.70	54	-19.30
	F/H/E/S H	Mode F/H/E/S PK/QP/AV H Peak	Mode Reading Level F/H/E/S PK/QP/AV dBµV H Peak 33.14	Mode Reading Level F/H/E/S PK/QP/AV dBµV dB H Peak 33.14 10.98	ModeReading LevelFSF/H/E/SPK/QP/AVdBµVdBdBµV/mHPeak33.1410.9844.13	ModeReading LevelFS@3mF/H/E/SPK/QP/AVdBµVdBdBµV/mdBµV/mHPeak33.1410.9844.1374

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Report No: E2/2015/80053 Issue Date: Oct. 06, 2015 Page: 39 of 45

Operation Mode :	2.4G	Test Date :	2015/8/28
Fundamental Frequency :	2440 MHz	Temp. / Humi. :	26.4deg_C/47RH
Operation Band :	TX CH MID	Test Engineer :	Vito
EUT Pol.:	E2	Measurement Antenna Pol. :	Vertical




Freq.	Note	Detector Mode	Spectum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	F/H/E/S	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
4880.00	Н	Peak	32.99	10.90	43.89	74	-30.11
4880.00	Н	Average	23.08	10.90	33.98	54	-20.02

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Report No: E2/2015/80053 Issue Date: Oct. 06, 2015 Page: 40 of 45

Operation Mode :	2.4G	Test Date :	2015/8/28
Fundamental Frequency :	2440 MHz	Temp. / Humi. :	26.4deg_C/47RH
Operation Band :	TX CH MID	Test Engineer :	Vito
EUT Pol.:	E2	Measurement Antenna Pol. :	Horizontal



Freq.	Note	Detector Mode	Spectum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	F/H/E/S	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
4880.00	Н	Peak	32.03	10.90	42.94	74	-31.06
4880.00	Н	Average	23.41	10.90	34.31	54	-19.69

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。




Report No: E2/2015/80053 Issue Date: Oct. 06, 2015 Page: 41 of 45

Operation Mode : Fundamental Frequency : **Operation Band :** EUT Pol.:

2.4G 2475 MHz **TX CH HIGH** E2

Test Date : Temp. / Humi. : Test Engineer : Measurement Antenna Pol. : 2015/8/28 26.4deg_C/47RH Vito Vertical



Freq.	Note	Detector	Spectum	Factor	Actual	Limit	Margin
		Mode	Reading Level		FS	@3m	
MHz	F/H/E/S	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
4950.00	Н	Peak	32.39	10.96	43.35	74	-30.65
4950.00	Н	Average	23.68	10.96	34.64	54	-19.36

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。




Report No: E2/2015/80053 Issue Date: Oct. 06, 2015 Page: 42 of 45

Operation Mode : Fundamental Frequency : **Operation Band :** EUT Pol.:

2.4G 2475 MHz **TX CH HIGH** E2

Test Date : Temp. / Humi. : Test Engineer : Measurement Antenna Pol. : 2015/8/28 26.4deg_C/47RH Vito Horizontal



Freq.	Note	Detector	Spectum	Factor	Actual	Limit	Margin
		Mode	Reading Level		FS	@3m	
MHz	F/H/E/S	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
4950.00	Н	Peak	31.80	10.96	42.76	74	-31.24
4950.00	Н	Average	23.19	10.96	34.15	54	-19.85

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sqs.com/terms</u> e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

y. No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號




8. 20 dB Bandwidth Measurement

8.1 Measurement Procedure

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set the spectrum analyzer as RBW=20kHz of the approximate emission bandwidth, VBW = 3 times RBW, Span= approximately 20dB below the peak level. Sweep=auto
- 4. Repeat above procedures until all frequency measured were complete.

8.2 Test SET-UP (Block Diagram of Configuration)



8.3 Measurement Equipment Used:

Conducted Emission Test Site								
EQUIPMENT	MFR	MODEL	SERIAL	LAST	CAL DUE.			
TYPE		NUMBER	NUMBER	CAL.				
Spectrum Analyzer	Agilent	N9010A	MY53400256	10/15/2014	10/14/2015			
Power Meter	Anritsu	ML2496A	1326001	06/23/2015	06/22/2016			
Power Sensor	Anritsu	MA2411B	1315048	06/23/2015	06/22/2016			
Power Sensor	Anritsu	MA2411B	1315049	06/23/2015	06/22/2016			
Coaxial Cable 30cm	WOKEN	00100A1F1A195 C	RF01	12/19/2014	12/18/2015			
DC Block	PASTERNACK	PE8210	RF29	12/19/2014	12/18/2015			
Splitter	RF-LAMBAD	RFLT2W1G18G	RF35	12/19/2014	12/18/2015			
Attenuator	WOKEN	218FS-10	RF23	12/19/2014	12/18/2015			
DC Power Supply	Agilent	E3640A	MY53140006	05/04/2015	05/03/2016			

8.4 Measurement Results:

2.403GHz = 1.172MHz 2.440GHz = 1.147MHz 2.475GHz = 1.147MHz

Refer to attached data chart.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.


除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



20dB Bandwidth Test Plot CH-Low



20dB Bandwidth Test Plot CH-Mid




Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms edocument.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is and/subject to the fullest extent of the law. By persecuted to the fullest extent of the law. SGS Taiwan Ltd. No.134, WuKungRoad, NewTaipeiIndustrialPark, WukuDistrict, NewTaipeiCity, Taiwan 24803/新北市五股區新北產業園區五工路 134 號



20dB Bandwidth Test Plot CH-High



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sqs.com/terms</u> e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

y. No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號