

ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT

INTENTIONAL RADIATOR CERTIFICATION TO FCC PART 15 SUBPART C REQUIREMENT

	OF		
Product Name:	Keyboard		
Brand Name:	hTC		
Model No.:	UG0B		
Model Difference:	N/A		
FCC ID:	O62-UG0B		
Report No.:	E2/2014/70017		
Issue Date:	Aug. 14, 2014		
FCC Rule Part:	§15.247, Cat: DTS		
	Darfon Electronics Corp.		
Prepared for:	167, Shanying Road, Gueishan, Taoyuan 33341, Taiwan, R.O.C.		
	SGS Taiwan Ltd.		
Prepared by:	Electronics & Communication Laboratory		
	No.2, Keji 1st Rd., Guishan Township, Taoyuan County, Taiwan 333		
	<i>Note:</i> This report shall not be reproduced except in full, without the written approval of SGS Taiwan Ltd. This document may be altered or revised by SGS Taiwan Ltd. per-		
Testing Lebo rato ry 0513	sonnel only, and shall be noted in the revision section of the document.		



VERIFICATION OF COMPLIANCE

Applicant:	Darfon Electronics Corp. 167, Shanying Road, Gueishan, Taoyuan 33341, Taiwan, R.O.C.
Product Name:	Keyboard
Brand Name:	hTC
Model No.:	UG0B
Model Difference:	N/A
FCC ID:	O62-UG0B
File Number:	E2/2014/70017
Date of test:	Jul. 25, 2014 ~ Aug. 08, 2014
Date of EUT Received:	Jul. 25, 2014

We hereby certify that:

The above equipment was tested by SGS Taiwan Ltd. Electronics & Communication Laboratory The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4:2009 the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.247.

The test results of this report relate only to the tested sample identified in this report.

Test By:	Jazz Hi	rang o	ate	Aug. 14, 2014
Prepared By:	Jazz Huang / Sr. E Tiffany)ate	Aug. 14, 2014
Approved By:	Tiffany Kao / C Jim Chang / Sup	hang D	Date	Aug. 14, 2014

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Version

Version No.	Date	Description
00	Aug. 14, 2014	Initial creation of document

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for elec-tronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms_e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to Electronic Documents are used except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or ap-pearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. No.134,WuKungRoad,NewTaipeildustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號



Report No.: E2/2014/70017 **Issue Date: Aug. 14, 2014** Page: 4 of 47

Table of Contents

1	GEN	NERAL INFORMATION	6
	1.1	Product Description	
	1.2	Related Submittal(s) / Grant (s)	7
	1.3	Test Methodology	7
	1.4	Test Facility	7
	1.5	Special Accessories	7
	1.6	Equipment Modifications	7
2	SYS'	TEM TEST CONFIGURATION	
	2.1	EUT Configuration	
	2.2	EUT Exercise	
	2.3	Test Procedure	
	2.4	Configuration of Tested System	9
3	SUM	AMARY OF TEST RESULTS	
4	DES	SCRIPTION OF TEST MODES	
5	MEA	ASUREMENT UNCERTAINTY	
6	CON	NDUCTED EMISSION TEST	
	6.1	Standard Applicable:	
	6.2	Measurement Equipment Used:	
	6.3	EUT Setup:	
	6.4	Test SET-UP (Block Diagram of Configuration)	
	6.5	Measurement Procedure:	
	6.6	Measurement Result:	
7	PEA	AK OUTPUT POWER MEASUREMENT	
	7.1	Standard Applicable:	
	7.2	Measurement Equipment Used:	
	7.3	Test Set-up:	
	7.4	Measurement Procedure:	
	7.5	Measurement Result:	
8	6dB	BANDWIDTH	
	8.1	Standard Applicable:	
	8.2	Measurement Equipment Used:	
	8.3	Test Set-up:	
	8.4	Measurement Procedure:	
	8.5	Measurement Result:	



9	BAN	D EDGES MEASUREMENT	
	9.1	Standard Applicable:	
	9.2	Measurement Equipment Used:	
	9.3	Test SET-UP:	
	9.4	Measurement Procedure:	
	9.5	Field Strength Calculation:	
	9.6	Measurement Result:	
10	SPUE	RIOUS RADIATED EMISSION TEST	
	10.1	Standard Applicable	
	10.2	Measurement Equipment Used:	
	10.3	Test SET-UP:	
	10.4	Measurement Procedure:	
	10.5	Field Strength Calculation	
	10.6	Measurement Result:	
11	PEAI	K POWER SPECTRAL DENSITY	
	11.1	Standard Applicable:	
	11.2	Measurement Equipment Used:	43
	11.3	Test Set-up:	43
	11.4	Measurement Procedure: (following the measurement procedure 10.2 of KDB558074):	43
	11.5	Measurement Result:	
12	ANT	ENNA REQUIREMENT	
	12.1	Standard Applicable:	
	12.2	Antenna Connected Construction:	



GENERAL INFORMATION 1

Product Description 1.1

General:

Product Name:	Keyboard			
Brand Name:	hTC			
Model No.:	UG0B	UG0B		
Model difference:	N/A			
Hardware Version:	N/A			
Software Version:	N/A			
3.7Vdc form Rechargeable Li-ion Battery or 5Vdc from Micro USB		Rechargeable Li-ion Battery or 5Vdc from Micro USB port		
Power Supply:	Battery	Model No.: AEC214298, Supplier: AEC		


Bluetooth V4.0:

Frequency Range:	2402 – 2480MHz
Bluetooth Version:	V4.0 single mode
Channel number:	40 channels
Modulation type:	GFSK
Transmit Power:	6.82dBm (Peak)
Antenna Designation:	Internal Antenna, Gain:0.29dBi

This test report applies for Bluetooth V4.0 function.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms_and_conditions.htm</u> and, for elec-tronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms_e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.





1.2 **Related Submittal(s) / Grant (s)**

This submittal(s) (test report) is intended for FCC ID: O62-UG0B filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules. The composite system (digital device) is compliance with Subpart B is authorized under a DoC procedure.

Test Methodology 1.3

Both conducted and radiated testing was performed according to the procedures in ANSI C63.4:2009. Radiated testing was performed at an antenna to EUT distance 3 meters.

Tested in accordance with Jun 2014 KDB558074 V03r02 for compliance to FCC 47CFR 15.247 requirements.

Test Facility 1.4

The measurement facilities used to collect the 3m Radiated Emission and AC power line conducted data are located on the address of SGS Taiwan Ltd. Electronics & Communication Laboratory No.2, Keji 1st Rd., Guishan Township, Taoyuan County, Taiwan which are constructed and calibrated to meet the FCC requirements in documents ANSI C63.4: 2009. FCC Registration Number: 628985. The address of SGS Taiwan Ltd. Electronics & Communication Laboratory 1F, No.134, Wukung Road New Taipei City TAIWAN 24803, Canada Registration Number: 4620A-5.

The 10 m Open Area Test Sites located on the address of SGS Taiwan Ltd. Electronics & Communication Laboratory No.2, Keji 1st Rd., Guishan Township, Taoyuan County, Taiwan which is constructed and calibrated to meet the CISPR 22/EN 55022 requirements. FCC Registration Number: 455997. The address of SGS Taiwan Ltd. Electronics & Communication Laboratory 1F, No.134, Wukung Road New Taipei City TAIWAN 24803, IC Registration Number: 4620A-6.

1.5 **Special Accessories**

There are no special accessories used while test was conducted.

Equipment Modifications 1.6

There was no modification incorporated into the EUT.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only



2 SYSTEM TEST CONFIGURATION

2.1 **EUT Configuration**

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 **EUT Exercise**

An engineering test mode (software/firmware) that applicant provided was utilized to manipulate the EUT into transmit, selection of the test channel, and modulation scheme.

2.3 **Test Procedure**

2.3.1 Conducted Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. According to the general criterion in Section 7.1 of ANSI C63.4:2009. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz, and the measurement procedure 7.3 in ANSI 63.4:2009 & 6.2.2 is followed to carry out the test. The CISPR Quasi-Peak and Average detector mode is employed according to §15.107

2.3.2 Radiated Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max, emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes and measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made "while keeping the antenna in the 'cone of radiation' from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response." is still within the 3dB illumination BW of the measurement antenna. according to the requirements in Section 8 and 13 and of ANSI C63.4:2009, & Section 6.3, 6.4, 6.5.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only

Chino Solution and Solution a tronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is frawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law



2.4 **Configuration of Tested System**

Fig. 2-1 Radiated Emission & Conducted (Antenna Port) Conducted Emission




Fig. 2-2 AC Power Line Configuration




Table 2-2 Equipment Used in Tested System

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Data Cable	Power Cord
1.	Notebook	Lenovo	L440	TP00057	Shield	Un-Shield
2.	Test Software	Uenergy Test	N/A	N/A	N/A	N/A
3.	CASIRA	CSR	DEV-PC-1309	1309	N/A	N/A
3.	DC Power Supply	Agilent	E3640A	MY53140006	N/A	N/A

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



FCC Rules	Description Of Test	Result
§15.207(a)	AC Power Line Conducted Emission	Compliant
§15.247(b) (3)	Peak Output Power	Compliant
§15.247(a)(2)	6dB Bandwidth	Compliant
§15.247(d)	100 KHz Bandwidth Of Frequency Band Edges	Compliant
§15.247(d)	Spurious Emission	Compliant
§15.247(e)	Peak Power Density	Compliant
§15.203	Antenna Requirement	Compliant

3 SUMMARY OF TEST RESULTS

DESCRIPTION OF TEST MODES 4

The EUT has been tested under operating condition.

Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Channel low (2402MHz), mid (2442MHz) and high (2480MHz) with BT 4.0 mode is chosen for full testing.

The field strength of radiation emission was measured as EUT stand-up position (H mode) and lie down position (E1, E2 mode) for BT 4.0 mode Transmitter for channel Low, Mid and High, the worst case E2 position was reported.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



MEASUREMENT UNCERTAINTY 5

Test Items	Uncertainty
AC Power Line Conducted Emission	+/- 2.586 dB
Peak Output Power	+/- 1.42 dB
6dB Bandwidth	+/- 123.36 Hz
100 KHz Bandwidth Of Frequency Band Edges	+/- 1.55 dB
Peak Power Density	+/- 1.55 dB
99% Power Bandwidth	+/- 123.36 Hz
Temperature	+/- 0.8 °C
Humidity	+/- 4.7 %
DC / AC Power Source	DC= +/- 1%, AC=+/- 0.2%

Radiated Spurious Emission:

Measurement uncertainty (Polarization : Vertical)	30MHz - 180MHz: +/- 3.37dB
	180MHz -417MHz: +/- 3.19dB
	0.417GHz-1GHz: +/- 3.19dB
	1GHz - 18GHz: +/- 4.04dB
	18GHz - 40GHz: +/- 4.04dB

	30MHz - 167MHz: +/- 4.22dB
Measurement uncertainty	167MHz -500MHz: +/- 3.44dB
(Polarization : Horizontal)	0.5GHz-1GHz: +/- 3.39dB
	1GHz - 18GHz: +/- 4.08dB
	18GHz - 40GHz: +/- 4.08dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



CONDUCTED EMISSION TEST 6

6.1 **Standard Applicable:**

According to §15.207, frequency range within 150KHz to 30MHz shall not exceed the Limit table as below.

Frequency range	Limits dB(uV)					
MHz	Quasi-peak	Average				
0.15 to 0.50	66 to 56	56 to 46				
0.50 to 5	56	46				
5 to 30	60	50				
Note						
1. The lower limit shall apply at the transition frequencies						
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.						

6.2 **Measurement Equipment Used:**

SGS Conducted Emission Test Site No.A									
Nome of Fauinment	Manufacturer	Model	Serial Number	Calibration	Calibration				
Name of Equipment	Manufacturer	Model	Serial Number	Date	Due				
EMI Test Receiver	R&S	ESCI 3	101311	2014/06/20	2015/06/19				
Coaxial Cables	N/A	N30N30-1042-150c m	N/A	2014/02/07	2015/02/06				
LISN	Schwarzbeck	NSLK 8127	8127-648	2014/06/10	2015/06/09				
LISN	Rolf-Heine	NNB-2/16Z	99012	2014/03/26	2015/03/25				


Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



6.3 EUT Setup:

- 1. The conducted emission tests were performed in the test site, using the setup in accordance with the ANSI C63.4:2009.
- 2. The AC/DC Power adaptor of EUT was plug-in LISN. The EUT was placed flushed with the rear of the table.
- 3. The LISN was connected with 120Vac/60Hz power source.

6.4 Test SET-UP (Block Diagram of Configuration)



6.5 Measurement Procedure:

- 1. The EUT was placed on a table which is 0.8m above ground plane.
- 2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 3. Repeat above procedures until all phases of power being supplied by given UE are completed

6.6 Measurement Result:

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.


Note: Refer to next page for measurement data and plots. Note2: The * reveals the worst-case results that closet to the limit.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms</u> and conditions for Electronic Documents at <u>www.sgs.com/terms</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents is unlawful and offenders may be prosecuted to the fullest extent of the law.



AC POWER LINE CONDUCTED EMISSION TEST DATA

Operation Mode:	Operation Mode			Test Date:	Aug. 08, 2014
Temperature:	24	Humidity:	67 %	Test By:	Jazz
		·		Probe:	L1/N




No.+	Mk.+	Freq.₽	Reading₽	Factor+?	Measurement	Limite	Over* ³	Detector ₽	Comment
÷	÷	(MHz)¢	dBuV+2	(dB)₊∂	(dBuV)+2	(dBuV)+	(dB)¢∂	¢	¢
1₽	*¢	0.1540+2	48.18+	0.09+3	48.27+2	65.78₽	-17.51+2	QP₊⊃	¢
2₽	ę	0.1900₽	44.92₽	0.08≁	45.00+2	64.04+2	-19.04+2	QP₄⊅	¢
-3₽	¢,	0.2100	40.56+2	0.08≁	40.64+2	63.21+2	-22.57+2	QP₊⊃	¢
4₽	÷	0.2460+2	39.48+2	0.10+2	39.58+2	61.89₽	-22.31+2	QP₄⊃	¢
-5₽	ę	0.3020¢	34.35+2	0.12+2	34.47*	60.19₽	-25.72+2	QP₄⊅	¢
<mark>6</mark> ₽	¢,	0.3260+2	32.77+2	0.13+2	32.90+2	59.55÷	-26.65+2	QP₊⊃	¢

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有说明,此根告结果僅對測試之樣品負責,同時此樣品僅保留的天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for elec-tronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms_e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or ap-reparatore of this document is unaveruent is unaveruent to any be prosecuted to the fulle at vertex of the law. pearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134號





No.+	Mk.+	Freq.*	Reading+	Factor+ ²	Measurement	Limite	Over* ³	Detector+2	Comment+ ²
	÷	(MHz)¢ ²	dBuX+2	(dB)+∂	(dBuV)+	(dBuV)+2	(dB)¢∂	¢	¢
1₽	ب *	0.1500+2	51.54+2	0.09₽	51.63+2	66.00₽	-14.37+2	Q₽₊⊃	¢
2₽	÷	0.1740₽	47.03₽	0.09₽	47.12*	64.77₽	-17.65+2	QP₄⊅	4
3₽	¢.	0.1980+2	43.51+2	0.09₽	43.60+2	63.69+2	-20.09+2	Q₽₽	¢
4≉2	÷	0.2340₽	41.35+2	0.10₽	41.45+2	62.31+2	-20.86+2	QP₄⊅	¢
5₽	÷.	0.2580₽	37.93₽	0.12+2	38.05+2	61.50+2	-23.45+2	QP₄⊃	¢
6₽	÷	0.2780₽	37.44*	0.12₽	37.56+2	60.88+2	-23.32+2	QP₄⊃	¢

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



7 PEAK OUTPUT POWER MEASUREMENT

7.1 Standard Applicable:

According to §15.247 (b)

(3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



7.2 **Measurement Equipment Used:**

	SGS Conducted Room(ALL)								
Name of Equipment	Manufacturer	Model	Serial Number	Calibration	Calibration				
Succession Augleman	Acilout		MX52400256	Date	Due				
Spectrum Analyzer	Agilent	N9010A	MY53400256	2013/10/26	2014/10/25				
Power Meter	Anritsu	ML2496A	1326001	2014/06/20	2015/06/19				
Power Sensor	Anritsu	MA2411B	1315048	2014/06/20	2015/06/19				
Power Sensor	Anritsu	MA2411B	1315049	2014/06/20	2015/06/19				
Coaxial Cable 30cm	WOKEN	00100A1F1A195C	2	2014/01/06	2015/01/05				
Coaxial Cable 30cm	WOKEN	00100A1F1A195C	3	2014/01/06	2015/01/05				
Coaxial Cable 80cm	WOKEN	00100A1F1A185C	1	2014/01/06	2015/01/05				
DC Block	Mini-Circuits	BLK-18-S+	4	2014/01/06	2015/01/05				
DC Block	PASTERNACK	PE8210	5	2014/01/06	2015/01/05				
Splitter	RF-LAMBAD	RFLT2W1G18G	11-JSPF412-019	2014/01/06	2015/01/05				
Splitter	WOKEN	NA	DOM35LW1A2	2014/01/06	2015/01/05				
Attenuator	Mini-Circuits	BW-S10W2+	6	2014/01/06	2015/01/05				
Attenuator	WOKEN	218FS-10	7	2014/01/06	2015/01/05				
Temperature Chamber	TERCHY	MHK-120LK	1020582	2014/06/18	2015/06/17				
Communication Tester	R&S	CMW500	131121	2014/01/16	2015/01/15				
Communication Tester	Anritsu	MT8820C	6201107337	2014/04/24	2015/04/23				
DC Power Supply	Agilent	E3640A	MY53140006	2014/05/31	2015/05/30				
DC Power Supply	Agilent	E3640A	MY53130054	2014/05/21	2015/05/20				

7.3 **Test Set-up:**



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測试之樣品負責,同時此樣品僅保留別天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for elec-tronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Inis document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or ap-pearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. SCET taken I to I and Wink unaPrad NewTainel/astr MukruPistrict NewTainel/City Taiwan2/4803/% th TAT SM 54, # TAT SM 54



7.4 Measurement Procedure:

1. Place the EUT on the table and set it in transmitting mode.

2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power meter or spectrum. (**Peak power setting on Spectrum:** Channel power function, RBW = 1MHz, VBW = 3MHz, Span: 30/60MHz, Detector =peak, Sweep = Auto. Setting on spectrum is adjusted based on the mandatory procedure in 9.1.2 of the KDB558074). Power Meter is used as the auxiliary test equipment to conduct the output power measurement. 9.1.3 in KDB558074 is followed.

(Avg. power setting on Spectrum: Channel power function, RBW = 1MHz, VBW = 3MHz, Span: 30/60MHz, Detector =Avg., Trace avg =100, Sweep = Auto, Setting on spectrum is adjusted based on the mandatory procedure in 9.2.2.4 of the KDB558074). Power Meter is used as the auxiliary test equipment to conduct the output power measurement. 9.2.3, option 3 in KDB558074 is followed.

3. Record the max. Reading as observed from Spectrum or Power Meter.

4. Repeat above procedures until all test default channel measured was complete.

Agilent Spectrum Analyzer - Swept SA				
RL RF 50 Ω DC	PNO: Fast +++ Trig: Free Run	Avg Type: Log-Pwr	08:02:17 PM Jul 08, 2014 TRACE 2 3 4 5 6 TYPE W	Frequency
Ref Offset 0.6 dB	IFGain:Low #Atten: 30 dB		ΔMkr3 624.0 μs -0.15 dB	Auto Tun
	1∆2	3∆4		Center Fre 2.442000000 GF
0.0 0.0				Start Fre 2.442000000 Gi
0.0	tradijed je verser bila in die	itereti		Stop Fr 2.442000000 G
enter 2.442000000 GHz es BW 8 MHz	#VBW 8.0 MHz	Sweep 1	Span 0 Hz .000 ms (1001 pts)	CF Sto 8.000000 M Auto M
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	303.0 μs (Δ) 1.14 dB 22.00 μs 4.40 dBm 624.0 μs (Δ) -0.15 dB 22.00 μs 4.40 dBm			Freq Offs 0
6 7 8 9 0				
		STATUS	,	

Duty Factor:

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms_and_conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms_e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號



7.5 **Measurement Result:**

BT4.0 mode:

CH Frequency			
		Peak Power Output(dBm)	Required Limit
	(MHz)		
0	2402	6.64	1 Watt = 30 dBm
20	2442	6.82	1 Watt = 30 dBm
39	2480	6.82	1 Watt = 30 dBm

		A mono do Domon		
СН	Frequency	Average Power Output(dBm)	Required Limit	
	(MHz)	• ` '		
0	2402	4.18	1 Watt = 30 dBm	
20	2442	4.49	1 Watt = 30 dBm	
39	2480	4.52	1 Watt = 30 dBm	

*Note: Measured by power meter, cable loss as 0.6dB that offsets on the power meter in Peak *Note: Measured by power meter, as cable loss+ Duty cycle factor that offsets on the power meter

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



8 **6dB BANDWIDTH**


8.1 **Standard Applicable:**

According to §15.247(a)(2), Systems using digital modulation techniques may operate in the 902 - 928 MHz,2400 - 2483.5 MHz bands. The minimum 6 dB bandwidth shall be at least 500kHz.

8.2 **Measurement Equipment Used:**

Refer to section 7.2 for details.

8.3 **Test Set-up:**



Measurement Procedure: 8.4

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set the spectrum analyzer as RBW = 100 kHz, VBW = 3*RBW, Span = 5MHz, Detector=Peak, Sweep=auto, the setting on spectrum is adjusted based on the procedure as guide in 8.1 option 1 of KDB558074.
- 4. Mark the peak frequency and -6dB (upper and lower) frequency.
- 5. Repeat above procedures until all test default channel measured were complete.

Chino Solution and Solution a tronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



8.5 **Measurement Result:**

BT4.0 mode

Frequency (MHz)	Bandwidth (kHz)	Bandwidth (kHz)	Result
2402	682.3	> 500	PASS
2442	689.7	> 500	PASS
2480	686.5	> 500	PASS


* Cable loss as 0.6dB that offsets on the spectrum.

Note: Refer to next page for plots.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



BT4.0 mode 6dB Band Width Test Data CH-Low



6dB Band Width Test Data CH-Mid




Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



6dB Band Width Test Data CH-High



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



9 BAND EDGES MEASUREMENT

9.1 Standard Applicable:

According to §15.247(c), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in15.209(a).

9.2 Measurement Equipment Used:

9.2.1 Conducted Emission at antenna port:

Refer to section 7.2 for details.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



9.2.2 Radiated emission:


	SGS SAC Chamber No.C (FCC/IC/NCC)							
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due			
EMI Test Receiver	R&S	ESU 40	100363	2014/04/12	2015/04/11			
Loop Antenna	ETS-Lindgren	6502	00143303	2014/01/16	2015/01/15			
Broadband Antenna	TESEQ	CBL 6112D	35240	2014/01/17	2015/01/16			
Horn Antenna	ETS-Lindgren	3117	00143272	2014/01/27	2015/01/26			
Horn Antenna	Schwarzbeck	BBHA9170	BBHA9170-184	2014/01/23	2015/01/22			
Horn Antenna	ETS-Lindgren	3160-09	00117911	2014/01/22	2015/01/21			
Horn Antenna	ETS-Lindgren	3160-10	00117783	2014/01/22	2015/01/21			
Pre Amplifier	R&S	SCU-18	10204	2014/03/26	2015/03/25			
Pre Amplifier	R&S	SCU-26	100780	2014/03/26	2015/03/25			
Pre Amplifier	R&S	SCU-40	100356	2014/03/26	2015/03/25			
Pre Amplifier	EMC Instruments	EMC330	980096	2014/03/26	2015/03/25			
Pre Amplifier	EMC Instruments	EMC184045	980135	2014/01/24	2015/01/23			
Coaxial Cable	Huber+Suhner	RG 214/U	W21.03	2014/03/26	2015/03/25			
Coaxial Cable	Huber+Suhner	RG 214/U	W22.03	2014/03/26	2015/03/25			
Coaxial Cable	Huber+Suhner	SUCCOFLEX 104	MY17413/4	2014/03/26	2015/03/25			
Coaxial Cable	Huber+Suhner	SUCCOFLEX 104	MY17404/4	2014/03/26	2015/03/25			
Coaxial Cable	Huber+Suhner	SUCCOFLEX 104	MY17394/4	2014/03/26	2015/03/25			
Coaxial Cable	Huber+Suhner	SUCCOFLEX 104	MY17386/4	2014/03/26	2015/03/25			
Coaxial Cable	Huber+Suhner	SUCCOFLEX 104	MY17388/4	2014/03/26	2015/03/25			
Attenuator	WOKEN	218FS-10	HY-151	2014/01/06	2015/01/05			
Communication Tester	R&S	CMW500	131121	2014/01/16	2015/01/15			
Communication Tester	Anritsu	MT8820C	6201107337	2014/04/23	2015/04/22			
Controller	MF	MF-7802	N/A	N.C.R.	N.C.R.			
Antenna Master	MF	N/A	N/A	N.C.R.	N.C.R.			
Turn Table	MF	N/A	N/A	N.C.R.	N.C.R.			
Site NSA	SGS	966 Chamber C	SAC-C	2014/03/05	2015/03/04			
Site VSWR	SGS	966 Chamber C	SAC-C	2014/04/10	2015/04/09			
Test Software	World-Pallas	Dr. E	V 3.0 Lite	N.C.R.	N.C.R.			

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for elec-tronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms_e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to Electronic Documents are used except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or ap-pearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. No.134,WuKungRoad,NewTaipeildustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號




9.3 **Test SET-UP:**

9.3.1 **Conducted Emission at antenna port:**




9.3.2 Radiated emission:

(A) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(B) Radiated Emission Test Set-UP Frequency Over 1 GHz



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



9.4 Measurement Procedure:

Unwanted Emissions into Non-Restricted Frequency Bands, Measurement Procedure followed by 11.1 of KDB558074 D01

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set start to edge frequency, and stop frequency of spectrum analyzer so as to encompass the spectrum to be examined.
- 4. Set the spectrum analyzer as RBW, VBW=300KHz, Detector = Peak, Sweep = auto
- 5. Mark the highest reading of the emission as the reference level measurement.
- 6. Set DL as the limit = reading on marker 1 20dBm
- 7. Marker on frequency, 2.3999GHz and 2.4836GHz, and examine shall 100 KHz immediately outside the authorized (2400~2483.5) be attenuated by 20dB at least relative to the maximum emission of power.
- 8. Repeat above procedures until all default test channel (low, middle, and high) was complete.

Unwanted Emission falling into Restricted Frequency Bands, Measurement Procedure followed by 12.1 of KDB558074 D01:

- 1. The EUT was placed on a turn table which is 0.8m above ground plane.
- 2. The turn table shall rotate 360 degrees to determine the position of maximum emission level.
- 3.EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emissions.
- 4. When measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made "while keeping the antenna in the 'cone of radiation' from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response." is still within the 3dB illumination BW of the measurement antenna.
- 5. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 6. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 7.On spectrum, following 8.1.2, and RBW = 1MHz, VBW = 3MHz, & Marker 2390MHz, and 2483.5MHz (Peak Measurement). Average Measurement: following 8.2 with the modification span to 1MHz, &RBW = 1MHz, VBW = 3MHz and peak marker function to obtain the highest reading on 2390, and 2483.5MHz.

Repeat above procedures until all default test channel (low, middle, and high) was complete

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. SGS Taiwan Ltd. No.134,WuKungRoad,NewTaipeilndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號



9.5 **Field Strength Calculation:**

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CL - AG

Where	FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
	RA = Reading Amplitude	AG = Amplifier Gain
	AF = Antenna Factor	

9.6 **Measurement Result:**


Note: Refer to next page spectrum analyzer data chart and tabular data sheets.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.


Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



BT4.0 mode **Band Edges Test Data CH-Low**



Band Edges Test Data CH-High



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Report No.: E2/2014/70017 **Issue Date: Aug. 14, 2014** Page: 30 of 47

Radiated Emission: BT4.0 mode:

T4.0 Test D	ate	:2014-08-08
402 MHz Temp.	/Humi.	:26.7deg_C / 52 RH
ANDEDGE LOW Engine	eer	:Vito
2 Plane Measu	rement Antenna Pol.	:VERTICAL
4 (D2 MHzTemp.NDEDGE LOWEngine	D2 MHzTemp./Humi.NDEDGE LOWEngineer

Actual FS($dB\mu V/m$) = SPA. Reading level($dB\mu V$) + Factor(dB)

Factor(dB) = Antenna Factor($dB\mu V/m$) + Cable Loss(dB) – Pre Amplifier Gain(dB)

Note : "F" : denotes Fundamental Frequency. ; "H" : denotes Harmonic Frequency.

"E": denotes Band Edge Frequency.; "S": denotes Spurious Frequency.

"---" : denotes Noise Floor.

The trace on RE(radiation emission) plot is as colored blue, and the detection manner we've employed is peak detector.

Freq.	Detector	Note	Spectrum	Factor	Actual	Limit	Margin
	Mode		Reading Level		FS	@3m	
MHz	PK/QP/AV	F/H/E/S	dBµV	dB	dBµV/m	dBµV/m	dB
2390.00	Peak	Е	44.05	3.14	47.19	74.00	-26.81
2390.00	Average	Е	32.60	3.14	35.74	54.00	-18.26

Operation Band	:BT4.0	Test Date	:2014-08-08
Fundamental Frequency	:2402 MHz	Temp./Humi.	:26.7deg_C / 52 RH
Operation Mode	:BANDEDGE LOW	Engineer	:Vito
EUT Pol.	:E2 Plane	Measurement Antenna Pol.	:HORIZONTAL

Actual FS($dB\mu V/m$) = SPA. Reading level($dB\mu V$) + Factor(dB)

Factor(dB) = Antenna Factor($dB\mu V/m$) + Cable Loss(dB) – Pre Amplifier Gain(dB)

"F" : denotes Fundamental Frequency. ; "H" : denotes Harmonic Frequency. Note :

"E": denotes Band Edge Frequency.; "S": denotes Spurious Frequency.

"---" : denotes Noise Floor.

The trace on RE(radiation emission) plot is as colored blue, and the detection manner we've employed is peak detector.

Freq.	Detector	Note	Spectrum	Factor	Actual	Limit	Margin
	Mode		Reading Level		FS	@3m	
MHz	PK/QP/AV	F/H/E/S	dBµV	dB	dBµV/m	dBµV/m	dB
2390.00	Peak	Е	43.47	3.14	46.61	74.00	-27.39
2390.00	Average	Е	32.59	3.14	35.73	54.00	-18.27

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Gines Galaxien in Little Searce and a condition of the Content of Content tronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is frawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law



Report No.: E2/2014/70017 **Issue Date: Aug. 14, 2014** Page: 31 of 47

Operation Band	:BT4.0	Test Date	:2014-08-08
Fundamental Frequency	:2480 MHz	Temp./Humi.	:26.7deg_C / 52 RH
Operation Mode	:BANDEDGE HIGH	Engineer	:Vito
EUT Pol.	:E2 Plane	Measurement Antenna Pol.	:VERTICAL

Actual FS($dB\mu V/m$) = SPA. Reading level($dB\mu V$) + Factor(dB)

Factor(dB) = Antenna Factor($dB\mu V/m$) + Cable Loss(dB) – Pre Amplifier Gain(dB)

"F" : denotes Fundamental Frequency. ; "H" : denotes Harmonic Frequency. Note :

"E": denotes Band Edge Frequency.; "S": denotes Spurious Frequency.

"---" : denotes Noise Floor.

The trace on RE(radiation emission) plot is as colored blue, and the detection manner we've employed is peak detector.

Freq.	Detector	Note	Spectrum	Factor	Actual	Limit	Margin
	Mode		Reading Level		FS	@3m	
MHz	PK/QP/AV	F/H/E/S	dBµV	dB	dBµV/m	dBµV/m	dB
2483.50	Peak	Е	44.90	3.35	48.26	74.00	-25.74
2483.50	Average	Е	33.53	3.35	36.88	54.00	-17.12

Operation Band	:BT4.0	Test Date	:2014-08-08
Fundamental Frequency	:2480 MHz	Temp./Humi.	:26.7deg_C / 52 RH
Operation Mode	:BANDEDGE HIGH	Engineer	:Vito
EUT Pol.	:E2 Plane	Measurement Antenna Pol.	:HORIZONTAL

Actual FS($dB\mu V/m$) = SPA. Reading level($dB\mu V$) + Factor(dB)

Factor(dB) = Antenna Factor($dB\mu V/m$) + Cable Loss(dB) – Pre Amplifier Gain(dB)

"F" : denotes Fundamental Frequency. ; "H" : denotes Harmonic Frequency. Note :

"E": denotes Band Edge Frequency.; "S": denotes Spurious Frequency.

"---" : denotes Noise Floor.

The trace on RE(radiation emission) plot is as colored blue, and the detection manner we've employed is peak detector.

Freq.	Detector	Note	Spectrum	Factor	Actual	Limit	Margin
	Mode		Reading Level		FS	@3m	
MHz	PK/QP/AV	F/H/E/S	dBµV	dB	dBµV/m	dBµV/m	dB
2483.50	Peak	Е	44.74	3.35	48.10	74.00	-25.90
2483.50	Average	Е	33.72	3.35	37.07	54.00	-16.93

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



10 SPURIOUS RADIATED EMISSION TEST

10.1 Standard Applicable

According to §15.247(d),

Emission at antenna port:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

Radiated Spurious Emission

Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

And according to §15.33(a) (1), for an intentional radiator operates below 10GHz, the frequency range of measurements: to the tenth harmonic of the highest fundamental frequency or to 40GHz, whichever is lower.

10.2 Measurement Equipment Used:

10.2.1 Conducted Emission at antenna port:

Refer to section 7.2 for details.

10.2.2 Radiated emission:

Refer to section 9.2.2 for details.

10.3 Test SET-UP:

10.3.1 Conducted Emission at antenna port:

Refer to section 8.3 for details.

10.3.2 Radiated emission:

Refer to section 9.3.2 for details.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



10.4 Measurement Procedure:

Radiated Emission:

- 1. The EUT was placed on a turn table which is 0.8m above ground plane.
- 2. The turn table shall rotate 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emissions.
- 4. When measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made "while keeping the antenna in the 'cone of radiation' from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response." is still within the 3dB illumination BW of the measurement antenna.
- 5. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 6. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. On spectrum, change spectrum mode in linear display mode, and reduce VBW = 10Hz if average reading is measured.
- 7. Repeat above procedures until all default test channel measured were complete.

Conducted Emission:

- 1. To connect Antenna Port of EUT to Spectrum.
- 2. Set RBW = 100K & VBW = 300K on Spectrum.
- Sweep the frequency to determine spurious emission as seen on spectrum from span of 30 to 3G, 3G to 8G, 8G to 13G, 13G to 18G and 18G to 26.5GHz, 18G to 40GHz (applicable if operation mode is 5GHz)
- 4. Via Software, combine 5 spans of frequency range into one plot
- 5. Repeat above procedures until all default test channel measured were complete.

10.5 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CL - AG

Where	FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
	RA = Reading Amplitude	AG = Amplifier Gain
	AF = Antenna Factor	

10.6 Measurement Result:

Note: Refer to next page spectrum analyzer data chart and tabular data sheets.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only


除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is advised to the fullest extent of the law. SGS Taiwan Ltd. No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市 五股區 新北產業園區五工路 134 號

Conducted Spurious Emission Measurement Result (BT4.0 mode) Ch Low 30MHz - 3GHz

Agilent Spectr	um Analyzer - Swept S	SA						- 0 -
RL	RF 50 Ω				ALIGN AUTO Type: Log-Pwr Hold:>100/100	TRAC	MAug 04, 2014	Frequency
10 dB/div	Ref Offset 0.6 o Ref 20.00 dE		Matten: 30			or r1 2.403	PINNNN	Auto Tune
10.0 0.00 -10.0								Center Free 1.515000000 GH
-20.0 -30.0 -40.0						d		Start Fre 30.000000 MH
-50.0 -60.0 -70.0						1 [1] (k. de la		Stop Fre 3.000000000 GH
Start 30 M #Res BW 1	SCL	# 2.403 0 GHz	VBW 300 kHz	FUNCTION	Sweep 9			CF Stej 297.000000 MH <u>Auto</u> Ma
2 3 4 5 6 7 8 9		2.905 0 GH2	0.700 08				,	Freq Offse 0 H
10 11			a.		STATU		-	


Ch Low 3GHz - 26.5GHz




Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Ch Mid 30MHz - 3GHz




Ch Mid 3GHz - 26.5GHz




Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Ch High 30MHz - 3GHz



Ch High 3GHz - 26.5GHz



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Report No.: E2/2014/70017 **Issue Date: Aug. 14, 2014** Page: 37 of 47

Radiated Spurious Emission Measurement Result (BT4.0 mode)

Operation Band	:BT4.0	Test Date	:2014-08-08
Fundamental Frequency	:2402 MHz	Temp./Humi.	:26.7deg_C / 52 RH
Operation Mode	:TX LOW	Engineer	:Vito
EUT Pol.	:E2 Plane	Measurement Antenna Pol.	:VERTICAL

Actual FS($dB\mu V/m$) = SPA. Reading level($dB\mu V$) + Factor(dB)

Factor(dB) = Antenna Factor($dB\mu V/m$) + Cable Loss(dB) – Pre Amplifier Gain(dB)

"F" : denotes Fundamental Frequency. ; "H" : denotes Harmonic Frequency. Note :

"E" : denotes Band Edge Frequency. ; "S" : denotes Spurious Frequency.

"---" : denotes Noise Floor.

16814.00

19216.00

21618.00

24020.00

Peak

Peak

Peak

Peak

Freq.	Detector	Note	Spectrum	Factor	Actual	Limit	Margin
	Mode		Reading Level		FS	@3m	
MHz	PK/QP/AV	F/H/E/S	dBµV	dB	dBµV/m	dBµV/m	dB
31.94	Peak	S	51.43	-16.84	34.60	40.00	-5.40
90.14	Peak	S	63.12	-24.71	38.40	43.50	-5.10
295.78	Peak	S	57.78	-19.22	38.56	46.00	-7.44
404.42	Peak	S	54.42	-15.50	38.92	46.00	-7.08
462.62	Peak	S	54.04	-14.75	39.29	46.00	-6.71
772.05	Peak	S	48.32	-10.34	37.98	46.00	-8.02
4804.00	Peak	Н	42.85	0.37	43.22	74.00	-30.78
4804.00	Average	Н	32.86	0.37	33.23	54.00	-20.77
7206.00	Peak	Н	45.43	4.69	50.12	74.00	-23.88
7206.00	Average	Н	34.87	4.69	39.56	54.00	-14.44
9608.00	Peak	Н					
12010.00	Peak	Н					
14412.00	Peak	Н					

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Η

Η

Η

Η



Report No.: E2/2014/70017 **Issue Date: Aug. 14, 2014** Page: 38 of 47

Operation Band	:BT4.0	Test Date	:2014-08-08
Fundamental Frequency	:2402 MHz	Temp./Humi.	:26.7deg_C / 52 RH
Operation Mode	:TX LOW	Engineer	:Vito
EUT Pol.	:E2 Plane	Measurement Antenna Pol.	:HORIZONTAL

Actual FS($dB\mu V/m$) = SPA. Reading level($dB\mu V$) + Factor(dB)

Factor(dB) = Antenna Factor($dB\mu V/m$) + Cable Loss(dB) – Pre Amplifier Gain(dB)

"F" : denotes Fundamental Frequency. ; "H" : denotes Harmonic Frequency. Note :

"E" : denotes Band Edge Frequency. ; "S" : denotes Spurious Frequency.

"---": denotes Noise Floor.

24020.00

Peak

Freq.	Detector	Note	Spectrum	Factor	Actual	Limit	Margin
	Mode		Reading Level		FS	@3m	
MHz	PK/QP/AV	F/H/E/S	dBµV	dB	dBµV/m	dBµV/m	dB
35.82	Peak	S	40.18	-19.03	21.15	40.00	-18.85
111.48	Peak	S	46.25	-22.03	24.22	43.50	-19.28
259.89	Peak	S	60.09	-19.27	40.82	46.00	-5.18
295.78	Peak	S	60.79	-19.22	41.57	46.00	-4.43
367.56	Peak	S	60.54	-16.85	43.69	46.00	-2.31
926.28	Peak	S	43.43	-9.20	34.23	46.00	-11.77
4804.00	Peak	Н	43.00	0.37	43.37	74.00	-30.63
4804.00	Average	Н	32.85	0.37	33.22	54.00	-20.78
7206.00	Peak	Н					
9608.00	Peak	Н					
12010.00	Peak	Н					
14412.00	Peak	Н					
16814.00	Peak	Н					
19216.00	Peak	Н					
21618.00	Peak	Н					

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Η



Report No.: E2/2014/70017 **Issue Date: Aug. 14, 2014** Page: 39 of 47

Operation Band	:BT4.0	Test Date	:2014-08-08
Fundamental Frequency	:2442 MHz	Temp./Humi.	:26.7deg_C / 52 RH
Operation Mode	:TX MID	Engineer	:Vito
EUT Pol.	:E2 Plane	Measurement Antenna Pol.	:VERTICAL

Actual FS($dB\mu V/m$) = SPA. Reading level($dB\mu V$) + Factor(dB)

Factor(dB) = Antenna Factor($dB\mu V/m$) + Cable Loss(dB) – Pre Amplifier Gain(dB)

"F" : denotes Fundamental Frequency. ; "H" : denotes Harmonic Frequency. Note :

"E" : denotes Band Edge Frequency. ; "S" : denotes Spurious Frequency.

"---" : denotes Noise Floor.

17094.00

19536.00

21978.00

24420.00

Peak

Peak

Peak

Peak

	: deficites i toise	1 1001.					
Freq.	Detector	Note	Spectrum	Factor	Actual	Limit	Margin
	Mode		Reading Level		FS	@3m	
MHz	PK/QP/AV	F/H/E/S	dBµV	dB	dBµV/m	dBµV/m	dB
35.82	Peak	S	52.66	-19.03	33.63	40.00	-6.37
159.98	Peak	S	52.05	-23.08	28.97	43.50	-14.53
295.78	Peak	S	57.63	-19.22	38.41	46.00	-7.59
404.42	Peak	S	55.33	-15.50	39.82	46.00	-6.18
772.05	Peak	S	46.77	-10.34	36.43	46.00	-9.57
926.28	Peak	S	45.06	-9.20	35.85	46.00	-10.15
4884.00	Peak	Н	42.41	0.41	42.82	74.00	-31.18
4884.00	Average	Н	33.53	0.41	33.94	54.00	-20.06
7326.00	Peak	Н	44.61	4.87	49.48	74.00	-24.52
7326.00	Average	Н	32.37	4.87	37.24	54.00	-16.76
9768.00	Peak	Н					
12210.00	Peak	Н					
14652.00	Peak	Н					

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Η

Η

Η

Η



Report No.: E2/2014/70017 **Issue Date: Aug. 14, 2014** Page: 40 of 47

Operation Band	:BT4.0	Test Date	:2014-08-08
Fundamental Frequency	:2442 MHz	Temp./Humi.	:26.7deg_C / 52 RH
Operation Mode	:TX MID	Engineer	:Vito
EUT Pol.	:E2 Plane	Measurement Antenna Pol.	:HORIZONTAL

Actual FS($dB\mu V/m$) = SPA. Reading level($dB\mu V$) + Factor(dB)

Factor(dB) = Antenna Factor($dB\mu V/m$) + Cable Loss(dB) – Pre Amplifier Gain(dB)

"F" : denotes Fundamental Frequency. ; "H" : denotes Harmonic Frequency. Note :

"E" : denotes Band Edge Frequency. ; "S" : denotes Spurious Frequency.

"---" : denotes Noise Floor.

19536.00

21978.00

24420.00

Peak

Peak

Peak

Freq.	Detector	Note	Spectrum	Factor	Actual	Limit	Margin
	Mode		Reading Level		FS	@3m	
MHz	PK/QP/AV	F/H/E/S	dBµV	dB	dBµV/m	dBµV/m	dB
63.95	Peak	S	51.01	-29.19	21.82	40.00	-18.18
111.48	Peak	S	46.36	-22.03	24.33	43.50	-19.17
259.89	Peak	S	61.18	-19.27	41.91	46.00	-4.09
303.54	Peak	S	60.14	-18.81	41.34	46.00	-4.66
344.28	Peak	S	60.29	-17.55	42.74	46.00	-3.26
419.94	Peak	S	56.99	-15.17	41.82	46.00	-4.18
926.28	Peak	S	43.84	-9.20	34.63	46.00	-11.37
4884.00	Peak	Н	42.65	0.41	43.07	74.00	-30.93
4884.00	Average	Н	32.81	0.41	33.22	54.00	-20.78
7326.00	Peak	Н					
9768.00	Peak	Н					
12210.00	Peak	Н					
14652.00	Peak	Н					
17094.00	Peak	Н					

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Η

Η

Η



Report No.: E2/2014/70017 **Issue Date: Aug. 14, 2014** Page: 41 of 47

Operation Band	:BT4.0	Test Date	:2014-08-08
Fundamental Frequency	:2480 MHz	Temp./Humi.	:26.7deg_C / 52 RH
Operation Mode	:TX HIGH	Engineer	:Vito
EUT Pol.	:E2 Plane	Measurement Antenna Pol.	:VERTICAL

Actual FS($dB\mu V/m$) = SPA. Reading level($dB\mu V$) + Factor(dB)

Factor(dB) = Antenna Factor($dB\mu V/m$) + Cable Loss(dB) – Pre Amplifier Gain(dB)

"F" : denotes Fundamental Frequency. ; "H" : denotes Harmonic Frequency. Note :

"E" : denotes Band Edge Frequency. ; "S" : denotes Spurious Frequency.

"---" : denotes Noise Floor.

Peak

Peak

Peak

Peak

17360.00 19840.00

22320.00

24800.00

Freq.	Detector	Note	Spectrum	Factor	Actual	Limit	Margin
	Mode		Reading Level		FS	@3m	
MHz	PK/QP/AV	F/H/E/S	dBµV	dB	dBµV∕m	dBµV/m	dB
31.94	Peak	S	48.09	-16.84	31.25	40.00	-8.75
159.98	Peak	S	49.39	-23.08	26.31	43.50	-17.19
259.89	Peak	S	55.90	-19.27	36.62	46.00	-9.38
295.78	Peak	S	54.18	-19.22	34.96	46.00	-11.04
367.56	Peak	S	50.26	-16.85	33.41	46.00	-12.59
427.70	Peak	S	49.45	-15.03	34.42	46.00	-11.58
4960.00	Peak	Н	45.43	0.62	46.05	74.00	-27.95
4960.00	Average	Н	35.79	0.62	36.41	54.00	-17.59
7440.00	Peak	Н	42.66	5.01	47.66	74.00	-26.34
7440.00	Average	Н	30.98	5.01	35.99	54.00	-18.01
9920.00	Peak	Н					
12400.00	Peak	Н					
14880.00	Peak	Н					

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Η

Η

Η

Η



Report No.: E2/2014/70017 **Issue Date: Aug. 14, 2014** Page: 42 of 47

Operation Band	:BT4.0	Test Date	:2014-08-08
Fundamental Frequency	:2480 MHz	Temp./Humi.	:26.7deg_C / 52 RH
Operation Mode	:TX HIGH	Engineer	:Vito
EUT Pol.	:E2 Plane	Measurement Antenna Pol.	:HORIZONTAL

Actual FS($dB\mu V/m$) = SPA. Reading level($dB\mu V$) + Factor(dB)

Factor(dB) = Antenna Factor($dB\mu V/m$) + Cable Loss(dB) – Pre Amplifier Gain(dB)

"F" : denotes Fundamental Frequency. ; "H" : denotes Harmonic Frequency. Note :

"E" : denotes Band Edge Frequency. ; "S" : denotes Spurious Frequency.

"---": denotes Noise Floor.

24800.00

Peak

Freq.	Detector	Note	Spectrum	Factor	Actual	Limit	Margin
	Mode		Reading Level		FS	@3m	
MHz	PK/QP/AV	F/H/E/S	dBµV	dB	dBµV/m	dBµV/m	dB
35.82	Peak	S	39.60	-19.03	20.57	40.00	-19.43
111.48	Peak	S	47.07	-22.03	25.04	43.50	-18.46
295.78	Peak	S	58.17	-19.22	38.95	46.00	-7.05
355.92	Peak	S	59.85	-17.04	42.81	46.00	-3.19
387.93	Peak	S	58.94	-16.32	42.63	46.00	-3.37
772.05	Peak	S	40.24	-10.34	29.90	46.00	-16.10
4960.00	Peak	Н	45.70	0.62	46.31	74.00	-27.69
4960.00	Average	Н	36.24	0.62	36.86	54.00	-17.14
7440.00	Peak	Н					
9920.00	Peak	Н					
12400.00	Peak	Н					
14880.00	Peak	Н					
17360.00	Peak	Н					
19840.00	Peak	Н					
22320.00	Peak	Н					

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Η



11 PEAK POWER SPECTRAL DENSITY

11.1 Standard Applicable:

According to §15.247(e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

11.2 Measurement Equipment Used:

Refer to section 7.2 for details.

11.3 Test Set-up:

Refer to section 8.3 for details.

11.4 Measurement Procedure: (following the measurement procedure 10.2 of KDB558074):

- 1. Set analyzer center frequency to DTS channel center frequency.
- 2. Set the span to 1.5 times the DTS channel bandwidth.
- 3. Set the RBW > 3 kHz.
- 4. Set the VBW \geq 3 x RBW.
- 5. Detector = peak.
- 6. Sweep time = auto couple.
- 7. Trace mode = max hold.
- 8. Allow trace to fully stabilize.
- 9. Use the peak marker function to determine the maximum amplitude level.
- 10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Chino Solution and Solution a tronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is frawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only



11.5 Measurement Result:

BT4.0 mode

Frequency	RF Power Density	Maximum Limit	Result
MHz	Reading (dBm)	(dBm)	
2402	-9.329	8	PASS
2442	-8.238	8	PASS
2480	-6.844	8	PASS

NOTE: cable loss as 0.6dB that offsets in the spectrum

Note: Refer to next page for plots.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms_and_conditions.htm</u> and, for elec-tronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms_e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134號



BT4.0 mode Power Spectral Density Test Plot (CH-Low)



Power Spectral Density Test Plot (CH-Mid)



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Power Spectral Density Test Plot (CH-High)



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Unless otherwise stated the results shown in this test report feiter only to the sample(s) tested and such sample(s) are relatined to so days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for elec-tronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

GS Taiwan Ltd. No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134號

12 ANTENNA REQUIREMENT

12.1 Standard Applicable:

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than furnished by the responsible party shall be used with the device.

12.2 Antenna Connected Construction:

The directional gains of antenna used for transmitting is 0.29dBi, and the antenna connector is designed with unique type RF connector and no consideration of replacement. Please see EUT photo and antenna spec. for details.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.