



Test Report

Product Name : 27MHz Mouse

Model No. : M333, M302

FCC ID. : O62M333

Applicant : Darfon Electronics Corp.

Address : 6, Feng-Shu Tsuen, Gueishan, Taoyuan 333,
Taiwan, R.O.C.

Date of Receipt : Feb. 17, 2006

Issued Date : March 16, 2006

Report No. : 062L074-RF-US-P03V01

The Test Results relate only to the samples tested.

The test report shall not be reproduced except in full without the written approval of Quietek Corporation.

This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

Test Report Certification

Test Date : March 16, 2006

Report No.: 062L074-RF-US-P03V01




Accredited by NIST (NVLAP)
NVLAP Lab Code: 200533-0

Product Name : 27MHz Mouse
Applicant : Darfon Electronics Corp.
Address : 6, Feng-Shu Tsuen, Gueishan, Taoyuan 333, Taiwan, R.O.C.
Manufacturer : Darfon Eletronics (Suzhou) Co., Ltd.
Model No. : M333, M302
FCC ID. : O62M333
Rated Voltage : AC 110V / 60Hz
Working Voltage : Battery 1.5V*2
Trade Name : BenQ
Measurement Standard : FCC CFR Title 47 Part 15 Subpart C: 2005
Measurement Procedure : ANSI C63.4: 2003
Test Result : Complied


The Test Results relate only to the samples tested.

The test report shall not be reproduced except in full without the written approval of Quietek Corporation.

This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

Documented By : 
(Gene Chang)



Tested By : 
(Tom Hsieh)


Approved By : 
(Gene Chang)

TABLE OF CONTENTS

Description	Page
1. GENERAL INFORMATION.....	4
1.1. EUT Description.....	4
1.2. Operation Description	5
1.3. Test System Details	6
1.4. Configuration of Test System.....	6
1.5. EUT Exercise Software	6
1.6. Test Facility	7
2. Conducted Emission.....	8
2.1. Test Equipment.....	8
2.2. Test Setup	8
2.3. Limits	8
2.4. Test Procedure	9
2.5. Uncertainty	9
2.6. Test Data of Conducted Emission	10
3. Radiated Emission.....	11
3.1. Test Equipment.....	11
3.2. Test Setup	11
3.3. Limits	12
3.4. Test Procedure	13
3.5. Uncertainty	13
3.6. Test Data of Radiated Emission	14
4. Band Edge	18
4.1. Test Equipment.....	18
4.2. Test Setup	18
4.3. Limit	19
4.4. Test Procedure	19
4.5. Test Result of Band Edge	20
5. Occupied Bandwidth.....	21
5.1. Test Equipment.....	21
5.2. Test Setup	21
5.3. Test Result of Occupied Bandwidth	22
6. EMI Reduction Method During Compliance Testing	23
Attachment 1: EUT Test Photographs	
Attachment 2: EUT Detailed Photographs	

1. GENERAL INFORMATION

1.1. EUT Description

Product Name : 27MHz Mouse
 Trade Name : BenQ
 FCC ID. : O62M333
 Model No. : M333, M302
 Working Voltage : Battery 1.5V*2
 Frequency Range : 27.045MHz
 Type of Modulation : FSK
 Type of antenna : Loop Antenna
 Number of Channel : 1
 Channel Control : N/A

Frequency of Each Channel:

Channel	Frequency
1	27.045 MHz

Note:

1. The EUT is a 27MHz Mouse.
2. The EUT has two models and consists of two circuit boards. One board is the sensor board and the other is the RF board. The sensor boards of two models are different. The RF boards of two models are almost the same but one model adds a converter used for commutation.
3. The worst case M333 is shown on the report.
4. These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with FCC CFR Title 47 Part 15 Subpart C: 2005 Paragraph 15.227.

Pre-Test Mode	
EMI	Mode 1: Normal Operation
Final Test Mode	
EMI	Mode 1: Normal Operation

1.2. Operation Description

The EUT is a 27MHz Mouse used in household and office PC system.

The device adapts FSK modulation. The loop antenna provides diversity function to improve the transmitting function.

The super generation type receiver was used. An external excitation was used when the test of receiver was performed.


1.3. Test System Details

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

	Product	Manufacturer	Model No.	Serial No.	FCC ID	Power Cord
(1)	N/A	N/A	N/A	N/A	N/A	N/A

	Signal Cable Type	Signal cable Description
A.	N/A	N/A

1.4. Configuration of Test System



1.5. EUT Exercise Software

- (1) Setup the EUT as shown in section 1.4.
- (2) Press and hold the left and the middle button.
- (3) Install the batteries.
- (4) Check that the cursor moves circularly on the notebook.
- (5) Remove the notebook and start the tests.

1.6. Test Facility

Ambient conditions in the laboratory:

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	20-35
Humidity (%RH)	25-75	50-65
Barometric pressure (mbar)	860-1060	950-1000

Site Description: June 22, 2001 File on
 Federal Communications Commission
 FCC Engineering Laboratory
 7435 Oakland Mills Road
 Columbia, MD 21046
 Reference 31040/SIT1300F2



July 03, 2001 Accreditation on NVLAP
 NVLAP Lab Code: 200533-0



Site Name: Quietek Corporation

Site Address: No. 5-22, Ruei-Shu Valley, Ruei-Ping Tsuen,
 Lin-Kou Shiang, Taipei,
 Taiwan, R.O.C.
 TEL: 886-2-8601-3788 / FAX : 886-2-8601-3789
 E-Mail : service@quietek.com



2. Conducted Emission


2.1. Test Equipment

The following test equipment are used during the conducted emission test:

Item	Instrument	Manufacturer	Type No./Serial No	Last Cal.	Remark
1	Test Receiver	R & S	ESCS 30/838251/001	May, 2005	
2	L.I.S.N.	R & S	ESH3-Z5/836679/0023	May, 2005	EUT
3	L.I.S.N.	R & S	ENV 4200/833209/0023	May, 2005	Peripherals
4	Pulse Limiter	R & S	ESH3-Z2	May, 2005	
6	No.1 Shielded Room				

Note: All equipment upon which need to calibrated are with calibration period of 1 year.

2.2. Test Setup



2.3. Limits

FCC Part 15 Subpart C Paragraph 15.207 (dBuV) Limit		
Frequency MHz	Limits	
	QP	AV
0.15 - 0.50	66-56	56-46
0.50-5.0	56	46
5.0 - 30	60	50

Remarks : In the above table, the tighter limit applies at the band edges.

2.4. Test Procedure

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs.)

Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2003 on conducted measurement.

Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.

2.5. Uncertainty

The measurement uncertainty is defined as ± 2.26 dB

2.6. Test Data of Conducted Emission

The EUT is powered by batteries. This test item is not performed

3. Radiated Emission


3.1. Test Equipment

The following test equipment are used during the radiated emission test:

Test Site	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
<input type="checkbox"/> Site # 1	Test Receiver	R & S	ESVS 10 / 834468/003	July, 2005
	Spectrum Analyzer	Advantest	R3162/ 00803480	May, 2005
	Pre-Amplifier	Advantest	BB525C/ 3307A01812	May, 2005
	Bilog Antenna	SCHAFFNER	CBL6112B / 2697	Nov., 2005
<input type="checkbox"/> Site # 2	Test Receiver	R & S	ESCS 30 / 836858 / 022	Nov., 2005
	Spectrum Analyzer	Advantest	R3162 / 100803466	May, 2005
	Pre-Amplifier	Advantest	BB525C/3307A01814	May, 2005
	Bilog Antenna	SCHAFFNER	CBL6112B / 2705	Oct., 2005
<input checked="" type="checkbox"/> Site # 3	Test Receiver	R & S	ESI 26 / 838786 / 004	May, 2005
	Spectrum Analyzer	Advantest	R3162 / 100803480	May, 2005
	Pre-Amplifier	QTK	QTK-AMP-03 / 0003	May, 2005
	Horn Antenna	ETS	3115 / 0005-6160	July, 2005
	Pre-Amplifier	QTK	QTK-AMP-01 / 0001	July, 2005
	Broadband Antenna	Schwarzbeck	VULB9166/1085	April, 2005
	Loop Antenna	R&S	HFH2-Z2/833799/004	July, 2005

- Note:
1. All equipments that need to calibrate are with calibration period of 1 year.
 2. Mark "X" test instruments are used to measure the final test results.

3.2. Test Setup



3.3. Limits

➤ FCC Part 15 Subpart C Paragraph 15.227 Limit

FCC Part 15 Subpart C Paragraph 15.227 Limits		
Fundamental Frequency MHz	Field strength of fundamental	
	uV/m	dBuV/m
26.96-27.28	10000	80.0

Remarks :

1. RF Voltage (dBuV) = 20 log RF Voltage (uV)
2. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.
3. The emission limit in this paragraph is based on measurement instrumentation employing an average detector. Measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.

➤ Frequencies in restricted band are complied to limits on Paragraph 15.209.

FCC Part 15 Subpart C Paragraph 15.209 Limits		
Frequency MHz	uV/m @3m	dBuV/m@3m
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

- Remarks :
1. RF Voltage (dBuV/m) = 20 log RF Voltage (uV/m)
 2. In the Above Table, the tighter limit applies at the band edges.
 3. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

3.4. Test Procedure

The EUT and its simulators are placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.

Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.4: 2003 on radiated measurement.

Radiated emissions were investigated over the frequency range from 30MHz to 1GHz using a receiver bandwidth of 120kHz. Radiated was performed at an antenna to EUT distance of 3 meters.

The frequency range from 30MHz to 10th harmonics is checked.

3.5. Uncertainty



The measurement uncertainty is defined as ± 3.19 dB

3.6. Test Data of Radiated Emission

Product : 27MHz Mouse
 Test Item : Fundamental Radiated Emission
 Test Site : No.3 OATS
 Test Voltage : AC 110V / 60Hz
 Test Mode : Mode 1: Normal Operation

Polarity	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)
Peak Detector							
X	27.045	-3.55	48.34	44.79	-55.21	100.000	80.000
Y	27.045	-3.55	56.50	52.95	-47.05	100.000	80.000
Z	27.045	-3.55	56.63	53.08	-46.92	100.000	80.000

Polarity X



Date: 23.FEB.2006 09:46:46


Polarity Y




Att 10 dB
INPUT 1

Det	MA/AV	Trd
ResBW	9 kHz	
Meas T	100 ms	Unit

FREQUENCY	27.0450000	MHz
LEVEL PK+	56.50	dB ∇ V
AV	55.21	dB ∇ V



Marker 1 [T1]
56.23 dB ∇ V
27.04400000 MHz



Date: 23.FEB.2006 09:49:25

Polarity Z




Att 10 dB
INPUT 1

Det	MA/AV	Trd
ResBW	9 kHz	
Meas T	100 ms	Unit

FREQUENCY	27.0450000	MHz
LEVEL PK+	56.63	dB ∇ V
AV	55.34	dB ∇ V



Marker 1 [T1]
56.50 dB ∇ V
27.04400000 MHz



Date: 23.FEB.2006 09:51:50

Product : 27MHz Mouse
 Test Item : General Radiated Emission
 Test Site : No.3 OATS
 Test Voltage : AC 110V / 60Hz
 Test Mode : Mode 1: Normal Operation

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
Horizontal					
177.930	9.727	7.800	17.528	-25.992	43.520
216.700	9.552	12.900	22.452	-23.568	46.020
354.900	15.224	8.120	23.344	-22.676	46.020
468.900	18.781	8.200	26.981	-19.039	46.020
539.250	19.518	3.160	22.678	-23.342	46.020
*648.300	20.951	8.600	29.551	-16.469	46.020

Note:

1. Reading values below 1GHz are quasi-peak and reading values above 1GHz are peak and/or average.
2. “ * ” means the worst emission level.
3. Measurement Level = Reading Level + Correct Factor

Product : 27MHz Mouse
 Test Item : General Radiated Emission
 Test Site : No.3 OATS
 Test Voltage : AC 110V / 60Hz
 Test Mode : Mode 1: Normal Operation

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
Vertical					
211.800	10.287	7.300	17.587	-25.933	43.520
243.400	12.541	2.780	15.321	-30.699	46.020
257.900	14.270	3.900	18.170	-27.850	46.020
500.450	18.354	6.300	24.654	-21.366	46.020
536.800	19.720	8.010	27.730	-18.290	46.020
*699.300	20.653	7.140	27.793	-18.227	46.020

Note:

1. Reading values below 1GHz are quasi-peak and reading values above 1GHz are peak and/or average.
2. “ * ” means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor

4. Band Edge

4.1. Test Equipment


The following test equipment are used during the radiated emission test:

Test Site	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
<input type="checkbox"/> Site # 1	Test Receiver	R & S	ESVS 10 / 834468/003	July, 2005
	Spectrum Analyzer	Advantest	R3162/ 00803480	May, 2005
	Pre-Amplifier	Advantest	BB525C/ 3307A01812	May, 2005
	Bilog Antenna	SCHAFFNER	CBL6112B / 2697	Nov., 2005
<input type="checkbox"/> Site # 2	Test Receiver	R & S	ESCS 30 / 836858 / 022	Nov., 2005
	Spectrum Analyzer	Advantest	R3162 / 100803466	May, 2005
	Pre-Amplifier	Advantest	BB525C/3307A01814	May, 2005
	Bilog Antenna	SCHAFFNER	CBL6112B / 2705	Oct., 2005
<input checked="" type="checkbox"/> Site # 3	Test Receiver	R & S	ESI 26 / 838786 / 004	May, 2005
	Spectrum Analyzer	HP	E4407B / US39440758	May, 2005
	Pre-Amplifier	QTK	QTK-AMP-03 / 0003	May, 2005
	Broadband Antenna	Schwarzbeck	VULB9166/1085	April, 2005
	Horn Antenna	ETS	3115 / 0005-6160	July, 2005
	Loop Antenna	R&S	HFH2-Z2/833799/004	July, 2005
	Pre-Amplifier	QTK	QTK-AMP-01 / 0001	July, 2005

- Note:
1. All equipments that need to calibrate are with calibration period of 1 year.
 2. Mark "X" test instruments are used to measure the final test results.

4.2. Test Setup

RF Radiated Measurement:



4.3. Limit

Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

4.4. Test Procedure

The EUT and its simulators are placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.

Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.4: 2003 on radiated measurement.

The additional latch filter below 1GHz was used to measure the level of harmonics radiated emission during field strength of harmonics measurement.



The bandwidth below 30MHz setting on the field strength meter is 10 kHz

4.5. Test Result of Band Edge

Product : 27MHz Mouse
 Test Item : Band Edge
 Test Site : No.3 OATS
 Test Mode : Mode 1: Normal Operation

RF Radiated Measurement: (Q-Peak Detector)

Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)
25.640	-6.076	23.06	16.984	-23.016	40.000



5. Occupied Bandwidth


5.1. Test Equipment

The following test equipments are used during the radiated emission tests:

Equipment	Manufacturer	Model No./Serial No.	Last Cal.
X Test Receiver	R & S	ESI 26 / 838786 / 004	May, 2005

Note: 1. All equipment upon which need to calibrated are with calibration period of 1 year.
 2. Mark "X" test instruments are used to measure the final test results.


5.2. Test Setup



5.3. Test Result of Occupied Bandwidth

Product : 27MHz Mouse
 Test Item : Occupied Bandwidth Data
 Test Site : No.3 Shielded Room
 Test Mode : Channel 1

Channel No.	Frequency (MHz)	Measurement Level (kHz)
1	27.045	9.18



Date: 24.FEB.2006 19:39:59


6. EMI Reduction Method During Compliance Testing

No modification was made during testing.


Attachment 1: EUT Test Photographs

Attachment 1: EUT Test Setup Photographs

Front View of Radiated Test




Back View of Radiated Test



Front View of Radiated Test



Back View of Radiated Test



Attachment 2: EUT Detailed Photographs

Attachment 2 : EUT Detailed Photographs

(1) EUT Photo (M333)



(2) EUT Photo (M333)



(3) EUT Photo (M333)




(4) EUT Photo (M333)




(5) EUT Photo (M333)




(6) EUT Photo (M333)



(7) EUT Photo (M333)



(8) EUT Photo (M333)



(9) EUT Photo (M302)



(10) EUT Photo (M302)




(11) EUT Photo (M302)




(12) EUT Photo (M302)




(13) EUT Photo (M302)



(14) EUT Photo (M302)



(15) EUT Photo (M302)



(16) EUT Photo (M302)

