



## Test Report

Product Name : 27MHz Mouse

Model No. : N331, N332

FCC ID. : O62N331

Applicant : Darfon Electronics Corp.

Address : 6, Feng-Shu Tsuen, Gueishan, Taoyuan 333,  
Taiwan, R.O.C.

Date of Receipt : Sep 12, 2005

Issued Date : Sep 26, 2005

Report No. : 059L082FI

The Test Results relate only to the samples tested.

The test report shall not be reproduced except in full without the written approval of Quietek Corporation.

This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

# Test Report Certification

Test Date : Sep 26, 2005

Report No.: 059L082FI



Accredited by NIST (NVLAP)  
NVLAP Lab Code: 200533-0

Product Name : 27MHz Mouse

Applicant : Darfon Electronics Corp.

Address : 6, Feng-Shu Tsuen, Gueishan, Taoyuan 333, Taiwan, R.O.C.

Manufacturer : Darfon Electronics Corp.

Model No. : N331, N332

FCC ID. : O62N331

Rated Voltage : DC 3V(Power by Battery)

Trade Name : BenQ, TDE Systems

Measurement Standard : FCC CFR Title 47 Part 15 Subpart C: 2003

Measurement Procedure : ANSI C63.4: 2003

Test Result : Complied

The Test Results relate only to the samples tested.

The test report shall not be reproduced except in full without the written approval of Quietek Corporation.

This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

Documented By : Genie Chang  
( Genie Chang )

Tested By : Tim Sung  
( Tim Sung )

Approved By : Gene Chang  
( Gene Chang )



## TABLE OF CONTENTS

Description	Page
<b>1. GENERAL INFORMATION.....</b>	<b>4</b>
1.1. EUT Description.....	4
1.2. Operation Description .....	5
1.3. Tested System Details.....	5
1.4. Configuration of tested System .....	5
1.5. EUT Exercise Software .....	5
1.6. Test Facility .....	6
<b>2. Conducted Emission.....</b>	<b>7</b>
2.1. Test Equipment.....	7
2.2. Test Setup .....	7
2.3. Limits .....	7
2.4. Test Procedure .....	8
2.5. Uncertainty .....	8
2.6. Test Data of Conducted Emission .....	9
<b>3. Radiated Emission.....</b>	<b>10</b>
3.1. Test Equipment.....	10
3.2. Test Setup .....	10
3.3. Limits .....	11
3.4. Test Procedure .....	12
3.5. Uncertainty .....	12
3.6. Test Data of Radiated Emission .....	13
<b>4. Band Edge .....</b>	<b>16</b>
4.1. Test Equipment.....	16
4.2. Test Setup .....	16
4.3. Limit .....	17
4.4. Test Procedure .....	17
4.5. Test Result of Band Edge .....	18
<b>5. Occupied Bandwidth.....</b>	<b>19</b>
5.1. Test Equipment.....	19
5.2. Test Setup .....	19
5.3. Test Result of Occupied Bandwidth .....	20
<b>6. EMI Reduction Method During Compliance Testing .....</b>	<b>21</b>
Attachment 1: EUT Test Photographs	
Attachment 2: EUT Detailed Photographs	

**1. GENERAL INFORMATION**

**1.1. EUT Description**

Product Name : 27MHz Mouse  
 Trade Name : BenQ, TDE Systems  
 FCC ID. : O62N331  
 Model No. : N331, N332  
 EUT Voltage : DC 3V(Power by Battery)  
 Frequency Range : 27MHz for Mouse  
 Type of Modulation : FSK  
 Type of antenna : Loop antenna  
 Channel Number : 1  
 Channel Control : Manual

Frequency of Each Channel:

Channel	Frequency
1	27 MHz (Mouse)

Note:

- The EUT is a 27MHz Mouse intends to use in household and office PC system or related application.
- The different of the each model is shown as below:

Model Number	Trade Name	Description
N331	BenQ	Electrify
N332	TDE Systems	Not Electrify

- These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with FCC CFR Title 47 Part 15 Subpart C:2003 Paragraph 15.227.

Pre-Test Mode	
EMI	Mode 1: Normal Operation-N331 Mode 2: Normal Operation-N332
Final Test Mode	
EMI	Mode 1: Normal Operation-N331

**1.2. Operation Description**

The EUT is a 27MHz Mouse intends to use in household and office PC system.

The device adapts FSK modulation. The loop antenna provides diversity function to improve the transmitting function.

The super generation type receiver was used. An external excitation was used when the test of receiver was performed.


**1.3. Test System Details**

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

Product	Manufacturer	Model No.	Serial No.	FCC ID	Power Cord
(1) N/A	N/A	N/A	N/A	N/A	N/A

Signal Cable Type	Signal cable Description
A. N/A	N/A

**1.4. Configuration of Test System**



**1.5. EUT Exercise Software**

- (1) Setup the test system as shown on 1.4.
- (2) Enable RF signal and confirm the EUT is active.
- (3) Adjust output capacity of EUT to the specification.

**1.6. Test Facility**

Ambient conditions in the laboratory:

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	20-35
Humidity (%RH)	25-75	50-65
Barometric pressure (mbar)	860-1060	950-1000

Site Description: June 22, 2001 File on  
 Federal Communications Commission  
 FCC Engineering Laboratory  
 7435 Oakland Mills Road  
 Columbia, MD 21046  
 Reference 31040/SIT1300F2



July 03, 2001 Accreditation on NVLAP  
 NVLAP Lab Code: 200533-0



Site Name: Quietek Corporation

Site Address: No. 5-22, Ruei-Shu Valley, Ruei-Ping Tsuen,  
 Lin-Kou Shiang, Taipei,  
 Taiwan, R.O.C.  
 TEL: 886-2-8601-3788 / FAX : 886-2-8601-3789  
 E-Mail : [service@quietek.com](mailto:service@quietek.com)



## 2. Conducted Emission


### 2.1. Test Equipment

The following test equipment are used during the conducted emission test:

Item	Instrument	Manufacturer	Type No./Serial No	Last Cal.	Remark
1	Test Receiver	R & S	ESCS 30/838251/001	May, 2005	
2	L.I.S.N.	R & S	ESH3-Z5/836679/0023	May, 2005	EUT
3	L.I.S.N.	R & S	ENV 4200/833209/0023	May, 2005	Peripherals
4	Pulse Limiter	R & S	ESH3-Z2	May, 2005	
6	No.1 Shielded Room			N/A	

Note: All equipment upon which need to calibrated are with calibration period of 1 year.

### 2.2. Test Setup



### 2.3. Limits

FCC Part 15 Subpart C Paragraph 15.207 (dBuV) Limit		
Frequency MHz	Limits	
	QP	AV
0.15 - 0.50	66-56	56-46
0.50-5.0	56	46
5.0 - 30	60	50

Remarks : In the above table, the tighter limit applies at the band edges.

## 2.4. Test Procedure

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs.)

Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2001 on conducted measurement.

Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.

## 2.5. Uncertainty

The measurement uncertainty is defined as  $\pm 2.02$  dB



## 2.6. Test Data of Conducted Emission

Owing to the DC operation of EUT, this test item is not performed.

### 3. Radiated Emission


#### 3.1. Test Equipment

The following test equipment are used during the radiated emission test:

Test Site	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
<input type="checkbox"/> Site # 1	Test Receiver	R & S	ESVS 10 / 834468/003	July, 2005
	Spectrum Analyzer	Advantest	R3162/ 00803480	May, 2005
	Pre-Amplifier	Advantest	BB525C/ 3307A01812	May, 2005
	Bilog Antenna	SCHAFFNER	CBL6112B / 2697	Nov., 2004
<input type="checkbox"/> Site # 2	Test Receiver	R & S	ESCS 30 / 836858 / 022	Nov., 2004
	Spectrum Analyzer	Advantest	R3162 / 100803466	May, 2005
	Pre-Amplifier	Advantest	BB525C/3307A01814	May, 2005
	Bilog Antenna	SCHAFFNER	CBL6112B / 2705	Oct., 2004
<input checked="" type="checkbox"/> Site # 3	Test Receiver	R & S	ESI 26 / 838786 / 004	May, 2005
	Spectrum Analyzer	Advantest	R3162 / 100803480	May, 2005
	Pre-Amplifier	QTK	QTK-AMP-03 / 0003	May, 2005
	Horn Antenna	ETS	3115 / 0005-6160	July, 2004
	Pre-Amplifier	QTK	QTK-AMP-01 / 0001	July, 2004
	Broadband Antenna	Schwarzbeck	VULB9166/1085	April, 2005

- Note:
1. All equipments that need to calibrate are with calibration period of 1 year.
  2. Mark "X" test instruments are used to measure the final test results.

#### 3.2. Test Setup



### 3.3. Limits

➤ FCC Part 15 Subpart C Paragraph 15.227 Limit

<b>FCC Part 15 Subpart C Paragraph 15.227 Limits</b>		
Fundamental Frequency MHz	Field strength of fundamental	
	uV/m	dBuV/m
26.96-27.28	10000	80.0

Remarks :

1. RF Voltage (dBuV) = 20 log RF Voltage (uV)
2. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.
3. The emission limit in this paragraph is based on measurement instrumentation employing an average detector. Measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.

➤ Frequencies in restricted band are complied to limits on Paragraph 15.209.

<b>FCC Part 15 Subpart C Paragraph 15.209 Limits</b>		
Frequency MHz	uV/m @3m	dBuV/m@3m
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

- Remarks :
1. RF Voltage (dBuV/m) = 20 log RF Voltage (uV/m)
  2. In the Above Table, the tighter limit applies at the band edges.
  3. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

### 3.4. Test Procedure

The EUT and its simulators are placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.

Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.4: 2003 on radiated measurement.

Radiated emissions were investigated over the frequency range from 30MHz to 1GHz using a receiver bandwidth of 120kHz. Radiated was performed at an antenna to EUT distance of 3 meters.

The frequency range from 30MHz to 10th harmonics is checked.

### 3.5. Uncertainty



The measurement uncertainty is defined as  $\pm 3.8$  dB

### 3.6. Test Data of Radiated Emission



Product : 27MHz Mouse  
 Test Item : Fundamental Radiated Emission  
 Test Site : No.3 OATS  
 Test Voltage : DC 3V(Power by Battery)  
 Test Mode : Mode 1: Normal Operation-N331

Polarity	Frequency (MHz)	Measurement	Limit	Result
X	27.048	42.65dBuV/m	80dBuV/m	Pass
Y	27.048	54.31dBuV/m	80dBuV/m	Pass
Z	27.048	54.61dBuV/m	80dBuV/m	Pass



Polarity X



Polarity Y



Polarity Z



Product : 27MHz Mouse  
 Test Item : General Radiated Emission  
 Test Site : No.3 OATS  
 Test Voltage : DC 3V(Power by Battery)  
 Test Mode : Mode 1: Normal Operation-N331

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
<b>Horizontal</b>					
54.084	7.474	14.110	21.584	-18.416	40.000
*81.128	9.559	19.090	28.649	-11.351	40.000
108.171	13.762	8.070	21.832	-21.688	43.520
135.214	13.499	5.370	18.869	-24.651	43.520
162.257	11.519	8.290	19.809	-23.711	43.520
189.299	10.436	7.580	18.016	-25.504	43.520
216.342	10.601	5.170	15.771	-30.249	46.020
243.385	13.333	5.670	19.003	-27.017	46.020
270.428	14.597	5.380	19.977	-26.043	46.020

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. “ \* ” means this data is the worst emission level.
3. Emission Level = Reading Level + Probe Factor + Cable Loss.

Product : 27MHz Mouse  
 Test Item : General Radiated Emission  
 Test Site : No.3 OATS  
 Test Voltage : DC 3V(Power by Battery)  
 Test Mode : Mode 1: Normal Operation-N331

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
<b>Vertical</b>					
54.084	7.156	14.600	21.756	-18.244	40.000
*81.128	9.113	19.680	28.793	-11.207	40.000
108.171	12.374	8.230	20.604	-22.916	43.520
135.214	12.620	7.940	20.560	-22.960	43.520
162.257	10.709	10.240	20.949	-22.571	43.520
189.299	10.618	12.810	23.428	-20.092	43.520
216.342	11.723	6.720	18.443	-27.577	46.020
243.385	13.592	6.490	20.082	-25.938	46.020
270.428	15.097	5.720	20.817	-25.203	46.020

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. “ \* ” means this data is the worst emission level.
3. Emission Level = Reading Level + Probe Factor + Cable Loss.

## 4. Band Edge

### 4.1. Test Equipment


The following test equipment are used during the radiated emission test:

Test Site	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
<input type="checkbox"/> Site # 1	Test Receiver	R & S	ESVS 10 / 834468/003	July, 2005
	Spectrum Analyzer	Advantest	R3162/ 00803480	May, 2005
	Pre-Amplifier	Advantest	BB525C/ 3307A01812	May, 2005
	Bilog Antenna	SCHAFFNER	CBL6112B / 2697	Nov., 2004
<input type="checkbox"/> Site # 2	Test Receiver	R & S	ESCS 30 / 836858 / 022	Nov., 2004
	Spectrum Analyzer	Advantest	R3162 / 100803466	May, 2005
	Pre-Amplifier	Advantest	BB525C/3307A01814	May, 2005
	Bilog Antenna	SCHAFFNER	CBL6112B / 2705	Oct., 2004
<input checked="" type="checkbox"/> Site # 3	Test Receiver	R & S	ESI 26 / 838786 / 004	May, 2005
	Spectrum Analyzer	HP	E4407B / US39440758	May, 2005
	Pre-Amplifier	QTK	QTK-AMP-03 / 0003	May, 2005
	Broadband Antenna	Schwarzbeck	VULB9166/1085	April, 2005
	Horn Antenna	ETS	3115 / 0005-6160	July, 2005
	Pre-Amplifier	QTK	QTK-AMP-01 / 0001	July, 2005

- Note:
1. All equipments that need to calibrate are with calibration period of 1 year.
  2. Mark "X" test instruments are used to measure the final test results.

### 4.2. Test Setup

#### RF Radiated Measurement:





### 4.3. Limit

Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

### 4.4. Test Procedure

The EUT and its simulators are placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.

Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.4: 2003 on radiated measurement.

The additional latch filter below 1GHz was used to measure the level of harmonics radiated emission during field strength of harmonics measurement.

The bandwidth below 30MHz setting on the field strength meter is 10 kHz

### 4.5. Test Result of Band Edge

Product : 27MHz Mouse  
 Test Item : Band Edge  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Normal Operation-N331

#### RF Radiated Measurement: (Average Detector)


Frequency (MHz)	Reading Level (dBuV/m)	Limit (dBuV/m)	Result
25.652	25.632	23.38	Pass




Att 10 dB INPUT 1  
 Det ResBW Meas T QP Trd Unit dBuV/m  
 9 kHz 500 ms

```

FREQUENCY      25.6320000 MHz
LEVEL QPK      23.38 dBuV/m
    
```



Marker 4 [T1]  
 23.38 dBuV/m  
 25.6320000 MHz



Date: 28.SEP.2005 15:28:25

## 5. Occupied Bandwidth


### 5.1. Test Equipment

The following test equipments are used during the radiated emission tests:

Equipment	Manufacturer	Model No./Serial No.	Last Cal.
X Spectrum Analyzer	HP	E4407B / US39440758	May, 2005

Note: 1. All equipment upon which need to calibrated are with calibration period of 1 year.  
 2. Mark "X" test instruments are used to measure the final test results.

### 5.2. Test Setup



### 5.3. Test Result of Occupied Bandwidth

Product : 27MHz Mouse  
 Test Item : Occupied Bandwidth Data-N331  
 Test Site : No.3 Shielded Room  
 Test Mode : Channel 1

Channel No.	Frequency (MHz)	Measurement Level (kHz)
Ch01	27.04	9.1709

Agilent 17:25:14 Sep 21, 2005 T

Ch Freq 27.0469 MHz Trig Free

**Occupied Bandwidth**

Ref 15 dBm #Atten 20 dB Mkr1 27.04315 MHz -9.994 dBm

Center 27.05 MHz Span 500 kHz  
 #Res BW 1 kHz VBW 1 kHz Sweep 1.019 s (401 pts)

<b>Occupied Bandwidth</b>	Occ BW % Pwr	99.00 %
9.1709 kHz	x dB	-6.00 dB
Transmit Freq Error	-2.747 kHz	
x dB Bandwidth	2.092 kHz*	

File  
 Catalog  
 Save  
 Load  
 Delete  
 Copy  
 Rename  
 More 1 of 2

## 6. EMI Reduction Method During Compliance Testing

No modification was made during testing.

## Attachment 1: EUT Test Photographs

**Attachment 1: EUT Test Setup Photographs**

Front View of Radiated Test



Back View of Radiated Test



## Attachment 2: EUT Detailed Photographs



**Attachment 2 : EUT Detailed Photographs**

(1) EUT Photo (N331)



(2) EUT Photo (N331)



(3) EUT Photo (N331)




(4) EUT Photo (N331)




(5) EUT Photo (N331)




(6) EUT Photo (N331)



(7) EUT Photo (N331)



(8) EUT Photo (N331)



(9) EUT Photo (N331)



(10) EUT Photo (N331)




(11) EUT Photo (N331)




(12) EUT Photo (N331)



(13) EUT Photo (N331)



(14) EUT Photo (N331)



(15) EUT Photo (N331)



(16) EUT Photo (N331)





(17) EUT Photo (N331)



(18) EUT Photo (N332)



(19) EUT Photo (N332)



(20) EUT Photo (N332)




(21) EUT Photo (N332)




(22) EUT Photo (N332)



(23) EUT Photo (N332)



(24) EUT Photo (N332)



(25) EUT Photo (N332)

