



FCC TEST REPORT

REPORT NO.: RF911105R02

MODEL NO.: UW320-IF

RECEIVED: Nov. 5, 2002

TESTED: Aug. 1 ~ Aug. 23, 2002,
Nov. 15 ~ Nov. 17, 2002

APPLICANT: BROMAX COMMUNICATIONS, INC.

ADDRESS: No. 20, Kuang Fu Road, Hsin Chu Industrial
Park, Hu Kou, Hsin Chu, Taiwan, R.O.C.

ISSUED BY: Advance Data Technology Corporation

LAB LOCATION: 47 14th Lin, Chiapau Tsun, Linko, Taipei,
Taiwan, R.O.C.

This test report consists of 59 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, NVLAP or any government agencies. The test results in the report only apply to the tested sample.



0528
ILAC MRA



Lab Code: 200102-0

Table of Contents

1	CERTIFICATION.....	4
2	SUMMARY OF TEST RESULTS	5
3	GENERAL INFORMATION	6
3.1	GENERAL DESCRIPTION OF EUT	6
3.2	DESCRIPTION OF TEST MODES	7
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS.....	7
3.4	DESCRIPTION OF SUPPORT UNITS.....	8
4	TEST TYPES AND RESULTS	9
4.1	CONDUCTED EMISSION MEASUREMENT.....	9
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	9
4.1.2	TEST INSTRUMENTS.....	9
4.1.3	TEST PROCEDURES	10
4.1.4	DEVIATION FROM TEST STANDARD	10
4.1.5	TEST SETUP.....	11
4.1.6	EUT OPERATING CONDITIONS	12
4.1.7	TEST RESULTS (A).....	13
4.1.8	TEST RESULTS (B).....	19
4.2	RADIATED EMISSION MEASUREMENT.....	25
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT	25
4.2.2	TEST INSTRUMENTS.....	26
4.2.3	TEST PROCEDURES	27
4.2.4	DEVIATION FROM TEST STANDARD	27
4.2.5	TEST SETUP.....	28
4.2.6	EUT OPERATING CONDITIONS	28
4.2.7	TEST RESULTS (A).....	29
4.2.8	TEST RESULTS (B).....	33
4.3	6dB BANDWIDTH MEASUREMENT	37
4.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT.....	37
4.3.2	TEST INSTRUMENTS.....	37
4.3.3	TEST PROCEDURE.....	38
4.3.4	DEVIATION FROM TEST STANDARD	38
4.3.5	TEST SETUP.....	38
4.3.6	EUT OPERATING CONDITIONS	38
4.3.7	TEST RESULTS	39
4.4	MAXIMUM PEAK OUTPUT POWER.....	43
4.4.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT.....	43
4.4.2	INSTRUMENTS.....	43
4.4.3	TEST PROCEDURES	44
4.4.4	DEVIATION FROM TEST STANDARD	44



4.4.5	TEST SETUP	44
4.4.6	EUT OPERATING CONDITIONS	44
4.4.7	TEST RESULTS	45
4.5	POWER SPECTRAL DENSITY MEASUREMENT	46
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	46
4.5.2	TEST INSTRUMENTS	46
4.5.3	TEST PROCEDURE	47
4.5.4	DEVIATION FROM TEST STANDARD	47
4.5.5	TEST SETUP	47
4.5.6	EUT OPERATING CONDITION	47
4.5.7	TEST RESULTS	48
4.6	BAND EDGES MEASUREMENT	52
4.6.1	LIMITS OF BAND EDGES MEASUREMENT	52
4.6.2	TEST INSTRUMENTS	52
4.6.3	TEST PROCEDURE	52
4.6.4	DEVIATION FROM TEST STANDARD	52
4.6.5	EUT OPERATING CONDITION	53
4.6.6	TEST RESULTS	53
4.7	ANTENNA REQUIREMENT	56
4.7.1	STANDARD APPLICABLE	56
4.7.2	ANTENNA CONNECTED CONSTRUCTION	56
5	PHOTOGRAPHS OF THE TEST CONFIGURATION	57
6	INFORMATION ON THE TESTING LABORATORIES	59



1 CERTIFICATION

PRODUCT : Wireless USB Adapter
BRAND NAME : BroMax
MODEL NO. : UW320-IF
APPLICANT : BROMAX COMMUNICATIONS, INC.
STANDARDS : 47 CFR Part 15, Subpart C (Section 15.247),
ANSI C63.4-1992

We, **Advance Data Technology Corporation**, hereby certify that one sample of the designation has been tested in our facility from Aug. 1 ~ Aug. 23 and Nov. 15 ~ Nov. 17, 2002. The test record, data evaluation and Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions herein specified.

CHECKED BY: Rennie Wang, **DATE:** November 25, 2002
Rennie Wang

APPROVED BY: Alan Lane **DATE:** November 25, 2002
Dr. Alan Lane
Manager

2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: 47 CFR Part 15, Subpart C			
Standard Section	Test Type and Limit	Result	REMARK
15.207	AC Power Conducted Emission Limit: 48dBuV	PASS	Meet the requirement of limit Minimum passing margin is -14.57dBuV at 0.17MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit
15.247(c)	Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit Minimum passing margin is -5.90dBuV at 4874.00MHz
15.247(d)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit
15.247(c)	Band Edge Measurement Limit: 20 dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Wireless USB Adapter
MODEL NO.	UW320-IF
POWER SUPPLY	5.0VDC from host equipment
MODULATION TYPE	BPSK, QPSK, CCK (DSSS)
TRANSFER RATE	1/2/5.5/11Mbps
FREQUENCY RANGE	2412MHz ~ 2462MHz
NUMBER OF CHANNEL	11
OUTPUT POWER	14.43dBm
ANTENNA TYPE	Dipole Antenna & Inverted F Antenna
DATA CABLE	1.4m (Shielded), 0.9m (Shielded)
I/O PORTS	USB port
ASSOCIATED DEVICES	NA

NOTE:

1. The EUT was designed with two outer appearances.
2. There are two antenna types provided to this EUT. Please see as following for details:

Item	Antenna Type	Antenna Gain (dBi)
1	Dipole	1
2	Inverted F	-1

3. For more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

Eleven channels are provided to this EUT.

Channel	Frequency	Channel	Frequency
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

- NOTE:** 1. Below 1 GHz, the channel 1, 6, and 11 were pre-tested in chamber. The channel 11, worst case one, was chosen for final test.
2. Above 1 GHz, the channel 1, 6, and 11 were tested individually.
3. For “Conducted Emission Measurement” and “Radiated Emission Measurement” test, there are two test results for the test. The test result A is for Antenna type 1, and the test result B is for Antenna type 2.

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a Wireless USB Adapter. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 15, Subpart C. (15.247)
ANSI C63.4 : 1992

All tests have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	PRINTER	EPSON	LQ-300+	DCGY017096	FCC DoC APPROVED
2	NOTEBOOK	DELL	PP01L	TW-09C748-12800- 19O-B220	FCC DoC APPROVED
3	MODEM	ACEEX	1414	980020569	IFAXDM1414

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	1.2m braid shielded wire, terminated with DB25 and Centronics connector via metallic frame, w/o core
2	NA
3	1.2 m braid shielded wire, terminated with DB25 and DB9 connector via metallic frame, w/o core.

NOTE: All power cords of the above support units are non shielded (1.8m).

4 TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. All emanations from a class B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
ROHDE & SCHWARZ Test Receiver	ESCS30	834115/016	Mar. 3, 2003
ROHDE & SCHWARZ Artificial Mains Network (For EUT)	ESH3-Z5	847265/023	Jan. 10, 2003
* ROHDE & SCHWARZ 4-wire ISN	ENY41	838119/028	Dec. 10, 2002
* ROHDE & SCHWARZ 2-wire ISN	ENY22	837497/018	Dec. 10, 2002
EMCO L.I.S.N. (For peripherals)	3825/2	9504-2359	July 10, 2003
Software	Cond-V2L	NA	NA
RF cable (JYEBAO)	5D-FB	Cable-C03.01	July 11, 2003
Terminator (For EMCO LISN)	NA	E1-01-300	Feb. 20, 2003
Terminator (For EMCO LISN)	NA	E1-01-301	Feb. 20, 2003
Shielded Room	Site 3	ADT-C03	NA
VCCI Site Registration No.	Site 3	C-274	NA

- NOTE:**
1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
 2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 3. “*”: These equipment are used for conducted telecom port test only (if tested).
 4. The test was performed in ADT Open Site No. 3.




4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels over 10dB under the prescribed limits could not be reported.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



- Note:** 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.



4.1.6 EUT OPERATING CONDITIONS

- a. Connected the EUT to a computer system placed on a testing table.
- b. The computer system ran a test program to enable EUT under transmission/receiving condition continuously at specific channel frequency.
- c. The computer system sent "H" messages to its screen.
- d. The computer system sent "H" messages to modem.
- e. The computer system sent "H" messages to printer and the printer prints them on paper.


4.1.7 TEST RESULTS (A)

EUT	Wireless USB Adapter	MODEL	UW320-IF
MODE	Channel 1	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	35 deg. C, 50 %RH, 1005 hPa	TESTED BY: Bunny Yao	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.170	0.10	48.67	-	48.77	-	64.98	54.98	-16.21	-
2	0.224	0.10	40.17	-	40.27	-	62.66	52.66	-22.39	-
3	0.338	0.10	34.44	-	34.54	-	59.26	49.26	-24.72	-
4	0.455	0.11	30.62	-	30.73	-	56.79	46.79	-26.06	-
5	13.035	0.66	21.19	-	21.85	-	60.00	50.00	-38.15	-
6	23.793	1.15	26.37	-	27.52	-	60.00	50.00	-32.48	-

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.




EUT	Wireless USB Adapter	MODEL	UW320-IF
MODE	Channel 1	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	35 deg. C, 50 %RH, 1005 hPa	TESTED BY: Bunny Yao	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.170	0.10	48.92	-	49.02	-	64.98	54.98	-15.96	-
2	0.224	0.10	39.36	-	39.46	-	62.66	52.66	-23.20	-
3	0.283	0.10	36.60	-	36.70	-	60.73	50.73	-24.03	-
4	0.338	0.10	33.65	-	33.75	-	59.26	49.26	-25.51	-
5	12.980	0.46	22.13	-	22.59	-	60.00	50.00	-37.41	-
6	19.469	0.77	24.82	-	25.59	-	60.00	50.00	-34.41	-

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.




EUT	Wireless USB Adapter	MODEL	UW320-IF
MODE	Channel 6	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	35 deg. C, 50 %RH, 1005 hPa	TESTED BY: Bunny Yao	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.173	0.10	46.42	-	46.52	-	64.79	54.79	-18.27	-
2	0.232	0.10	36.49	-	36.59	-	62.38	52.38	-25.79	-
3	0.232	0.10	34.94	-	35.04	-	62.38	52.38	-27.34	-
4	3.867	0.39	25.61	-	26.00	-	56.00	46.00	-30.00	-
5	18.188	0.89	27.34	-	28.23	-	60.00	50.00	-31.77	-
6	23.793	1.15	26.15	-	27.30	-	60.00	50.00	-32.70	-

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.




EUT	Wireless USB Adapter	MODEL	UW320-IF
MODE	Channel 6	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	35 deg. C, 50 %RH, 1005 hPa	TESTED BY: Bunny Yao	

No	Freq.	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.166	0.10	42.78	-	42.88	-	65.18	55.18	-22.30	-
2	0.224	0.10	38.72	-	38.82	-	62.66	52.66	-23.84	-
3	0.279	0.10	31.31	-	31.41	-	60.85	50.85	-29.44	-
4	0.341	0.10	35.96	-	36.06	-	59.17	49.17	-23.11	-
5	18.117	0.69	27.76	-	28.45	-	60.00	50.00	-31.55	-
6	20.770	0.78	20.99	-	21.77	-	60.00	50.00	-38.23	-

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.




EUT	Wireless USB Adapter	MODEL	UW320-IF
MODE	Channel 11	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	35 deg. C, 50 %RH, 1005 hPa	TESTED BY: Bunny Yao	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.173	0.10	45.95	-	46.05	-	64.79	54.79	-18.74	-
2	0.232	0.10	35.39	-	35.49	-	62.38	52.38	-26.89	-
3	0.399	0.10	31.41	-	31.51	-	57.88	47.88	-26.37	-
4	12.563	0.65	21.01	-	21.66	-	60.00	50.00	-38.34	-
5	18.777	0.93	26.20	-	27.13	-	60.00	50.00	-32.87	-
6	23.797	1.15	24.36	-	25.51	-	60.00	50.00	-34.49	-

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.




EUT	Wireless USB Adapter	MODEL	UW320-IF
MODE	Channel 11	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	35 deg. C, 50 %RH, 1005 hPa	TESTED BY: Bunny Yao	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.170	0.10	47.32	-	47.42	-	64.98	54.98	-17.56	-
2	0.224	0.10	37.77	-	37.87	-	62.66	52.66	-24.79	-
3	0.287	0.10	34.95	-	35.05	-	60.62	50.62	-25.57	-
4	3.867	0.29	24.36	-	24.65	-	56.00	46.00	-31.35	-
5	3.867	0.29	24.37	-	24.66	-	56.00	46.00	-31.34	-
6	18.082	0.68	26.38	-	27.06	-	60.00	50.00	-32.94	-

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.




4.1.8 TEST RESULTS (B)

EUT	Wireless USB Adapter	MODEL	UW320-IF
MODE	Channel 1	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	25 deg. C, 67 %RH, 1005 hPa	TESTED BY: Cody Chang	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.170	0.10	49.62	-	49.72	-	64.98	54.98	-15.26	-
2	0.228	0.10	44.83	-	44.93	-	62.52	52.52	-17.59	-
3	0.283	0.10	37.63	-	37.73	-	60.73	50.73	-23.00	-
4	0.341	0.10	33.46	-	33.56	-	59.17	49.17	-25.61	-
5	3.401	0.44	30.36	-	30.80	-	56.00	46.00	-25.20	-
6	3.794	0.48	32.05	-	32.53	-	56.00	46.00	-23.47	-

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.




EUT	Wireless USB Adapter	MODEL	UW320-IF
MODE	Channel 1	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	25 deg. C, 67 %RH, 1005 hPa	TESTED BY: Cody Chang	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.170	0.10	50.31	-	50.41	-	64.98	54.98	-14.57	-
2	0.228	0.10	45.87	-	45.97	-	62.52	52.52	-16.55	-
3	0.283	0.10	38.19	-	38.29	-	60.73	50.73	-22.44	-
4	0.341	0.10	35.73	-	35.83	-	59.17	49.17	-23.34	-
5	0.455	0.11	32.86	-	32.97	-	56.79	46.79	-23.82	-
6	3.918	0.40	28.14	-	28.54	-	56.00	46.00	-27.46	-

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.




EUT	Wireless USB Adapter	MODEL	UW320-IF
MODE	Channel 6	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	25 deg. C, 67 %RH, 1005 hPa	TESTED BY: Cody Chang	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.170	0.10	48.04	-	48.14	-	64.98	54.98	-16.84	-
2	0.228	0.10	44.03	-	44.13	-	62.52	52.52	-18.39	-
3	0.287	0.10	36.01	-	36.11	-	60.62	50.62	-24.51	-
4	0.341	0.10	32.39	-	32.49	-	59.17	49.17	-26.68	-
5	0.400	0.10	28.69	-	28.79	-	57.85	47.85	-29.06	-
6	3.821	0.48	33.11	-	33.59	-	56.00	46.00	-22.41	-

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.




EUT	Wireless USB Adapter	MODEL	UW320-IF
MODE	Channel 6	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	25 deg. C, 67 %RH, 1005 hPa	TESTED BY: Cody Chang	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.172	0.10	49.62	-	49.72	-	64.86	54.86	-15.14	-
2	0.228	0.10	45.63	-	45.73	-	62.52	52.52	-16.79	-
3	0.283	0.10	37.36	-	37.46	-	60.73	50.73	-23.27	-
4	0.341	0.10	35.47	-	35.57	-	59.17	49.17	-23.60	-
5	0.455	0.11	29.84	-	29.95	-	56.79	46.79	-26.84	-
6	13.477	0.47	26.18	-	26.65	-	60.00	50.00	-33.35	-

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.




EUT	Wireless USB Adapter	MODEL	UW320-IF
MODE	Channel 11	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	25 deg. C, 67 %RH, 1005 hPa	TESTED BY: Cody Chang	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.170	0.10	47.46	-	47.56	-	64.98	54.98	-17.42	-
2	0.228	0.10	43.31	-	43.41	-	62.52	52.52	-19.11	-
3	0.287	0.10	36.05	-	36.15	-	60.62	50.62	-24.47	-
4	0.341	0.10	32.33	-	32.43	-	59.17	49.17	-26.74	-
5	0.459	0.11	27.10	-	27.21	-	56.72	46.72	-29.51	-
6	3.598	0.46	30.65	-	31.11	-	56.00	46.00	-24.89	-

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.




EUT	Wireless USB Adapter	MODEL	UW320-IF
MODE	Channel 11	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	25 deg. C, 67 %RH, 1005 hPa	TESTED BY: Cody Chang	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.170	0.10	48.62	-	48.72	-	64.98	54.98	-16.26	-
2	0.228	0.10	45.01	-	45.11	-	62.52	52.52	-17.41	-
3	0.287	0.10	37.57	-	37.67	-	60.62	50.62	-22.95	-
4	0.341	0.10	34.93	-	35.03	-	59.17	49.17	-24.14	-
5	0.459	0.11	30.22	-	30.33	-	56.72	46.72	-26.39	-
6	3.656	0.38	26.35	-	26.73	-	56.00	46.00	-29.27	-

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
* HP Spectrum Analyzer	8590L	3544A01176	May 13, 2003
* HP Preamplifier	8447D	2944A08485	Apr. 29, 2003
* HP Preamplifier	8449B	3008A01201	Dec. 06, 2002
* HP Preamplifier	8449B	3008A01292	Aug. 07, 2003
* ROHDE & SCHWARZ TEST RECEIVER	ESMI	839013/007 839379/002	Jan. 27, 2003
SCHWARZBECK Tunable Dipole Antenna	VHA 9103 UHA 9105	E101051 E101055	Nov. 23, 2002
ANTENNA (Large Biconical)	VHBA9123	449	Dec. 10, 2002
* CHASE BILOG Antenna	CBL6112A	2221	Aug. 02, 2003
* SCHWARZBECK Horn Antenna	BBHA9120-D1	D130	Jul. 03, 2003
* EMCO Horn Antenna	3115	9312-4192	Apr. 09, 2003
* EMCO Turn Table	1060	1115	NA
* SHOSHIN Tower	AP-4701	A6Y005	NA
* Software	AS61D4	NA	NA
* ANRITSU RF Switches	MP59B	M35046	Jan. 25, 2003
* TIMES RF cable	LMR-600	CABLE-ST5-01	Jul. 12, 2003
Open Field Test Site	Site 5	ADT-R05	Jul. 19, 2003
VCCI Site Registration No.	Site 5	R-1039	NA

- NOTE:** 1. The measurement uncertainty is less than $\pm 3.0\text{dB}$, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.
3. "*" = These equipment are used for the final measurement.
4. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
5. The test was performed in ADT Open Site No. 5.



4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using the quasi-peak method or average method as specified and then reported in Data sheet peak mode and QP mode.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 300 Hz for Average detection (AV) at frequency above 1GHz.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6

4.2.7 TEST RESULTS (A)

EUT	Wireless USB Adapter	MODEL	UW320-IF
MODE	Channel 11	FREQUENCY RANGE	30-1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	35 deg. C, 50%RH, 1005 hPa	TESTED BY: Bunny Yao	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	144.00	24.3 QP	43.50	-19.20	1.48H	132	11.12	10.58	2.60	0.00	-13.18
2	176.00	25.0 QP	43.50	-18.50	1.64H	124	12.64	9.08	3.28	0.00	-12.37
3	240.00	27.6 QP	46.00	-18.40	1.14H	258	12.03	11.41	4.16	0.00	-15.57
4	264.00	24.3 QP	46.00	-21.70	1.53H	58	6.98	12.89	4.44	0.00	-17.32
5	296.00	26.0 QP	46.00	-20.00	1.28H	130	7.96	13.12	4.92	0.00	-18.05
6	336.00	31.6 QP	46.00	-14.40	1.31H	84	12.22	13.92	5.45	0.00	-19.38
7	360.00	25.3 QP	46.00	-20.70	1.39H	226	4.95	14.58	5.77	0.00	-20.36
8	400.00	32.0 QP	46.00	-14.00	1.25H	327	9.63	16.11	6.27	0.00	-22.38
9	460.00	30.5 QP	46.00	-15.50	1.35H	186	6.86	16.53	7.11	0.00	-23.65

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	72.00	24.5 QP	40.00	-15.50	1.11V	78	16.56	6.45	1.50	0.00	-7.94
2	84.00	24.4 QP	40.00	-15.60	1.41V	115	15.04	7.63	1.71	0.00	-9.35
3	108.00	26.1 QP	43.50	-17.40	1.41V	265	13.15	10.87	2.08	0.00	-12.95
4	144.00	23.0 QP	43.50	-20.50	1.25V	48	9.82	10.58	2.60	0.00	-13.19
5	176.00	21.5 QP	43.50	-22.00	1.42V	277	9.14	9.08	3.28	0.00	-12.37
6	240.00	28.8 QP	46.00	-17.20	1.82V	54	13.23	11.41	4.16	0.00	-15.57
7	384.00	24.5 QP	46.00	-21.50	1.64V	71	2.94	15.50	6.06	0.00	-21.57
8	396.00	23.7 QP	46.00	-22.30	1.29V	264	1.54	15.96	6.20	0.00	-22.16
9	528.00	26.3 QP	46.00	-19.70	1.14V	142	0.86	17.62	7.82	0.00	-25.45

- REMARKS:
1. Emission level(dBuV/m)=Raw Value(dBuV) – Correction Factor(dB)
 2. Correction Factor(dB) = Pre-Amplifier Factor (dB) - Antenna Factor (dB) - Cable Factor (dB)
 3. Pre-Amplifier Factor (dB) = 0, when the test receiver is used to read the value and because it did not use the Pre-Amplifier.
 4. The other emission levels were very low against the limit.
 5. Margin value = Emission level – Limit value.

EUT	Wireless USB Adapter	MODEL	UW320-IF
MODE	Channel 1	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	35 deg. C, 50%RH, 1005 hPa	TESTED BY: Bunny Yao	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	2374.00	32.1 AV	54.00	-21.90	1.27H	19	34.46	27.52	4.98	34.90	2.40
2	2374.00	44.4 PK	74.00	-29.60	1.27H	19	46.83	27.52	4.98	34.90	2.40
3	*2412.00	96.1 PK	-	-	1.31H	15	63.38	27.67	5.10	0.00	-32.77
4	*2412.00	87.7 AV	-	-	1.31H	15	54.92	27.67	5.10	0.00	-32.77
5	4824.00	40.7 AV	54.00	-13.30	1.16H	2	36.63	31.52	7.23	34.63	-4.12
6	4824.00	49.8 PK	74.00	-24.20	1.13H	2	45.64	31.52	7.23	34.63	-4.12

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	2374.00	49.7 PK	74.00	-24.30	1.07V	54	52.10	27.52	4.98	34.90	2.40
2	2374.00	37.4 AV	54.00	-16.60	1.07V	54	39.80	27.52	4.98	34.90	2.40
3	*2412.00	101.3 PK	-	-	1.00V	51	68.56	27.67	5.10	0.00	-32.77
4	*2412.00	92.8 AV	-	-	1.00V	51	60.02	27.67	5.10	0.00	-32.77
5	4824.00	47.6 AV	54.00	-6.40	1.14V	71	43.48	31.52	7.23	34.63	-4.12
6	4824.00	59.3 PK	74.00	-14.70	1.14V	71	55.23	31.52	7.23	34.63	-4.12

- REMARKS:
1. Emission level(dBuV/m)=Raw Value(dBuV) – Correction Factor(dB)
 2. Correction Factor(dB) = Pre-Amplifier Factor (dB) - Antenna Factor (dB) - Cable Factor (dB)
 3. Pre-Amplifier Factor (dB) = 0, when the test receiver is used to read the value and because it did not use the Pre-Amplifier.
 4. The other emission levels were very low against the limit.
 5. Margin value = Emission level – Limit value.
 6. “ * ” = Fundamental frequency

EUT	Wireless USB Adapter	MODEL	UW320-IF
MODE	Channel 6	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	35 deg. C, 50%RH, 1005 hPa	TESTED BY: Bunny Yao	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	*2437.00	87.9 AV	-	-	1.31H	41	55.00	27.81	5.08	0.00	-32.89
2	*2437.00	96.7 PK	-	-	1.31H	41	63.82	27.81	5.08	0.00	-32.89
3	4874.00	41.1 AV	54.00	-12.90	1.03H	32	36.90	31.59	7.21	34.63	-4.17
4	4874.00	49.7 PK	74.00	-24.30	1.03H	32	45.50	31.59	7.21	34.63	-4.18

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	*2437.00	101.8 PK	-	-	1.06V	67	68.92	27.81	5.08	0.00	-32.89
2	*2437.00	93.7 AV	-	-	1.06V	67	60.78	27.81	5.08	0.00	-32.89
3	4874.00	56.2 PK	74.00	-17.80	1.13V	49	52.00	31.59	7.21	34.63	-4.18
4	4874.00	48.1 AV	54.00	-5.90	1.13V	49	43.90	31.59	7.21	34.63	-4.17

- REMARKS:
1. Emission level(dBuV/m)=Raw Value(dBuV) – Correction Factor(dB)
 2. Correction Factor(dB) = Pre-Amplifier Factor (dB) - Antenna Factor (dB) - Cable Factor (dB)
 3. Pre-Amplifier Factor (dB) = 0, when the test receiver is used to read the value and because it did not use the Pre-Amplifier.
 4. The other emission levels were very low against the limit.
 5. Margin value = Emission level – Limit value.
 6. “ * ” = Fundamental frequency



EUT	Wireless USB Adapter	MODEL	UW320-IF
MODE	Channel 11	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	35 deg. C, 50%RH, 1005 hPa	TESTED BY: Bunny Yao	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	*2462.00	87.5 AV	-	-	1.36H	4	54.56	27.81	5.08	0.00	-32.89
2	*2462.00	95.9 PK	-	-	1.36H	4	63.05	27.81	5.08	0.00	-32.89
3	2500.00	33.4 AV	54.00	-20.60	1.28H	41	35.26	27.96	5.06	34.90	1.89
4	2500.00	45.2 PK	74.00	-28.80	1.28H	41	47.12	27.96	5.06	34.90	1.90
5	4924.00	49.2 PK	74.00	-24.80	1.08H	44	45.00	31.66	7.21	34.62	-4.25
6	4924.00	40.5 AV	54.00	-13.50	1.08H	44	36.23	31.66	7.21	34.62	-4.25

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	*2462.00	92.7 AV	-	-	1.08V	64	59.81	27.81	5.08	0.00	-32.89
2	*2462.00	101.0 PK	-	-	1.08V	64	68.06	27.81	5.08	0.00	-32.89
3	2500.00	39.5 AV	54.00	-14.50	1.00V	67	41.41	27.96	5.06	34.90	1.89
4	2500.00	51.1 PK	74.00	-22.90	1.00V	67	52.99	27.96	5.06	34.90	1.90
5	4924.00	48.0 AV	54.00	-6.00	1.00V	57	43.70	31.66	7.21	34.62	-4.25
6	4924.00	55.0 PK	74.00	-19.00	1.00V	57	50.71	31.66	7.21	34.62	-4.25

- REMARKS:
1. Emission level(dBuV/m)=Raw Value(dBuV) – Correction Factor(dB)
 2. Correction Factor(dB) = Pre-Amplifier Factor (dB) - Antenna Factor (dB) - Cable Factor (dB)
 3. Pre-Amplifier Factor (dB) = 0, when the test receiver is used to read the value and because it did not use the Pre-Amplifier.
 4. The other emission levels were very low against the limit.
 5. Margin value = Emission level – Limit value.
 6. “ * ” = Fundamental frequency

4.2.8 TEST RESULTS (B)

EUT	Wireless USB Adapter	MODEL	UW320-IF
MODE	Channel 11	FREQUENCY RANGE	30-1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	25 deg. C, 60%RH, 1005 hPa	TESTED BY: Gary Chang	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	240.00	27.0 QP	46.00	-19.00	1.32H	124	11.04	11.41	4.55	0.00	-15.96
2	336.00	31.0 QP	46.00	-15.00	1.05H	303	11.55	13.92	5.53	0.00	-19.45
3	352.00	31.2 QP	46.00	-14.80	1.04H	3	11.16	14.31	5.73	0.00	-20.04
4	384.00	28.4 QP	46.00	-17.60	1.06H	224	6.88	15.50	6.02	0.00	-21.52
5	432.00	29.5 QP	46.00	-16.50	1.02H	100	6.79	16.28	6.43	0.00	-22.71
6	748.20	32.0 QP	46.00	-14.00	1.41H	266	3.11	20.14	8.75	0.00	-28.89

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	132.00	30.2 QP	43.50	-13.30	1.28V	351	15.67	11.16	3.37	0.00	-14.53
2	176.00	29.5 pk	43.50	-14.00	1.01V	95	45.31	9.08	3.80	28.71	15.84
3	180.00	29.1 QP	43.50	-14.40	1.09V	26	16.32	8.91	3.86	0.00	-12.79
4	240.00	27.0 QP	46.00	-19.00	1.27V	216	11.04	11.41	4.55	0.00	-15.96
5	336.00	31.5 QP	46.00	-14.50	1.47V	350	12.05	13.92	5.53	0.00	-19.45
6	420.00	30.1 QP	46.00	-15.90	1.05V	153	7.56	16.21	6.33	0.00	-22.55
7	440.00	27.0 QP	46.00	-19.00	1.35V	63	4.20	16.32	6.49	0.00	-22.80
8	528.00	29.0 QP	46.00	-17.00	1.06V	291	4.37	17.62	7.00	0.00	-24.64
9	748.00	30.2 QP	46.00	-15.80	1.47V	307	1.31	20.14	8.75	0.00	-28.90

- REMARKS:
1. Emission level(dBuV/m)=Raw Value(dBuV) – Correction Factor(dB)
 2. Correction Factor(dB) = Pre-Amplifier Factor (dB) - Antenna Factor (dB) - Cable Factor (dB)
 3. Pre-Amplifier Factor (dB) = 0, when the test receiver is used to read the value and because it did not use the Pre-Amplifier.
 4. The other emission levels were very low against the limit.
 5. Margin value = Emission level – Limit value.

EUT	Wireless USB Adapter	MODEL	UW320-IF
MODE	Channel 1	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60%RH, 1005 hPa	TESTED BY: Gary Chang	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	2372.00	46.2 PK	74.00	-27.80	1.55H	331	53.00	27.52	2.40	36.73	6.80
2	*2412.00	107.5 PK	-	-	1.00H	338	114.00	27.67	2.53	36.72	6.52
3	*2412.00	99.5 AV	-	-	1.00H	338	106.00	27.67	2.53	36.72	6.52
4	4824.00	48.0 PK	74.00	-26.00	1.64H	27	49.20	31.52	4.01	36.70	1.18
5	7236.00	48.0 PK	74.00	-26.00	1.50H	283	43.20	36.20	5.58	37.00	-4.78
6	9648.00	50.4 PK	74.00	-23.60	1.02H	15	43.80	38.45	5.76	37.63	-6.59

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	2385.00	51.5 PK	74.00	-22.50	1.28V	3	58.00	27.67	2.53	36.72	6.52
2	2385.00	40.5 AV	54.00	-13.50	1.28V	3	47.00	27.67	2.53	36.72	6.52
3	*2412.00	97.0 AV	-	-	1.90V	0	103.50	27.67	2.53	36.72	6.53
4	*2412.00	104.5 PK	-	-	1.90V	0	111.00	27.67	2.53	36.72	6.53
5	4824.00	48.8 PK	74.00	-25.20	1.11V	337	50.00	31.52	4.01	36.70	1.18
6	7236.00	46.8 PK	74.00	-27.20	1.34V	13	42.00	36.20	5.58	37.00	-4.78
7	9648.00	51.1 PK	74.00	-22.90	1.27V	274	44.50	38.45	5.76	37.63	-6.58

- REMARKS:
1. Emission level(dBuV/m)=Raw Value(dBuV) – Correction Factor(dB)
 2. Correction Factor(dB) = Pre-Amplifier Factor (dB) - Antenna Factor (dB) - Cable Factor (dB)
 3. Pre-Amplifier Factor (dB) = 0, when the test receiver is used to read the value and because it did not use the Pre-Amplifier.
 4. The other emission levels were very low against the limit.
 5. Margin value = Emission level – Limit value.
 6. “ * ” = Fundamental frequency



EUT	Wireless USB Adapter	MODEL	UW320-IF
MODE	Channel 6	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60%RH, 1005 hPa	TESTED BY: Gary Chang	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	*2437.00	107.6 PK	-	-	1.00H	333	113.80	27.81	2.66	36.71	6.24
2	*2437.00	99.4 AV	-	-	1.00H	333	105.60	27.81	2.66	36.71	6.24
3	4874.00	48.4 PK	74.00	-25.60	1.54H	15	49.50	31.59	4.03	36.70	1.08
4	7311.00	48.9 PK	74.00	-25.10	1.11H	306	44.00	36.26	5.65	37.02	-4.90
5	9748.00	50.3 PK	74.00	-23.70	1.37H	135	43.80	38.50	5.66	37.65	-6.51

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	*2437.00	107.0 PK	-	-	1.23V	51	113.20	27.81	2.66	36.71	6.24
2	*2437.00	99.1 AV	-	-	1.23V	51	105.30	27.81	2.66	36.71	6.24
3	4874.00	47.9 PK	74.00	-26.10	1.27V	8	49.00	31.59	4.03	36.70	1.08
4	7311.00	48.4 PK	74.00	-25.60	1.19V	0	43.50	36.26	5.65	37.02	-4.91
5	9748.00	53.5 PK	74.00	-20.50	1.33V	266	47.00	38.50	5.66	37.65	-6.51
6	9748.00	46.5 AV	54.00	-7.50	1.33V	266	40.00	38.50	5.66	37.65	-6.51

- REMARKS:
1. Emission level(dBuV/m)=Raw Value(dBuV) – Correction Factor(dB)
 2. Correction Factor(dB) = Pre-Amplifier Factor (dB) - Antenna Factor (dB) - Cable Factor (dB)
 3. Pre-Amplifier Factor (dB) = 0, when the test receiver is used to read the value and because it did not use the Pre-Amplifier.
 4. The other emission levels were very low against the limit.
 5. Margin value = Emission level – Limit value.
 6. “ * ” = Fundamental frequency



EUT	Wireless USB Adapter	MODEL	UW320-IF
MODE	Channel 11	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60%RH, 1005 hPa	TESTED BY: Gary Chang	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	*2463.00	107.0 PK	-	-	1.19H	252	113.20	27.81	2.66	36.71	6.24
2	*2463.00	98.8 AV	-	-	1.19H	252	105.00	27.81	2.66	36.71	6.24
3	2491.00	50.0 PK	74.00	-24.00	1.29H	249	56.00	27.96	2.78	36.70	5.96
4	4924.00	44.0 PK	74.00	-30.00	1.65H	9	45.00	31.66	4.06	36.70	1.00
5	7387.00	48.6 PK	74.00	-25.40	1.13H	176	43.50	36.40	5.79	37.05	-5.14
6	9850.00	50.5 PK	74.00	-23.50	1.54H	319	44.00	38.54	5.59	37.67	-6.46

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	*2463.00	98.3 AV	-	-	1.19V	36	104.50	27.81	2.66	36.71	6.24
2	*2463.00	106.6 PK	-	-	1.19V	36	112.80	27.81	2.66	36.71	6.24
3	2498.00	48.0 PK	74.00	-26.00	1.16V	4	54.00	27.96	2.78	36.70	5.96
4	4924.00	47.5 PK	74.00	-26.50	1.10V	36	48.50	31.66	4.06	36.70	1.00
5	7387.00	48.6 PK	74.00	-25.40	1.25V	296	43.50	36.40	5.79	37.05	-5.14
6	9850.00	52.5 PK	74.00	-21.50	1.24V	9	46.00	38.54	5.59	37.67	-6.46
7	9850.00	45.5 AV	54.00	-8.50	1.24V	9	39.00	38.54	5.59	37.67	-6.46

- REMARKS:
1. Emission level(dBuV/m)=Raw Value(dBuV) – Correction Factor(dB)
 2. Correction Factor(dB) = Pre-Amplifier Factor (dB) - Antenna Factor (dB) - Cable Factor (dB)
 3. Pre-Amplifier Factor (dB) = 0, when the test receiver is used to read the value and because it did not use the Pre-Amplifier.
 4. The other emission levels were very low against the limit.
 5. Margin value = Emission level – Limit value.
 6. “ * ” = Fundamental frequency

4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	July 24, 2003

Notes:

1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 kHz RBW and 100 kHz VBW. The 6 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6 dB.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation

4.3.5 TEST SETUP



4.3.6 EUT OPERATING CONDITIONS


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 TEST RESULTS

EUT	Wireless USB Adapter	MODEL	UW320-IF
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	23 deg. C, 68 %RH, 1005 hPa
TESTED BY: Steven Lu			

CHANNEL	CHANNEL FREQUENCY (MHz)	6 dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	11.68	0.5	PASS
6	2437	11.72	0.5	PASS
11	2462	11.68	0.5	PASS


CH1



Date: 16.NOV.2002 11:25:17




CH6



Date: 16.NOV.2002 11:28:23

CH11



4.4 MAXIMUM PEAK OUTPUT POWER

4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

4.4.2 INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
Peak Power Sensor	NRV-Z32	100013	Feb. 21, 2003
Power Meter	NRVS	100026	Feb. 21, 2003

- NOTE:** 1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.4.3 TEST PROCEDURES

The transmitter output was connected to the peak power meter.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation

4.4.5 TEST SETUP



4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6

4.4.7 TEST RESULTS

EUT	Wireless USB Adapter	MODEL	UW320-IF
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	23 deg. C, 68 %RH, 1005 hPa
TESTED BY: Steven Lu			

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	14.40	30	PASS
6	2437	14.43	30	PASS
11	2462	14.43	30	PASS

4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	July 24, 2003

NOTE: 1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.5.3 TEST PROCEDURE


The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3 kHz RBW and 30 kHz VBW, set sweep time = span/3 kHz. The power spectral density was measured and recorded.

The sweep time is allowed to be longer than span/3 kHz for a full response of the mixer in the spectrum analyzer.

4.5.4 DEVIATION FROM TEST STANDARD

No deviation

4.5.5 TEST SETUP



4.5.6 EUT OPERATING CONDITION


Same as Item 4.3.6

4.5.7 TEST RESULTS


EUT	Wireless USB Adapter	MODEL	UW320-IF
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	23 deg. C, 68 %RH, 1005 hPa
TESTED BY: Steven Lu			

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3 kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-9.78	8	PASS
6	2437	-9.72	8	PASS
11	2462	-9.37	8	PASS


CH1



CH6



CH11



Date: 16.NOV.2002 11:39:41

4.6 BAND EDGES MEASUREMENT

4.6.1 LIMITS OF BAND EDGES MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100KHz Resolution Bandwidth).

4.6.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	July 24, 2003

NOTE:

- 1.The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
- 2.The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz with suitable frequency span including 100 kHz bandwidth from band edge. The band edges was measured and recorded.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation



4.6.5 EUT OPERATING CONDITION


Same as Item 4.3.6

4.6.6 TEST RESULTS


The spectrum plots are attached on the following 2 pages. D2 line indicates the highest level, D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(C).

NOTE1: The band edge emission plot on the following first page shows 52.42dB delta between carrier maximum power and local maximum emission in restrict band (2.3750GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.8 (page 34) is 99.5dBuV/m, so the maximum field strength in restrict band is $99.5 - 52.42 = 47.08$ dBuV/m which is under 54 dBuV/m limit.

NOTE2: The band edge emission plot on the following second page shows 53.47dB delta between carrier maximum power and local maximum emission in restrict band (2.4998GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.8 is 98.8dBuV/m, so the maximum field strength in restrict band is $98.8 - 53.47 = 45.33$ dBuV/m which is under 54 dBuV/m limit.



Date: 16.NOV.2002 11:20:53



Date: 16.NOV.2002 11:32:31



4.7 ANTENNA REQUIREMENT

4.7.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.7.2 ANTENNA CONNECTED CONSTRUCTION

There are two antennas provided to this EUT. One is Dipole antenna with UFL connector. Another is Inverted F antenna with no connector. The maximum Gain of the antenna is 1dBi only.

5 PHOTOGRAPHS OF THE TEST CONFIGURATION

CONDUCTED EMISSION TEST



RADIATED EMISSION TEST





6 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025, Guide 25 or EN 45001:

USA	FCC, NVLAP, UL
Germany	TUV Rheinland
Japan	VCCI
New Zealand	MoC
Norway	NEMKO
R.O.C.	BSMI, DGT, CNLA

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

www.adt.com.tw/index.5/phtml.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC Lab:

Tel: 886-2-26052180

Fax: 886-2-26052943

Hsin Chu EMC Lab:

Tel: 886-35-935343

Fax: 886-35-935342

Lin Kou Safety Lab:

Tel: 886-2-26093195

Fax: 886-2-26093184

Lin Kou RF&Telecom Lab

Tel: 886-3-3270910

Fax: 886-3-3270892

Email: service@mail.adt.com.tw

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.