

MPE Calculation page

MPE Calculator	Dynastream	Test Number	090702A
MPE uses EIRP for calculation. EIRP is based on TX power added to the antenna gain in dBi.			
dBi = dB gain compared to an isotropic radiator.			
S = power density in mW/cm <sup>2</sup>		Antenna Gain (dBi)	2.2
Output Power		dBd + 2.17 = dBi	dBi to dBd 2.17
Tx Frequency (MHz)	2441	(Watts)	0.000238
Cable Loss (dB)		(dBm)	-6.23
Antenna minus cable (dBi)			2.20
Calculated ERP (mw)		0.240	Radiated (EIRP) dBm -4.034
Calculated EIRP (mw)		0.395	
			Radiated (ERP) dBm -6.204
<b>Occupational Limit</b>	<b>5.00000</b>	Power density (S) = EIRP ----- = mW/cm <sup>2</sup> 4 p r <sup>2</sup> [ r (cm), EIRP (mW)]	
<b>General Public Limit</b>	<b>1.00000</b>		
FCC radio frequency radiation exposure limits per 1.1310			
Frequency (MHz)	Occupational Limit	Public Limit	
300-1,500	f/300	f/1500	
1,500-10,000	5	1	
FCC radio frequency radiation exposure limits per 1.1310			
Frequency (MHz)	Occupational Limit @ Tx Freq (mW/cm <sup>2</sup> )	Public Limit @ Tx Freq (mW/cm <sup>2</sup> )	
300-1,500	8.136666667	1.627333333	
1,500-10,000	5	1	
EIRP	Distance	Distance	S
milliwatts	cm	inches	mW/cm <sup>2</sup>
0.395	10.00	3.94	0.00031
0.395	9.00	3.54	0.00039
0.395	8.00	3.15	0.00049
0.395	7.00	2.76	0.00064
0.395	6.00	2.36	0.00087
0.395	5.00	1.97	0.00126
0.395	4.00	1.57	0.00196
0.395	3.00	1.18	0.00349
0.395	2.00	0.79	0.00786
0.395	1.00	0.39	0.03143
0.395	0.50	0.20	0.12573
0.395	0.40	0.16	0.19645
0.395	0.30	0.12	0.34924
0.395	0.20	0.08	0.78579
0.395	0.18	0.07	0.97011
Frequency (MHz)	Occupational Limit minimum Distance (cm)	Public Limit minimum distance (cm)	
300-1,500	N/A	N/A	
1,500-10,000	N/A	0.18	