

MPE Calculation page

MPE Calculator	Dynastream	Test Number	090419
MPE uses EIRP for calculation. EIRP is based on TX power added to the antenna gain in dBi.			
	dBi = dB gain compared to an isotropic radiator.		
	S = power density in mW/cm ²	Antenna Gain (dBi)	2.2
	Output Power (Watts)	dBd + 2.17 = dBi	dBi to dBd 2.17
Tx Frequency (MHz)	2440	0.000465	0.03
Cable Loss (dB)	0.0	(dBm) -3.33	Antenna minus cable (dBi) 2.20
	Calculated ERP (mw)	0.468	Radiated (EIRP) dBm -1.129
	Calculated EIRP (mw)	0.771	Radiated (ERP) dBm -3.299
Occupational Limit	5.00000	Power density (S) = EIRP ----- = mW/cm ² 4 π r ² [r (cm), EIRP (mW)]	
General Public Limit	1.00000		
FCC radio frequency radiation exposure limits per 1.1310			
Frequency (MHz)	Occupational Limit	Public Limit	
300-1,500	f/300	f/1500	
1,500-10,000	5	1	
FCC radio frequency radiation exposure limits per 1.1310			
Frequency (MHz)	Occupational Limit @ Tx Freq (mW/cm ²)	Public Limit @ Tx Freq (mW/cm ²)	
300-1,500	8.133333333	1.626666667	
1,500-10,000	5	1	
EIRP	Distance	Distance	S
milliwatts	cm	inches	mW/cm ²
0.771	10.00	3.94	0.00061
0.771	9.00	3.54	0.00076
0.771	8.00	3.15	0.00096
0.771	7.00	2.76	0.00125
0.771	6.00	2.36	0.00170
0.771	5.00	1.97	0.00245
0.771	4.00	1.57	0.00384
0.771	3.00	1.18	0.00682
0.771	2.00	0.79	0.01534
0.771	1.00	0.39	0.06136
0.771	0.50	0.20	0.24545
0.771	0.40	0.16	0.38352
0.771	0.25	0.10	0.98182
0.771	0.20	0.08	1.53409
0.771	0.19	0.07	1.69982
Frequency (MHz)	Occupational Limit minimum Distance (cm)	Public Limit minimum distance (cm)	
300-1,500	N/A	N/A	
1,500-10,000	N/A	0.25	