

MPE Calculation page

MPE Calculator	Dynastream	Test Number	090518	
MPE uses EIRP for calculation. EIRP is based on TX power added to the antenna gain in dBi.				
	dBi = dB gain compared to an isotropic radiator.			
	S = power density in mW/cm^2	Antenna Gain (dBi)	2.2	
	Output Power	dBd + 2.17 = dBi	dBi to dBd 2.17	
Tx Frequency (MHz)	2457	(Watts)	0.000627	
		Antenna minus cable (dBi)	2.20	
Cable Loss (dB)	0.0	(dBm)	-2.03	
	Calculated ERP (mw)	0.631	Radiated (EIRP) dBm 0.17	
	Calculated EIRP (mw)	1.040		
			Radiated (ERP) dBm -1.999	
Occupational Limit	Power density (S) = EIRP ----- = mW/cm^2 4 p r^2 [r (cm), EIRP (mW)]			
5.00000				
General Public Limit				
1.00000				
	FCC radio frequency radiation exposure limits per 1.1310			
	Frequency (MHz)	Occupational Limit	Public Limit	
	300-1,500	f/300	f/1500	
	1,500-10,000	5	1	
	FCC radio frequency radiation exposure limits per 1.1310			
	Frequency (MHz)	Occupational Limit @ Tx Freq (mW/cm^2)	Public Limit @ Tx Freq (mW/cm^2)	
	300-1,500	8.19	1.638	
	1,500-10,000	5	1	
	EIRP	Distance	Distance	S
	milliwatts	cm	inches	mW/cm^2
	1.040	10.00	3.94	0.00083
	1.040	9.00	3.54	0.00102
	1.040	8.00	3.15	0.00129
	1.040	7.00	2.76	0.00169
	1.040	6.00	2.36	0.00230
	1.040	5.00	1.97	0.00331
	1.040	4.00	1.57	0.00517
	1.040	3.00	1.18	0.00920
	1.040	2.00	0.79	0.02069
	1.040	1.00	0.39	0.08278
	1.040	0.50	0.20	0.33111
	1.040	0.40	0.16	0.51736
	1.040	0.30	0.12	0.91975
	1.040	0.28	0.11	1.05583
	1.040	0.20	0.08	2.06943
	Frequency (MHz)	Occupational Limit minimum Distance (cm)	Public Limit minimum distance (cm)	
	300-1,500	N/A	N/A	
	1,500-10,000	N/A	0.30	