

ATTACHMENT O – SAR TEST PLOTS (2 of 3)

Test Laboratory: HCT

MODEL: CDM7075

Company : UTStarcom Inc.

Mode : PCS 1900 / Channel : 25

Liquid Temperature : 21.5 °C

Date Tested : February 03, 2006

DUT: CDM7075; Type: Folder; Serial: #1

Communication System: PCS1900; Frequency: 1851.25 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1851.25$ MHz; $\sigma = 1.41$ mho/m; $\epsilon_r = 40.3$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1607; ConvF(5.14, 5.14, 5.14); Calibrated: 2005-08-30

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn614; Calibrated: 2005-04-21

- Phantom: SAM 1800/1900 MHz; Type: SAM

Left touch 25/Area Scan (51x101x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (interpolated) = 1.25 mW/g

Left touch 25/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 26.8 V/m; Power Drift = 0.088 dB

Peak SAR (extrapolated) = 1.74 W/kg

SAR(1 g) = 1.09 mW/g; SAR(10 g) = 0.602 mW/g

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 1.22 mW/g

Left touch 25/Zoom Scan (5x5x7)/Cube 1: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm


Reference Value = 26.8 V/m; Power Drift = 0.088 dB

Peak SAR (extrapolated) = 1.08 W/kg

SAR(1 g) = 0.758 mW/g; SAR(10 g) = 0.458 mW/g

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.821 mW/g



Test Laboratory: HCT

MODEL: CDM7075

Company: UTStarcom Inc.

Mode: PCS1900 / Channel: 25

Liquid Temperature: 21.5 °C

Date Tested: February 03, 2006

DUT: CDM7075; Type: Folder; Serial: #1

Communication System: PCS1900; Frequency: 1851.25 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1851.25 \text{ MHz}$; $\sigma = 1.41 \text{ mho/m}$; $\epsilon_r = 40.3$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1607; ConvF(5.14, 5.14, 5.14); Calibrated: 2005-08-30

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn614; Calibrated: 2005-04-21

- Phantom: SAM 1800/1900 MHz; Type: SAM

Left touch 25/Area Scan (61x101x1): Measurement grid: $\Delta x = 15\text{mm}$, $\Delta y = 15\text{mm}$

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (interpolated) = 0.411 mW/g

Left touch 25/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $\Delta x = 8\text{mm}$, $\Delta y = 8\text{mm}$, $\Delta z = 5\text{mm}$


Reference Value = 17.2 V/m; Power Drift = 0.044 dB

Peak SAR (extrapolated) = 0.660 W/kg

SAR(1 g) = 0.372 mW/g; SAR(10 g) = 0.192 mW/g

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.436 mW/g



0 dB = 0.436mW/g

Test Laboratory: HCT

MODEL: CDM7075

Company : UTStarcom Inc.

Mode : PCS 1900 / Channel : 600

Liquid Temperature : 21.5 °C

Date Tested : February 03, 2006

DUT: CDM7075; Type: Folder; Serial: #1

Communication System: PCS1900; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 40.2$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1607; ConvF(5.14, 5.14, 5.14); Calibrated: 2005-08-30

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn614; Calibrated: 2005-04-21

- Phantom: SAM 1800/1900 MHz; Type: SAM

Left touch 600/Area Scan (51x101x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (interpolated) = 1.52 mW/g

Left touch 600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 30.4 V/m; Power Drift = 0.197 dB

Peak SAR (extrapolated) = 2.10 W/kg

SAR(1 g) = 1.3 mW/g; SAR(10 g) = 0.716 mW/g

Maximum value of SAR (measured) = 1.48 mW/g


Left touch 600/Zoom Scan (5x5x7)/Cube 1: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 30.4 V/m; Power Drift = 0.197 dB

Peak SAR (extrapolated) = 1.24 W/kg

SAR(1 g) = 0.861 mW/g; SAR(10 g) = 0.513 mW/g

Maximum value of SAR (measured) = 0.949 mW/g



0 dB = 0.949mW/g

Test Laboratory: HCT

MODEL: CDM7075

Company : UTStarcom Inc.

Mode : PCS 1900 / Channel : 600

Liquid Temperature : 21.5 °C

Date Tested : February 03, 2006

DUT: CDM7075; Type: Folder; Serial: #1

Communication System: PCS1900; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 40.2$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1607; ConvF(5.14, 5.14, 5.14); Calibrated: 2005-08-30

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn614; Calibrated: 2005-04-21

- Phantom: SAM 1800/1900 MHz; Type: SAM

Left touch 600/Area Scan (61x101x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (interpolated) = 0.414 mW/g


Left touch 600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 17.6 V/m; Power Drift = -0.082 dB

Peak SAR (extrapolated) = 0.631 W/kg

SAR(1 g) = 0.366 mW/g; SAR(10 g) = 0.205 mW/g

Maximum value of SAR (measured) = 0.425 mW/g



Test Laboratory: HCT

MODEL: CDM7075

Company : UTStarcom Inc.

Mode : PCS1900 / Channel : 1175

Liquid Temperature : 21.5 °C

Date Tested : February 03, 2006

DUT: CDM7075; Type: Folder; Serial: #1

Communication System: PCS1900; Frequency: 1908.75 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1908.75$ MHz; $\sigma = 1.45$ mho/m; $\epsilon_r = 40$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1607; ConvF(5.14, 5.14, 5.14); Calibrated: 2005-08-30

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn614; Calibrated: 2005-04-21

- Phantom: SAM 1800/1900 MHz; Type: SAM

Left touch 1175/Area Scan (51x101x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (interpolated) = 1.47 mW/g

Left touch 1175/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm


Reference Value = 29.4 V/m; Power Drift = -0.192 dB

Peak SAR (extrapolated) = 2.07 W/kg

SAR(1 g) = 1.27 mW/g; SAR(10 g) = 0.700 mW/g

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 1.41 mW/g



0 dB = 1.41 mW/g

Test Laboratory: HCT

MODEL: CDM7075

Company : UTStarcom Inc.

Mode : PCS 1900 / Channel : 1175

Liquid Temperature : 21.5 °C

Date Tested : February 03, 2006

DUT: CDM7075; Type: Folder; Serial: #1

Communication System: PCS1900; Frequency: 1908.75 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1908.75 \text{ MHz}$; $\sigma = 1.45 \text{ mho/m}$; $\epsilon_r = 40$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1607; ConvF(5.14, 5.14, 5.14); Calibrated: 2005-08-30

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn614; Calibrated: 2005-04-21

- Phantom: SAM 1800/1900 MHz; Type: SAM

Left touch 1175/Area Scan (61x101x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (interpolated) = 0.637 mW/g

Left touch 1175/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$


Reference Value = 21.4 V/m; Power Drift = 0.019 dB

Peak SAR (extrapolated) = 0.915 W/kg

SAR(1 g) = 0.545 mW/g; SAR(10 g) = 0.309 mW/g

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.597 mW/g



0 dB = 0.597mW/g

Test Laboratory: HCT

MODEL: CDM7075

Company : UTStarcom Inc.

Mode : PCS 1900 / Channel : 25

Liquid Temperature : 21.5 °C

Date Tested : February 03, 2006

DUT: CDM7075; Type: Folder; Serial: #1

Communication System: PCS 1900; Frequency: 1851.25 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1851.25$ MHz; $\sigma = 1.41$ mho/m; $\epsilon_r = 40.3$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1607; ConvF(5.14, 5.14, 5.14); Calibrated: 2005-08-30

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn614; Calibrated: 2005-04-21

- Phantom: SAM 1800/1900 MHz; Type: SAM

Right touch 25/Area Scan (51x101x1): Measurement grid: $\Delta x = 15$ mm, $\Delta y = 15$ mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (interpolated) = 1.16 mW/g

Right touch 25/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $\Delta x = 8$ mm, $\Delta y = 8$ mm, $\Delta z = 5$ mm


Reference Value = 28.0 V/m; Power Drift = -0.170 dB

Peak SAR (extrapolated) = 1.75 W/kg

SAR(1 g) = 1.11 mW/g; SAR(10 g) = 0.628 mW/g

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 1.24 mW/g



0 dB = 1.24mW/g

Test Laboratory: HCT

MODEL: CDM7075

Company : UTStarcom Inc.

Mode : PCS 1900 / Channel : 25

Liquid Temperature : 21.5 °C

Date Tested : February 03, 2006

DUT: CDM7075; Type: Folder; Serial: #1

Communication System: PCS 1900; Frequency: 1851.25 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1851.25$ MHz; $\sigma = 1.41$ mho/m; $\epsilon_r = 40.3$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1607; ConvF(5.14, 5.14, 5.14); Calibrated: 2005-08-30

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn614; Calibrated: 2005-04-21

- Phantom: SAM 1800/1900 MHz; Type: SAM

Right touch 25/Area Scan (51x101x1): Measurement grid: $\Delta x = 15$ mm, $\Delta y = 15$ mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (interpolated) = 0.555 mW/g

Right touch 25/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $\Delta x = 8$ mm, $\Delta y = 8$ mm, $\Delta z = 5$ mm


Reference Value = 14.0 V/m; Power Drift = 0.143 dB

Peak SAR (extrapolated) = 0.815 W/kg

SAR(1 g) = 0.486 mW/g; SAR(10 g) = 0.267 mW/g

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.510 mW/g



Test Laboratory: HCT

MODEL: CDM7075

Company : UTStarcom Inc.

Mode : PCS 1900 / Channel : 600

Liquid Temperature : 21.5 °C

Date Tested : February 03, 2006

DUT: CDM7075; Type: Folder; Serial: #1

Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 40.2$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1607; ConvF(5.14, 5.14, 5.14); Calibrated: 2005-08-30

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn614; Calibrated: 2005-04-21

- Phantom: SAM 1800/1900 MHz; Type: SAM

Right touch 600/Area Scan (51x101x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (interpolated) = 1.45 mW/g


Right touch 600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 29.8 V/m; Power Drift = -0.061 dB

Peak SAR (extrapolated) = 2.15 W/kg

SAR(1 g) = 1.35 mW/g; SAR(10 g) = 0.761 mW/g

Maximum value of SAR (measured) = 1.52 mW/g



Test Laboratory: HCT

MODEL: CDM7075

Company : UTStarcom Inc.

Mode : PCS 1900 / Channel : 600

Liquid Temperature : 21.5 °C

Date Tested : February 03, 2006

DUT: CDM7075; Type: Folder; Serial: #1

Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 40.2$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1607; ConvF(5.14, 5.14, 5.14); Calibrated: 2005-08-30

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn614; Calibrated: 2005-04-21

- Phantom: SAM 1800/1900 MHz; Type: SAM

Right touch 600/Area Scan (51x101x1): Measurement grid: $\Delta x = 15$ mm, $\Delta y = 15$ mm

Maximum value of SAR (interpolated) = 0.535 mW/g


Right touch 600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $\Delta x = 8$ mm, $\Delta y = 8$ mm, $\Delta z = 5$ mm

Reference Value = 14.9 V/m; Power Drift = 0.049 dB

Peak SAR (extrapolated) = 0.828 W/kg

SAR(1 g) = 0.483 mW/g; SAR(10 g) = 0.267 mW/g

Maximum value of SAR (measured) = 0.523 mW/g



Test Laboratory: HCT

MODEL: CDM7075

Company : UTStarcom Inc.

Mode : PCS 1900 / Channel : 1175

Liquid Temperature : 21.5 °C

Date Tested : February 03, 2006

DUT: CDM7075; Type: Folder; Serial: #1

Communication System: PCS 1900; Frequency: 1908.75 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1908.75$ MHz; $\sigma = 1.45$ mho/m; $\epsilon_r = 40$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1607; ConvF(5.14, 5.14, 5.14); Calibrated: 2005-08-30

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn614; Calibrated: 2005-04-21

- Phantom: SAM 1800/1900 MHz; Type: SAM

Right touch 1175/Area Scan (51x101x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (interpolated) = 1.45 mW/g

Right touch 1175/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm


Reference Value = 29.7 V/m; Power Drift = -0.206 dB

Peak SAR (extrapolated) = 2.17 W/kg

SAR(1 g) = 1.36 mW/g; SAR(10 g) = 0.759 mW/g

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 1.54 mW/g



0 dB = 1.54mW/g

Test Laboratory: HCT

MODEL: CDM7075

Company : UTStarcom Inc.

Mode : PCS 1900 / Channel : 1175

Liquid Temperature : 21.5 °C

Date Tested : February 03, 2006

DUT: CDM7075; Type: Folder; Serial: #1

Communication System: PCS 1900; Frequency: 1908.75 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1908.75$ MHz; $\sigma = 1.45$ mho/m; $\epsilon_r = 40$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1607; ConvF(5.14, 5.14, 5.14); Calibrated: 2005-08-30

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn614; Calibrated: 2005-04-21

- Phantom: SAM 1800/1900 MHz; Type: SAM

Right touch 1175/Area Scan (51x101x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (interpolated) = 0.837 mW/g

Right touch 1175/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 19.2 V/m; Power Drift = 0.081 dB

Peak SAR (extrapolated) = 1.34 W/kg

SAR(1 g) = 0.790 mW/g; SAR(10 g) = 0.431 mW/g

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.864 mW/g

Right touch 1175/Zoom Scan (5x5x7)/Cube 1: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm


Reference Value = 19.2 V/m; Power Drift = 0.081 dB

Peak SAR (extrapolated) = 1.18 W/kg

SAR(1 g) = 0.564 mW/g; SAR(10 g) = 0.308 mW/g

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.781 mW/g



Test Laboratory: HCT

MODEL: CDM7075

Company : UTStarcom Inc.

Mode : PCS 1900 / Channel : 600

Liquid Temperature : 21.5 °C

Date Tested : February 03, 2006

DUT: CDM7075; Type: Folder; Serial: #1

Communication System: PCS1900; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.44 \text{ mho/m}$; $\epsilon_r = 40.2$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1607; ConvF(5.14, 5.14, 5.14); Calibrated: 2005-08-30

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn614; Calibrated: 2005-04-21

- Phantom: SAM 1800/1900 MHz; Type: SAM

Left tilt 600/Area Scan (61x101x1): Measurement grid: $\Delta x = 15 \text{ mm}$, $\Delta y = 15 \text{ mm}$

Maximum value of SAR (interpolated) = 0.959 mW/g


Left tilt 600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $\Delta x = 8 \text{ mm}$, $\Delta y = 8 \text{ mm}$, $\Delta z = 5 \text{ mm}$

Reference Value = 10.1 V/m; Power Drift = -0.003 dB

Peak SAR (extrapolated) = 1.22 W/kg

SAR(1 g) = 0.794 mW/g; SAR(10 g) = 0.454 mW/g

Maximum value of SAR (measured) = 0.875 mW/g



Test Laboratory: HCT

MODEL: CDM7075

Company : UTStarcom Inc.

Mode : PCS 1900 / Channel : 600

Liquid Temperature : 21.5 °C

Date Tested : February 03, 2006

DUT: CDM7075; Type: Folder; Serial: #1

Communication System: PCS1900; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 40.2$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1607; ConvF(5.14, 5.14, 5.14); Calibrated: 2005-08-30
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn614; Calibrated: 2005-04-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

Left tilt 600/Area Scan (61x101x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (interpolated) = 0.143 mW/g


Left tilt 600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 6.79 V/m; Power Drift = -0.052 dB

Peak SAR (extrapolated) = 0.186 W/kg

SAR(1 g) = 0.128 mW/g; SAR(10 g) = 0.081 mW/g

Maximum value of SAR (measured) = 0.137 mW/g



Test Laboratory: HCT

MODEL: CDM7075

Company : UTStarcom Inc.

Mode : PCS 1900 / Channel : 600

Liquid Temperature : 21.5 °C

Date Tested : February 03, 2006

DUT: CDM7075; Type: Folder; Serial: #1

Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 40.2$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1607; ConvF(5.14, 5.14, 5.14); Calibrated: 2005-08-30

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn614; Calibrated: 2005-04-21

- Phantom: SAM 1800/1900 MHz; Type: SAM

Right tilt 600/Area Scan (61x101x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (interpolated) = 0.847 mW/g


Right tilt 600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 9.75 V/m; Power Drift = 0.169 dB

Peak SAR (extrapolated) = 1.02 W/kg

SAR(1 g) = 0.683 mW/g; SAR(10 g) = 0.401 mW/g

Maximum value of SAR (measured) = 0.760 mW/g



0 dB = 0.760mW/g

Test Laboratory: HCT

MODEL: CDM7075

Company : UTStarcom Inc.

Mode : PCS 1900 / Channel : 600

Liquid Temperature : 21.5 °C

Date Tested : February 03, 2006

DUT: CDM7075; Type: Folder; Serial: #1

Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 40.2$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1607; ConvF(5.14, 5.14, 5.14); Calibrated: 2005-08-30

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn614; Calibrated: 2005-04-21

- Phantom: SAM 1800/1900 MHz; Type: SAM

Right tilt 600/Area Scan (61x101x1): Measurement grid: $\Delta x = 15$ mm, $\Delta y = 15$ mm

Maximum value of SAR (interpolated) = 0.119 mW/g

Right tilt 600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $\Delta x = 8$ mm, $\Delta y = 8$ mm, $\Delta z = 5$ mm

Reference Value = 6.55 V/m; Power Drift = 0.084 dB

Peak SAR (extrapolated) = 0.161 W/kg

SAR(1 g) = 0.109 mW/g; SAR(10 g) = 0.069 mW/g

Maximum value of SAR (measured) = 0.117 mW/g



0 dB = 0.117mW/g