



HCT CO., LTD.

SAN 136-1, AMI-RI, BUBAL-EUP, ICHEON-SI, KYOUNGKI-DO, 467-701, KOREA

TEL: +82 31 639 8565 FAX: +82 31 639 8525 www.hct.co.kr

CERTIFICATE OF COMPLIANCE

RF TEST REPORT

UTStarcom, Inc.

555 Wireless Boulevard hauppauge, NY 11788

Date of Issue: December 28, 2007

Test Report No.: HCT-SAR07-1211

Test Site: HCT CO., LTD.

FCC :

O6Y-CDM7126

APPLICANT :

UTStarcom, Inc.

EUT Type: Tri – Band CDMA Phone with Bluetooth (CDMA / PCS CDMA / AWS CDMA)
Tx Frequency: 824.70 — 848.31 MHz (CDMA) / 1 851.25 — 1 908.75 MHz (PCS CDMA)
1 711.25 — 1753.75 MHz (AWS CDMA) / 2 402 – 2 480 MHz (Bluetooth)
Rx Frequency: 869.70 — 893.31 MHz (CDMA) / 1 931.25 — 1 988.75 MHz (PCS CDMA)
2 111.25 — 2153.75 MHz (AWS CDMA) / 2 402 – 2 480 MHz (Bluetooth)
Max. RF Output Power: 0.337 W ERP CDMA (25.28 dBm) / 0.290 W EIRP PCS CDMA (24.63 dBm)
0.301 W EIRP AWS CDMA (24.79 dBm)
Trade Name/Model(s): UTStarcom / CDM7126C, CDM7126M
FCC Classification: Licensed Portable Transmitter Held to Ear (PCE)
Application Type: Certification
FCC Rule Part(s): §2, §22, §24, §27
Maximum SAR: 0.939 W/kg CDMA835 Head SAR / 0.561 W/kg CDMA835 Body SAR
1.13 W/kg PCS1900 Head SAR / 0.259 W/kg PCS1900 Body SAR
0.575 W/kg AWS1700 Head SAR / 0.317 W/kg AWS1700 Body SAR
Antenna Specifications: Manufacturer: KOMATECH Co., Ltd.
Part No.: KI-24414 Gain: -6.4 dBi (Length = 21.1 (± 0.2 mm))
Emission Designator(s): 1M28F9W (CDMA) / 1M29F9W (PCS CDMA) / 1M29F9W (AWS CDMA)

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in § 2.947.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

HCT Co., Ltd. Certifies that no party to this application has been denied FCC benefits pursuant to section 5301 of the Anti- Drug Abuse Act of 1998, 21 U.S. C. 853(a)

Report prepared by

: Young-Kwan Kim

Test Engineer of RF Part

Approved by

: Sang-Jun Lee

Manager of RF Part

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

Table of Contents

1. SCOPE -----	3
2. INTRODUCTION -----	4
3. DESCRIPTION OF TESTS -----	5
3.1 Conducted RF Power Test-----	5
3.2 Effective Radiated Power-----	6
3.3 Occupied Bandwidth-----	7
3.4 Spurious and Harmonic Emissions at Antenna Terminal-----	9
3.5 Field Strength of Spurious Radiation-----	10
3.6 Frequency Stability-----	11
4. CONDUCTED RF POWER TEST DATA -----	12
5. RADIATED POWER TEST DATA-----	13
5.1 Effective Radiated Power Output (CDMA) -----	13
5.2 Equivalent Isotropic Radiated Power (E.I.R.P.) (PCS CDMA) -----	14
5.3 Equivalent Isotropic Radiated Power (E.I.R.P.) (AWS CDMA) -----	15
6. RADIATED SPURIOUS EMISSION MEASUREMENT TEST DATA-----	16
6.1 CDMA Radiated Measurements-----	16
6.2 PCS CDMA Radiated Measurements-----	19
6.3 AWS CDMA Radiated Measurements-----	22
7. FREQUENCY STABILITY TEST DATA-----	25
7.1 FREQUENCY STABILITY (CDMA) -----	25
7.2 FREQUENCY STABILITY (PCS CDMA) -----	26
7.3 FREQUENCY STABILITY (AWS CDMA) -----	27
8. LIST OF TEST EQUIPMENT-----	28
9. SAMPLE CALCULATIONS-----	29
10. CONCLUSION-----	30
11. TEST PLOTS -----	31

MEASUREMENT REPORT

1. SCOPE

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.

General Information

Company Name:	UTStarcom, Inc.
Address:	555 Wireless Boulevard hauppauge, NY 11788
Tel. / Fax :	+ 82-2-368-8939/ + 82-2-2057-0182
E-Mail:	john.seo@utstar.com

- FCC: O6Y-CDM7126
- Quantity: Quantity production is planned
- EUT Type: Tri – Band CDMA Phone with Bluetooth (CDMA / PCS CDMA / AWS CDMA)
- Trade Name: UTStarcom
- Model(s): CDM7126C, CDM7126M
- Serial Number(s): #1
- Emission Designator(s): 1M28F9W (CDMA) / 1M29F9W (PCS CDMA) / 1M29F9W (AWS CDMA)
- Tx Frequency: 824.70 — 848.31 MHz (CDMA) / 1 851.25 — 1 908.75 MHz (PCS CDMA)
1 711.25 — 1753.75 MHz (AWS CDMA) / 2 402 – 2 480 MHz (Bluetooth)
- Rx Frequency: 869.70 — 893.31 MHz (CDMA) / 1 931.25 — 1 988.75 MHz (PCS CDMA)
2 111.25 — 2 153.75 MHz (AWS CDMA) / 2 402 – 2 480 MHz (Bluetooth)
- Application Type: Certification
- FCC Classification: Licensed Portable Transmitter Held to Ear (PCE)
- FCC Rule Part(s): §2, §22, §24, §27
- Modulation(s): CDMA / PCS CDMA / AWS CDMA
- Antenna Type: Intenna
- Max RF. Output Power: 0.337 W ERP CDMA (25.28 dBm) / 0.290 W EIRP PCS CDMA (24.63 dBm)
0.301 W EIRP AWS CDMA (24.79 dBm)
- Date(s) of Tests: December 19, 2007 – December 21, 2007
- Place of Tests: HCT CO., LTD.
Icheon, Kyounki-Do, KOREA
- Report Serial No.: HCT-SAR07-1211

2. INTRODUCTION

EUT DESCRIPTION

The UTStarcom, Inc. CDM7126 Tri-mode Dual-band Phone (CDMA / PCS CDMA / AWS CDMA) phone. Its basic purpose is used for communications. It transmits from CDMA (824.70 ~ 848.31), PCS CDMA (1 851.25 ~ 1 908.75), AWS CDMA (1 711.25 ~ 1 753.75) MHz and receives from CDMA (869.70 ~ 893.31), PCS CDMA (1 931.25 ~ 1 988.75), AWS CDMA (2 111.25 ~ 2 153.75) MHz. The RF power is rated at CDMA (0.337 W), PCS CDMA (0.290 W), AWS CDMA (0.301 W).

MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.


Test Facility

The open area test site and conducted measurement facility used to collect the radiated data are located at the 254-1, Maekok-Ri, Hobup-Myun, Ichon-Si, Kyongki-Do, 467-701, KOREA. The site is constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22. Detailed description of test facility was submitted to the Commission and accepted dated July 23, 2003(Registration Number: 90661)

3. DESCRIPTION OF TESTS

3.1 Conducted RF Power Test

Test Set-up



Test Procedure


According to FCC §2.1046 (A), for transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, power output shall be measured at the RF output terminals when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in § 2.1033(c). The electrical characteristics of the radio frequency load attached to the output terminals when this test is made shall be stated.

- 1) The EUT was coupled to the spectrum analyzer and the base station simulator through a power divider. The radio frequency load attached to the EUT antenna terminal was 50 Ohm. The loss of the cables the test system is calibrated to correct the reading.
- 2) The spectrum analyzer was set to Maxpeak Detector function and Maximum hold mode.
- 3) The resolution bandwidth of the spectrum analyzer was comparable to the emission bandwidth.

For GSM signal, VBW = RBW = 1 MHz; for CDMA signal, VBW = RBW = 3 MHz.

3.2 Effective Radiated Power.

Test Set-up



[Open Field Test Site]

Test Procedure


The measurement facilities used for this test have been documented in previous filings with the commission pursuant to section 2.948.

The open field test site is situated in open field with ground screen whose site attenuation characteristics meet ANSI C63.4 –2003. A mast capable of lifting the receiving antenna from a height of one to four meters is used together with a turn-able wooden platform mounted at three from the antenna mast.

- 1) The EUT mounted on a wooden tripod is 0.8 meter above test site ground level.
- 2) During the test, the turn table is rotated and the antenna height is also varied from 1 to 4 meters until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with $\lambda/2$ dipole antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (4).
- 6) The signal generator output level is the rating of effective radiated power (ERP).
- 7) The instrument settings used (RBW/ VBW) during ERP/ EIRP output power measurement are as Below;
 - Below 1 GHz : RBW 3 MHz, VBW 3 MHz
 - Above 1 GHz : RBW 3 MHz, VBW 3 MHz

3.3 Occupied bandwidth.

Test Set-up




Test Procedure

The EUT was setup to maximum output power at its lowest channel. The occupied bandwidth was measured using a spectrum analyzer. The measurements are repeated for the highest and a middle channel. The EUT's occupied bandwidth is measured as the width of the signal between two points, one below the carrier center frequency and one above the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power. Plots of the EUT's occupied bandwidth are shown herein.

3.4 Spurious and Harmonic Emissions at Antenna Terminal.

Test Set-up




Test Procedure

The EUT was setup to maximum output power at its lowest channel. The Resolution BW of the analyzer is set to 1 % of the emission bandwidth to show compliance with the - 13 dBm limit, in the 1 MHz bands immediately outside and adjacent to the edge of the frequency block. The 1 MHz RBW was used to scan from 10 MHz to 10 GHz. (PCS Mode : 10 MHz to 20 GHz). A display line was placed at - 13 dBm to show compliance. The high, lowest and a middle channel were tested for out of band measurements.

3.5 Field strength of spurious radiation .

Test Set-up



[Open Field Test Site]

Test Procedure

The measurement facilities used for this test have been documented in previous filings with the commission pursuant to section 2.948.


The open field test site is situated in open field with ground screen whose site attenuation characteristics meet ANSI C63.4 –2003. A mast capable of lifting the receiving antenna from a height of one to four meters is used together with a turn-able wooden platform mounted at three from the antenna mast.

- 1) The unit mounted on a wooden table 1.5 m × 1.0 m × 0.80 m is 0.8 meter above test site ground level.
- 2) During the emission test, the turn table is rotated and the EUT is manipulated to find the configuration resulting in maximum emission under normal condition of installation and operation.
- 3) The antenna height and polarization are also varied from 1 to 4 meters until the maximum signal is found.
- 4) The spectrum shall be scanned up to the 10th harmonic of the fundamental frequency.
- 5) The instrument settings used (RBW/ VBW) during ERP/ EIRP output power measurement are as below ;
 - Below 1 GHz : RBW 3 MHz, VBW 3 MHz
 - Above 1 GHz : RBW 3 MHz, VBW 3 MHz

3.6 Frequency stability.

3.6.1 Frequency stability with variation of ambient temperature.

Test Set-up



Test Procedure

The frequency stability of the transmitter is measured by:

- Temperature:** The temperature is varied from - 30 °C to + 50 °C using an environmental chamber.
- Primary Supply Voltage:** The primary supply voltage is varied from battery end point to 115 % of the voltage normally at the input to the device or at the power supply terminals if cables are not normally supplied.

Specification — The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency.


Time Period and Procedure:

- The carrier frequency of the transmitter and the individual oscillators is measured at room temperature (25 °C to 27 °C to provide a reference).
- The equipment is subjected to an overnight “soak” at - 30 °C without any power applied.
- After the overnight “soak” at 30 °C (usually 14-16 hours), the equipment is turned on in a “standby” condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter and the individual oscillators is made within a three minute interval after applying power to the transmitter.
- Frequency measurements are made at 10 °C interval up to room temperature. At least a period of one and one half-hour is provided to allow stabilization of the equipment at each temperature level.
- Again the transmitter carrier frequency and the individual oscillators is measured at room temperature to begin measurement of the upper temperature levels.
- Frequency were made at 10 °C intervals starting at - 30 °C up to + 50 °C allowing at least two hours at each temperature for stabilization. In all measurements the frequency is measured within three minutes after applying power to the transmitter.
- The artificial load is mounted external to the temperature chamber.

NOTE: The EUT is tested down to the battery endpoint.

3.6.2 Frequency stability with variation of primary supply voltage.

Test Set-up



Test Procedure

- 1) The primary supply is varied in steps of from battery end point to 115 % of the nominal supply voltage, or reduce primary supply voltage to the battery operating end point.
- 2) The frequency is recorded each 10 °C step.

4. Conducted RF Power Test Data

4.1 Maximum Power Output table for IC: O6Y-CDM7126

Band	Channel	SO2	SO2	SO55	SO55	TDSO SO32
		RC1/1	RC3/3	RC1/1	RC3/3	RC3/3
CDMA	1013	24.00	24.03	24.00	23.96	24.04
	384	24.02	24.01	24.04	24.07	24.12
	777	24.02	24.10	24.11	24.11	24.17
PCS CDMA	25	24.00	24.08	24.12	24.14	24.19
	600	23.87	23.87	23.86	23.85	23.92
	1175	23.80	23.81	23.79	23.85	23.90
AWS CDMA	25	24.10	24.11	24.08	24.14	24.21
	425	23.93	23.90	23.90	23.87	23.93
	875	24.00	24.02	24.06	24.07	24.14

5. Radiated Power Test Data

5.1 Effective Radiated Power Output (CDMA)

Radiated measurements at 3 meters

Modulation: CDMA

Freq. Tuned (MHz)	REF. LEVEL (dBm)	POL (H/V)	ERP (W)	ERP (dBm)	ANTENNA
824.70	- 22.31	H	0.305	24.84	INTENNA
835.89	- 22.03	H	0.325	25.12	INTENNA
848.31	- 21.87	H	0.337	25.28	INTENNA

NOTES:

Effective Radiated Power Output Measurements by Substitution Method

According to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the dipole is measured. The ERP is recorded.

5.2 Equivalent Isotropic Radiated Power (E.I.R.P.) PCS CDMA

Radiated measurements at 3 meters

Modulation: PCS CDMA

Freq. Tuned (MHz)	RFF. LEVEL (dBm)	POL (H/V)	EIRP (W)	EIRP (dBm)	ANTENNA
1 851.25	- 28.93	H	0.290	24.63	INTENNA
1 880.00	- 29.22	H	0.272	24.34	INTENNA
1 908.75	- 29.36	H	0.263	24.20	INTENNA

NOTES:

Equivalent Isotropic Radiated Power Measurements by Substitution Method

According to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A Horn antenna was substituted in place of the EUT. This Horn antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the Horn antenna is measured. The difference between the gain of the horn and an isotropic antenna is taken into consideration and the EIRP is recorded.

5.3 Equivalent Isotropic Radiated Power (E.I.R.P.) AWS CDMA

Radiated measurements at 3 meters

Modulation: AWS CDMA

Freq. Tuned (MHz)	RFF. LEVEL (dBm)	POL (H/V)	EIRP (W)	EIRP (dBm)	ANTENNA
1 711.25	- 28.77	H	0.301	24.79	INTENNA
1 731.25	- 29.21	H	0.272	24.35	INTENNA
1 753.75	- 28.98	H	0.287	24.58	INTENNA

NOTES:

Equivalent Isotropic Radiated Power Measurements by Substitution Method

According to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A Horn antenna was substituted in place of the EUT. This Horn antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the Horn antenna is measured. The difference between the gain of the horn and an isotropic antenna is taken into consideration and the EIRP is recorded.

6. Radiated Spurious Emission Measurement Test Data

6.1 CELLULAR CDMA Radiated Measurements

Field Strength of SPURIOUS Radiation

■ OPERATING FREQUENCY:	824.70 MHz
■ CHANNEL:	1013 (Low)
■ MEASURED OUTPUT POWER:	25.28 dBm = 0.337 W
■ MODULATION SIGNAL:	CDMA (Internal)
■ DISTANCE:	3 meters
■ LIMIT: - (43 + 10 log ₁₀ (W)) =	- 38.27 dBc

Freq. (MHz)	LEVEL@ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1 649.40	- 49.84	7.3	- 42.54	H	- 62.52
2 474.10	- 66.99	8.3	- 58.69	H	- 78.17
3 298.80	- 64.72	9.7	- 55.02	H	- 73.60

NOTES:

Radiated Spurious Emission Measurements by Substitution Method

According to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1 GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

Field Strength of SPURIOUS Radiation

■ OPERATING FREQUENCY:	836.52 MHz
■ CHANNEL:	384 (Mid)
■ MEASURED OUTPUT POWER:	25.28 dBm = 0.337 W
■ MODULATION SIGNAL:	CDMA (Internal)
■ DISTANCE:	3 meters
■ LIMIT: - $(43 + 10 \log_{10} (W))$ =	- 38.27 dBc

Freq. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1 671.78	- 44.45	7.3	- 37.15	H	- 57.13
2 507.67	- 65.33	8.3	- 57.03	H	- 76.51
3 343.56	- 62.82	9.7	- 53.12	H	- 71.70

NOTES:

Radiated Spurious Emission Measurements by Substitution Method

According to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1 GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

Field Strength of SPURIOUS Radiation

■ OPERATING FREQUENCY:	848.31 MHz
■ CHANNEL:	777 (High)
■ MEASURED OUTPUT POWER:	25.28 dBm = 0.337 W
■ MODULATION SIGNAL:	CDMA (Internal)
■ DISTANCE:	3 meters
■ LIMIT: - (43 + 10 log ₁₀ (W)) =	- 38.27 dBc

Freq. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1 696.62	- 46.02	7.3	- 38.72	H	- 58.70
2 544.93	- 61.23	8.3	- 52.93	H	- 72.41
3 393.24	- 63.47	9.7	- 53.77	H	- 72.35

NOTES:

Radiated Spurious Emission Measurements by Substitution Method

According to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1 GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

6.2 CELLULAR PCS CDMA Radiated Measurements

Field Strength of SPURIOUS Radiation

■ OPERATING FREQUENCY:	1 851.25 MHz
■ CHANNEL:	25 (Low)
■ MEASURED OUTPUT POWER:	24.63 dBm = 0.290 W
■ MODULATION SIGNAL:	PCS CDMA (Internal)
■ DISTANCE:	3 meters
■ LIMIT: - $(43 + 10 \log_{10} (W))$ =	- 37.62 dBc

Freq. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
3 702.50	- 65.81	12.4	- 53.41	H	- 68.64
5 553.75	- 71.34	11.7	- 59.64	H	- 76.07
7 405.00	- 68.46	11.5	- 56.96	H	- 74.09

NOTES:

Radiated Spurious Emission Measurements by Substitution Method

According to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1 GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

Field Strength of SPURIOUS Radiation

■ OPERATING FREQUENCY:	1 880.00 MHz
■ CHANNEL:	600 (Middle)
■ MEASURED OUTPUT POWER:	24.63 dBm = 0.290 W
■ MODULATION SIGNAL:	PCS CDMA (Internal)
■ DISTANCE:	3 meters
■ LIMIT: - $(43 + 10 \log_{10} (W))$ =	- 37.62 dBc

Freq. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
3 760.00	- 60.52	12.4	- 48.12	H	- 63.35
5 640.00	-70.81	11.7	- 59.11	H	- 75.54
7 520.00	- 68.33	11.5	- 56.83	H	- 73.96

NOTES:

Radiated Spurious Emission Measurements by Substitution Method

According to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1 GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

Field Strength of SPURIOUS Radiation

■ OPERATING FREQUENCY:	1 908.75 MHz
■ CHANNEL:	1175 (High)
■ MEASURED OUTPUT POWER:	24.63 dBm = 0.290 W
■ MODULATION SIGNAL:	PCS CDMA (Internal)
■ DISTANCE:	3 meters
■ LIMIT: - (43 + 10 log ₁₀ (W)) =	- 37.62 dBc

Freq. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
3 817.50	- 63.91	12.4	- 51.51	H	- 66.74
5 726.25	- 72.02	11.7	- 60.32	H	- 76.75
7 635.00	- 68.42	11.5	- 56.92	H	- 74.05

NOTES:

Radiated Spurious Emission Measurements by Substitution Method

According to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1 GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

6.3 CELLULAR PCS CDMA Radiated Measurements

Field Strength of SPURIOUS Radiation

■ OPERATING FREQUENCY:	1 711.25 MHz
■ CHANNEL:	25 (Low)
■ MEASURED OUTPUT POWER:	24.79 dBm = 0.301 W
■ MODULATION SIGNAL:	AWS CDMA (Internal)
■ DISTANCE:	3 meters
■ LIMIT: - (43 + 10 log ₁₀ (W)) =	- 37.78 dBc

Freq. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
3 422.50	- 78.44	12.4	- 66.04	H	- 81.43
5 133.75	- 76.12	11.7	- 64.42	H	- 81.01
6 845.00	- 74.26	11.5	- 62.76	H	- 80.05

NOTES:

Radiated Spurious Emission Measurements by Substitution Method

According to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1 GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

Field Strength of SPURIOUS Radiation

■ OPERATING FREQUENCY:	1 731.25 MHz
■ CHANNEL:	425 (Middle)
■ MEASURED OUTPUT POWER:	24.79 dBm = 0.301 W
■ MODULATION SIGNAL:	AWS CDMA (Internal)
■ DISTANCE:	3 meters
■ LIMIT: - (43 + 10 log ₁₀ (W)) =	- 37.78 dBc

Freq. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
3 462.50	- 81.69	12.4	- 69.29	H	- 84.68
5 193.75	- 74.82	11.7	- 63.12	H	- 79.71
6 925.00	- 75.21	11.5	- 63.71	H	- 81.00

NOTES:

Radiated Spurious Emission Measurements by Substitution Method

According to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1 GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

Field Strength of SPURIOUS Radiation

■ OPERATING FREQUENCY:	1 753.75 MHz
■ CHANNEL:	875 (High)
■ MEASURED OUTPUT POWER:	24.79 dBm = 0.301 W
■ MODULATION SIGNAL:	AWS CDMA (Internal)
■ DISTANCE:	3 meters
■ LIMIT: - (43 + 10 log ₁₀ (W)) =	- 37.78 dBc

Freq. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
3 507.50	- 78.97	12.4	- 66.57	H	- 81.96
5 261.25	- 74.77	11.7	- 63.07	H	- 79.66
7 015.00	- 75.23	11.5	- 63.73	H	- 81.02

NOTES:

Radiated Spurious Emission Measurements by Substitution Method

According to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer.


For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1 GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

7. Frequency Stability Test Data

7.1 FREQUENCY STABILITY (CDMA)

OPERATING FREQUENCY: 836 520 000 Hz
 CHANNEL: 384
 REFERENCE VOLTAGE: 3.7 VDC
 DEVIATION LIMIT: $\pm 0.00025\%$ or 2.5 ppm


Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.70	+20(Ref)	836,520,032	32	0.000004	0.017
100%		-30	836,519,949	-51	-0.000006	-0.027
100%		-20	836,519,957	-43	-0.000005	-0.023
100%		-10	836,519,954	-46	-0.000006	-0.024
100%		0	836,520,038	38	0.000005	0.020
100%		+10	836,519,966	-34	-0.000004	-0.018
100%		+20	836,520,032	32	0.000004	0.017
100%		+30	836,520,049	49	0.000006	0.026
100%		+40	836,519,959	-41	-0.000005	-0.022
100%		+50	836,520,053	53	0.000006	0.028
115%	4.26	+20	836,519,959	-41	-0.000005	-0.022
Batt. Endpoint	3.21	+20	836,520,048	48	0.000006	0.026



7.2 FREQUENCY STABILITY (PCS CDMA)

OPERATING FREQUENCY: 1 880 000 000 Hz
 CHANNEL: 600
 REFERENCE VOLTAGE: 3.7 VDC
 DEVIATION LIM IT: $\pm 0.000\ 25\ \%$ or 2.5 ppm


Voltage (%)	Power (VDC)	Temp. (℃)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.70	+20(Ref)	1,800,000,031	31	0.000004	0.016
100%		-30	1,800,000,061	61	0.000007	0.032
100%		-20	1,799,999,953	-47	-0.000006	-0.025
100%		-10	1,800,000,053	53	0.000006	0.028
100%		0	1,799,999,960	-40	-0.000005	-0.021
100%		+10	1,800,000,028	28	0.000003	0.015
100%		+20	1,800,000,031	31	0.000004	0.016
100%		+30	1,799,999,960	-40	-0.000005	-0.021
100%		+40	1,800,000,054	54	0.000006	0.029
100%		+50	1,800,000,063	63	0.000008	0.034
115%	4.26	+20	1,799,999,949	-51	-0.000006	-0.027
Batt. Endpoint	3.21	+20	1,799,999,948	-52	-0.000006	-0.028



7.3 FREQUENCY STABILITY (AWS CDMA)

OPERATING FREQUENCY: 1 731 250 000 Hz
 CHANNEL: 425
 REFERENCE VOLTAGE: 3.7 VDC
 DEVIATION LIMIT: $\pm 0.00025\%$ or 2.5 ppm

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.70	+20(Ref)	1,731,250,035	35	0.000004	0.019
100%		-30	1,731,249,946	-54	-0.000006	-0.029
100%		-20	1,731,250,053	53	0.000006	0.028
100%		-10	1,731,249,963	-37	-0.000004	-0.020
100%		0	1,731,250,031	31	0.000004	0.016
100%		+10	1,731,249,958	-42	-0.000005	-0.022
100%		+20	1,731,250,035	35	0.000004	0.019
100%		+30	1,731,250,043	43	0.000005	0.023
100%		+40	1,731,249,949	-51	-0.000006	-0.027
100%		+50	1,731,250,049	49	0.000006	0.026
115%	4.26	+20	1,731,249,953	-47	-0.000006	-0.025
Batt. Endpoint	3.21	+20	1,731,250,056	56	0.000007	0.030



8. LIST OF TEST EQUIPMENT

Manufacture	Model/ Equipment	Serial Number	Calibration Date	Calibration Interval	Calibration Due
R&S	ES140/ Spectrum Analyzer	831564/003	11/06/2007	Annual	11/06/2008
Advantest	R3273/ Spectrum Analyzer	J04821	03/15/2007	Annual	03/15/2008
HP	8664A/ Signal Generator	3744A02069	04/10/2007	Annual	04/10/2008
Agilent	E4416A/ Power Meter	GB41291412	01/22/2007	Annual	01/22/2008
Agilent	E9327A/ Power Sensor	US40440910	01/24/2007	Annual	01/24/2008
Agilent	HP8901B/ Modulation Analyzer	3438A05231	08/04/2007	Annual	08/04/2008
Agilent	8903A/ Audio Analyzer	2433A04322	08/04/2007	Annual	08/04/2008
R&S	CMU200/ Base Station	839117/011	01/28/2007	Annual	01/28/2008
Agilent	8960 (E5515C)/ Base Station	GB44400269	02/11/2007	Annual	02/11/2008
Tescom	TC-3000/ Bluetooth Simulator	3000A4900112	01/22/2007	Annual	01/22/2008
MITEQ	AMF-6D-01180-35-20P/ AMP	990893	02/24/2007	Annual	02/24/2008
Wainwright	WHK1.2/15G-10EF/H.P.F	2	06/28/2007	Annual	06/28/2008
Wainwright	WHK3.3/18G-10EF/H.P.F	1	06/28/2007	Annual	06/28/2008
Agilent	778D/ Dual Directional Coupler	16072	11/09/2007	Annual	11/09/2008
Agilent	1506A/ Power Divider	99441	11/10/2007	Annual	11/10/2008
Digital	EP-3010/ Power Supply	3110117	12/29/2007	Annual	12/29/2008
Schwarzbeck	UHAP/ Dipole Antenna	630	11/13/2007	Annual	11/13/2008
Schwarzbeck	UHAP/ Dipole Antenna	605	11/13/2007	Annual	11/13/2008
R&S	HFH2-Z2/ Loop Antenna	881056/070	12/11/2007	Annual	12/11/2008
Schwarzbeck	VULB9160/ TRILOG Antenna	3150	03/19/2007	Annual	03/19/2008
Schwarzbeck	VULB9160/ TRILOG Antenna	4150	01/23/2007	Annual	01/23/2008
Korea Engineering	KR-1005L / Chamber	KRAB07063-2CH	01/08/2007	Annual	01/08/2008
Schwarzbeck	BBHA 9120D/ Horn Antenna	147	03/31/2007	Biennial	03/31/2008
Schwarzbeck	BBHA 9120D/ Horn Antenna	1201	05/02/2007	Biennial	05/02/2008

9. SAMPLE CALCULATIONS

A. ERP Sample Calculation

Freq. Tuned (MHz)	REF. LEVEL (dBm)	POL (H/V)	ERP (W)	ERP (dBm)	ANTENNA
824.70	- 22.31	H	0.305	24.84	INTENNA

- 1) The EUT mounted on a wooden tripod is 0.8 meter above test site ground level.
- 2) During the test, the turn table is rotated and the antenna height is also varied from 1 to 4 meters until the maximum signal is found.
- 3) Record the field strength meter's level. (**LEVEL**)
- 4) Replace the EUT with dipole antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with cable loss is the rating of effective radiated power (**ERP**).
(Cable loss means the factor between Signal Generator and Transmitting Antenna.)

For more details, please refer to the test set-up procedure.

B. Emission Designator

Emission Designator = 1M28F9W

CDMA BW = 1.28 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data)


(Measured at the 99.75 % power bandwidth)

10. CONCLUSION


The data collected shows that the Tri – Band CDMA Phone with Bluetooth (CDMA / PCS CDMA / AWS CDMA) **FCC ID: O6Y-CDM7126** complies with all the requirements of Parts 22, 24, 27 of the FCC rules.

11. TEST PLOTS


■ CDMA MODE (1013 CH.) Conducted Spurious




■ CDMA MODE (384 CH.) Conducted Spurious




■ CDMA MODE (777 CH.) Conducted Spurious




■ PCS CDMA MODE (25 CH.) Conducted Spurious




■ PCS CDMA MODE (600 CH.) Conducted Spurious




■ PCS CDMA MODE (1175 CH.) Conducted Spurious




■ AWS CDMA MODE (25 CH.) Conducted Spurious




■ AWS CDMA MODE (425 CH.) Conducted Spurious




■ AWS CDMA MODE (875 CH.) Conducted Spurious




■ CDMA MODE (1013 CH.) : Channel Power




■ CDMA MODE (384 CH.) : Channel Power




■ CDMA MODE (777 CH.) : Channel Power




■ PCS CDMA MODE (25 CH.) : Channel Power




■ PCS CDMA MODE (600 CH.) : Channel Power




■ PCS CDMA MODE (1175 CH.) : Channel Power




■ AWS CDMA MODE (25 CH.) : Channel Power




■ AWS CDMA MODE (425 CH.) : Channel Power




■ AWS CDMA MODE (875 CH.) : Channel Power




■ CDMA Mode (384 CH.) : Occupied Bandwidth



■ PCS CDMA Mode (600 CH) : Occupied Bandwidth




■ AWS CDMA Mode (425 CH) : Occupied Bandwidth




■ CDMA Mode (1013 CH.) : Band Edge



■ CDMA Mode (777 CH.) : Band Edge




■ PCS CDMA Mode (25 CH.) : Band Edge



■ PCS CDMA Mode (1175 CH.) : Band Edge




■ AWS CDMA Mode (25 CH.) : Band Edge




■ AWS CDMA Mode (875 CH.) : Band Edge



■ CDMA Mode (1013 CH) : SPURIOUS EMISSION-RECEIVER OPERRATING



■ CDMA Mode (384 CH) : SPURIOUS EMISSION-RECEIVER OPERATING



■ CDMA Mode (777 CH) : SPURIOUS EMISSION-RECEIVER OPERRATING

