

APPENDIX L: ADDITIONAL INFORMATION

Radiated Test Data - OATS 1 Mode: Digital/Receiver Limit/Distance: FCC B/3M

Temperature: 50°F					Humidity: 91%				
Emission Frequency (MHz)	Test Detector	Antenna Polarity (H/V)	Turntable Azimuth (deg)	Antenna Height (m)	Analyzer Reading (dBuV)	Site Correction Factor (dB/m)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
38.600	Qp	V	90	1.0	42.3	-16.9	25.4	40.0	-14.6
57.660	Qp	V	145	1.0	37.0	-23.0	14.0	40.0	-26.0
76.980	Qp	V	90	1.0	46.3	-23.2	23.1	40.0	-16.9
153.740	Qp	V	45	1.0	39.3	-17.9	21.4	43.5	-22.1
268.880	Qp	V	270	1.0	35.8	-15.9	19.9	46.0	-26.1
345.640	Qp	V	90	1.0	37.4	-13.8	23.6	46.0	-22.4
384.020	Qp	V	225	1.0	37.7	-12.6	25.1	46.0	-20.9
403.210	Qp	V	45	1.0	39.3	-12.1	27.2	46.0	-18.8
441.590	Qp	V	45	1.0	37.7	-11.0	26.7	46.0	-19.3
614.300	Qp	V	90	1.0	38.5	-7.5	31.0	46.0	-15.0
978.910	Qp	V	45	1.0	34.5	-3.8	30.7	54.0	-23.3

TEST PERSONNEL:

Signature:
Typed/Printed
Name:



Rachid Sehb

Test Date:

May 18, 2003

Position:

Test Engineer