

# \* RF Exposure

### 1. Regulation

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this Chapter.

Limits for Maximum Permissive Exposure: RF exposure is calculated.

Emility for Maximum 1 orimissive Exposure. In exposure is calculated.						
Frequency Range	Electric Field	Magnetic Field	Power Density	Averaging Time		
	Strength [V/m]	Strength [A/m]	$[mW/cm^2]$	[minute]		
Limits for General Population / Uncontrolled Exposure						
0.3 ~ 1.34	614	1.63	*(100)	30		
1.34 ~ 30	824/f	2.19/f	$*(180/f^2)$	30		
30 ~ 300	27.5	0.073	0.2	30		
300 ~ 1 500	/	/	f/1 500	30		
1 500 ~ 15 000	/	/	1.0	30		

f=frequency in ML, \*= plane-wave equivalent power density

#### MPE (Maximum Permissive Exposure) Prediction

Predication of MPE limit at a given distance: Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2 \quad (\Rightarrow R = \sqrt{PG/4\pi S})$$

 $S = power density [mW/cm^2]$ 

P = Power input to antenna [mW]

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna [cm]

KCTL-TIR001-002/0

Page: (1) /(2) Pages



### 2. RF Exposure Compliance Issue

The information should be included in the user's manual:

This appliance and its antenna must not be co-located or operation in conjunction with any other antenna or transmitter. A minimum separation distance of 20 cm must be maintained between the antenna and the person for this appliance to satisfy the RF exposure requirements.

# 3. Calculation Result of RF Exposure

Mode	Target power	Tune up tolerance	Max tune up power	Max tune up power	Ant Gain	Ant Gain	Power Density at 20 cm	Limit
	[dBm]	[dB]	[dBm]	[mW]	[dBi]	[mW]	[mW/cm²]	[mW/cm²]
WiFi 5G Band 4 802.11n_HT40 _MIMO_5 795 ₩b	22.00	±2.00	24.00	251.19	3.00	2.00	0.099 71	1.000 00
RF4CE _ Lowest_2 425 MHz	0.50	±2.00	2.50	1.78	5.59	3.62	0.001 28	1.000 00
Total							0.100 99	1.000 00

# 4. Target power and tolerance, Max tuneup power

#### -WiFi 5G Band 1, Band 4

Mode	Target power [dBm]	Tolerance [dB]	Max tuneup power [dBm]	Average Power [dBm]
WiFi 5G Band 1 802.11n_HT40_MIMO _5 190 ₩z	14.00	±2.00	16.00	15.13
WiFi 5G Band 1 802.11n_HT40_MIMO _5 230 Mb	14.00	±2.00	16.00	15.12
WiFi 5G Band 4 802.11n_HT40_MIMO _5 755 Mb	17.00	±2.00	19.00	18.95
WiFi 5G Band 4 802.11n_HT40_MIMO _5 795 ₩z	22.00	±2.00	24.00	23.54

#### -RF4CE

Mode	Target power [dBm]	Tolerance [dB]	Max tuneup power [dBm]	Average Power [dBm]
Lowest_2 425 Mbz	0.50	±2.00	2.50	2.28
Middle_2 450 Mbz	0.50	±2.00	2.50	1.85
Highest_2 475 Mbz	0.50	±2.00	2.50	1.75