

*** RF Exposure**

1. Regulation

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this Chapter.

Limits for Maximum Permissible Exposure: RF exposure is calculated.

Frequency Range	Electric Field Strength [V/m]	Magnetic Field Strength [A/m]	Power Density [mW/cm ²]	Averaging Time [minute]
Limits for General Population / Uncontrolled Exposure				
0.3 ~ 1.34	614	1.63	*(100)	30
1.34 ~ 30	824/f	2.19/f	*(180/f ²)	30
30 ~ 300	27.5	0.073	0.2	30
300 ~ 1 500	/	/	f/1 500	30
1 500 ~ 15 000	/	/	1.0	30

f=frequency in MHz, *= plane-wave equivalent power density

MPE (Maximum Permissible Exposure) Prediction

Predication of MPE limit at a given distance: Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2 \quad (\Rightarrow R = \sqrt{PG/4\pi S})$$

S = power density [mW /cm²]

P = Power input to antenna [mW]

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna [cm]

EUT: Maximum peak output power = 2.28 [mW] (3.57 dBm)	
Antenna gain = 2.04 (3.1 dBi)	
100 mW, at 20 cm from an antenna 6 [dBi]	$S = PG/4\pi R^2 = 100 \times 3.98 / (4 \times \pi \times 400) = 0.07918 \text{ [mW/cm}^2\text{]} < 1.0 \text{ [mW/cm}^2\text{]}$
2.28 mW, at 20 cm from an antenna 3.1 [dBi]	$S = PG/4\pi R^2 = 0.00092 \text{ [mW/cm}^2\text{]} < 1.0 \text{ [mW/cm}^2\text{]}$

2. RF Exposure Compliance Issue

The information should be included in the user's manual:

This appliance and its antenna must not be co-located or operation in conjunction with any other antenna or transmitter. A minimum separation distance of 20 cm must be maintained between the antenna and the person for this appliance to satisfy the RF exposure requirements.

3. Calculation Result of RF Exposure

*** ANT 1**

Channel	Frequency [MHz]	Ant Gain	power [dBm]	power [mW]	Power Density at 20 cm [mW/cm ²]
Lowest	2 425	2.04	3.56	2.27	0.000 92
Middle	2 450	2.04	3.57	2.28	0.000 92
Highest	2 475	2.04	3.26	2.12	0.000 86

*** ANT 2**

Channel	Frequency [MHz]	Ant Gain	power [dBm]	power [mW]	Power Density at 20 cm [mW/cm ²]
Lowest	2 425	1.26	2.63	1.83	0.000 46
Middle	2 450	1.26	2.71	1.87	0.000 47
Highest	2 475	1.26	2.32	1.71	0.000 43