

TEST REPORT

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 443-390, Korea
TEL: 82-70-5008-1021 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR16-SRF0017

Page (1) of (47)

KCTL

1. Client

- Name : HUMAX Co., Ltd
- Address : (Yubang-dong)2, Yeongmun-ro, Cheoin-gu, Yongin-si,
Gyeonggi-do, Korea
- Date of Receipt : 2016-07-27

2. Use of Report : -

3. Name of Product and Model : Digital Cable Receiver / Spectrum101-H

4. Manufacturer and Country of Origin : HUMAX Co., Ltd / Korea

FCC ID: : 06ZSPECTRUM101-H

5. Date of Test : 2016-08-25 ~ 2016-09-23

6. Test method used : FCC Part 15 Subpart C, 15.247 ANSI C63.10-2013

7. Test Results : Refer to the test result in the test report

Affirmation	Tested by	Technical Manager
	Name : DoKyun Lee (Signature)	Name : ChangMin Kim (Signature)

2016-09-27

KCTL Inc.

As a test result of the sample which was submitted from the client, this report does not guarantee the whole product quality. This test report should not be used and copied without a written agreement by KCTL Inc.

REPORT REVISION HISTORY

Date	Revision	Page No
2016-09-27	Originally issued	-

This report shall not be reproduced except in full, without the written approval of KCTL Inc. This document may be altered or revised by KCTL Inc. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KCTL Inc. will constitute fraud and shall nullify the document.

[Contents]

1. Client information	4
2. Laboratory information	5
3. Description of E.U.T.	6
3.1 Basic description.....	6
3.2 General description.....	6
3.3 Test frequency.....	7
3.4 Test Voltage	7
4. Summary of test results	8
4.1 Standards & results.....	8
4.2 Uncertainty.....	8
5. Test results	9
5.1 Antenna Requirement.....	9
5.2 Maximum Peak Output Power	10
5.3 Peak Power Spectral Density	12
5.4 6 dB Bandwidth(DTS Channel Bandwidth).....	17
5.5 Spurious Emission, Band Edge, and Restricted bands	25
5.6 Conducted Emission.....	45
6. Test equipment used for test	47

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 443-390, Korea
TEL: 82-70-5008-1021 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR16-SRF0017

Page (4) of (47)



1. Client information

Applicant: HUMAX Co., Ltd
Address: (Yubang-dong)2, Yeongmun-ro, Cheoin-gu, Yongin-si,
Gyeonggi-do, Korea
Telephone number: +82-31-776-6748
Facsimile number: +82-31 776 6029
Contact person: Nak Yool, Sung / nysung@humaxdigital.com

Manufacturer: HUMAX Co., Ltd
Address: (Yubang-dong)2, Yeongmun-ro, Cheoin-gu Yongin-si,
Gyeonggi-do, Korea

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 443-390, Korea
TEL: 82-70-5008-1021 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR16-SRF0017

Page (5) of (47)

KCTL

2. Laboratory information

Address


KCTL Inc.

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 443-390, Korea
Telephone Number: +82-70-5008-1021 Facsimile Number: +82-505-299-8311

Certificate

KOLAS No.: KT231
FCC Site Designation No.: KR0040
FCC Site Registration No.: 687132
VCCI Site Registration No.: R-3327, G-198, C-3706, T-1849
IC Site Registration No.:8035A

SITE MAP



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 443-390, Korea
TEL: 82-70-5008-1021 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR16-SRF0017

Page (6) of (47)



3. Description of E.U.T.

3.1 Basic description

Applicant	HUMAX Co., Ltd
Address of Applicant	(Yubang-dong)2, Yeongmun-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea
Manufacturer	HUMAX Co., Ltd
Address of Manufacturer	(Yubang-dong)2, Yeongmun-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea
Type of equipment	Digital Cable Receiver
Basic Model	Spectrum101-H
Serial number	N/A

3.2 General description

Frequency Range	2 425 MHz ~ 2 475 MHz
Type of Modulation	O-QPSK
The number of channels	3 ch
Type of Antenna	PCB Antenna
Antenna Gain	Ant 0: 3.5 dBi Ant 1: 3.6 dBi
Transmit Power	3.05 dBm
Power supply	DC 12 V
Product SW/HW Version	Rev. 0.0.1 / Rev. 0.2
Radio SW/HW Version	v2.4.7.2 / Rev. 0.2
Test SW Version	Tera Term 4.87
RF power setting in TEST SW	3 dBm

Note : The above EUT information was declared by the manufacturer.

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 443-390, Korea
TEL: 82-70-5008-1021 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR16-SRF0017

Page (7) of (47)



3.3 Test frequency

	Frequency
Lowest frequency	2 425 MHz
Middle frequency	2 450 MHz
Highest frequency	2 475 MHz

3.4 Test Voltage

Mode	Voltage
Norminal Voltage	DC 12 V

4. Summary of test results

4.1 Standards & results

FCC Rule Reference	IC Rule Reference	Parameter	Report Section	Test Result
15.203, 15.247(b)(4)	-	Antenna Requirement	5.1	C
15.247(b)(3)	RSS-247, 5.4(4)	Maximum Peak Output Power	5.2	C
15.247(e)	RSS-247, 5.2	Peak Power Spectral Density	5.3	C
15.247(a)(2)	RSS-247, 5.2	6 dB Channel Bandwidth	5.4	C
-	RSS-247, 5.2	Occupied Bandwidth	5.4	C
15.247(d), 15.205(a), 15.209(a)	RSS-247, 5.5 RSS-GEN, 8.9, 10	Spurious Emission, Band Edge, and Restricted bands	5.5	C
15.207(a)	RSS-GEN, 8.8	Conducted Emissions	5.6	C
Note: C = complies NC = Not complies NT = Not tested NA = Not Applicable				

- The general test methods used to test this device is ANSI C63.10:2013

4.2 Uncertainty

Measurement Item	Expanded Uncertainty $U = kUc (k = 2)$	
Conducted RF power	1.44 dB	
Conducted Spurious Emissions	1.52 dB	
Radiated Spurious Emissions	30 MHz ~ 300 MHz:	+ 4.94 dB, - 5.06 dB
		+ 4.93 dB, - 5.05 dB
	300 MHz ~ 1 000 MHz:	+ 4.97 dB, - 5.08 dB
		+ 4.84 dB, - 4.96 dB
Conducted Emissions	9 kHz ~ 150 kHz:	3.75 dB
	150 kHz ~ 30 MHz:	3.36 dB

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 443-390, Korea
TEL: 82-70-5008-1021 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR16-SRF0017

Page (9) of (47)



5. Test results

5.1 Antenna Requirement

5.1.1 Regulation

According to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

And according to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

5.1.2 Result

- Complied

The transmitter has permanently attached PCB antenna(internal antenna).

5.2 Maximum Peak Output Power

5.2.1 Regulation

According to §15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2 400-2 483.5 MHz, and 5 725-5 850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

According to §15.247(b)(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

5.2.2 Measurement Procedure

These test measurement settings are specified in section 9.0 of 558074 D01 DTS Meas Guidance.

5.2.2.1 PKPM1 Peak power meter method

The maximum peak conducted output power may be measured using a broadband peak RF power meter.

The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 443-390, Korea
TEL: 82-70-5008-1021 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR16-SRF0017

Page (11) of (47)



5.2.3 Test Result

- Complied

ANT 0

Channel	Frequency [MHz]	Result [dBm]	Limit [dBm]	Margin [dB]	Average Power [dBm]
Lowest	2 425	3.05	30.00	26.95	2.74
Middle	2 450	2.84	30.00	27.16	2.61
Highest	2 475	2.74	30.00	27.26	2.46

ANT 1

Channel	Frequency [MHz]	Result [dBm]	Limit [dBm]	Margin [dB]	Average Power [dBm]
Lowest	2 425	1.54	30.00	28.46	1.25
Middle	2 450	1.44	30.00	28.56	1.14
Highest	2 475	1.44	30.00	28.56	1.05

-NOTE:

1. We took the insertion loss of the cable loss into consideration within the measuring instrument.

5.3 Peak Power Spectral Density

5.3.1 Regulation

According to §15.247(e), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

5.3.2 Measurement Procedure

These test measurement settings are specified in section 10.0 of 558074 D01 DTS Meas Guidance.

5.3.2.1 Method PKPSD (peak PSD)

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance, and is optional if the maximum conducted (average) output power was used to demonstrate compliance.

- 1) Set analyzer center frequency to DTS channel center frequency.
- 2) Set the span to 1.5 times the DTS bandwidth.
- 3) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- 4) Set the VBW $\geq 3 \times \text{RBW}$.
- 5) Detector = peak.
- 6) Sweep time = auto couple.
- 7) Trace mode = max hold.
- 8) Allow trace to fully stabilize.
- 9) Use the peak marker function to determine the maximum amplitude level within the RBW.
- 10) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 443-390, Korea
TEL: 82-70-5008-1021 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR16-SRF0017

Page (13) of (47)



5.3.3 Test Result

- Complied

ANT 0

Channel	Frequency [MHz]	Result (RBW=100 kHz) [dBm]	Result (RBW=3 kHz) [dB m]	Limit	Margin [dBm]
Lowest	2 425	-0.27	-11.18	8 dBm/3 kHz	19.18
Middle	2 450	-0.16	-11.05	8 dBm/3 kHz	19.05
Highest	2 475	-0.36	-11.19	8 dBm/3 kHz	19.19

ANT 1

Channel	Frequency [MHz]	Result (RBW=100 kHz) [dBm]	Result (RBW=3 kHz) [dB m]	Limit	Margin [dBm]
Lowest	2 425	-1.63	-12.22	8 dBm/3 kHz	20.22
Middle	2 450	-1.69	-12.18	8 dBm/3 kHz	20.18
Highest	2 475	-1.77	-12.47	8 dBm/3 kHz	20.47

-NOTE:


1. We took the insertion loss of the cable loss into consideration within the measuring instrument.

5.3.4 Test Plot


Figure 1. Plot of the Power Density

Ant 0

Lowest Channel (2 425 MHz)



Middle Channel (2 450 MHz)




KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 443-390, Korea
TEL: 82-70-5008-1021 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR16-SRF0017
Page (15) of (47)




Highest Channel (2 475 MHz)



Ant 1

Lowest Channel (2 425 MHz)



5.4 6 dB Bandwidth(DTS Channel Bandwidth)

5.4.1 Regulation

According to §15.247(a)(2) Systems using digital modulation techniques may operate in the 902–928 MHz, 2 400–2 483.5 MHz, and 5 725–5 850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

5.4.2 Measurement Procedure

These test measurement settings are specified in section 8.0 of 558074 D01 DTS Meas Guidance.

5.4.2.1 DTS Channel Bandwidth-Option 1

- 1) Set RBW = 100 kHz.
- 2) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- 3) Detector = Peak.
- 4) Trace mode = max hold.
- 5) Sweep = auto couple.
- 6) Allow the trace to stabilize.
- 7) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.4.2.2 DTS Channel Bandwidth Measurement Procedure-Option 2

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = 100 kHz, VBW $\geq 3 \times$ RBW, peak detector with maximum hold) is implemented by the instrumentation function.

When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 443-390, Korea
TEL: 82-70-5008-1021 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR16-SRF0017

Page (18) of (47)



5.4.3 Test Result

- Complied

Ant 0

Channel	Frequency [MHz]	6 dB Bandwidth [MHz]	Min. Limit [MHz]	Occupied Bandwidth (99 % BW) [MHz]
Lowest	2 425	1.61	0.50	2.39
Middle	2 450	1.61	0.50	2.39
Highest	2 475	1.61	0.50	2.39

Ant 1

Channel	Frequency [MHz]	6 dB Bandwidth [MHz]	Min. Limit [MHz]	Occupied Bandwidth (99 % BW) [MHz]
Lowest	2 425	1.62	0.50	2.39
Middle	2 450	1.59	0.50	2.41
Highest	2 475	1.59	0.50	2.39

-NOTE:

1. We took the insertion loss of the cable loss into consideration within the measuring instrument.

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 443-390, Korea
TEL: 82-70-5008-1021 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR16-SRF0017
Page (19) of (47)




5.4.4 Test Plot

Figure 2. Plot of the 6dB Bandwidth & Occupied Bandwidth


Ant 0

6 dB Bandwidth

Lowest Channel (2 425 MHz)



Middle Channel (2 450 MHz)




KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 443-390, Korea
TEL: 82-70-5008-1021 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR16-SRF0017
Page (20) of (47)




Highest Channel (2 475 MHz)



OBW

Lowest Channel (2 425 MHz)




KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 443-390, Korea
TEL: 82-70-5008-1021 FAX: 82-505-299-8311
www.kctl.co.kr


Report No.:
KR16-SRF0017
Page (21) of (47)



Middle Channel (2 450 MHz)



Highest Channel (2 475 MHz)



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 443-390, Korea
TEL: 82-70-5008-1021 FAX: 82-505-299-8311
www.kctl.co.kr


Report No.:
KR16-SRF0017
Page (22) of (47)




Ant 1

6 dB Bandwidth

Lowest Channel (2 425 MHz)



Middle Channel (2 450 MHz)




KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 443-390, Korea
TEL: 82-70-5008-1021 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR16-SRF0017
Page (23) of (47)




Highest Channel (2 475 MHz)




OBW


Lowest Channel (2 425 MHz)



Middle Channel (2 450 MHz)



Highest Channel (2 475 MHz)



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 443-390, Korea
TEL: 82-70-5008-1021 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR16-SRF0017

Page (25) of (47)



5.5 Spurious Emission, Band Edge, and Restricted bands

5.5.1 Regulation

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

According to §15.209(a), Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field strength ($\mu\text{V}/\text{m}$)	Measurement distance (m)
0.009 - 0.490	2 400/F(kHz)	300
0.490 - 1.705	24 000/F(kHz)	30
1.705 - 30	30	30
30 - 88	100**	3
88 - 216	150**	3
216 - 960	200**	3
Above 960	500	3

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54–72 MHz, 76–88 MHz, 174–216 MHz or 470–806 MHz.

However, operation within these frequency bands is permitted under other sections of this part, e.g., §§15.231 and 15.241.

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 443-390, Korea
TEL: 82-70-5008-1021 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR16-SRF0017

Page (26) of (47)



According to § 15.205(a) and (b), only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.009 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
0.495 - 0.505	16.694 75 - 16.695 25	608 - 614	5.35 - 5.46
2.173 5 - 2.190 5	16.804 25 - 16.804 75	960 - 1 240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1 300 - 1 427	8.025 - 8.5
4.177 25 - 4.177 75	37.5 - 38.25	1 435 - 1 626.5	9.0 - 9.2
4.207 25 - 4.207 75	73 - 74.6	1 645.5 - 1 646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1 660 - 1 710	10.6 - 12.7
6.267 75 - 6.268 25	108 - 121.94	1 718.8 - 1 722.2	13.25 - 13.4
6.311 75 - 6.312 25	123 - 138	2 200 - 2 300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2 310 - 2 390	15.35 - 16.2
8.362 - 8.366	156.524 75 - 156.525 25	2 483.5 - 2 500	17.7 - 21.4
8.376 25 - 8.386 75	156.7 - 156.9	2 690 - 2 900	22.01 - 23.12
8.414 25 - 8.414 75	162.012 5 - 167.17	3 260 - 3 267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3 332 - 3 339	31.2 - 31.8
12.519 75 - 12.520 25	240 - 285	3 345.8 - 3 358	36.43 - 36.5
12.576 75 - 12.577 25	322 - 335.4	3 600 - 4 400	Above 38.6
13.36 - 13.41			

The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in §15.209. At frequencies equal to or less than 1 000 MHz, compliance with the limits in §15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1 000 MHz, compliance with the emission limits in §15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in §15.35 apply to these measurements.

5.5.2 Measurement Procedure

5.5.2.1 Band-edge Compliance of RF Conducted Emissions

5.5.2.1.1 Reference Level Measurement

Establish a reference level by using the following procedure:

- 1) Set instrument center frequency to DTS channel center frequency.
- 2) Set the span to ≥ 1.5 times the DTS bandwidth.
- 3) Set the RBW = 100 kHz.
- 4) Set the VBW $\geq 3 \times$ RBW.
- 5) Detector = peak.
- 6) Sweep time = auto couple.
- 7) Trace mode = max hold.
- 8) Allow trace to fully stabilize.
- 9) Use the peak marker function to determine the maximum PSD level.

5.5.2.1.2 Emissions Level Measurement

- 1) Set the center frequency and span to encompass frequency range to be measured.
- 2) Set the RBW = 100 kHz.
- 3) Set the VBW $\geq 3 \times$ RBW.
- 4) Detector = peak.
- 5) Ensure that the number of measurement points \geq span/RBW
- 6) Sweep time = auto couple.
- 7) Trace mode = max hold.
- 8) Allow trace to fully stabilize.
- 9) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in 11.1 a) or 11.1 b). Report the three highest emissions relative to the limit.

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 443-390, Korea
TEL: 82-70-5008-1021 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR16-SRF0017

Page (28) of (47)



5.5.2.2 Conducted Spurious Emissions

Set the spectrum analyzer as follows:

- 1) Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.
- 2) RBW = 100 kHz
- 3) VBW \geq RBW
- 4) Sweep = auto
- 5) Detector function = peak
- 6) Trace = max hold
- 7) Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded.
- 8) Each frequency found during preliminary measurements was re-examined and investigated.
The test-receiver system was set up to average, peak, and quasi-peak detector function with specified bandwidth.

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 443-390, Korea
TEL: 82-70-5008-1021 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR16-SRF0017

Page (29) of (47)


KCTL

5.5.2.3 Radiated Spurious Emissions

- 1) The preliminary and final radiated measurements were performed to determine the frequency producing the maximum emissions in at a 10m anechoic chamber. The EUT was tested at a distance 3 meters.
- 2) The EUT was placed on the top of the 0.8-meter height, 1 × 1.5 meter non-metallic table. To find the maximum emission levels, the height of a measuring antenna was changed and the turntable was rotated 360°.
- 3) The antenna polarization was also changed from vertical to horizontal. The spectrum was scanned from 9 kHz to 30 MHz using the loop antenna, and from 30 to 1 000 MHz using the TRILOG broadband antenna, and from 1 000 MHz to 26 500 MHz using the horn antenna.
- 4) Each frequency found during preliminary measurements was re-examined and investigated. The test-receiver system was set up to average, peak, and quasi-peak detector function with specified bandwidth.
- 5) The 0.8m height is for below 1 G testing, and 1.5m is for above 1G testing.

Note

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1 GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection and frequency above 1 GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Average detection (AV) at frequency above 1 GHz.
(Detector=RMS, Average type=power, Perform a trace average: at least 100 traces)



Note: In zero-span status, Above plots prove that 100% duty-cycle.

5.5.3 Test Result

- Complied

1. Conducted Spurious Emissions was shown in figure 3.
Note: We took the insertion loss of the cable into consideration within the measuring instrument.
2. Measured value of the Field strength of spurious Emissions (Radiated)
3. It tested x,y and z – 3 axis each, mentioned only worst case data at this report.

- Below 1 GHz data (worst-case)

Lowest Channel (2 425 MHz)_ANT 0

Frequency [MHz]	Receiver Bandwidth [kHz]	Pol. [V/H]	Reading [dB(μV)]	Cable Loss [dB]	Amp Gain [dB]	Antenna Factor [dB]	Factor [dB]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]
Quasi-Peak DATA. Emissions below 30 MHz										
Below 30.00	Not Detected	-	-	-	-	-	-	-	-	-
Quasi-Peak DATA. Emissions below 1 GHz										
374.96	120	V	43.90	4.45	-32.60	15.25	-12.90	31.00	46.00	15.00
625.10	120	H	45.80	6.19	-32.87	19.38	-7.30	38.50	46.00	7.50
810.00	120	H	33.30	6.54	-32.58	20.94	-5.10	28.20	46.00	17.80
875.11	120	H	43.90	6.75	-32.20	21.85	-3.60	40.30	46.00	5.70
Above 900.00	Not Detected	-	-	-	-	-	-	-	-	-

Lowest Channel (2 425 MHz)_ANT 1

Frequency [MHz]	Receiver Bandwidth [kHz]	Pol. [V/H]	Reading [dB(μV)]	Cable Loss [dB]	Amp Gain [dB]	Antenna Factor [dB]	Factor [dB]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]
Quasi-Peak DATA. Emissions below 30 MHz										
Below 30.00	Not Detected	-	-	-	-	-	-	-	-	-
Quasi-Peak DATA. Emissions below 1 GHz										
375.08	120	V	49.20	4.45	-32.60	15.25	-12.90	36.30	46.00	9.70
624.97	120	H	46.30	6.20	-32.87	19.37	-7.30	39.00	46.00	7.00
810.12	120	H	38.60	6.54	-32.58	20.94	-5.10	33.50	46.00	12.50
875.11	120	V	41.10	6.75	-32.20	21.85	-3.60	37.50	46.00	8.50
Above 900.00	Not Detected	-	-	-	-	-	-	-	-	-

NOTE 1. Factor = Cable loss + Amp gain + Antenna factor

NOTE 2. Although these tests were performed other than open field test site, adequate comparison measurements were confirmed against 30 m open field test site.

Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 937606.

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 443-390, Korea
TEL: 82-70-5008-1021 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR16-SRF0017

Page (31) of (47)



- Above 1 GHz data_ANT 0

Lowest channel (2 425 MHz)

Frequency [MHz]	Receiver Bandwidth [kHz]	Pol. [V/H]	Reading [dB(μV)]	Cable Loss [dB]	Amp Gain [dB]	Antenna Factor [dB]	Factor [dB]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]
Peak DATA. Emissions above 1 GHz										
1 125.00	1 000	V	71.50	3.33	-62.76	28.73	-30.70	40.80	74.00	33.20
1 591.88	1 000	V	70.50	3.95	-64.05	29.90	-30.20	40.30	74.00	33.70
2 385.63 ¹⁾	1 000	V	68.80	4.79	-61.03	31.54	-24.70	44.10	74.00	29.90
4 850.31	1 000	V	68.80	6.47	-61.45	34.88	-20.10	48.70	74.00	25.30
15 190.62	1 000	H	59.80	11.62	-60.76	40.04	-9.10	50.70	74.00	23.30
19 175.12	1 000	H	49.20	12.80	-52.10	44.60	5.30	54.50	74.00	19.50
24 464.25	1 000	V	47.30	14.70	-52.40	45.20	7.50	54.80	74.00	19.20
Above 25 000.00	Not Detected	-	-	-	-	-	-	-	-	-
Average DATA. Emissions above 1 GHz										
1 125.00	1 000	V	65.10	3.33	-62.76	28.73	-30.70	34.40	54.00	19.60
1 591.88	1 000	V	59.60	3.95	-64.05	29.90	-30.20	29.40	54.00	24.60
2 385.63 ¹⁾	1 000	V	54.10	4.79	-61.03	31.54	-24.70	29.40	54.00	24.60
4 850.31	1 000	V	63.50	6.47	-61.45	34.88	-20.10	43.40	54.00	10.60
15 190.62	1 000	H	46.90	11.62	-60.76	40.04	-9.10	37.80	54.00	16.20
19 175.12	1 000	H	33.50	12.80	-52.10	44.60	5.30	38.80	54.00	15.20
24 464.25	1 000	V	32.70	14.70	-52.40	45.20	7.50	40.20	54.00	13.80
Above 25 000.00	Not Detected	-	-	-	-	-	-	-	-	-

¹⁾ Restricted band.

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 443-390, Korea
TEL: 82-70-5008-1021 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR16-SRF0017

Page (32) of (47)

**Middle channel (2 450 MHz)**

Frequency [MHz]	Receiver Bandwidth [kHz]	Pol. [V/H]	Reading [dB(μV)]	Cable Loss [dB]	Amp Gain [dB]	Antenna Factor [dB]	Factor [dB]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]
Peak DATA. Emissions above 1 GHz										
1 996.25	1 000	V	71.10	4.49	-62.71	30.92	-27.30	43.80	74.00	30.20
4 897.44	1 000	V	67.80	6.50	-61.41	35.01	-19.90	47.90	74.00	26.10
5 807.31	1 000	V	71.20	7.00	-62.33	35.33	-20.00	51.20	74.00	22.80
19 092.25	1 000	V	48.50	12.80	-52.00	44.50	5.30	53.80	74.00	20.20
24 683.12	1 000	H	46.90	14.80	-52.40	45.30	7.70	54.60	74.00	19.40
Above 25 000.00	Not Detected	-	-	-	-	-	-	-	-	-
Average DATA. Emissions above 1 GHz										
1 996.25	1 000	V	55.40	4.49	-62.71	30.92	-27.30	28.10	54.00	25.90
4 897.44	1 000	V	62.10	6.50	-61.41	35.01	-19.90	42.20	54.00	11.80
5 807.31	1 000	V	60.20	7.00	-62.33	35.33	-20.00	40.20	54.00	13.80
19 092.25	1 000	V	33.50	12.80	-52.00	44.50	5.30	38.80	54.00	15.20
24 683.12	1 000	H	32.70	14.80	-52.40	45.30	7.70	40.40	54.00	13.60
Above 25 000.00	Not Detected	-	-	-	-	-	-	-	-	-

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 443-390, Korea
TEL: 82-70-5008-1021 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR16-SRF0017
Page (33) of (47)

**Highest channel (2 475 MHz)**

Frequency [MHz]	Receiver Bandwidth [kHz]	Pol. [V/H]	Reading [dB(μV)]	Cable Loss [dB]	Amp Gain [dB]	Antenna Factor [dB]	Factor [dB]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]
Peak DATA. Emissions above 1 GHz										
1 752.81	1 000	V	76.70	4.17	-63.48	30.31	-29.00	47.70	74.00	26.30
1 125.31	1 000	V	73.90	3.33	-62.76	28.73	-30.70	43.20	74.00	30.80
2 483.75 ¹⁾	1 000	V	72.70	4.87	-61.07	31.70	-24.50	48.20	74.00	25.80
4 948.19	1 000	V	69.90	6.54	-61.48	35.14	-19.80	50.10	74.00	23.90
16 167.56	1 000	H	60.90	11.90	-61.09	41.09	-8.10	52.80	74.00	21.20
18 471.75	1 000	H	48.60	12.60	-51.70	44.20	5.10	53.70	74.00	20.30
24 662.94	1 000	V	47.20	14.80	-52.40	45.30	7.70	54.90	74.00	19.10
Above 25 000.00	Not Detected	-	-	-	-	-	-	-	-	-
Average DATA. Emissions above 1 GHz										
1 752.81	1 000	V	55.50	4.17	-63.48	30.31	-29.00	26.50	54.00	27.50
1 125.31	1 000	V	70.00	3.33	-62.76	28.73	-30.70	39.30	54.00	14.70
2 483.75 ¹⁾	1 000	V	56.70	4.87	-61.07	31.70	-24.50	32.20	54.00	21.80
4 948.19	1 000	V	62.40	6.54	-61.48	35.14	-19.80	42.60	54.00	11.40
16 167.56	1 000	H	48.10	11.90	-61.09	41.09	-8.10	40.00	54.00	14.00
18 471.75	1 000	H	33.10	12.60	-51.70	44.20	5.10	38.20	54.00	15.80
24 662.94	1 000	V	33.40	14.80	-52.40	45.30	7.70	41.10	54.00	12.90
Above 25 000.00	Not Detected	-	-	-	-	-	-	-	-	-

¹⁾ Restricted band.

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 443-390, Korea
TEL: 82-70-5008-1021 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR16-SRF0017

Page (34) of (47)



- Above 1 GHz data_Ant 1

Lowest channel (2 425 MHz)

Frequency [MHz]	Receiver Bandwidth [kHz]	Pol. [V/H]	Reading [dB(μV)]	Cable Loss [dB]	Amp Gain [dB]	Antenna Factor [dB]	Factor [dB]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]
Peak DATA. Emissions above 1 GHz										
1 125.00	1 000	V	71.40	3.33	-62.76	28.73	-30.70	40.70	74.00	33.30
1 595.94	1 000	V	70.90	3.96	-63.97	29.91	-30.10	40.80	74.00	33.20
2 387.81 ¹⁾	1 000	V	67.80	4.79	-61.04	31.55	-24.70	43.10	74.00	30.90
4 850.31	1 000	V	68.70	6.47	-61.45	34.88	-20.10	48.60	74.00	25.40
7 273.63	1 000	H	66.80	7.62	-61.66	35.84	-18.20	48.60	74.00	25.40
18 881.87	1 000	V	48.60	12.70	-51.90	44.40	5.20	53.80	74.00	20.20
24 819.12	1 000	V	46.90	14.90	-52.50	45.40	7.80	54.70	74.00	19.30
Above 25 000.00	Not Detected	-	-	-	-	-	-	-	-	-
Average DATA. Emissions above 1 GHz										
1 125.00	1 000	V	63.90	3.33	-62.76	28.73	-30.70	33.20	54.00	20.80
1 595.94	1 000	V	59.90	3.96	-63.97	29.91	-30.10	29.80	54.00	24.20
2 387.81 ¹⁾	1 000	V	55.80	4.79	-61.04	31.55	-24.70	31.10	54.00	22.90
4 850.31	1 000	V	62.10	6.47	-61.45	34.88	-20.10	42.00	54.00	12.00
7 273.63	1 000	H	57.30	7.62	-61.66	35.84	-18.20	39.10	54.00	14.90
18 881.87	1 000	V	32.70	12.70	-51.90	44.40	5.20	37.90	54.00	16.10
24 819.12	1 000	V	33.50	14.90	-52.50	45.40	7.80	41.30	54.00	12.70
Above 25 000.00	Not Detected	-	-	-	-	-	-	-	-	-

¹⁾ Restricted band.

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 443-390, Korea
TEL: 82-70-5008-1021 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR16-SRF0017

Page (35) of (47)

**Middle channel (2 450 MHz)**

Frequency [MHz]	Receiver Bandwidth [kHz]	Pol. [V/H]	Reading [dB(μV)]	Cable Loss [dB]	Amp Gain [dB]	Antenna Factor [dB]	Factor [dB]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]
Peak DATA. Emissions above 1 GHz										
1 736.25	1 000	V	72.30	4.15	-63.52	30.27	-29.10	43.20	74.00	30.80
4 901.06	1 000	H	69.80	6.51	-61.43	35.02	-19.90	49.90	74.00	24.10
15 511.44	1 000	V	60.90	11.71	-60.59	40.38	-8.50	52.40	74.00	21.60
18 665.12	1 000	H	48.00	12.60	-51.80	44.30	5.10	53.10	74.00	20.90
25 803.00	1 000	V	46.60	14.90	-52.00	46.20	9.10	55.70	74.00	18.30
Above 25 000.00	Not Detected	-	-	-	-	-	-	-	-	-
Average DATA. Emissions above 1 GHz										
1 736.25	1 000	V	54.30	4.15	-63.52	30.27	-29.10	25.20	54.00	28.80
4 901.06	1 000	H	63.10	6.51	-61.43	35.02	-19.90	43.20	54.00	10.80
15 511.44	1 000	V	47.30	11.71	-60.59	40.38	-8.50	38.80	54.00	15.20
18 665.12	1 000	H	33.60	12.60	-51.80	44.30	5.10	38.70	54.00	15.30
25 803.00	1 000	V	32.70	14.90	-52.00	46.20	9.10	41.80	54.00	12.20
Above 25 000.00	Not Detected	-	-	-	-	-	-	-	-	-

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 443-390, Korea
TEL: 82-70-5008-1021 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR16-SRF0017

Page (36) of (47)

**Highest channel (2 475 MHz)**

Frequency [MHz]	Receiver Bandwidth [kHz]	Pol. [V/H]	Reading [dB(μV)]	Cable Loss [dB]	Amp Gain [dB]	Antenna Factor [dB]	Factor [dB]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]
Peak DATA. Emissions above 1 GHz										
1 125.00	1 000	V	74.30	3.33	-62.76	28.73	-30.70	43.60	74.00	30.40
2 393.13	1 000	V	70.80	4.80	-60.96	31.56	-24.60	46.20	74.00	27.80
2 483.75 ¹⁾	1 000	V	73.30	4.87	-61.07	31.70	-24.50	48.80	74.00	25.20
4 950.00	1 000	H	68.80	6.54	-61.49	35.15	-19.80	49.00	74.00	25.00
15 536.81	1 000	V	59.80	11.71	-60.51	40.40	-8.40	51.40	74.00	22.60
19 523.62	1 000	V	48.20	12.90	-52.00	44.70	5.60	53.80	74.00	20.20
24 643.81	1 000	H	47.30	14.80	-52.50	45.30	7.60	54.90	74.00	19.10
Above 25 000.00	Not Detected	-	-	-	-	-	-	-	-	-
Average DATA. Emissions above 1 GHz										
1 125.00	1 000	V	71.00	3.33	-62.76	28.73	-30.70	40.30	54.00	13.70
2 393.13	1 000	V	58.70	4.80	-60.96	31.56	-24.60	34.10	54.00	19.90
2 483.75 ¹⁾	1 000	V	67.20	4.87	-61.07	31.70	-24.50	42.70	54.00	11.30
4 950.00	1 000	H	62.10	6.54	-61.49	35.15	-19.80	42.30	54.00	11.70
15 536.81	1 000	V	48.60	11.71	-60.51	40.40	-8.40	40.20	54.00	13.80
19 523.62	1 000	V	33.10	12.90	-52.00	44.70	5.60	38.70	54.00	15.30
24 643.81	1 000	H	32.50	14.80	-52.50	45.30	7.60	40.10	54.00	13.90
Above 25 000.00	Not Detected	-	-	-	-	-	-	-	-	-

¹⁾ Restricted band.


5.5.4 Test Plot

Figure 3. Plot of the Band-edge & Conducted Spurious Emissions


- Ant 0

Lowest Channel (2 425 MHz)

Reference



Band-edge



- Result of 2 400.0 MHz (F1 ~ F2: 2 390 MHz ~ 2 400 MHz)


KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 443-390, Korea
TEL: 82-70-5008-1021 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR16-SRF0017
Page (38) of (47)




Conducted Spurious Emissions



Middle Channel (2 450 MHz)

Reference




KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 443-390, Korea
TEL: 82-70-5008-1021 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR16-SRF0017
Page (39) of (47)




Conducted Spurious Emissions



Highest Channel (2 475 MHz)

Reference




KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 443-390, Korea
TEL: 82-70-5008-1021 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR16-SRF0017
Page (40) of (47)




Band-edge



- Result of 2 483.5 MHz (F1 ~ F2: 2 483.5 MHz ~ 2 500 MHz)

Conducted Spurious Emissions



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 443-390, Korea
TEL: 82-70-5008-1021 FAX: 82-505-299-8311
www.kctl.co.kr


Report No.:
KR16-SRF0017
Page (41) of (47)




-Ant 1

Lowest Channel (2 425 MHz)

Reference



Band-edge



- Result of 2 400.0 MHz (F1 ~ F2: 2 390 MHz ~ 2 400 MHz)


KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 443-390, Korea
TEL: 82-70-5008-1021 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR16-SRF0017
Page (42) of (47)




Conducted Spurious Emissions



Middle Channel (2 450 MHz)

Reference




KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 443-390, Korea
TEL: 82-70-5008-1021 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR16-SRF0017
Page (43) of (47)




Conducted Spurious Emissions



Highest Channel (2 475 MHz)

Reference




KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 443-390, Korea
TEL: 82-70-5008-1021 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR16-SRF0017
Page (44) of (47)




Band-edge



- Result of 2 483.5 MHz (F1 ~ F2: 2 483.5 MHz ~ 2 500 MHz)

Conducted Spurious Emissions



5.6 Conducted Emission

5.6.1 Regulation

According to §15.207(a), for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56 *	56 to 46 *
0.5 – 5	56	46
5 – 30	60	50

* Decreases with the logarithm of the frequency.

According to §15.107(a), for unintentional device, except for Class A digital devices, line conducted emission limits are the same as the above table.

5.6.2 Measurement Procedure


- 1) The EUT was placed on a wooden table of size, 1 m by 1.5 m, raised 80 cm in which is located 40 cm away from the vertical wall and 1.5m away from the side wall of the shielded room.
- 2) Each current-carrying conductor of the EUT power cord was individually connected through a 50 Ω /50 μ H LISN, which is an input transducer to a Spectrum Analyzer or an EMI/Field Intensity Meter, to the input power source.
- 3) Exploratory measurements were made to identify the frequency of the emission that had the highest amplitude relative to the limit by operating the EUT in a range of typical modes of operation, cable position, and with a typical system equipment configuration and arrangement. Based on the exploratory tests of the EUT, the one EUT cable configuration and arrangement and mode of operation that had produced the emission with the highest amplitude relative to the limit was selected for the final measurement.
- 4) The final test on all current-carrying conductors of all of the power cords to the equipment that comprises the EUT (but not the cords associated with other non-EUT equipment is the system) was then performed over the frequency range of 0.15 MHz to 30 MHz.
- 5) The measurements were made with the detector set to PEAK amplitude within a bandwidth of 10 kHz or to QUASI-PEAK and AVERAGE within a bandwidth of 9 kHz. The EUT was in transmitting mode during the measurements.

5.6.3 Test Result

- Complied

Figure 4. plot of Conducted Emission

- Conducted worst-case data : Lowest Channel (2 425 MHz)



Final Result

--- N Phase ---

No.	Frequency [MHz]	Reading QP [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB]	Result QP [dB(uV)]	Result CAV [dB(uV)]	Limit QP [dB(uV)]	Limit AV [dB(uV)]	Margin QP [dB]	Margin CAV [dB]
1	0.17068	26.7	9.0	10.1	36.8	19.1	64.9	54.9	28.1	35.8
2	6.13916	17.0	11.7	9.8	26.8	21.5	60.0	50.0	33.2	28.5
3	8.93195	16.2	10.7	9.9	26.1	20.6	60.0	50.0	33.9	29.4
4	14.13392	17.9	12.6	10.0	27.9	22.6	60.0	50.0	32.1	27.4

--- L1 Phase ---

No.	Frequency [MHz]	Reading QP [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB]	Result QP [dB(uV)]	Result CAV [dB(uV)]	Limit QP [dB(uV)]	Limit AV [dB(uV)]	Margin QP [dB]	Margin CAV [dB]
1	0.15538	34.0	22.0	9.9	43.9	31.9	65.7	55.7	21.8	23.8
2	0.15922	33.0	22.2	10.0	43.0	32.2	65.5	55.5	22.5	23.3
3	0.19558	27.8	13.2	10.0	37.8	23.2	63.8	53.8	26.0	30.6
4	0.51712	19.5	11.9	9.9	29.4	21.8	56.0	46.0	26.6	24.2
5	1.53001	21.0	12.7	9.8	30.8	22.5	56.0	46.0	25.2	23.5
6	2.63214	21.3	13.4	9.8	31.1	23.2	56.0	46.0	24.9	22.8
7	2.85215	21.7	13.0	9.8	31.5	22.8	56.0	46.0	24.5	23.2
8	7.24408	17.2	11.5	9.9	27.1	21.4	60.0	50.0	32.9	28.6

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 443-390, Korea
TEL: 82-70-5008-1021 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR16-SRF0017

Page (47) of (47)



6. Test equipment used for test

	Equipment Name	Manufacturer	Model No.	Serial No.	Next Cal. Date
■	Spectrum Analyzer	R & S	FSV30	100808	17.08.31
■	DC Power Supply	Tektronix	PS2520G	TW50517	17.03.04
■	Signal Generator	R & S	SMR40	100007	17.06.02
■	Wideband Power Sensor	R & S	NRP-Z81	100677	17.01.08
■	EMI TEST RECEIVER	R & S	ESCI	100732	17.08.25
■	Bi-Log Antenna	SCHWARZBECK	VULB 9163	552	18.06.27
■	Amplifier	SONOMA INSTRUMENT	310N	186280	17.04.07
■	Attenuator	SCHWARZBECK	DGA9552N	BU2404	17.04.08
■	Horn antenna	ETS.lindgren	3116	00086635	17.05.03
■	Horn antenna	ETS.lindgren	3117	161225	17.05.03
■	AMPLIFIER	L-3 Narda-MITEQ	AMF-7D-01001800-22-10P	2003683	17.08.26
■	AMPLIFIER	L-3 Narda-MITEQ	JS44-18004000-33-8P	2000996	17.08.26
■	LOOP Antenna	R & S	HFH2-Z2	100355	18.03.03
■	Antenna Mast	MATURO	AM4.0	079/3440509	-
■	Turn Table	MATURO	CO2000-SOFT	-	-
■	Highpass Filter	WT	WT-A1698-HS	WT160411001	17.07.08
■	Vector Signal Generator	R & S	SMBV100A	257566	17.01.07
■	Cable Assembly	HUER+SUHNER	SUCOFLEX 102	MY3571/2	-
■	TWO-LINE V - NETWORK	R & S	ENV216	101358	17.08.11