





FCC PART 15.247 TEST REPORT

For

Humax Co., Ltd.

HUMAX Village, 11-4, Sunae-dong, Bundang-gu, Seongnam city, Gyeonggi-do, 463-825,
South Korea

FCC ID: O6ZX1

Report Type: Original Report	Product Name: 11n Wireless Roaming Extender
Test Engineer: <u>Lorin Bian</u>	
Report Number: <u>RDG170303007</u>	
Report Date: <u>2017-03-14</u>	
Reviewed By: <u>Henry Ding</u> EMC Leader	
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Chengdu) 5040, HuiLongWan Plaza, No. 1, ShaWan Road, JinNiu District, ChengDu, China Tel: 028-65523123, Fax: 028-65525125 www.baclcorp.com

Note: This test report was prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Chengdu). Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. This report was valid only with a valid digital signature.

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE.....	6
EQUIPMENT MODIFICATIONS	9
SUPPORT EQUIPMENT LIST AND DETAILS	9
EXTERNAL CABLE	9
BLOCK DIAGRAM OF TEST SETUP	9
SUMMARY OF TEST RESULTS	10
FCC §15.247 (i) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	11
APPLICABLE STANDARD.....	11
FCC §15.203 - ANTENNA REQUIREMENT	12
APPLICABLE STANDARD.....	12
ANTENNA CONNECTOR CONSTRUCTION	12
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS.....	13
APPLICABLE STANDARD.....	13
MEASUREMENT UNCERTAINTY	13
EUT SETUP.....	14
EMI TEST RECEIVER SETUP	14
TEST PROCEDURE	14
CORRECTED AMPLITUDE & MARGIN CALCULATION	15
TEST EQUIPMENT LIST AND DETAILS	15
TEST DATA	15
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	18
APPLICABLE STANDARD.....	18
MEASUREMENT UNCERTAINTY	18
EUT SETUP.....	19
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	20
TEST PROCEDURE	20
CORRECTED AMPLITUDE & MARGIN CALCULATION	20
TEST EQUIPMENT LIST AND DETAILS	21
TEST DATA	21
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH	26
APPLICABLE STANDARD.....	26
TEST PROCEDURE	26
TEST EQUIPMENT LIST AND DETAILS	26
TEST DATA	26
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER	34
APPLICABLE STANDARD.....	34
TEST PROCEDURE	34

TEST EQUIPMENT LIST AND DETAILS	34
TEST DATA	34
FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE	36
APPLICABLE STANDARD	36
TEST PROCEDURE	36
TEST EQUIPMENT LIST AND DETAILS	36
TEST DATA	37
FCC §15.247(e) - POWER SPECTRAL DENSITY	46
APPLICABLE STANDARD	46
TEST PROCEDURE	46
TEST EQUIPMENT LIST AND DETAILS	46
TEST DATA	46

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The **Humax Co., Ltd.**'s product, model number: **QUANTUM X1 (FCC ID: O6ZX1)** (the "EUT") in this report was a **11n Wireless Roaming Extender**, which was measured approximately: 10 cm (L) x 6.8 cm (W) x 4.9 cm (H), rated input voltage: AC100-240V.

**All measurement and test data in this report was gathered from final production sample, serial number: 170303007 (assigned by the BACL, Chengdu). It may have deviation from any other sample. The EUT supplied by the applicant was received on 2017-03-03, and EUT conformed to test requirement.*

Objective

This report is prepared on behalf of **Humax Co., Ltd.** in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communications Commission's rules

The tests were performed in order to determine the compliance of the EUT with FCC Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

N/A

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Chengdu). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

The uncertainty of any RF tests which use conducted method measurement is ± 3.17 dB, the uncertainty of any radiation on emissions measurement is:

30M~200MHz: ± 4.7 dB;
200M~1GHz: ± 6.0 dB;
1G~6GHz: ± 5.13 dB;
6G~25GHz: ± 5.47 dB;

And the uncertainty will not be taken into consideration for all test data recorded in the report.

Test Facility

The test site used by BACL to collect test data is located in the 5040, HuiLongWan Plaza, No. 1, ShaWan Road, JinNiu District, Chengdu, China

Test site at BACL has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on April 24, 2015. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 560332. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in testing mode, which was provided by manufacturer. For 2.4GHz band, 11 channels are provided:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For 802.11b, 802.11g, and 802.11n ht20 modes were tested with channel 1, 6 and 11. For 802.11n ht40 mode were tested with Channel 3, 6 and 9.

The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rates bandwidths, and modulations.

EUT Exercise Software


The software "MP_TEST" was used for testing, which was provided by manufacturer. The worst condition was setting by the software as following table:

Test Mode	Test Software Version	MP_TEST		
		Test Frequency	2412MHz	2437MHz
802.11b	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	1Mbps	1Mbps	1Mbps
	Power Level Setting Chain0	40	40	40
	Power Level SettingChain1	42	42	42
802.11g	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	6Mbps	6Mbps	6Mbps
	Power Level Setting Chain0	40	40	40
	Power Level Setting Chain1	44	44	44
802.11n ht20	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	MCS0	MCS0	MCS0
	Power Level Setting Chain0&1	45	45	45
802.11n ht40	Test Frequency	2422MHz	2437MHz	2452MHz
	Data Rate	MCS0	MCS0	MCS0
	Power Level Setting Chain0&1	48	48	48

The duty cycle as below:


Test Mode	T _{on} (ms)	T _{on+off} (ms)	Duty Cycle (%)	Minimum Transmission Duration (T) (ms)
802.11b	2	2	100%	/
802.11g	8.51	8.58	99.18%	/
802.11n ht20	8.55	8.60	99.42%	/
802.11n ht40	0.664	0.824	80.58%	0.664

802.11b




Date: 13.MAR.2017 19:05:25

802.11g




Date: 13.MAR.2017 19:57:45

802.11n ht20



Date: 13.MAR.2017 20:06:21

802.11n ht40



Date: 13.MAR.2017 20:10:01

Equipment Modifications

No modification was made to the EUT tested.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
lenovo	laptop	TP00067A	PF-0MRADG 16/08

External Cable

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
RJ 45 Cable	no	no	10	EUT	Laptop

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i) & §1.1310 & §2.1091	Maximum Permissible Exposure (MPE)	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliant
§15.247(b)(3)	Maximum conducted output power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

FCC §15.247 (i) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247(i) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Frequency (MHz)	Antenna Gain		Tune-up Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
	(dBi)	(numeric)	(dBm)	(mW)			
2412-2462	4	2.51	25	316.23	20.00	0.1581	1.0

Note: The maximum tune-up power including tolerance is 25dBm, that declared by manufacturer.

Result: The device meet FCC MPE at 20 cm distance

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Antenna Connector Construction

The EUT has 2 internal antennas, and the antenna gain is 4.0 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cispr} of Table 1, then:

–compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
–non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cispr} of Table 1, then:


–compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit;
–non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit.

Based on CISPR 16-4-2:2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Chengdu) is ± 3.17 dB (150 kHz to 30 MHz).

Table 1 – Values of U_{cispr}

Measurement	U_{cispr}
Conducted disturbance at mains port using AMN (150 kHz to 30 MHz)	3.4 dB

EUT Setup



- Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to an AC 120 V/60 Hz power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

V_C (cord. Reading): corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN

C_f : Correction Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS 30	836858/0016	2016-12-02	2017-12-01
Rohde & Schwarz	L.I.S.N.	ENV216	3560.6550.06	2016-12-02	2017-12-01
Rohde & Schwarz	PULSE LIMITER	ESH3Z2	357.8810.52	2016-10-31	2017-10-30
N/A	Conducted Cable	NO.5	N/A	2016-11-10	2017-11-09
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A

* **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data


Environmental Conditions

Temperature:	24.3 °C
Relative Humidity:	44%
ATM Pressure:	97.6kPa

The testing was performed by Lorin Bian on 2017-03-07.

Test Mode: Operating


AC120 V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.541050	36.0	9.000	L1	19.7	20.0	56.0	Compliance
0.732382	33.4	9.000	L1	19.7	22.6	56.0	Compliance
0.805868	35.3	9.000	L1	19.7	20.7	56.0	Compliance
0.900972	33.3	9.000	L1	19.7	22.7	56.0	Compliance
1.289541	39.4	9.000	L1	19.7	16.6	56.0	Compliance
1.548915	32.3	9.000	L1	19.7	23.7	56.0	Compliance

Frequency (MHz)	Average (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.536756	24.0	9.000	L1	19.7	22.0	46.0	Compliance
0.831967	25.1	9.000	L1	19.7	20.9	46.0	Compliance
1.239175	30.5	9.000	L1	19.7	15.5	46.0	Compliance
1.289541	31.3	9.000	L1	19.7	14.7	46.0	Compliance
16.777473	28.8	9.000	L1	20.1	21.2	50.0	Compliance
20.804674	29.1	9.000	L1	20.1	20.9	50.0	Compliance

AC120 V, 60 Hz, Neutral:



Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.419276	34.3	9.000	N	19.6	23.2	57.5	Compliance
0.541050	29.2	9.000	N	19.6	26.8	56.0	Compliance
0.720803	27.7	9.000	N	19.6	28.3	56.0	Compliance
0.805868	28.1	9.000	N	19.6	27.9	56.0	Compliance
1.239175	35.3	9.000	N	19.6	20.7	56.0	Compliance
1.289541	37.7	9.000	N	19.6	18.3	56.0	Compliance

Frequency (MHz)	Average (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.419276	22.2	9.000	N	19.6	25.3	47.5	Compliance
1.239175	29.8	9.000	N	19.6	16.2	46.0	Compliance
1.289541	32.8	9.000	N	19.6	13.2	46.0	Compliance
15.616430	23.9	9.000	N	19.9	26.1	50.0	Compliance
16.777473	22.2	9.000	N	19.9	27.8	50.0	Compliance
20.804674	24.7	9.000	N	20.0	25.3	50.0	Compliance

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cispr} of Table 2, then:

–compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
–non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cispr} of Table 2, then:

–compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit;
–non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit.

Based on CISPR 16-4-2-2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Chengdu) is:

30M~200MHz: ±4.7 dB;

200M~1GHz: ±6.0 dB;

1G~6GHz: ±5.13dB;


6G~25GHz: ±5.47 dB;

Table 2 – Values of U_{cispr}


Measurement	U_{cispr}
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

30MHz-1000MHz:

Detector	RBW	Video B/W	IF B/W
QP	120 kHz	300 kHz	120kHz

1GHz- 25GHz:

Detector	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
Ave.	>98%	1MHz	10 Hz
	<98%	1MHz	1/T

Note: T is minimum transmission duration

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Loss} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	Amplifier	8447D	2944A10442	2016-12-02	2017-12-01
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2016-12-02	2017-12-01
Sunol Sciences	Broadband Antenna	JB3	A101808	2016-04-10	2019-04-09
Rohde & Schwarz	Spectrum Analyzer	FSEM30	100018	2016-12-02	2017-12-01
ETS	Horn Antenna	3115	003-6076	2016-12-02	2017-12-01
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-0113024	2014-06-16	2017-06-15
Mini-circuits	Amplifier	ZVA-183-S+	771001215	2016-05-20	2017-05-19
HP	Amplifier	8449B	3008A00277	2016-12-02	2017-12-01
EMCT	Semi-Anechoic Chamber	966	N/A	2015-04-24	2018-04-23
N/A	RF Cable (below 1GHz)	NO.1	N/A	2016-11-10	2017-11-09
N/A	RF Cable (below 1GHz)	NO.4	N/A	2016-11-10	2017-11-09
N/A	RF Cable (above 1GHz)	NO.2	N/A	2016-11-10	2017-11-09
WEINSCHL ENGINEERING	Attenuator	1A10dB	AA4135	2016-11-10	2017-11-09

* **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	23.4 °C
Relative Humidity:	50 %
ATM Pressure:	98.2 kPa

* The testing was performed by Lorin Bian on 2017-03-08

Test Mode: Transmitting

30MHz-25GHz:

802.11b Mode(Chain 0 was the worst)

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412	85.17	PK	H	23.50	3.00	0.00	111.67	N/A	N/A
2412	80.34	AV	H	23.50	3.00	0.00	106.84	N/A	N/A
2412	76.58	PK	V	23.50	3.00	0.00	103.08	N/A	N/A
2412	72.18	AV	V	23.50	3.00	0.00	98.68	N/A	N/A
2390	33.23	PK	H	23.57	3.00	0.00	59.8	74	14.2
2390	19.41	AV	H	23.57	3.00	0.00	45.98	54	8.02
4824	28.18	PK	H	30.84	5.11	26.87	37.26	74	36.74
4824	15.41	AV	H	30.84	5.11	26.87	24.49	54	29.51
7236	26.04	PK	H	34.77	6.18	26.36	40.63	74	33.37
7236	13.72	AV	H	34.77	6.18	26.36	28.31	54	25.69
9648	17.24	PK	H	37.09	7.79	26.20	35.92	74	38.08
9648	4.75	AV	H	37.09	7.79	26.20	23.43	54	30.57
2929	37.61	PK	H	24.06	3.37	26.48	38.56	74	35.44
2929	23.74	AV	H	24.06	3.37	26.48	24.69	54	29.31
235	53.27	QP	H	12.10	1.12	27.57	38.92	46.00	7.08
249.22	46.58	QP	H	12.30	1.23	27.53	32.58	46.00	13.42
Middle Channel: 2437 MHz									
2437	85.16	PK	H	23.41	3.00	0.00	111.57	N/A	N/A
2437	81.00	AV	H	23.41	3.00	0.00	107.41	N/A	N/A
2437	76.45	PK	V	23.41	3.00	0.00	102.86	N/A	N/A
2437	71.82	AV	V	23.41	3.00	0.00	98.23	N/A	N/A
4874	28.87	PK	H	31.00	5.09	26.87	38.09	74	35.91
4874	14.37	AV	H	31.00	5.09	26.87	23.59	54	30.41
7311	25.64	PK	H	34.92	6.21	26.40	40.37	74	33.63
7311	11.16	AV	H	34.92	6.21	26.40	25.89	54	28.11
9748	18.98	PK	H	37.15	7.72	26.26	37.59	74	36.41
9748	6.20	AV	H	37.15	7.72	26.26	24.81	54	29.19
3089	34.68	PK	H	24.70	3.56	26.44	36.5	74	37.5
3089	21.31	AV	H	24.70	3.56	26.44	23.13	54	30.87
235	53.54	QP	H	12.10	1.12	27.57	39.19	46.00	6.81
249.22	46.72	QP	H	12.30	1.23	27.53	32.72	46.00	13.28
High Channel: 2462 MHz									
2462	85.32	PK	H	23.33	2.99	0.00	111.64	N/A	N/A
2462	80.81	AV	H	23.33	2.99	0.00	107.13	N/A	N/A
2462	74.44	PK	V	23.33	2.99	0.00	100.76	N/A	N/A
2462	70.12	AV	V	23.33	2.99	0.00	96.44	N/A	N/A
2483.5	34.61	PK	H	23.26	2.99	0.00	60.86	74	13.14
2483.5	20.44	AV	H	23.26	2.99	0.00	46.69	54	7.31
4924	29.13	PK	H	31.16	5.07	26.88	38.48	74	35.52
4924	14.41	AV	H	31.16	5.07	26.88	23.76	54	30.24
7386	25.41	PK	H	35.07	6.25	26.43	40.3	74	33.7
7386	12.67	AV	H	35.07	6.25	26.43	27.56	54	26.44
9848	17.43	PK	H	37.21	7.65	26.33	35.96	74	38.04
9848	4.65	AV	H	37.21	7.65	26.33	23.18	54	30.82
235	54.38	QP	H	12.10	1.12	27.57	40.03	46.00	5.97
249.22	47.14	QP	H	12.30	1.23	27.53	33.14	46.00	12.86

802.11g Mode(Chain 0 was the worst)

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412	83.12	PK	H	23.50	3.00	0.00	109.62	N/A	N/A
2412	71.86	AV	H	23.50	3.00	0.00	98.36	N/A	N/A
2412	75.24	PK	V	23.50	3.00	0.00	101.74	N/A	N/A
2412	65.03	AV	V	23.50	3.00	0.00	91.53	N/A	N/A
2390	35.75	PK	H	23.57	3.00	0.00	62.32	74	11.68
2390	20.25	AV	H	23.57	3.00	0.00	46.82	54	7.18
4824	29.10	PK	H	30.84	5.11	26.87	38.18	74	35.82
4824	15.56	AV	H	30.84	5.11	26.87	24.64	54	29.36
7236	25.68	PK	H	34.77	6.18	26.36	40.27	74	33.73
7236	13.40	AV	H	34.77	6.18	26.36	27.99	54	26.01
9648	18.47	PK	H	37.09	7.79	26.20	37.15	74	36.85
9648	4.00	AV	H	37.09	7.79	26.20	22.68	54	31.32
3067	35.02	PK	H	24.58	3.53	26.43	36.7	74	37.3
3067	21.04	AV	H	24.58	3.53	26.43	22.72	54	31.28
235	53.91	QP	H	12.10	1.12	27.57	39.56	46.00	6.44
249.22	47.58	QP	H	12.30	1.23	27.53	33.58	46.00	12.42
Middle Channel: 2437 MHz									
2437	82.82	PK	H	23.41	3.00	0.00	109.23	N/A	N/A
2437	71.91	AV	H	23.41	3.00	0.00	98.32	N/A	N/A
2437	75.75	PK	V	23.41	3.00	0.00	102.16	N/A	N/A
2437	65.21	AV	V	23.41	3.00	0.00	91.62	N/A	N/A
4874	28.22	PK	H	31.00	5.09	26.87	37.44	74	36.56
4874	15.45	AV	H	31.00	5.09	26.87	24.67	54	29.33
7311	25.80	PK	H	34.92	6.21	26.40	40.53	74	33.47
7311	11.44	AV	H	34.92	6.21	26.40	26.17	54	27.83
9748	18.50	PK	H	37.15	7.72	26.26	37.11	74	36.89
9748	5.70	AV	H	37.15	7.72	26.26	24.31	54	29.69
3243	31.97	PK	H	25.56	3.79	26.50	34.82	74	39.18
3243	18.07	AV	H	25.56	3.79	26.50	20.92	54	33.08
235	53.44	QP	H	12.10	1.12	27.57	39.09	46.00	6.91
249.22	48.02	QP	H	12.30	1.23	27.53	34.02	46.00	11.98
High Channel: 2462 MHz									
2462	81.92	PK	H	23.33	2.99	0.00	108.24	N/A	N/A
2462	71.21	AV	H	23.33	2.99	0.00	97.53	N/A	N/A
2462	74.34	PK	V	23.33	2.99	0.00	100.66	N/A	N/A
2462	63.91	AV	V	23.33	2.99	0.00	90.23	N/A	N/A
2483.5	39.96	PK	H	23.26	2.99	0.00	66.21	74	7.79
2483.5	21.17	AV	H	23.26	2.99	0.00	47.42	54	6.58
4924	28.10	PK	H	31.16	5.07	26.88	37.45	74	36.55
4924	14.66	AV	H	31.16	5.07	26.88	24.01	54	29.99
7386	25.13	PK	H	35.07	6.25	26.43	40.02	74	33.98
7386	12.73	AV	H	35.07	6.25	26.43	27.62	54	26.38
9848	17.54	PK	H	37.21	7.65	26.33	36.07	74	37.93
9848	5.75	AV	H	37.21	7.65	26.33	24.28	54	29.72
2960	36.40	PK	H	24.12	3.39	26.45	37.46	74	36.54
2960	23.43	AV	H	24.12	3.39	26.45	24.49	54	29.51
235	53.87	QP	H	12.10	1.12	27.57	39.52	46.00	6.48
249.22	45.67	QP	H	12.30	1.23	27.53	31.67	46.00	14.33

802.11 n ht20 Mode(MIMO was the worst)

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412	83.60	PK	H	23.50	3.00	0.00	110.1	N/A	N/A
2412	71.87	AV	H	23.50	3.00	0.00	98.37	N/A	N/A
2412	74.39	PK	V	23.50	3.00	0.00	100.89	N/A	N/A
2412	62.93	AV	V	23.50	3.00	0.00	89.43	N/A	N/A
2390	41.02	PK	H	23.57	3.00	0.00	67.59	74	6.41
2390	24.54	AV	H	23.57	3.00	0.00	51.11	54	2.89
4824	28.00	PK	H	30.84	5.11	26.87	37.08	74	36.92
4824	14.94	AV	H	30.84	5.11	26.87	24.02	54	29.98
7236	25.99	PK	H	34.77	6.18	26.36	40.58	74	33.42
7236	12.81	AV	H	34.77	6.18	26.36	27.4	54	26.6
9648	18.29	PK	H	37.09	7.79	26.20	36.97	74	37.03
9648	4.25	AV	H	37.09	7.79	26.20	22.93	54	31.07
3173	32.34	PK	H	25.17	3.69	26.47	34.73	74	39.27
3173	19.74	AV	H	25.17	3.69	26.47	22.13	54	31.87
235	54.14	QP	H	12.10	1.12	27.57	39.79	46.00	6.21
249.22	45.81	QP	H	12.30	1.23	27.53	31.81	46.00	14.19
Middle Channel: 2437 MHz									
2437	82.70	PK	H	23.41	3.00	0.00	109.11	N/A	N/A
2437	71.02	AV	H	23.41	3.00	0.00	97.43	N/A	N/A
2437	73.89	PK	V	23.41	3.00	0.00	100.3	N/A	N/A
2437	63.20	AV	V	23.41	3.00	0.00	89.61	N/A	N/A
4874	29.04	PK	H	31.00	5.09	26.87	38.26	74	35.74
4874	14.78	AV	H	31.00	5.09	26.87	24	54	30
7311	25.58	PK	H	34.92	6.21	26.40	40.31	74	33.69
7311	11.72	AV	H	34.92	6.21	26.40	26.45	54	27.55
9748	18.57	PK	H	37.15	7.72	26.26	37.18	74	36.82
9748	5.68	AV	H	37.15	7.72	26.26	24.29	54	29.71
3317	31.22	PK	H	25.98	3.91	26.52	34.59	74	39.41
3317	18.02	AV	H	25.98	3.91	26.52	21.39	54	32.61
235	54.98	QP	H	12.10	1.12	27.57	40.63	46.00	5.37
249.22	46.23	QP	H	12.30	1.23	27.53	32.23	46.00	13.77
High Channel: 2462 MHz									
2462	83.15	PK	H	23.33	2.99	0.00	109.47	N/A	N/A
2462	71.87	AV	H	23.33	2.99	0.00	98.19	N/A	N/A
2462	75.20	PK	V	23.33	2.99	0.00	101.52	N/A	N/A
2462	64.14	AV	V	23.33	2.99	0.00	90.46	N/A	N/A
2483.5	38.04	PK	H	23.26	2.99	0.00	64.29	74	9.71
2483.5	21.07	AV	H	23.26	2.99	0.00	47.32	54	6.68
4924	29.01	PK	H	31.16	5.07	26.88	38.36	74	35.64
4924	14.03	AV	H	31.16	5.07	26.88	23.38	54	30.62
7386	25.71	PK	H	35.07	6.25	26.43	40.6	74	33.4
7386	12.73	AV	H	35.07	6.25	26.43	27.62	54	26.38
9848	17.57	PK	H	37.21	7.65	26.33	36.1	74	37.9
9848	4.33	AV	H	37.21	7.65	26.33	22.86	54	31.14
3070	35.39	PK	H	24.59	3.54	26.44	37.08	74	36.92
3070	21.38	AV	H	24.59	3.54	26.44	23.07	54	30.93
235	54.51	QP	H	12.10	1.12	27.57	40.16	46.00	5.84
249.22	46.67	QP	H	12.30	1.23	27.53	32.67	46.00	13.33

802.11 n ht40 Mode(MIMO was the worst)

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2422 MHz									
2422	80.79	PK	H	23.47	3.00	0.00	107.26	N/A	N/A
2422	69.55	AV	H	23.47	3.00	0.00	96.02	N/A	N/A
2422	73.37	PK	V	23.47	3.00	0.00	99.84	N/A	N/A
2422	62.46	AV	V	23.47	3.00	0.00	88.93	N/A	N/A
2390	36.71	PK	H	23.57	3.00	0.00	63.28	74	10.72
2390	22.61	AV	H	23.57	3.00	0.00	49.18	54	4.82
4844	28.55	PK	H	30.90	5.10	26.87	37.68	74	36.32
4844	15.06	AV	H	30.90	5.10	26.87	24.19	54	29.81
7266	26.09	PK	H	34.83	6.19	26.38	40.73	74	33.27
7266	12.41	AV	H	34.83	6.19	26.38	27.05	54	26.95
9688	18.47	PK	H	37.11	7.76	26.23	37.11	74	36.89
9688	4.89	AV	H	37.11	7.76	26.23	23.53	54	30.47
3183	32.79	PK	H	25.22	3.70	26.48	35.23	74	38.77
3183	19.54	AV	H	25.22	3.70	26.48	21.98	54	32.02
235	54.04	QP	H	12.10	1.12	27.57	39.69	46.00	6.31
249.22	47.11	QP	H	12.30	1.23	27.53	33.11	46.00	12.89
Middle Channel: 2437 MHz									
2437	81.63	PK	H	23.41	3.00	0.00	108.04	N/A	N/A
2437	69.70	AV	H	23.41	3.00	0.00	96.11	N/A	N/A
2437	73.83	PK	V	23.41	3.00	0.00	100.24	N/A	N/A
2437	62.71	AV	V	23.41	3.00	0.00	89.12	N/A	N/A
4874	28.03	PK	H	31.00	5.09	26.87	37.25	74	36.75
4874	15.00	AV	H	31.00	5.09	26.87	24.22	54	29.78
7311	26.09	PK	H	34.92	6.21	26.40	40.82	74	33.18
7311	12.23	AV	H	34.92	6.21	26.40	26.96	54	27.04
9748	18.77	PK	H	37.15	7.72	26.26	37.38	74	36.62
9748	5.50	AV	H	37.15	7.72	26.26	24.11	54	29.89
3496	32.46	PK	H	26.98	4.17	26.59	37.02	74	36.98
3496	18.77	AV	H	26.98	4.17	26.59	23.33	54	30.67
235	52.97	QP	H	12.10	1.12	27.57	38.62	46.00	7.38
249.22	45.75	QP	H	12.30	1.23	27.53	31.75	46.00	14.25
High Channel: 2452 MHz									
2452	78.63	PK	H	23.36	3.00	0.00	104.99	N/A	N/A
2452	67.35	AV	H	23.36	3.00	0.00	93.71	N/A	N/A
2452	69.18	PK	V	23.36	3.00	0.00	95.54	N/A	N/A
2452	58.50	AV	V	23.36	3.00	0.00	84.86	N/A	N/A
2483.5	38.41	PK	H	23.26	2.99	0.00	64.66	74	9.34
2483.5	25.57	AV	H	23.26	2.99	0.00	51.82	54	2.18
4904	28.76	PK	H	31.09	5.08	26.87	38.06	74	35.94
4904	14.28	AV	H	31.09	5.08	26.87	23.58	54	30.42
7356	26.05	PK	H	35.01	6.23	26.42	40.87	74	33.13
7356	12.20	AV	H	35.01	6.23	26.42	27.02	54	26.98
9808	18.68	PK	H	37.18	7.68	26.30	37.24	74	36.76
9808	4.56	AV	H	37.18	7.68	26.30	23.12	54	30.88
2961	36.14	PK	H	24.12	3.40	26.45	37.21	74	36.79
2961	23.38	AV	H	24.12	3.40	26.45	24.45	54	29.55
235	53.24	QP	H	12.10	1.12	27.57	38.89	46.00	7.11
249.22	45.89	QP	H	12.30	1.23	27.53	31.89	46.00	14.11


FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH

Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2016-12-02	2017-12-01
N/A	RF Cable	N/A	N/A	Each Time	/

* **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	22.1~23.4 °C
Relative Humidity:	38~50 %
ATM Pressure:	98.2~99.7 kPa


* The testing was performed by Lorin Bian from 2017-03-08 to 2017-03-13.

Test Mode: Transmitting (Test performed at Chain 0 only)

Test Result: Compliant. Please refer to the following table and plots.


Test mode	Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
802.11b	Low	2412	10.16	≥0.5
	Middle	2437	10.08	≥0.5
	High	2462	10.16	≥0.5
802.11g	Low	2412	16.64	≥0.5
	Middle	2437	16.64	≥0.5
	High	2462	16.64	≥0.5
802.11n20	Low	2412	17.92	≥0.5
	Middle	2437	17.84	≥0.5
	High	2462	17.84	≥0.5
802.11 n40	Low	2422	36.64	≥0.5
	Middle	2437	36.64	≥0.5
	High	2452	36.64	≥0.5

802.11b Low Channel




Date: 8.MAR.2017 15:02:24

802.11b Middle Channel




Date: 8.MAR.2017 15:14:21

802.11b High Channel




Date: 8.MAR.2017 15:18:16

802.11g Low Channel




Date: 8.MAR.2017 15:21:15

802.11g Middle Channel




Date: 8.MAR.2017 15:23:35

802.11g High Channel




Date: 8.MAR.2017 15:26:28

802.11n ht20 Low Channel




Date: 8.MAR.2017 15:29:57

802.11n ht20 Middle Channel




Date: 8.MAR.2017 15:33:20

802.11n ht20 High Channel




Date: 8.MAR.2017 15:35:59

802.11n ht40 Low Channel




Date: 8.MAR.2017 15:40:16

802.11n ht40 Middle Channel



Date: 8.MAR.2017 15:43:18

802.11n ht40 High Channel



Date: 13.MAR.2017 11:21:30


FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
3. Add a correction factor to the display.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	Wideband Power Sensor	N1921A	MY54170074	2017-01-03	2018-01-03
Agilent	P-Series Power Meter	N1912A	MY5000798	2017-01-03	2018-01-03
N/A	RF Cable	N/A	N/A	Each Time	/

* **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	23.4 °C
Relative Humidity:	50 %
ATM Pressure:	98.2kPa

* The testing was performed by Lorin Bian on 2017-03-08.

Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table.

Test mode	Channel	Frequency (MHz)	Max Peak Conducted Output Power (dBm)		Total (dBm)	Limit (dBm)
			Chain 0	Chain 1		
802.11b	Low	2412	20.51	19.36	/	30
	Middle	2437	20.19	19.55	/	30
	High	2462	19.9	19.57	/	30
802.11g	Low	2412	19.33	19.39	/	30
	Middle	2437	19.07	19.53	/	30
	High	2462	18.75	19.55	/	30
802.11n20	Low	2412	20.28	21.44	23.91	30
	Middle	2437	20.53	20.95	23.76	30
	High	2462	20.11	20.55	23.35	30
802.11n40	Low	2422	22.1	20.92	24.56	30
	Middle	2437	22.38	20.58	24.58	30
	High	2452	18.1	19.76	22.02	30

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2016-12-02	2017-12-01
N/A	RF Cable	N/A	N/A	Each Time	/

* **Statement of Traceability:** BAAC (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	22.1~23.4 °C
Relative Humidity:	38~50 %
ATM Pressure:	98.2~99.7 kPa


* The testing was performed by Lorin Bian from 2017-03-08 to 2017-03-13.

Test mode: Transmitting

Test Result: Compliant. Please refer to following plots.


Chain 0:

802.11b: Band Edge, Left Side




Date: 8.MAR.2017 15:13:06

802.11b: Band Edge, Right Side




Date: 8.MAR.2017 15:19:54

802.11g: Band Edge, Left Side




Date: 8.MAR.2017 15:23:00

802.11g: Band Edge, Right Side




Date: 8.MAR.2017 15:28:24

802.11n ht20 Band Edge, Left Side




Date: 8.MAR.2017 15:31:50

802.11n ht20 Band Edge, Right Side




Date: 8.MAR.2017 15:37:39

802.11n ht40 Band Edge, Left Side



Date: 8.MAR.2017 15:42:13


802.11n ht40 Band Edge, Right Side



Date: 13.MAR.2017 11:23:41


Chain 1:

802.11b: Band Edge, Left Side




Date: 8.MAR.2017 16:14:29

802.11b: Band Edge, Right Side




Date: 8.MAR.2017 16:19:25

802.11g: Band Edge, Left Side




Date: 8.MAR.2017 16:22:18

802.11g: Band Edge, Right Side




Date: 8.MAR.2017 16:26:44

802.11n ht20 Band Edge, Left Side




Date: 8.MAR.2017 15:52:38

802.11n ht20 Band Edge, Right Side




Date: 8.MAR.2017 15:58:06

802.11n ht40 Band Edge, Left Side



Date: 8.MAR.2017 16:01:11

802.11n ht40 Band Edge, Right Side



Date: 13.MAR.2017 11:26:59

FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set the VBW $\geq 3 \times \text{RBW}$.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2016-12-02	2017-12-01
N/A	RF Cable	N/A	N/A	Each Time	/

* **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	22.1~23.4 °C
Relative Humidity:	38~50 %
ATM Pressure:	98.2~99.7 kPa

* The testing was performed by Lorin Bian on 2017-03-08 to 2017-03-13.

Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table and plots

Test mode	Channel	Frequency (MHz)	PSD (dBm/3kHz)		Total (dBm/3kHz)	Limit (dBm/3kHz)
			Chain 0	Chain 1		
802.11b	Low	2412	-13.62	-14.61	/	≤8
	Middle	2437	-13.87	-14.44	/	≤8
	High	2462	-14.17	-14.46	/	≤8
802.11g	Low	2412	-16.2	-15.79	/	≤8
	Middle	2437	-16.31	-15.75	/	≤8
	High	2462	-16.43	-15.56	/	≤8
802.11n20	Low	2412	-14.32	-13.98	-11.14	≤7
	Middle	2437	-14.42	-14.15	-11.27	≤7
	High	2462	-14.82	-15.08	-11.94	≤7
802.11n40	Low	2422	-14.09	-15.65	-11.79	≤7
	Middle	2437	-13.24	-15	-11.02	≤7
	High	2452	-18.55	-18	-15.26	≤7

Note:

The 2 antenna maximum antenna gains are 4.0 dBi, and employed Cyclic Delay Diversity (CDD) for 802.11 MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power density measurements on IEEE 802.11 devices,


$$\text{Array Gain} = 10 \log(\text{NANT}/\text{NSS}) \text{ dB.}$$

So:

$$\text{Directional gain} = \text{GANT} + \text{Array Gain} = 4 + 10 * \log(2) = 7 \text{ dBi}$$


Chain 0:

Power Spectral Density, 802.11b Low Channel




Date: 8.MAR.2017 15:03:39

Power Spectral Density, 802.11b Middle Channel




Date: 8.MAR.2017 15:15:39

Power Spectral Density, 802.11b High Channel




Date: 8.MAR.2017 15:19:36

Power Spectral Density, 802.11g Low Channel




Date: 8.MAR.2017 15:22:37

Power Spectral Density, 802.11g Middle Channel




Date: 8.MAR.2017 15:24:53

Power Spectral Density, 802.11g High Channel




Date: 8.MAR.2017 15:27:51

Power Spectral Density, 802.11n ht20 Low Channel




Date: 8.MAR.2017 15:31:20

Power Spectral Density, 802.11n ht20 Middle Channel




Date: 8.MAR.2017 15:34:52

Power Spectral Density, 802.11n ht20 High Channel




Date: 8.MAR.2017 15:37:21

Power Spectral Density, 802.11n ht40 Low Channel




Date: 8.MAR.2017 15:41:49

Power Spectral Density, 802.11n ht40 Middle Channel



Date: 8.MAR.2017 15:44:52


Power Spectral Density, 802.11n ht40 High Channel



Date: 13.MAR.2017 11:23:20


Chain 1:

Power Spectral Density, 802.11b Low Channel




Date: 8.MAR.2017 16:14:06

Power Spectral Density, 802.11b Middle Channel




Date: 8.MAR.2017 16:16:22

Power Spectral Density, 802.11b High Channel




Date: 8.MAR.2017 16:19:07

Power Spectral Density, 802.11g Low Channel




Date: 8.MAR.2017 16:21:54

Power Spectral Density, 802.11g Middle Channel




Date: 8.MAR.2017 16:24:27

Power Spectral Density, 802.11g High Channel




Date: 8.MAR.2017 16:26:27

Power Spectral Density, 802.11n ht20 Low Channel




Date: 8.MAR.2017 15:52:14

Power Spectral Density, 802.11n ht20 Middle Channel




Date: 8.MAR.2017 15:55:22

Power Spectral Density, 802.11n ht20 High Channel




Date: 8.MAR.2017 15:57:49

Power Spectral Density, 802.11n ht40 Low Channel




Date: 8.MAR.2017 16:00:47

Power Spectral Density, 802.11n ht40 Middle Channel



Date: 8.MAR.2017 16:05:57

Power Spectral Density, 802.11n ht40 High Channel



Date: 13.MAR.2017 11:26:33

***** **END OF REPORT** *****