



FCC TEST REPORT

REPORT NO.: RF920422R04
MODEL NO.: GL2411MP-MP
RECEIVED: Apr. 22, 2003
TESTED: May 5 ~ May 8, 2003

APPLICANT: Global Sun Technology, Inc.

ADDRESS: No.13, Tung Yuan Rd., Jung Li Industrial Park,
Jung Li City, Taoyuan Hsien, Taiwan, R.O.C.

ISSUED BY: Advance Data Technology Corporation

LAB LOCATION: 47 14th Lin, Chiapau Tsun, Linko, Taipei,
Taiwan, R.O.C.

This test report consists of 61 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, NVLAP or any government agencies. The test results in the report only apply to the tested sample.



0528
ILAC MRA



Lab Code: 200102-0



Table of Contents

1	CERTIFICATION	4
2	SUMMARY OF TEST RESULTS	5
3	GENERAL INFORMATION	6
3.1	GENERAL DESCRIPTION OF EUT	6
3.2	DESCRIPTION OF TEST MODES	7
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS	7
3.4	DESCRIPTION OF SUPPORT UNITS	8
4	TEST TYPES AND RESULTS	9
4.1	CONDUCTED EMISSION MEASUREMENT	9
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	9
4.1.2	TEST INSTRUMENTS	9
4.1.3	TEST PROCEDURES	10
4.1.4	TEST SETUP	10
4.1.5	EUT OPERATING CONDITIONS	11
4.1.6	TEST RESULTS	12
4.2	RADIATED EMISSION MEASUREMENT	18
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT	18
4.2.2	TEST INSTRUMENTS	19
4.2.3	TEST PROCEDURES	20
4.2.4	TEST SETUP	21
4.2.5	EUT OPERATING CONDITIONS	21
4.2.6	TEST RESULTS (A)	22
4.2.7	TEST RESULTS (B)	27
4.2.8	TEST RESULTS (C)	32
4.3	6dB BANDWIDTH MEASUREMENT	37
4.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT	37
4.3.2	TEST INSTRUMENTS	37
4.3.3	TEST PROCEDURE	38
4.3.4	TEST SETUP	38
4.3.5	EUT OPERATING CONDITIONS	38
4.3.6	TEST RESULTS	39
4.4	MAXIMUM PEAK OUTPUT POWER	43
4.4.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT	43
4.4.2	TEST INSTRUMENTS	43
4.4.3	TEST PROCEDURES	44



4.4.4	TEST SETUP	44
4.4.5	EUT OPERATING CONDITIONS	44
4.4.6	TEST RESULTS	45
4.5	POWER SPECTRAL DENSITY MEASUREMENT	46
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	46
4.5.2	TEST INSTRUMENTS	46
4.5.3	TEST PROCEDURE	47
4.5.4	TEST SETUP	47
4.5.5	EUT OPERATING CONDITIONS	47
4.5.6	TEST RESULTS	48
4.6	BAND EDGES MEASUREMENT	52
4.6.1	LIMITS OF BAND EDGES MEASUREMENT	52
4.6.2	TEST INSTRUMENTS	52
4.6.3	TEST PROCEDURE	52
4.6.4	EUT OPERATING CONDITION	52
4.6.5	TEST RESULTS	53
4.7	ANTENNA REQUIREMENT	56
4.7.1	STANDARD APPLICABLE	56
4.7.2	ANTENNA CONNECTED CONSTRUCTION	56
5	PHOTOGRAPHS OF THE TEST CONFIGURATION	57
6	INFORMATION ON THE TESTING LABORATORIES	61



1 CERTIFICATION

PRODUCT : 11Mbps WLAN Mini PCI Card
BRAND NAME : GLOBAL SUN
MODEL NO. : GL2411MP-MP
APPLICANT : Global Sun Technology, Inc.
STANDARDS : 47 CFR Part 15, Subpart C (Section 15.247),
ANSI C63.4-1992

We, **Advance Data Technology Corporation**, hereby certify that one sample of the designation has been tested in our facility from May 5 ~ May 8, 2003, The test record, data evaluation and Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions herein specified.

CHECKED BY: Rennie Wang, **DATE:** May 14, 2003
Rennie Wang

APPROVED BY: Dr. Alan Lane, **DATE:** May 14, 2003
Dr. Alan Lane
Manager



2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: 47 CFR Part 15, Subpart C			
Standard Section	Test Type and Limit	Result	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit Minimum passing margin is -15.19dBuV at 0.170MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit
15.247(c)	Transmitter Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit Minimum passing margin is -2.70dBuV at 7312.00MHz
15.247(d)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit
15.247(c)	Band Edge Measurement Limit: 20 dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit



3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	11Mbps WLAN Mini PCI Card
MODEL NO.	GL2411MP-MP
POWER SUPPLY	3.3VDC from host equipment
MODULATION TYPE	BPSK, QPSK, CCK
RADIO TECHNOLOGY	DSSS
TRANSFER RATE	1/2/5.5/11Mbps
FREQUENCY RANGE	2412MHz ~ 2462MHz
NUMBER OF CHANNEL	11
OUTPUT POWER	19.92dBm
ANTENNA TYPE	Dipole and Inverted F
DATA CABLE	NA
I/O PORTS	NA
ASSOCIATED DEVICES	NA

NOTE:

- Four sets of antennas were provided to this EUT. Please refer to the following for details and refer to EUT photo for outer appearances.

Item	Antenna Type		Antenna Gain (dBi)	
	Main	Aux.	Main	Aux.
1	Dipole	Dipole	1	1
2	Dipole	Dipole	2	2
3	Dipole	Inverted F	2	-1
4	Dipole	Inverted F	1	-1

*Item 1, 2, & 3, the worst case, were chosen for final test.

- For more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



3.2 DESCRIPTION OF TEST MODES

Eleven channels are provided to this EUT.

Channel	Frequency	Channel	Frequency
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

NOTE:

1. Below 1 GHz, the channel 1, 6, and 11 were pre-tested in chamber. The channel 11, worst case one, was chosen for final test.
2. Above 1 GHz, the channel 1, 6, and 11 were tested individually.
3. Data rate with 11Mbps, the worst case, was chosen for final test.
4. For "Radiated Emission Measurement test (section 4.2)", three test results were provided to this EUT. The test result A was tested with Antenna item 1 (please refer to NOTE 1 of section 3.1), the test result B was tested with Antenna item 2, and the test result C was tested with Antenna item 3.

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a 11Mbps WLAN Mini PCI Card. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 15, Subpart C. (15.247)

ANSI C63.4 : 1992

All tests have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK	Dell	PP01L	TW-09C748-12800-190-B220	FCC DoC APPROVED
2	PRINTER	EPSON	LQ-300+	DCGY017096	FCC DoC APPROVED
3	MODEM	ACEEX	1414	980020569	IFAXDM1414

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	1.2m braid shielded wire, terminated with DB25 and Centronics connector via metallic frame, w/o core
3	1.2 m braid shielded wire, terminated with DB25 and DB9 connector via metallic frame, w/o core.

NOTE: All power cords of the above support units are non shielded (1.8m).



4 TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS


DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
ROHDE & SCHWARZ Test Receiver	ESCS30	847793/022	Mar. 10, 2004
ROHDE & SCHWARZ Artificial Mains Network (for EUT)	ESH2-Z5	828075/003	July 23, 2003
ROHDE & SCHWARZ 200-A Four-line V-Network	ENV4200	830326/018	Oct. 30, 2003
* ROHDE & SCHWARZ 4-wire ISN	ENY41	838119/028	Nov. 29, 2003
* ROHDE & SCHWARZ 2-wire ISN	ENY22	837497/018	Nov. 29, 2003
EMCO-L.I.S.N. (for peripheral)	3825/2	90031627	July 23, 2003
Software	Cond-V2M1	NA	NA
RF cable (JYEBAO)	5D-FB	Cable-C05.01	July 19, 2003
LYNICS Terminator (For EMCO LISN)	0900510	E1-01-305	Feb. 23, 2004
LYNICS Terminator (For EMCO LISN)	0900510	E1-01-306	Feb. 23, 2004

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. “*”: These equipment are used for conducted telecom port test only (if tested).
 3. The test was performed in ADT Shielded Room No. 5.
 4. The VCCI Site Registration No. is C-1093.

4.1.3 TEST PROCEDURES

- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched. Emission levels over 10dB under the prescribed limits could not be reported

4.1.4 TEST SETUP



- Note:**
- Support units were connected to second LISN.
 - Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.



4.1.5 EUT OPERATING CONDITIONS

- a. Connected the EUT to a computer system placed on a testing table.
- b. The computer system ran a test program to enable EUT under transmission/receiving condition continuously at specific channel frequency.
- c. The computer system sent "H" messages to its screen.
- d. The computer system sent "H" messages to modem.
- e. The computer system sent "H" messages to printer, and the printer prints them on paper.




4.1.6 TEST RESULTS

EUT	11Mbps WLAN Mini PCI Card	MODEL	GL2411MP-MP
MODE	Channel 1	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60%RH, 991 hPa	TESTED BY: Gary Chang	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.173	0.10	48.37	-	48.47	-	64.79	54.79	-16.32	-
2	0.228	0.10	44.36	-	44.46	-	62.52	52.52	-18.06	-
3	0.287	0.10	37.88	-	37.98	-	60.62	50.62	-22.64	-
4	0.341	0.10	35.07	-	35.17	-	59.17	49.17	-24.00	-
5	5.246	0.44	23.99	-	24.43	-	60.00	50.00	-35.57	-
6	20.051	1.10	28.76	-	29.86	-	60.00	50.00	-30.14	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.






EUT	11Mbps WLAN Mini PCI Card	MODEL	GL2411MP-MP
MODE	Channel 1	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60%RH, 991 hPa	TESTED BY: Gary Chang	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]		Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.170	0.10	49.69	-	49.79	-	64.98	54.98	-15.19	-
2	0.228	0.10	42.98	-	43.08	-	62.52	52.52	-19.44	-
3	0.287	0.10	35.87	-	35.97	-	60.62	50.62	-24.65	-
4	3.875	0.29	31.43	-	31.72	-	56.00	46.00	-24.28	-
5	13.621	0.47	22.74	-	23.21	-	60.00	50.00	-36.79	-
6	20.211	0.80	29.00	-	29.80	-	60.00	50.00	-30.20	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.






EUT	11Mbps WLAN Mini PCI Card	MODEL	GL2411MP-MP
MODE	Channel 6	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60%RH, 991 hPa	TESTED BY: Gary Chang	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]		Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.170	0.10	48.99	-	49.09	-	64.98	54.98	-15.89	-
2	0.228	0.10	44.06	-	44.16	-	62.52	52.52	-18.36	-
3	0.287	0.10	38.49	-	38.59	-	60.62	50.62	-22.03	-
4	0.341	0.10	34.80	-	34.90	-	59.17	49.17	-24.27	-
5	13.578	0.74	23.40	-	24.14	-	60.00	50.00	-35.86	-
6	19.895	1.09	28.74	-	29.83	-	60.00	50.00	-30.17	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.






EUT	11Mbps WLAN Mini PCI Card	MODEL	GL2411MP-MP
MODE	Channel 6	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60%RH, 991 hPa	TESTED BY: Gary Chang	

No	Freq.	Corr. Factor	Reading Value [dB (Uv)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.
1	0.170	0.10	47.27	-	47.37	-	64.98	54.98	-17.61	-
2	0.228	0.10	42.18	-	42.28	-	62.52	52.52	-20.24	-
3	0.287	0.10	36.05	-	36.15	-	60.62	50.62	-24.47	-
4	3.828	0.29	31.68	-	31.97	-	56.00	46.00	-24.03	-
5	13.473	0.47	23.69	-	24.16	-	60.00	50.00	-35.84	-
6	19.781	0.79	28.34	-	29.13	-	60.00	50.00	-30.87	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.






EUT	11Mbps WLAN Mini PCI Card	MODEL	GL2411MP-MP
MODE	Channel 11	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60%RH, 991 hPa	TESTED BY: Gary Chang	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]		Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.173	0.10	47.61	-	47.71	-	64.79	54.79	-17.08	-
2	0.228	0.10	43.30	-	43.40	-	62.52	52.52	-19.12	-
3	0.287	0.10	37.74	-	37.84	-	60.62	50.62	-22.78	-
4	0.400	0.10	33.08	-	33.18	-	57.85	47.85	-24.67	-
5	13.195	0.73	25.52	-	26.25	-	60.00	50.00	-33.75	-
6	20.109	1.10	28.22	-	29.32	-	60.00	50.00	-30.68	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.






EUT	11Mbps WLAN Mini PCI Card	MODEL	GL2411MP-MP
MODE	Channel 11	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Netural (N)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60%RH, 991 hPa	TESTED BY: Gary Chang	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]		Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.170	0.10	47.07	-	47.17	-	64.98	54.98	-17.81	-
2	0.228	0.10	42.24	-	42.34	-	62.52	52.52	-20.18	-
3	0.287	0.10	35.79	-	35.89	-	60.62	50.62	-24.73	-
4	3.766	0.29	29.68	-	29.97	-	56.00	46.00	-26.03	-
5	12.906	0.46	24.74	-	25.20	-	60.00	50.00	-34.80	-
6	17.414	0.64	27.68	-	28.32	-	60.00	50.00	-31.68	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.





4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
* HP Spectrum Analyzer	8590L	3544A01176	May 13, 2003
* HP Preamplifier	8447D	2944A08485	May 1, 2004
* HP Preamplifier	8449B	3008A01201	Dec. 01, 2003
* HP Preamplifier	8449B	3008A01292	Aug. 07, 2003
* Spectrum Analyzer	8593E	3926A04191	Mar. 24, 2004
* Test Receiver	ESI7	838496/016	Feb. 23, 2004
SCHAFFNER Tunable Dipole Antenna	VHBA 9123	459	Nov. 22, 2003
SCHWARZBECK Tunable Dipole Antenna	UHA 9105	977	
* CHASE BILOG Antenna	CBL6112A	2221	Aug. 02, 2003
* SCHWARZBECK Horn Antenna	BBHA9120-D1	D130	July 03, 2003
* EMCO Horn Antenna	3115	9312-4192	Mar. 23, 2004
* EMCO Turn Table	1060	1115	NA
* SHOSHIN Tower	AP-4701	A6Y005	NA
* Software	ADT_Radiate d_V5.09	NA	NA
* ANRITSU RF Switches	MP59B	M35046	Jul. 11. 2003
* TIMES RF cable	LMR-600	CABLE-ST5-01	Jul. 11. 2003

- NOTE:**
1. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.
 2. "*" = These equipment are used for the final measurement.
 3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
 4. The test was performed in ADT Open Site No. 5.
 5. The VCCI Site Registration No. is R-1039.




4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 300 Hz for Average detection (AV) at frequency above 1GHz.

4.2.4 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.5 EUT OPERATING CONDITIONS

Same as 4.1.5



4.2.6 TEST RESULTS (A)

EUT	11Mbps WLAN Mini PCI Card	MODEL	GL2411MP-MP
MODE	Channel 11	FREQUENCY RANGE	Below 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	25 deg. C, 60 % RH, 991 hPa	TESTED BY: Gary Chang	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	132.00	34.8 QP	43.50	-8.70	1.18 H	62	22.10	12.70
2	220.00	33.8 QP	46.00	-12.20	1.18 H	95	21.00	12.80
3	308.00	33.8 QP	46.00	-12.20	1.85 H	75	16.90	16.90
4	352.00	26.1 QP	46.00	-19.90	1.64 H	124	8.40	17.70
5	396.00	34.0 QP	46.00	-12.00	1.64 H	55	15.00	19.00
6	484.00	33.7 QP	46.00	-12.30	1.74 H	97	13.00	20.70
7	572.00	33.2 QP	46.00	-12.80	1.31 H	45	11.40	21.80
8	660.00	31.4 QP	46.00	-14.60	1.68 H	65	8.60	22.80
9	748.00	31.4 QP	46.00	-14.60	1.32 H	35	7.30	24.10
10	880.00	29.2 QP	46.00	-16.80	1.15 H	45	4.00	25.20

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.



EUT	11Mbps WLAN Mini PCI Card	MODEL	GL2411MP-MP
MODE	Channel 11	FREQUENCY RANGE	Below 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	25 deg. C, 60 % RH, 991 hPa	TESTED BY: Gary Chang	

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	132.00	29.2 QP	43.50	-14.30	1.52 V	35	16.50	12.70
2	220.00	28.4 QP	46.00	-17.60	1.14 V	305	15.60	12.80
3	308.00	24.9 QP	46.00	-21.10	1.81 V	62	8.00	16.90
4	352.00	26.8 QP	46.00	-19.20	1.30 V	52	9.10	17.70
5	484.00	27.6 QP	46.00	-18.40	1.42 V	324	6.90	20.70
6	572.00	31.0 QP	46.00	-15.00	1.14 V	78	9.20	21.80
7	660.00	29.5 QP	46.00	-16.50	1.05 V	84	6.70	22.80
8	704.00	27.5 QP	46.00	-18.50	1.10 V	32	4.40	23.10
9	748.00	27.6 QP	46.00	-18.40	1.46 V	94	3.50	24.10
10	836.00	27.1 QP	46.00	-18.90	1.62 V	95	2.10	25.00

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.



EUT	11Mbps WLAN Mini PCI Card	MODEL	GL2411MP-MP
MODE	Channel 1	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60 % RH, 991 hPa	TESTED BY: Gary Chang	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2412.00	98.0 PK			1.62 H	34	68.30	29.70
1	*2412.00	94.0 AV			1.62 H	34	64.30	29.70
2	3216.00	49.2 PK	78.00	-28.80	1.77 H	62	17.70	31.50
3	4824.00	46.5 PK	74.00	-27.50	1.32 H	65	11.20	35.30
4	7237.00	53.6 PK	78.00	-24.40	1.14 H	35	12.50	41.10
4	7237.00	48.0 AV	74.00	-26.00	1.14 H	35	6.90	31.50

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2389.00	50.0 PK	74.00	-24.00	1.52 V	34	20.40	29.60
1	2389.00	45.2 AV	54.00	-8.80	1.52 V	34	15.60	29.60
2	*2412.00	107.0 PK			1.52 V	34	77.30	29.70
2	*2412.00	103.0 AV			1.52 V	34	73.30	29.70
3	3216.00	54.1 PK	87.00	-32.90	1.15 V	360	22.60	31.50
3	3216.00	51.9 AV	83.00	-31.10	1.15 V	360	20.40	31.50
4	4824.00	47.7 PK	74.00	-26.30	1.07 V	84	12.40	35.30
5	7237.00	59.2 PK	87.00	-27.80	1.13 V	65	18.10	41.10
5	7237.00	52.2 AV	83.00	-30.80	1.13 V	65	11.10	35.30

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “ : Fundamental frequency



EUT	11Mbps WLAN Mini PCI Card	MODEL	GL2411MP-MP
MODE	Channel 6	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60 % RH, 991 hPa	TESTED BY: Gary Chang	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	96.3 PK			1.04 H	85	66.60	29.70
1	*2437.00	92.9 AV			1.04 H	85	63.20	29.70
2	3249.00	47.0 PK	76.30	-29.30	1.15 H	32	15.40	31.60
3	4874.00	47.3 PK	74.00	-26.70	1.30 H	55	11.80	35.50
4	7312.00	49.1 PK	74.00	-24.90	1.30 H	45	7.80	41.30
5	9748.00	55.6 PK	76.30	-20.70	1.10 H	45	11.90	43.70
5	9748.00	48.4 AV	72.90	-24.50	1.10 H	45	4.70	31.60

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	108.0 PK			1.13 V	65	78.30	29.70
1	*2437.00	104.0 AV			1.13 V	65	74.30	29.70
2	3249.00	50.4 PK	88.00	-37.60	1.18 V	91	18.80	31.60
2	3249.00	47.8 AV	84.00	-36.20	1.18 V	91	16.20	31.60
3	4874.00	49.0 PK	74.00	-25.00	1.25 V	51	13.50	35.50
4	7312.00	57.4 PK	74.00	-16.60	1.13 V	62	16.10	41.30
4	7312.00	51.3 AV	54.00	-2.70	1.13 V	62	10.00	35.50
5	9748.00	55.7 PK	88.00	-32.30	1.30 V	352	12.00	43.70
5	9748.00	50.0 AV	84.00	-34.00	1.30 V	352	6.30	41.30

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “ : Fundamental frequency



EUT	11Mbps WLAN Mini PCI Card	MODEL	GL2411MP-MP
MODE	Channel 11	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60 % RH, 991 hPa	TESTED BY: Gary Chang	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	98.1 PK			1.04 H	85	68.30	29.80
1	*2462.00	94.1 AV			1.04 H	85	64.30	29.80
2	3282.00	44.0 PK	74.00	-30.00	1.36 H	95	12.40	31.60
3	4924.00	46.0 PK	74.00	-28.00	1.52 H	315	10.30	35.70
4	7388.00	54.1 PK	74.00	-19.90	1.16 H	35	12.60	41.50
4	7388.00	44.1 AV	54.00	-9.90	1.16 H	35	2.60	31.60

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	107.7 PK			1.12 V	65	77.90	29.80
1	*2462.00	103.4 AV			1.12 V	65	73.60	29.80
2	2483.60	51.5 PK	74.00	-22.50	1.12 V	65	21.60	29.90
2	2483.60	46.3 AV	54.00	-7.70	1.12 V	65	16.40	29.90
3	3282.00	52.6 PK	74.00	-21.40	1.04 V	85	21.00	31.60
3	3282.00	45.3 AV	54.00	-8.70	1.04 V	85	13.70	31.60
4	4924.00	47.9 PK	74.00	-26.10	1.85 V	57	12.20	35.70
5	9848.00	59.0 PK	87.70	-28.70	1.65 V	258	15.20	43.80
5	9848.00	51.0 AV	83.40	-32.40	1.65 V	258	7.20	35.70

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “ : Fundamental frequency



4.2.7 TEST RESULTS (B)

EUT	11Mbps WLAN Mini PCI Card	MODEL	GL2411MP-MP
MODE	Channel 11	FREQUENCY RANGE	Below 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	25 deg. C, 60 % RH, 991 hPa	TESTED BY: Gary Chang	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	132.00	34.0 QP	43.50	-9.50	1.15 H	35	21.30	12.70
2	220.00	40.5 QP	46.00	-5.50	1.18 H	52	27.70	12.80
3	308.00	36.1 QP	46.00	-9.90	1.52 H	74	19.20	16.90
4	352.00	29.3 QP	46.00	-16.70	1.30 H	57	11.60	17.70
5	396.00	35.1 QP	46.00	-10.90	1.07 H	32	16.10	19.00
6	484.00	27.0 QP	46.00	-19.00	1.85 H	62	6.30	20.70
7	660.00	28.7 QP	46.00	-17.30	1.42 H	228	5.90	22.80
8	748.00	30.5 QP	46.00	-15.50	1.62 H	35	6.40	24.10

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.



EUT	11Mbps WLAN Mini PCI Card	MODEL	GL2411MP-MP
MODE	Channel 11	FREQUENCY RANGE	Below 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	25 deg. C, 60 % RH, 991 hPa	TESTED BY: Gary Chang	

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	132.00	23.6 QP	43.50	-19.90	1.82 V	35	10.90	12.70
2	220.00	30.1 QP	46.00	-15.90	1.85 V	41	17.30	12.80
3	308.00	28.6 QP	46.00	-17.40	1.18 V	74	11.70	16.90
4	352.00	26.4 QP	46.00	-19.60	1.58 V	84	8.70	17.70
5	396.00	24.9 QP	46.00	-21.10	1.15 V	36	5.90	19.00
6	484.00	23.1 QP	46.00	-22.90	1.52 V	74	2.40	20.70
7	660.00	25.9 QP	46.00	-20.10	1.41 V	58	3.10	22.80
8	748.00	27.5 QP	46.00	-18.50	2.25 V	14	3.40	24.10

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.



EUT	11Mbps WLAN Mini PCI Card	MODEL	GL2411MP-MP
MODE	Channel 1	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60 % RH, 991 hPa	TESTED BY: Gary Chang	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2412.00	101.7 PK			1.11 H	171	72.00	29.70
1	*2412.00	97.6 AV			1.11 H	171	67.90	29.70
2	3216.00	49.0 PK	81.70	-32.70	1.15 H	35	17.40	31.50
3	4824.00	44.2 PK	74.00	-29.80	1.41 H	25	8.90	35.30
4	7236.00	49.5 PK	81.70	-32.20	1.19 H	202	8.40	41.10
5	9648.00	53.8 PK	81.70	-27.90	1.57 H	120	10.30	43.60
5	9648.00	45.9 AV	77.60	-31.70	1.57 H	120	2.40	31.50

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2412.00	105.4 PK			1.35 V	158	75.70	29.70
1	*2412.00	102.2 AV			1.35 V	158	72.50	29.70
2	3216.00	61.5 PK	85.40	-23.90	1.04 V	85	29.90	31.50
2	3216.00	59.0 AV	82.20	-23.20	1.04 V	85	27.40	31.50
3	4824.00	46.4 PK	74.00	-27.60	1.44 V	203	11.10	35.30
4	7236.00	54.1 PK	85.40	-31.30	1.45 V	41	13.00	41.10
4	7236.00	45.3 AV	82.20	-36.90	1.45 V	41	4.20	35.30
5	9648.00	55.6 PK	85.40	-29.80	1.11 V	228	12.10	43.60
5	9648.00	47.9 AV	82.20	-34.30	1.11 V	228	4.40	41.10

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ” : Fundamental frequency



EUT	11Mbps WLAN Mini PCI Card	MODEL	GL2411MP-MP
MODE	Channel 6	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60 % RH, 991 hPa	TESTED BY: Gary Chang	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	99.1 PK			1.15 H	85	69.40	29.70
1	*2437.00	95.0 AV			1.15 H	85	65.30	29.70
2	3248.00	49.8 PK	79.10	-29.30	1.05 H	144	18.20	31.60
3	4874.00	45.9 PK	74.00	-28.10	1.69 H	104	10.40	35.50
4	7310.00	49.6 PK	74.00	-24.40	1.35 H	204	8.40	41.30
5	9748.00	52.9 PK	79.10	-26.20	1.01 H	52	9.20	43.70
5	9748.00	45.2 AV	75.00	-29.80	1.01 H	52	1.50	31.60
6	12185.00	54.5 PK	74.00	-19.50	1.47 H	130	9.20	45.30
6	12185.00	46.0 AV	54.00	-8.00	1.47 H	130	0.70	35.50

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	106.0 PK			1.16 V	105	76.30	29.70
1	*2437.00	102.5 AV			1.16 V	105	72.80	29.70
2	3249.00	59.6 PK	86.00	-26.40	1.16 V	105	28.00	31.60
2	3249.00	56.0 AV	82.50	-26.50	1.16 V	105	24.40	31.60
3	4874.00	48.1 PK	74.00	-25.90	1.32 V	6	12.60	35.50
4	7311.00	54.0 PK	74.00	-20.00	1.73 V	88	12.80	41.30
4	7311.00	44.2 AV	54.00	-9.80	1.73 V	88	3.00	35.50
5	9748.00	53.8 PK	86.00	-32.20	1.33 V	182	10.10	43.70
5	9748.00	45.6 AV	82.50	-36.90	1.33 V	182	1.90	41.30

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “ : Fundamental frequency



EUT	11Mbps WLAN Mini PCI Card	MODEL	GL2411MP-MP
MODE	Channel 11	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60 % RH, 991 hPa	TESTED BY: Gary Chang	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	98.4 PK			1.06 H	107	68.50	29.80
1	*2462.00	95.1 AV			1.06 H	107	65.30	29.80
2	3282.00	49.1 PK	78.40	-29.30	1.09 H	100	17.50	31.60
3	4924.00	44.6 PK	74.00	-29.40	1.55 H	199	8.90	35.70
4	7386.00	51.7 PK	74.00	-22.30	1.43 H	151	10.20	41.50
4	7386.00	42.3 AV	54.00	-11.70	1.43 H	151	0.80	31.60

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	107.9 PK			1.80 V	215	78.10	29.80
1	*2462.00	104.1 AV			1.80 V	215	74.30	29.80
2	3282.00	62.4 PK	87.90	-25.50	1.56 V	184	30.80	31.60
2	3282.00	60.1 AV	84.10	-24.00	1.56 V	184	28.50	31.60
3	4924.00	47.6 PK	74.00	-26.40	1.42 V	265	11.90	35.70
4	7386.00	55.4 PK	74.00	-18.60	1.47 V	173	13.90	41.50
4	7386.00	46.3 AV	54.00	-7.70	1.47 V	173	4.80	35.70
5	9847.00	54.4 PK	87.90	-33.50	1.17 V	205	10.70	43.80
5	9847.00	46.0 AV	84.10	-38.10	1.17 V	205	2.30	41.50

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ” : Fundamental frequency



4.2.8 TEST RESULTS (C)

EUT	11Mbps WLAN Mini PCI Card	MODEL	GL2411MP-MP
MODE	Channel 11	FREQUENCY RANGE	Below 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	25 deg. C, 60 % RH, 991 hPa	TESTED BY: Gary Chang	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	220.01	40.7 QP	46.00	-5.30	1.59 H	133	27.90	12.80
2	308.01	41.6 QP	46.00	-4.40	1.28 H	148	24.70	16.90
3	396.01	38.4 QP	46.00	-7.60	1.17 H	54	19.40	19.00
4	484.01	34.6 QP	46.00	-11.40	1.10 H	69	13.90	20.70
5	572.01	32.8 QP	46.00	-13.20	1.00 H	78	11.00	21.80
6	660.01	36.4 QP	46.00	-9.60	1.70 H	129	13.50	22.80
7	748.01	35.1 QP	46.00	-10.90	1.32 H	35	11.00	24.10
8	835.99	34.6 QP	46.00	-11.40	1.23 H	90	9.60	25.00
9	880.01	35.7 QP	46.00	-10.30	1.33 H	85	10.50	25.20

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.



EUT	11Mbps WLAN Mini PCI Card	MODEL	GL2411MP-MP
MODE	Channel 11	FREQUENCY RANGE	Below 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	25 deg. C, 60 % RH, 991 hPa	TESTED BY: Gary Chang	

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	264.00	31.5 QP	46.00	-14.50	1.13 V	320	14.80	16.70
2	396.01	30.9 QP	46.00	-15.10	1.20 V	74	11.90	19.00
3	484.01	28.9 QP	46.00	-17.10	1.33 V	107	8.20	20.70
4	572.02	31.7 QP	46.00	-14.30	1.01 V	117	9.90	21.80
5	660.02	32.5 QP	46.00	-13.50	1.60 V	142	9.60	22.80
6	704.05	34.1 QP	46.00	-11.90	1.26 V	208	11.00	23.10
7	748.02	33.5 QP	46.00	-12.50	1.68 V	152	9.40	24.10
8	880.00	31.2 QP	46.00	-14.80	1.18 V	32	6.00	25.20

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.



EUT	11Mbps WLAN Mini PCI Card	MODEL	GL2411MP-MP
MODE	Channel 1	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60 % RH, 991 hPa	TESTED BY: Gary Chang	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2412.00	99.0 PK			1.52 H	136	69.30	29.70
1	*2412.00	95.2 AV			1.52 H	136	65.60	29.70
2	3216.00	49.0 PK	79.00	-30.00	1.10 H	85	17.40	31.50
3	4824.00	45.2 PK	74.00	-28.80	1.22 H	134	9.90	35.30
4	7236.00	51.2 PK	79.00	-27.80	1.42 H	86	10.10	41.10
4	7236.00	43.0 AV	75.20	-32.20	1.42 H	86	1.90	31.50
5	9648.00	52.2 PK	79.00	-26.80	1.15 H	164	8.70	43.60
5	9648.00	45.9 AV	75.20	-29.30	1.15 H	164	2.40	35.30

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2412.00	104.7 PK			1.15 V	15	75.00	29.70
1	*2412.00	101.2 AV			1.15 V	15	71.50	29.70
2	3216.00	55.2 PK	84.70	-29.50	1.12 V	185	23.70	31.50
2	3216.00	52.8 AV	81.20	-28.40	1.12 V	185	21.20	31.50
3	4824.00	44.9 PK	74.00	-29.10	1.25 V	203	9.60	35.30
4	7236.00	54.2 PK	84.70	-30.50	1.42 V	52	13.10	41.10
4	7236.00	43.0 AV	81.20	-38.20	1.42 V	52	1.90	35.30
5	9648.00	53.4 PK	84.70	-31.30	1.17 V	203	9.90	43.60
5	9648.00	45.1 AV	81.20	-36.10	1.17 V	203	1.60	41.10

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “ : Fundamental frequency



EUT	11Mbps WLAN Mini PCI Card	MODEL	GL2411MP-MP
MODE	Channel 6	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60 % RH, 991 hPa	TESTED BY: Gary Chang	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	98.5 PK			1.09 H	205	68.80	29.70
1	*2437.00	96.7 AV			1.09 H	205	67.00	29.70
2	3249.00	47.1 PK	78.50	-31.40	1.47 H	207	15.50	31.60
3	4874.00	44.2 PK	74.00	-29.80	1.19 H	22	8.70	35.50
4	7311.00	50.6 PK	74.00	-23.40	1.41 H	203	9.40	41.30
4	7311.00	42.1 AV	54.00	-11.90	1.41 H	203	0.90	31.60

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	104.0 PK			1.44 V	161	74.30	29.70
1	*2437.00	101.6 AV			1.44 V	161	71.90	29.70
2	3249.00	53.6 PK	84.40	-30.40	1.03 V	86	22.00	31.60
2	3249.00	51.0 AV	81.60	-30.60	1.03 V	86	19.40	31.60
3	4874.00	44.9 PK	74.00	-29.10	1.12 V	79	9.40	35.50
4	7311.00	52.9 PK	74.00	-21.10	1.32 V	58	11.70	41.30
4	7311.00	43.7 AV	54.00	-10.30	1.32 V	58	2.50	35.50

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “ : Fundamental frequency



EUT	11Mbps WLAN Mini PCI Card	MODEL	GL2411MP-MP
MODE	Channel 11	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60 % RH, 991 hPa	TESTED BY: Gary Chang	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	98.7 PK			1.40 H	157	68.90	29.80
1	*2462.00	95.5 AV			1.40 H	157	65.70	29.80
2	3282.00	47.1 PK	78.70	-31.60	1.38 H	41	15.50	31.60
3	4924.00	44.4 PK	74.00	-29.60	1.10 H	154	8.70	35.70
4	7386.00	51.3 PK	74.00	-22.70	1.36 H	104	9.80	41.50
4	7386.00	43.3 AV	54.00	-10.70	1.36 H	104	1.80	31.60

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	103.6 PK			1.46 V	109	73.80	29.80
1	*2462.00	100.9 AV			1.46 V	109	71.10	29.80
2	3282.00	50.5 PK	83.60	-33.10	1.65 V	67	18.90	31.60
2	3282.00	48.1 AV	80.90	-32.80	1.65 V	67	16.50	31.60
3	4924.00	45.1 PK	74.00	-28.90	1.10 V	85	9.40	35.70
4	7386.00	53.9 PK	74.00	-20.10	1.28 V	41	12.40	41.50
4	7386.00	45.3 AV	54.00	-8.70	1.28 V	41	3.80	35.70
5	9848.00	53.0 PK	83.60	-30.60	1.74 V	75	9.30	43.80
5	9848.00	44.9 AV	80.90	-36.00	1.74 V	75	1.20	41.50

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ” : Fundamental frequency



4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	July 24, 2003


NOTE:

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 kHz RBW and 100 kHz VBW. The 6 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6 dB.

4.3.4 TEST SETUP



For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

4.3.5 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.




4.3.6 TEST RESULTS

EUT	11Mbps WLAN Mini PCI Card	MODEL	GL2411MP-MP
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	25 deg. C, 67%RH, 991 hPa
TESTED BY: Ansen Lei			

CHANNEL	CHANNEL FREQUENCY (MHz)	6 dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	9.86	0.5	PASS
6	2437	9.86	0.5	PASS
11	2462	9.90	0.5	PASS




CH1






CH6





CH11





4.4 MAXIMUM PEAK OUTPUT POWER

4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

4.4.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
POWER METER	E4416A	GB41291118	Jul. 30, 2003
PEAK POWER SENSOR	E9327A	US40440722	Jul. 30, 2003


NOTE:

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.4.3 TEST PROCEDURES

The transmitter output was connected to the peak power meter.

4.4.4 TEST SETUP



4.4.5 EUT OPERATING CONDITIONS

Same as Item 4.3.5



4.4.6 TEST RESULTS

EUT	11Mbps WLAN Mini PCI Card	MODEL	GL2411MP-MP
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	25 deg. C, 67%RH, 991 hPa
TESTED BY: Ansen Lei			

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	19.92	30	PASS
6	2437	19.88	30	PASS
11	2462	19.85	30	PASS



4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	July 24, 2003


NOTE:

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.5.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3 kHz RBW and 30 kHz VBW, set sweep time=span/3kHz. The power spectral density was measured and recorded. The sweep time is allowed to be longer than span/3KHz for a full response of the mixer in the spectrum analyzer.

4.5.4 TEST SETUP



4.5.5 EUT OPERATING CONDITIONS

Same as 4.3.5




4.5.6 TEST RESULTS

EUT	11Mbps WLAN Mini PCI Card	MODEL	GL2411MP-MP
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	25 deg. C, 67%RH, 991 hPa
TESTED BY: Ansen Lei			

CHANNEL NUMBER	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3 KHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-7.15	8	PASS
6	2437	-8.80	8	PASS
11	2462	-7.14	8	PASS




CH1






CH6





CH11





4.6 BAND EDGES MEASUREMENT

4.6.1 LIMITS OF BAND EDGES MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100KHz Resolution Bandwidth).

4.6.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	July 24, 2003

NOTE:

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz with suitable frequency span including 100 kHz bandwidth from band edge. The band edges was measured and recorded.

4.6.4 EUT OPERATING CONDITION


Same as Item 4.3.5




4.6.5 TEST RESULTS

The spectrum plots are attached on the following 2 pages. D2 line indicates the highest level, D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(C).

NOTE: The band edge emission plot on the following 2 pages shows 55.69dB / 55.38dB delta between carrier maximum power and local maximum emission in restrict band (2.3855GHz / 2.4841GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 (Page 31) is 104.1dBuV/m, so the maximum field strength in restrict band is $104.1 - 55.38 = 48.72$ dBuV/m which is under 54 dBuV/m limit.







4.7 ANTENNA REQUIREMENT

4.7.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.7.2 ANTENNA CONNECTED CONSTRUCTION

The antennas used in this product are Dipole and Inverted-F Antenna without antenna connector. And the maximum Gain of this antenna is 2dBi.

5 PHOTOGRAPHS OF THE TEST CONFIGURATION CONDUCTED EMISSION TEST





RADIATED EMISSION TEST







6 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025, Guide 25 or EN 45001:

USA	FCC, NVLAP
Germany	TUV Rheinland
Japan	VCCI
New Zealand	MoC
Norway	NEMKO
R.O.C.	BSMI, DGT, CNLA

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

www.adt.com.tw/index.5/phtml.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC Lab:

Tel: 886-2-26052180

Fax: 886-2-26052943

Hsin Chu EMC Lab:

Tel: 886-35-935343

Fax: 886-35-935342

Lin Kou Safety Lab:

Tel: 886-2-26093195

Fax: 886-2-26093184

Lin Kou RF&Telecom Lab

Tel: 886-3-3270910

Fax: 886-3-3270892

Email: service@mail.adt.com.tw

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.