



5.4 PEAK POWER EXCURSION MEASUREMENT

5.4.1 LIMITS OF PEAK POWER EXCURSION MEASUREMENT

Frequency Band	Limit
5.15 – 5.25 GHz	13dB
5.25 – 5.35 GHz	13dB
5.725 – 5.825 GHz	13dB

5.4.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
PEAK POWER SENSOR	E9327A	US40440722	July 30, 2003
POWER METER	E4416A	GB41291118	July 30, 2003

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.




5.4.3 TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer.
2. Set the spectrum bandwidth span to view the entire spectrum.
3. Using peak detector and Max-hold function for Trace 1 (RB=1MHz, VB=3MHz) and 2 (RB=1MHz, VB=300kHz).
4. The largest difference between Trace 1 and Trace 2 in any 1MHz band on any frequency was recorded.

5.4.4 DEVIATION FROM TEST STANDARD

No deviation

5.4.5 TEST SETUP



5.4.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.




5.4.7 TEST RESULTS

EUT	5.0/2.4GHz Wireless Network Mini PCI	MODEL	GL2554MP-0A
ENVIRONMENTAL CONDITIONS	24deg. C, 65%RH, 1005hPa	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Ansen Lei		

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER EXCURSION (dB)	PEAK to AVERAGE EXCURSION LIMIT (dB)	PASS/FAIL
1	5180	5.83	13	PASS
4	5240	4.91	13	PASS
5	5260	8.23	13	PASS
8	5320	4.89	13	PASS
9	5745	5.78	13	PASS
12	5805	5.26	13	PASS




CHANNEL 1






CHANNEL 4






CHANNEL 5






CHANNEL 9





CHANNEL 12





5.5 PEAK POWER SPECTRAL DENSITY MEASUREMENT

5.5.1 LIMITS OF PEAK POWER SPECTRAL DENSITY MEASUREMENT

Frequency Band	Limit
5.15 – 5.25GHz	4dBm
5.25 – 5.35GHz	11dBm
5.725 – 5.825GHz	17dBm

5.5.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	July 24, 2003

NOTE The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

5.5.3 TEST PROCEDURES

1. The transmitter output was connected to the spectrum analyzer.
2. Set RBW=1MHz, VBW=3MHz. The PPSD is the highest level found across the emission in any 1MHz band.

5.5.4 DEVIATION FROM TEST STANDARD

No deviation

5.5.5 TEST SETUP



5.5.6 EUT OPERATING CONDITIONS

Same as 5.3.6




5.5.7 TEST RESULTS

EUT	5.0/2.4GHz Wireless Network Mini PCI	MODEL	GL2554MP-0A
ENVIRONMENTAL CONDITIONS	24deg. C, 65%RH, 1005hPa	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Ansen Lei		

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 1MHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	5180	-1.86	4	PASS
4	5240	-1.73	4	PASS
5	5260	-0.36	11	PASS
8	5320	0.21	11	PASS
9	5745	-1.79	17	PASS
12	5805	-2.89	17	PASS




CHANNEL 1






CHANNEL 4






CHANNEL 5






CHANNEL 8






CHANNEL 9





CHANNEL 12





5.6 FREQUENCY STABILITY

5.6.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT

The frequency tolerance of the carrier signal shall be maintained within +/- 0.02% of the operating frequency over a temperature variation of -30 degrees to 50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C.

5.6.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
ANRITSU SPECTRUM ANALYZER	MS2667C	M10281	Mar. 15, 2003
WIT STANDARD TEMPERATURE AND HUMIDITY CHAMBER	TH-4S-C	W901030	Jun. 24, 2003

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


5.6.3 TEST PROCEDURE

1. The EUT was placed inside the environmental test chamber and powered by nominal DC voltage.
2. Turn the EUT on and couple its output to a spectrum analyzer.
3. Turn the EUT off and set the chamber to the highest temperature specified.
4. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT on and measure the operating frequency after 2, 5, and 10 minutes.
5. Repeat step 2 and 3 with the temperature chamber set to the lowest temperature.
6. The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.

5.6.4 DEVIATION FROM TEST STANDARD

No deviation

5.6.5 TEST SETUP



5.6.6 EUT OPERATING CONDITION

Same as Item 4.1.6

5.6.7 TEST RESULTS

		Operating frequency: 5180MHz				Limit : $\pm 0.02\%$	
Temp. (°C)	Power supply (VDC)	2 minute		5 minute		10 minute	
		(MHz)	(%)	(MHz)	(%)	(MHz)	(%)
50	126.5	5319.9202	-0.0015000	5319.9206	-0.0014925	5319.9205	-0.0014944
	110.0	5319.9202	-0.0015000	5319.9208	-0.0014887	5319.9205	-0.0014944
	93.5	5319.9204	-0.0014962	5319.9207	-0.0014906	5319.9207	-0.0014906
40	126.5	5319.9132	-0.0016316	5319.9135	-0.0016259	5319.9135	-0.0016259
	110.0	5319.9132	-0.0016316	5319.9133	-0.0016297	5319.9137	-0.0016222
	93.5	5319.9133	-0.0016297	5319.9133	-0.0016297	5319.9136	-0.0016241
30	126.5	5319.9123	-0.0016485	5319.9120	-0.0016541	5319.9129	-0.0016372
	110.0	5319.9123	-0.0016485	5319.9121	-0.0016523	5319.9127	-0.0016410
	93.5	5319.9125	-0.0016447	5319.9121	-0.0016523	5319.9126	-0.0016429
20	126.5	5319.9111	-0.0016711	5319.9115	-0.0016635	5319.9112	-0.0016692
	110.0	5319.9110	-0.0016729	5319.9115	-0.0016635	5319.9112	-0.0016692
	93.5	5319.9110	-0.0016729	5319.9117	-0.0016598	5319.9113	-0.0016673
10	126.5	5319.9156	-0.0015865	5319.9162	-0.0015752	5319.9165	-0.0015695
	110.0	5319.9157	-0.0015846	5319.9162	-0.0015752	5319.9165	-0.0015695
	93.5	5319.9157	-0.0015846	5319.9163	-0.0015733	5319.9168	-0.0015639
0	126.5	5319.9174	-0.0015526	5319.9121	-0.0016523	5319.9133	-0.0016297
	110.0	5319.9125	-0.0016447	5319.9122	-0.0016504	5319.9132	-0.0016316
	93.5	5319.9128	-0.0016391	5319.9122	-0.0016504	5319.9135	-0.0016259
-10	126.5	5319.9126	-0.0016429	5319.9127	-0.0016410	5319.9133	-0.0016297
	110.0	5319.9126	-0.0016429	5319.9128	-0.0016391	5319.9130	-0.0016353
	93.5	5319.9128	-0.0016391	5319.9128	-0.0016391	5319.9131	-0.0016335
-20	126.5	5319.9155	-0.0015883	5319.9154	-0.0015902	5319.9152	-0.0015940
	110.0	5319.9155	-0.0015883	5319.9153	-0.0015921	5319.9150	-0.0015977
	93.5	5319.9157	-0.0015846	5319.9156	-0.0015865	5319.9151	-0.0015959
-30	126.5	5319.9195	-0.0015132	5319.9197	-0.0015094	5319.9195	-0.0015132
	110.0	5319.9195	-0.0015132	5319.9197	-0.0015094	5319.9193	-0.0015169
	93.5	5319.9197	-0.0015094	5319.9196	-0.0015113	5319.9193	-0.0015169



5.7 BAND EDGES MEASUREMENT

5.7.1 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	July 24, 2003

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

5.7.2 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. Set both RBW and VBW of spectrum analyzer to 1MHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

5.7.3 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.

5.7.4 TEST RESULTS


For signals in the restricted bands above and below the 5.15 to 5.35GHz allocated band a measurement was made of the amplitude of the spurious emissions with respect to the intentional signals. The relative amplitude, in dBc, was applied to the average and peak filed strength of the intentional signal made on the OATS to calculate the field strength of the unintentional signals.


The spectrum plots (Peak RBW=VBW=1MHz; Average RBW=1MHz, VBW=300Hz) are attached on the following 8 pages.



Channel 1 (5180 MHz)

The band edge emission plot on the following 2 pages shows 45.57dBc (Peak) / 48.76 dBc (Average) between carrier maximum power and local maximum emission in restrict band. The emission of carrier strength list in the test result of channel 1 is 93.1dBuV/m, so the maximum field strength in restrict band is $93.1 - 48.76 = 44.34$ dBuV/m which is under 54dBuV/m limit.









Channel 8 (5320 MHz)

The band edge emission plot on the following 2 pages shows 42.82dBc (Peak) / 48.39dBc (Average) between carrier maximum power and local maximum emission in restrict band. The emission of carrier strength list in the test result of channel 8 is 94.9dBuV/m, so the maximum field strength in restrict band is 94.9-48.39=46.51dBuV/m which is under 54dBuV/m limit.







5.8 ANTENNA REQUIREMENT

5.8.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.407(a), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

5.8.2 ANTENNA CONNECTED CONSTRUCTION

The antenna used in this product is Dipole antenna without connector. The maximum Gain of the antenna is 2dBi.

6. PHOTOGRAPHS OF THE TEST CONFIGURATION CONDUCTED EMISSION TEST





RADIATED EMISSION TEST







7. INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025, Guide 25 or EN 45001:

USA	FCC, NVLAP, UL
Germany	TUV Rheinland
Japan	VCCI
New Zealand	MoC
Norway	NEMKO
R.O.C.	BSMI, DGT, CNLA

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

www.adt.com.tw/index.5/phtml.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC Lab:

Tel: 886-2-26052180

Fax: 886-2-26052943

Hsin Chu EMC Lab:

Tel: 886-35-935343

Fax: 886-35-935342

Lin Kou Safety Lab:

Tel: 886-2-26093195

Fax: 886-2-26093184

Lin Kou RF&Telecom Lab

Tel: 886-3-3270910

Fax: 886-3-3270892

Email: service@mail.adt.com.tw

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.