



# FCC TEST REPORT

**REPORT NO.:** RF930708L09

**MODEL NO.:** WL 01 2454 25M

(Refer to page 6 for other models)

**RECEIVED:** July 08, 2004

**TESTED:** July 09, 2004 ~ July 11, 2004

**APPLICANT:** GLOBAL SUN TECHNOLOGY INC.

**ADDRESS:** NO.13 Tung Yuan Rd., Jung Li Industrial Park, Jung Li City, Tao Yuan Hsien, Taiwan, R. O. C.

**ISSUED BY:** Advance Data Technology Corporation

**LAB LOCATION:** No. 19, Hwa Ya 2nd Rd., Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This test report consists of 68 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA or any government agencies. The test results in the report only apply to the tested sample.



0528  
ILAC MRA



## Table of Contents

1	CERTIFICATION .....	4
2	SUMMARY OF TEST RESULTS .....	5
3	GENERAL INFORMATION .....	6
3.1	GENERAL DESCRIPTION OF EUT .....	6
3.2	DESCRIPTION OF TEST MODES .....	7
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS .....	7
3.4	DESCRIPTION OF SUPPORT UNITS .....	8
3.5	CONFIGURATION OF SYSTEM UNDER TEST .....	9
4	TEST TYPES AND RESULTS .....	10
4.1	CONDUCTED EMISSION MEASUREMENT .....	10
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT .....	10
4.1.2	TEST INSTRUMENTS .....	10
4.1.3	TEST PROCEDURES .....	11
4.1.4	DEVIATION FROM TEST STANDARD .....	11
4.1.5	TEST SETUP .....	12
4.1.6	EUT OPERATING CONDITIONS .....	13
4.1.7	TEST RESULTS .....	14
4.2	RADIATED EMISSION MEASUREMENT .....	20
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT .....	20
4.2.2	TEST INSTRUMENTS .....	21
4.2.3	TEST PROCEDURES .....	22
4.2.4	DEVIATION FROM TEST STANDARD .....	22
4.2.5	TEST SETUP .....	23
4.2.6	EUT OPERATING CONDITIONS .....	23
4.2.7	TEST RESULTS .....	24
4.3	6dB BANDWIDTH MEASUREMENT .....	32
4.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT .....	32
4.3.2	TEST INSTRUMENTS .....	32
4.3.3	TEST PROCEDURE .....	32
4.3.4	DEVIATION FROM TEST STANDARD .....	32
4.3.5	TEST SETUP .....	33



4.3.6	EUT OPERATING CONDITIONS.....	33
4.3.7	TEST RESULTS.....	34
4.4	MAXIMUM PEAK OUTPUT POWER .....	42
4.4.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT .....	42
4.4.2	TEST INSTRUMENTS .....	42
4.4.3	TEST PROCEDURES.....	42
4.4.4	DEVIATION FROM TEST STANDARD .....	42
4.4.5	TEST SETUP .....	43
4.4.6	EUT OPERATING CONDITIONS.....	43
4.4.7	TEST RESULTS.....	44
4.5	POWER SPECTRAL DENSITY MEASUREMENT .....	45
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT .....	45
4.5.2	TEST INSTRUMENTS .....	45
4.5.3	TEST PROCEDURE .....	46
4.5.4	DEVIATION FROM TEST STANDARD .....	46
4.5.5	TEST SETUP .....	46
4.5.6	EUT OPERATING CONDITIONS.....	46
4.5.7	TEST RESULTS.....	47
4.6	BAND EDGES MEASUREMENT .....	55
4.6.1	LIMITS OF BAND EDGES MEASUREMENT .....	55
4.6.2	TEST INSTRUMENTS .....	55
4.6.3	TEST PROCEDURE .....	55
4.6.4	DEVIATION FROM TEST STANDARD .....	55
4.6.5	EUT OPERATING CONDITION .....	56
4.6.6	TEST RESULTS.....	56
4.7	ANTENNA REQUIREMENT .....	65
4.7.1	STANDARD APPLICABLE .....	65
4.7.2	ANTENNA CONNECTED CONSTRUCTION.....	65
5	PHOTOGRAPHS OF THE TEST CONFIGURATION.....	66
6	INFORMATION ON THE TESTING LABORATORIES .....	68



## 1 CERTIFICATION

**PRODUCT NAME :** 802.11g Wireless LAN Network Adapter  
**MODEL NO.:** WL 01 2454 25M  
(Refer to page 6 for other models)  
**BRAND NAME :** GLOBAL SUN (Refer to page 6 for other brands)  
**APPLICANT :** GLOBAL SUN TECHNOLOGY INC.  
**TESTED :** July 09, 2004 ~ July 11, 2004  
**TEST ITEM :** ENGINEERING SAMPLE  
**STANDARDS :** FCC Part 15, Subpart C (Section 15.247),  
ANSI C63.4-2001

The above equipment has been tested by **Advance Data Technology Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**PREPARED BY:** Wendy Liao, **DATE:** July 13, 2004

Wendy Liao

**APPROVED BY:** Cody Chang, **DATE:** July 13, 2004

Cody Chang /  
Supervisor

## 2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
Standard Section	Test Type and Limit	Result	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit Minimum passing margin is -15.86dB at 0.224MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System. Limit: min. 500kHz	PASS	Meet the requirement of limit
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit
15.247(c)	Transmitter Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit Minimum passing margin is -2.41dB at 2390.00MHz
15.247(d)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit
15.247(c)	Band Edge Measurement Limit: 20dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit

**NOTE:** The information of measurement uncertainty is available upon the customer's request.

### 3 GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

<b>PRODUCT NAME</b>	802.11g Wireless LAN Network Adapter
<b>MODEL NO.</b>	WL 01 2454 25M
<b>POWER SUPPLY</b>	3.3Vdc from host equipment
<b>MODULATION TYPE</b>	BPSK, QPSK, CCK, 16QAM, 64QAM
<b>RADIO TECHNOLOGY</b>	DSSS, OFDM
<b>TRANSFER RATE</b>	1/2/5.5/6/9/11/12/18/24/36/48/54Mbps
<b>FREQUENCY RANGE</b>	2412MHz ~ 2462MHz
<b>NUMBER OF CHANNEL</b>	11
<b>OUTPUT POWER</b>	15.3dBm
<b>ANTENNA TYPE</b>	Printed antenna with 0dBi gain
<b>DATA CABLE</b>	NA
<b>I/O PORTS</b>	NA
<b>ASSOCIATED DEVICES</b>	NA

**NOTE:**

- The following OEMs were provided to this EUT. They are identical to each other except for their model number and brand name due to marketing requirement.

ITEM	MODEL NO.	BRAND
1	WL54G-CB	Lantech
2	WL-3564	Planet
3	Skyl@cer pc card 4054G	Topcom
4	KLS-5205	KCROP
5	NWP-0107-G	Etherwan
6	EWP-0107-G	Etherwan
7	WLL-3210M	ORIGO
8	WL-GI-300B	Dynamode
9	DW300G	Dynamode
10	14100:PC-Card Wireless 54G	Q-TEC
11	00062777	Hama
12	IS33340 PCCARD Wireless LAN card	ISINE
13	6700G	AT&T

- The EUT, operates in the 2.4GHz frequency range, lets you connect IEEE 802.11g or IEEE 802.11b devices to the network. With its high-speed data transmissions of up to 54Mbps.
- The above EUT information was declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

### 3.2 DESCRIPTION OF TEST MODES

Eleven channels are provided to this EUT.

Channel	Frequency	Channel	Frequency
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

**NOTE:**

1. Below 1GHz, the channel 1, 6, and 11 were pre-tested in chamber. The channel 11, the worst case, was chosen for final test.
2. Above 1GHz, the channel 1, 6, and 11 were tested individually.
3. From our experience and technical viewpoint, we have chosen data rates 11Mbps for CCK technique and 6Mbps for OFDM technique, as the worst cases for the test among other data rates.

### 3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C. (15.247)**

**ANSI C63.4:2001**

All test items have been performed and recorded as per the above standards.

**NOTE:** The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



### 3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK COMPUTER	DELL	PP05L	20838027664	E2K24CLNS
2	PRINTER	EPSON	LQ-300+	DCGY054146	FCC DoC Approved
3	MODEM	ACEEX	1414V/3	0401008260	IFAXDM1414

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	1.2m shielded cable without core
3	1.2m shielded cable without core

**NOTE:** All power cords of the above support units are non shielded (1.8m).



### 3.5 CONFIGURATION OF SYSTEM UNDER TEST



## 4 TEST TYPES AND RESULTS

### 4.1 CONDUCTED EMISSION MEASUREMENT

#### 4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
  2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
  3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

#### 4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESCS30	100288	Dec. 11, 2004
RF signal cable Woken	5D-FB	Cable-HyC02-01	Mar. 07, 2005
LISN ROHDE & SCHWARZ	ESH2-Z5	100100	Mar. 10, 2005
LISN ROHDE & SCHWARZ	ESH3-Z5	100311	Mar. 04, 2005
Software ADT	ADT_Cond_V3	NA	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
  2. The test was performed in HwaYa Shielded Room 2.
  3. The VCCI Site Registration No. is C-2047.




#### 4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels Limit -20dB was not recorded.

#### 4.1.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.1.5 TEST SETUP



**Note: 1. Support units were connected to second LISN.**

2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.



#### 4.1.6 EUT OPERATING CONDITIONS


- a. Connected the EUT to a notebook system placed on a testing table.
- b. The notebook system ran a test program (provided by manufacturer) to enable EUT under transmission/receiving condition continuously at specific channel frequency.
- c. The notebook system sent "H" messages to its screen.
- d. The notebook system sent "H" messages to modem.
- e. The notebook system sent "H" messages to printer, and the printer printed them on paper.
- f. Steps c ~ e were repeated.

## 4.1.7 TEST RESULTS

<b>EUT</b>	802.11g Wireless LAN Network Adapter	<b>MODEL</b>	WL 01 2454 25M
<b>CHANNEL</b>	Channel 1	<b>6dB BANDWIDTH</b>	9kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Line (L)
<b>ENVIRONMENTAL CONDITIONS</b>	25deg.C, 65%RH, 991hPa	<b>TESTED BY:</b> Match Tsui	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.216	0.10	43.37	-	43.47	-	62.96	52.96	-19.48	-
2	0.341	0.11	34.82	-	34.93	-	59.17	49.17	-24.24	-
3	0.552	0.15	30.70	-	30.85	-	56.00	46.00	-25.15	-
4	4.508	0.34	27.11	-	27.45	-	56.00	46.00	-28.55	-
5	12.371	0.61	29.93	-	30.54	-	60.00	50.00	-29.46	-
6	20.098	0.92	27.81	-	28.73	-	60.00	50.00	-31.27	-


- REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.  
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.  
3. The emission levels of other frequencies were very low against the limit.  
4. Margin value = Emission level - Limit value  
5. Correction factor = Insertion loss + Cable loss  
6. Emission Level = Correction Factor + Reading Value.



<b>EUT</b>	802.11g Wireless LAN Network Adapter	<b>MODEL</b>	WL 01 2454 25M
<b>CHANNEL</b>	Channel 1	<b>6dB BANDWIDTH</b>	9kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Neutral (N)
<b>ENVIRONMENTAL CONDITIONS</b>	25deg.C, 65%RH, 991hPa	<b>TESTED BY:</b> Match Tsui	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.216	0.10	44.12	-	44.22	-	62.96	52.96	-18.73	-
2	0.338	0.11	35.62	-	35.73	-	59.26	49.26	-23.54	-
3	0.568	0.15	30.72	-	30.87	-	56.00	46.00	-25.13	-
4	4.160	0.31	26.74	-	27.05	-	56.00	46.00	-28.95	-
5	12.703	0.53	28.99	-	29.52	-	60.00	50.00	-30.48	-
6	17.691	0.61	29.04	-	29.65	-	60.00	50.00	-30.35	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.



<b>EUT</b>	802.11g Wireless LAN Network Adapter	<b>MODEL</b>	WL 01 2454 25M
<b>CHANNEL</b>	Channel 6	<b>6dB BANDWIDTH</b>	9kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Line (L)
<b>ENVIRONMENTAL CONDITIONS</b>	25deg.C, 65%RH, 991hPa	<b>TESTED BY:</b> Match Tsui	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.213	0.10	38.85	-	38.95	-	63.11	53.11	-24.16	-
2	0.338	0.11	35.52	-	35.63	-	59.26	49.26	-23.64	-
3	0.548	0.15	30.62	-	30.77	-	56.00	46.00	-25.23	-
4	4.176	0.32	25.55	-	25.87	-	56.00	46.00	-30.13	-
5	12.652	0.62	30.12	-	30.74	-	60.00	50.00	-29.26	-
6	19.484	0.90	27.89	-	28.79	-	60.00	50.00	-31.21	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.






<b>EUT</b>	802.11g Wireless LAN Network Adapter	<b>MODEL</b>	WL 01 2454 25M
<b>CHANNEL</b>	Channel 6	<b>6dB BANDWIDTH</b>	9kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Neutral (N)
<b>ENVIRONMENTAL CONDITIONS</b>	25deg.C, 65%RH, 991hPa	<b>TESTED BY:</b> Match Tsui	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.224	0.10	46.52	-	46.62	-	62.66	52.66	-16.04	-
2	0.334	0.11	35.76	-	35.87	-	59.36	49.36	-23.49	-
3	0.334	0.11	35.76	-	35.87	-	59.36	49.36	-23.49	-
4	5.211	0.35	26.31	-	26.66	-	60.00	50.00	-33.34	-
5	12.426	0.52	28.98	-	29.50	-	60.00	50.00	-30.50	-
6	20.555	0.66	26.25	-	26.91	-	60.00	50.00	-33.09	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.



<b>EUT</b>	802.11g Wireless LAN Network Adapter	<b>MODEL</b>	WL 01 2454 25M
<b>CHANNEL</b>	Channel 11	<b>6dB BANDWIDTH</b>	9kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Line (L)
<b>ENVIRONMENTAL CONDITIONS</b>	25deg.C, 65%RH, 991hPa	<b>TESTED BY:</b> Match Tsui	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.220	0.10	45.64	-	45.74	-	62.81	52.81	-17.07	-
2	0.443	0.12	33.45	-	33.57	-	57.01	47.01	-23.43	-
3	0.552	0.15	31.38	-	31.53	-	56.00	46.00	-24.47	-
4	4.469	0.33	27.71	-	28.04	-	56.00	46.00	-27.96	-
5	13.336	0.64	30.17	-	30.81	-	60.00	50.00	-29.19	-
6	18.246	0.84	29.05	-	29.89	-	60.00	50.00	-30.11	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.



<b>EUT</b>	802.11g Wireless LAN Network Adapter	<b>MODEL</b>	WL 01 2454 25M
<b>CHANNEL</b>	Channel 11	<b>6dB BANDWIDTH</b>	9kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Neutral (N)
<b>ENVIRONMENTAL CONDITIONS</b>	25deg.C, 65%RH, 991hPa	<b>TESTED BY:</b> Match Tsui	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.224	0.10	46.70	-	46.80	-	62.66	52.66	-15.86	-
2	0.451	0.13	35.29	-	35.42	-	56.86	46.86	-21.45	-
3	0.568	0.15	31.06	-	31.21	-	56.00	46.00	-24.79	-
4	4.188	0.31	26.63	-	26.94	-	56.00	46.00	-29.06	-
5	13.363	0.54	29.18	-	29.72	-	60.00	50.00	-30.28	-
6	20.719	0.66	25.83	-	26.49	-	60.00	50.00	-33.51	-

- REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.  
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.  
3. The emission levels of other frequencies were very low against the limit.  
4. Margin value = Emission level - Limit value  
5. Correction factor = Insertion loss + Cable loss  
6. Emission Level = Correction Factor + Reading Value.





## 4.2 RADIATED EMISSION MEASUREMENT

### 4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



#### 4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESIB7	100188	Jan. 13, 2005
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100039	Dec. 15, 2004
BILOG Antenna SCHWARZBECK	VULB9168	9168-157	Feb. 03, 2005
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-407	Feb. 03, 2005
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA 9170241	Feb. 23, 2005
Preamplifier Agilent	8449B	3008A01961	Jan. 22, 2005
Preamplifier Agilent	8447D	2944A10629	Jan. 14, 2005
RF signal cable HUBER+SUHNER	SUCOFLEX 104	218182/4	Mar. 04, 2005
RF signal cable HUBER+SUHNER	SUCOFLEX 104	218194/4	Mar. 04, 2005
Software ADT.	ADT_Radiated_V5.14	NA	NA
Antenna Tower ADT.	AT100	AT93021702	NA
Turn Table ADT.	TT100.	TT93021702	NA
Controller ADT.	SC100.	SC93021702	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
  2. The test was performed in HwaYa Chamber 1.
  3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
  4. The IC Site Registration No. is IC4924-2.



#### 4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


**NOTE:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.

#### 4.2.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

#### 4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6

## 4.2.7 TEST RESULTS

<b>EUT</b>	802.11g Wireless LAN Network Adapter	<b>MODEL</b>	WL 01 2454 25M
<b>CHANNEL</b>	Channel 11	<b>FREQUENCY RANGE</b>	Below 1000MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Quasi-Peak
<b>ENVIRONMENTAL CONDITIONS</b>	25deg. C, 65%RH, 991hPa	<b>TESTED BY:</b> Match Tsui	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	68.88	21.90 QP	40.00	-18.10	2.50 H	76	9.19	12.71
2	119.42	35.99 QP	43.50	-7.51	1.25 H	259	23.02	12.97
3	166.07	31.90 QP	43.50	-11.60	1.50 H	64	17.59	14.30
4	201.06	36.83 QP	43.50	-6.67	1.00 H	19	25.42	11.41
5	232.16	32.64 QP	46.00	-13.36	1.25 H	253	20.05	12.59
6	249.66	30.18 QP	46.00	-15.82	1.25 H	13	16.97	13.22
7	267.15	28.26 QP	46.00	-17.74	1.25 H	247	14.60	13.66
8	300.20	34.06 QP	46.00	-11.94	1.00 H	19	19.55	14.50
9	335.19	34.35 QP	46.00	-11.65	1.00 H	343	19.04	15.31
10	457.66	34.08 QP	46.00	-11.92	1.75 H	250	15.91	18.17
11	465.43	30.22 QP	46.00	-15.78	2.00 H	4	11.95	18.27
12	640.38	29.47 QP	46.00	-16.53	1.25 H	334	7.92	21.55
13	722.02	29.03 QP	46.00	-16.97	1.25 H	133	6.18	22.84
14	801.72	30.14 QP	46.00	-15.86	1.00 H	211	6.31	23.83
15	970.84	31.41 QP	54.00	-22.59	1.25 H	142	5.71	25.71

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.



<b>EUT</b>	802.11g Wireless LAN Network Adapter	<b>MODEL</b>	WL 01 2454 25M
<b>CHANNEL</b>	Channel 11	<b>FREQUENCY RANGE</b>	Below 1000MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Quasi-Peak
<b>ENVIRONMENTAL CONDITIONS</b>	25deg. C, 65%RH, 991hPa	<b>TESTED BY:</b> Match Tsui	

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	37.78	34.79 QP	40.00	-5.21	1.75 V	19	19.92	14.87
2	53.33	33.01 QP	40.00	-6.99	1.00 V	136	18.64	14.37
3	68.88	37.39 QP	40.00	-2.61	1.25 V	343	24.68	12.71
4	82.48	33.29 QP	40.00	-6.71	1.25 V	172	23.27	10.03
5	99.98	34.75 QP	43.50	-8.75	1.00 V	256	23.77	10.98
6	123.31	29.30 QP	43.50	-14.20	1.00 V	25	16.04	13.26
7	201.06	31.72 QP	43.50	-11.78	1.75 V	121	20.30	11.41
8	234.11	29.19 QP	46.00	-16.81	2.00 V	337	16.48	12.71
9	267.15	28.80 QP	46.00	-17.20	1.75 V	10	15.14	13.66
10	300.20	29.44 QP	46.00	-16.56	1.50 V	352	14.93	14.50
11	335.19	33.69 QP	46.00	-12.31	1.50 V	16	18.38	15.31
12	401.28	30.42 QP	46.00	-15.58	1.00 V	346	13.63	16.78
13	457.66	36.16 QP	46.00	-9.84	1.00 V	310	17.99	18.17
14	667.60	30.44 QP	46.00	-15.56	1.75 V	31	8.54	21.90
15	832.83	30.19 QP	46.00	-15.81	1.75 V	31	6.12	24.06

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.

<b>EUT</b>	802.11g Wireless LAN Network Adapter	<b>MODEL</b>	WL 01 245425M
<b>CHANNEL</b>	Channel 1	<b>FREQUENCY RANGE</b>	1~ 25GHz
<b>MODE</b>	CCK		
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>ENVIRONMENTAL CONDITIONS</b>	25deg. C, 64%RH, 991hPa	<b>TESTED BY:</b> Match Tsui	

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2360.00	53.59 PK	74.00	-20.41	1.51 H	77	22.92	30.67
1	2360.00	41.89 AV	54.00	-12.11	1.51 H	77	11.22	30.67
2	2387.00	53.54 PK	74.00	-20.46	1.49 H	77	22.76	30.78
2	2387.00	45.40 AV	54.00	-8.60	1.49 H	77	14.62	30.78
3	*2412.00	111.34 PK			1.49 H	77	80.46	30.88
3	*2412.00	103.20 AV			1.49 H	77	72.32	30.88
4	4824.00	53.41 PK	74.00	-20.59	1.00 H	323	16.96	36.45
4	4824.00	39.66 AV	54.00	-14.34	1.00 H	323	3.21	36.45

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1052.00	43.35 PK	74.00	-30.65	1.10 V	350	16.66	26.68
1	1052.00	38.22 AV	54.00	-15.78	1.10 V	350	11.54	26.68
2	2360.00	45.15 PK	74.00	-28.85	1.16 V	223	14.48	30.67
2	2360.00	32.36 AV	54.00	-21.64	1.16 V	223	1.69	30.67
3	2387.00	44.32 PK	74.00	-29.68	1.16 V	165	13.54	30.78
3	2387.00	36.38 AV	54.00	-17.62	1.16 V	165	5.6	30.78
4	*2412.00	102.12 PK			1.16 V	165	71.24	30.88
4	*2412.00	94.18 AV			1.16 V	165	63.30	30.88
5	4824.00	51.06 PK	74.00	-22.94	1.19 V	32	14.61	36.45
5	4824.00	37.71 AV	54.00	-16.29	1.19 V	32	1.26	36.45

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + CorrectionFactor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* ” : Fundamental frequency.

<b>EUT</b>	802.11g Wireless LAN Network Adapter	<b>MODEL</b>	WL 01 2454 25M
<b>CHANNEL</b>	Channel 6	<b>FREQUENCY RANGE</b>	1~ 25GHz
<b>MODE</b>	CCK		
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>ENVIRONMENTAL CONDITIONS</b>	25deg. C, 64%RH, 991hPa	<b>TESTED BY:</b> Match Tsui	

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1053.00	41.50 PK	74.00	-32.50	1.00 H	118	14.82	26.69
1	1053.00	34.44 AV	54.00	-19.56	1.00 H	118	7.75	26.69
2	1750.00	59.17 PK	74.00	-14.83	1.02 H	289	31.20	27.97
2	1750.00	45.29 AV	54.00	-8.71	1.02 H	289	17.32	27.97
3	2360.00	47.28 PK	74.00	-26.72	1.28 H	345	16.61	30.67
3	2360.00	36.97 AV	54.00	-17.03	1.28 H	345	6.3	30.67
4	*2437.00	112.29 PK			1.37 H	57	81.31	30.98
4	*2437.00	104.33 AV			1.37 H	57	73.35	30.98
5	4874.00	56.29 PK	74.00	-17.71	1.08 H	357	19.68	36.61
5	4874.00	43.74 AV	54.00	-10.26	1.08 H	357	7.13	36.61

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1053.00	44.04 PK	74.00	-29.96	1.00 V	343	17.36	26.69
1	1053.00	38.88 AV	54.00	-15.12	1.00 V	343	12.19	26.69
2	2360.00	47.77 PK	74.00	-26.23	1.24 V	314	17.10	30.67
2	2360.00	34.27 AV	54.00	-19.73	1.24 V	314	3.6	30.67
3	*2437.00	101.17 PK			1.03 V	235	70.19	30.98
3	*2437.00	93.19 AV			1.03 V	235	62.21	30.98
4	4874.00	51.76 PK	74.00	-22.24	1.29 V	25	15.15	36.61
4	4874.00	39.07 AV	54.00	-14.93	1.29 V	25	2.46	36.61

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + CorrectionFactor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “ : Fundamental frequency.

<b>EUT</b>	802.11g Wireless LAN Network Adapter	<b>MODEL</b>	WL 01 2454 25M
<b>CHANNEL</b>	Channel 11	<b>FREQUENCY RANGE</b>	1~ 25GHz
<b>MODE</b>	CCK		
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>ENVIRONMENTAL CONDITIONS</b>	25deg. C, 64%RH, 991hPa	<b>TESTED BY:</b> Match Tsui	

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1053.00	41.81 PK	74.00	-32.19	1.00 H	118	15.13	26.69
1	1053.00	34.63 AV	54.00	-19.37	1.00 H	118	7.94	26.69
2	2360.00	52.03 PK	74.00	-21.97	1.08 H	30	21.36	30.67
2	2360.00	40.67 AV	54.00	-13.33	1.08 H	30	10.00	30.67
3	*2462.00	110.83 PK			1.08 H	34	79.75	31.08
3	*2462.00	102.63 AV			1.08 H	34	71.55	31.08
4	2486.00	54.94 PK	74.00	-19.06	1.08 H	34	23.76	31.18
4	2486.00	46.74 AV	54.00	-7.26	1.08 H	34	15.56	31.18
5	4924.00	56.89 PK	74.00	-17.11	1.11 H	360	20.09	36.80
5	4924.00	43.34 AV	54.00	-10.66	1.11 H	360	6.54	36.80

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1053.00	44.25 PK	74.00	-29.75	1.08 V	343	17.57	26.69
1	1053.00	38.85 AV	54.00	-15.15	1.08 V	343	12.16	26.69
2	*2462.00	104.41 PK			1.16 V	179	73.33	31.08
2	*2462.00	96.30 AV			1.16 V	179	65.22	31.08
3	2486.00	48.52 PK	74.00	-25.48	1.16 V	179	17.34	31.18
3	2486.00	40.41 AV	54.00	-13.59	1.16 V	179	9.23	31.18
4	4924.00	54.55 PK	74.00	-19.45	1.15 V	306	17.75	36.80
4	4924.00	42.10 AV	54.00	-11.90	1.15 V	306	5.30	36.80

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + CorrectionFactor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* ” : Fundamental frequency.

<b>EUT</b>	802.11g Wireless LAN Network Adapter	<b>MODEL</b>	WL 01 2454 25M
<b>CHANNEL</b>	Channel 1	<b>FREQUENCY RANGE</b>	1~ 25GHz
<b>MODE</b>	OFDM		
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>ENVIRONMENTAL CONDITIONS</b>	25deg. C, 64%RH, 991hPa	<b>TESTED BY:</b> Match Tsui	

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2360.00	57.53 PK	74.00	-16.47	1.38 H	46	26.86	30.67
1	2360.00	46.07 AV	54.00	-7.93	1.38 H	46	15.40	30.67
2	2390.00	60.78 PK	74.00	-13.22	1.36 H	54	29.99	30.79
2	<b>2390.00</b>	<b>51.59 AV</b>	<b>54.00</b>	<b>-2.41</b>	<b>1.36 H</b>	<b>54</b>	<b>20.80</b>	<b>30.79</b>
3	*2412.00	109.79 PK			1.36 H	54	78.91	30.88
3	*2412.00	100.60 AV			1.36 H	54	69.72	30.88
4	4824.00	50.29 PK	74.00	-23.71	1.03 H	31	13.84	36.45
4	4824.00	38.03 AV	54.00	-15.97	1.03 H	31	1.58	36.45

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1053.00	43.82 PK	74.00	-30.18	1.00 V	339	17.14	26.69
1	1053.00	38.24 AV	54.00	-15.76	1.00 V	339	11.55	26.69
2	2390.00	51.37 PK	74.00	-22.63	1.13 V	177	20.58	30.79
2	2390.00	41.69 AV	54.00	-12.31	1.13 V	177	10.90	30.79
3	*2412.00	100.38 PK			1.13 V	177	69.50	30.88
3	*2412.00	90.70 AV			1.13 V	177	59.82	30.88
4	4824.00	50.76 PK	74.00	-23.24	1.12 V	260	14.31	36.45
4	4824.00	36.73 AV	54.00	-17.27	1.12 V	260	0.28	36.45

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “ : Fundamental frequency.

<b>EUT</b>	802.11g Wireless LAN Network Adapter	<b>MODEL</b>	WL 01 2454 25M
<b>CHANNEL</b>	Channel 6	<b>FREQUENCY RANGE</b>	1~ 25GHz
<b>MODE</b>	OFDM		
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>ENVIRONMENTAL CONDITIONS</b>	25deg. C, 64%RH, 991hPa	<b>TESTED BY:</b> Match Tsui	

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1052.00	41.69 PK	74.00	-32.31	1.00 H	118	15.00	26.68
1	1052.00	34.96 AV	54.00	-19.04	1.00 H	118	8.28	26.68
2	2360.00	52.90 PK	74.00	-21.10	1.33 H	360	22.23	30.67
2	2360.00	42.17 AV	54.00	-11.83	1.33 H	360	11.50	30.67
3	*2437.00	107.82 PK			1.08 H	32	76.84	30.98
3	*2437.00	98.55 AV			1.08 H	32	67.57	30.98
4	4874.00	54.60 PK	74.00	-19.40	1.10 H	358	17.99	36.61
4	4874.00	40.71 AV	54.00	-13.29	1.10 H	358	4.10	36.61

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2360.00	46.83 PK	74.00	-27.17	1.25 V	139	16.16	30.67
1	2360.00	34.59 AV	54.00	-19.41	1.25 V	139	3.92	30.67
2	*2437.00	102.46 PK			1.21 V	162	71.48	30.98
2	*2437.00	93.04 AV			1.21 V	162	62.06	30.98
3	4874.00	51.66 PK	74.00	-22.34	1.22 V	100	15.05	36.61
3	4874.00	38.88 AV	54.00	-15.12	1.22 V	100	2.27	36.61

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + CorrectionFactor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* ” : Fundamental frequency.

<b>EUT</b>	802.11g Wireless LAN Network Adapter	<b>MODEL</b>	WL 01 2454 25M
<b>CHANNEL</b>	Channel 11	<b>FREQUENCY RANGE</b>	1~ 25GHz
<b>MODE</b>	OFDM		
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>ENVIRONMENTAL CONDITIONS</b>	25deg. C, 64%RH, 991hPa	<b>TESTED BY:</b> Match Tsui	

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1053.00	41.98 PK	74.00	-32.02	1.35 H	233	15.30	26.69
1	1053.00	36.01 AV	54.00	-17.99	1.35 H	233	9.32	26.69
2	2360.00	55.48 PK	74.00	-18.52	1.10 H	31	24.81	30.67
2	2360.00	44.39 AV	54.00	-9.61	1.10 H	31	13.72	30.67
3	*2462.00	108.56 PK			1.07 H	34	77.48	31.08
3	*2462.00	99.46 AV			1.07 H	34	68.38	31.08
4	2483.50	60.35 PK	74.00	-13.65	1.07 H	34	29.18	31.17
4	2483.50	51.25 AV	54.00	-2.75	1.07 H	34	20.08	31.17
5	4924.00	57.97 PK	74.00	-16.03	1.07 H	357	21.17	36.80
5	4924.00	44.67 AV	54.00	-9.33	1.07 H	357	7.87	36.80

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1053.00	41.72 PK	74.00	-32.28	1.53 V	174	15.04	26.69
1	1053.00	34.93 AV	54.00	-19.07	1.53 V	174	8.24	26.69
2	2360.00	47.47 PK	74.00	-26.53	1.23 V	161	16.80	30.67
2	2360.00	35.63 AV	54.00	-18.37	1.23 V	161	4.96	30.67
3	*2462.00	103.31 PK			1.14 V	178	72.23	31.08
3	*2462.00	93.88 AV			1.14 V	178	62.80	31.08
4	2483.50	55.10 PK	74.00	-18.90	1.14 V	178	23.93	31.17
4	2483.50	45.67 AV	54.00	-8.33	1.14 V	178	14.50	31.17
5	4924.00	54.10 PK	74.00	-19.90	1.06 V	275	17.30	36.80
5	4924.00	40.50 AV	54.00	-13.50	1.06 V	275	3.70	36.80

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + CorrectionFactor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* ” : Fundamental frequency.

### 4.3 6dB BANDWIDTH MEASUREMENT

#### 4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

#### 4.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2004

**NOTE:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

#### 4.3.3 TEST PROCEDURE


The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 1kHz RBW and 10kHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

#### 4.3.4 DEVIATION FROM TEST STANDARD

No deviation



#### 4.3.5 TEST SETUP



For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

#### 4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.


## 4.3.7 TEST RESULTS

<b>EUT</b>	802.11g Wireless LAN Network Adapter	<b>MODEL</b>	WL 01 2454 25M
<b>MODE</b>	CCK	<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz
<b>ENVIRONMENTAL CONDITIONS</b>	25deg. C, 65%RH, 991hPa	<b>TESTED BY</b>	Match Tsui

<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>6dB BANDWIDTH (MHz)</b>	<b>MINIMUM LIMIT (MHz)</b>	<b>PASS/FAIL</b>
1	2412	8.88	0.5	PASS
6	2437	8.96	0.5	PASS
11	2462	9.44	0.5	PASS




CH1






CH6



L PK  
 VIEW



CH11







<b>EUT</b>	802.11g Wireless LAN Network Adapter	<b>MODEL</b>	WL 01 2454 25M
<b>MODE</b>	OFDM	<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz
<b>ENVIRONMENTAL CONDITIONS</b>	25deg. C, 65%RH, 991hPa	<b>TESTED BY</b>	Match Tsui

<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>6dB BANDWIDTH (MHz)</b>	<b>MINIMUM LIMIT (MHz)</b>	<b>PASS/FAIL</b>
1	2412	16.60	0.5	PASS
6	2437	16.60	0.5	PASS
11	2462	16.56	0.5	PASS

CH1




CH6





CH11



#### 4.4 MAXIMUM PEAK OUTPUT POWER

##### 4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

##### 4.4.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2004
AGILENT SIGNAL GENERATOR	E8257C	MY43320668	Dec. 31, 2004
TEKTRONIX OSCILLOSCOPE	TDS 220	C019167	Feb. 1, 2005
NARDA DETECTOR	4503A	FSCM99899	NA

**NOTE:**

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

##### 4.4.3 TEST PROCEDURES

1. A detector was used on the output port of the EUT. An oscilloscope was used to read the response of the detector.
2. Replaced the EUT by the signal generator. The center frequency of the S.G was adjusted to the center frequency of the measured channel.
3. Adjusted the power to have the same reading on oscilloscope. Record the power level.

##### 4.4.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.4.5 TEST SETUP



#### 4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.1.6.

## 4.4.7 TEST RESULTS

<b>EUT</b>	802.11g Wireless LAN Network Adapter	<b>MODEL</b>	WL 01 2454 25M
<b>MODE</b>	CCK	<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz
<b>ENVIRONMENTAL CONDITIONS</b>	25deg. C, 65%RH, 991hPa	<b>TESTED BY</b>	Match Tsui

<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>PEAK POWER OUTPUT (dBm)</b>	<b>PEAK POWER LIMIT (dBm)</b>	<b>PASS/FAIL</b>
1	2412	15.20	30	PASS
6	2437	15.30	30	PASS
11	2462	15.10	30	PASS

<b>EUT</b>	802.11g Wireless LAN Network Adapter	<b>MODEL</b>	WL 01 2454 25M
<b>MODE</b>	OFDM	<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz
<b>ENVIRONMENTAL CONDITIONS</b>	25deg. C, 65%RH, 991hPa	<b>TESTED BY</b>	Match Tsui

<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>PEAK POWER OUTPUT (dBm)</b>	<b>PEAK POWER LIMIT (dBm)</b>	<b>PASS/FAIL</b>
1	2412	15.00	30	PASS
6	2437	15.00	30	PASS
11	2462	15.00	30	PASS

## 4.5 POWER SPECTRAL DENSITY MEASUREMENT

### 4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

### 4.5.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2004

**NOTE:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


#### 4.5.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3kHz RBW and 30kHz VBW, set sweep time=span/3kHz. The power spectral density was measured and recorded. The sweep time is allowed to be longer than span/3kHz for a full response of the mixer in the spectrum analyzer.

#### 4.5.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.5.5 TEST SETUP



#### 4.5.6 EUT OPERATING CONDITIONS


Same as 4.1.6

## 4.5.7 TEST RESULTS

<b>EUT</b>	802.11g Wireless LAN Network Adapter	<b>MODEL</b>	WL 01 2454 25M
<b>MODE</b>	CCK	<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz
<b>ENVIRONMENTAL CONDITIONS</b>	25deg. C, 65%RH, 991hPa	<b>TESTED BY</b>	Match Tsui


<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz )</b>	<b>RF POWER LEVEL IN 3kHz BW (dBm)</b>	<b>MAXIMUM LIMIT (dBm)</b>	<b>PASS/FAIL</b>
1	2412	-9.32	8	PASS
6	2437	-9.22	8	PASS
11	2462	-8.94	8	PASS

CH1






CH6





CH11






<b>EUT</b>	802.11g Wireless LAN Network Adapter	<b>MODEL</b>	WL 01 2454 25M
<b>MODE</b>	OFDM	<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz
<b>ENVIRONMENTAL CONDITIONS</b>	25deg. C, 65%RH, 991hPa	<b>TESTED BY</b>	Match Tsui


<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz )</b>	<b>RF POWER LEVEL IN 3kHz BW (dBm)</b>	<b>MAXIMUM LIMIT (dBm)</b>	<b>PASS/FAIL</b>
1	2412	-15.06	8	PASS
6	2437	-14.71	8	PASS
11	2462	-14.76	8	PASS



CH1




CH6





CH11



## 4.6 BAND EDGES MEASUREMENT

### 4.6.1 LIMITS OF BAND EDGES MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

### 4.6.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2004

**NOTE:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. Set both RBW and VBW of spectrum analyzer to 1MHz and 10Hz with suitable frequency span including 100MHz bandwidth from band edge. The band edges were measured and recorded.

### 4.6.4 DEVIATION FROM TEST STANDARD

No deviation



#### 4.6.5 EUT OPERATING CONDITION

Same as Item 4.1.6

#### 4.6.6 TEST RESULTS

The spectrum plots are attached on the following 8 pages. D2 line indicates the highest level, D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(C).

**NOTE 1:** The band edge emission plot of the CCK technique on the following 1 ~ 2 pages show 50.67dB delta between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 103.2dBuV/m, so the maximum field strength in restrict band is  $103.2 - 50.67 = 52.53$ dBuV/m which is under 54dBuV/m limit.

**NOTE 2:** The band edge emission plot of the CCK technique on the following 3 ~ 4 pages show 50.96dB delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 102.63dBuV/m, so the maximum field strength in restrict band is  $102.63 - 50.96 = 51.67$ dBuV/m which is under 54dBuV/m limit.


**NOTE 3:** The band edge emission plot of the OFDM technique on the following 5 ~ 6 pages show 59.22dB delta between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 100.6dBuV/m, so the maximum field strength in restrict band is  $100.6 - 59.22 = 41.38$ dBuV/m which is under 54dBuV/m limit.


**NOTE 4:** The band edge emission plot of the OFDM technique on the following 7 ~ 8 pages show 58.48dB delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 99.46dBuV/m, so the maximum field strength in restrict band is  $99.46 - 58.48 = 40.98$ dBuV/m which is under 54dBuV/m limit.







1 PK  
VIEW
























## **4.7 ANTENNA REQUIREMENT**

### **4.7.1 STANDARD APPLICABLE**

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### **4.7.2 ANTENNA CONNECTED CONSTRUCTION**


The antenna type used in this product is Printed Antenna without antenna connector. The maximum Gain of this antenna is only 0dBi.

## 5 PHOTOGRAPHS OF THE TEST CONFIGURATION

### CONDUCTED EMISSION TEST



## RADIATED EMISSION TEST





## 6 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025, Guide 25 or EN 45001:

<b>USA</b>	FCC, NVLAP, UL
<b>Germany</b>	TUV Rheinland
<b>Japan</b>	VCCI
<b>Norway</b>	NEMKO
<b>Canada</b>	INDUSTRY CANADA , CSA
<b>R.O.C.</b>	CNLA, BSMI, DGT
<b>Netherlands</b>	Telefication
<b>Singapore</b>	PSB , GOST-ASIA(MOU)
<b>Russia</b>	CERTIS(MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

[www.adt.com.tw/index.5/phtml](http://www.adt.com.tw/index.5/phtml). If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab:**

Tel: 886-2-26052180

Fax: 886-2-26052943

**Hsin Chu EMC/RF Lab:**

Tel: 886-3-5935343

Fax: 886-3-5935342

**Hwa Ya EMC/RF/Safety/Telecom Lab:**

Tel: 886-3-3183232

Fax: 886-3-3185050

**Linko RF Lab.**

Tel: 886-3-3270910

Fax: 886-3-3270892

**Email:** [service@mail.adt.com.tw](mailto:service@mail.adt.com.tw)

**Web Site:** [www.adt.com.tw](http://www.adt.com.tw)

The address and road map of all our labs can be found in our web site also.

Report Format Version 1.0