



# FCC TEST REPORT

**REPORT NO.:** RF921127R01A

**MODEL NO.:** WL 01 2454 NM

(Refer to page 6 for the other models)

**RECEIVED:** NA

**TESTED:** November 27 ~ December 02, 2003

**APPLICANT:** GLOBAL SUN TECHNOLOGY INC.

**ADDRESS:** NO.13 Tung Yuan Rd., Jung Li Industrial Park  
Jung Li City, Tao Yuan Hsien, Taiwan

**ISSUED BY:** Advance Data Technology Corporation

**LAB LOCATION:** 47 14th Lin, Chiapau Tsun, Linko, Taipei,  
Taiwan, R.O.C.

This test report consists of 63 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA or any government agencies. The test results in the report only apply to the tested sample.



0528  
ILAC MRA



## Table of Contents

1	CERTIFICATION .....	4
2	SUMMARY OF TEST RESULTS .....	5
3	GENERAL INFORMATION.....	6
3.1	GENERAL DESCRIPTION OF EUT .....	6
3.2	DESCRIPTION OF TEST MODES .....	7
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS .....	7
3.4	DESCRIPTION OF SUPPORT UNITS .....	8
3.5	CONFIGURATION OF SYSTEM UNDER TEST.....	8
4	TEST TYPES AND RESULTS .....	9
4.1	CONDUCTED EMISSION MEASUREMENT .....	9
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT.....	9
4.1.2	TEST INSTRUMENTS.....	9
4.1.3	TEST PROCEDURES .....	10
4.1.4	DEVIATION FROM TEST STANDARD .....	10
4.1.5	TEST SETUP.....	11
4.1.6	EUT OPERATING CONDITIONS .....	11
4.1.7	TEST RESULTS .....	12
4.2	RADIATED EMISSION MEASUREMENT .....	18
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT.....	18
4.2.2	TEST INSTRUMENTS.....	19
4.2.3	TEST PROCEDURES .....	20
4.2.4	DEVIATION FROM TEST STANDARD .....	20
4.2.5	TEST SETUP.....	21
4.2.6	EUT OPERATING CONDITIONS .....	21
4.2.7	TEST RESULTS .....	22
4.2.8	TEST RESULTS (FOR CCK).....	23
4.2.9	TEST RESULTS (FOR OFDM).....	26
4.3	6dB BANDWIDTH MEASUREMENT.....	29
4.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT .....	29
4.3.2	TEST INSTRUMENTS.....	29
4.3.3	TEST PROCEDURE.....	30
4.3.4	DEVIATION FROM TEST STANDARD .....	30
4.3.5	TEST SETUP.....	30
4.3.6	EUT OPERATING CONDITIONS .....	30




4.3.7	TEST RESULTS (FOR CCK).....	31
4.3.8	TEST RESULTS (FOR OFDM).....	35
4.4	MAXIMUM PEAK OUTPUT POWER .....	39
4.4.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT .....	39
4.4.2	TEST INSTRUMENTS.....	39
4.4.3	TEST PROCEDURES .....	40
4.4.4	DEVIATION FROM TEST STANDARD .....	40
4.4.5	TEST SETUP.....	40
4.4.6	EUT OPERATING CONDITIONS .....	40
4.4.7	TEST RESULTS (FOR CCK).....	41
4.4.8	TEST RESULTS (FOR OFDM).....	42
4.5	POWER SPECTRAL DENSITY MEASUREMENT .....	43
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT .....	43
4.5.2	TEST INSTRUMENTS.....	43
4.5.3	TEST PROCEDURE.....	44
4.5.4	DEVIATION FROM TEST STANDARD .....	44
4.5.5	TEST SETUP.....	44
4.5.6	EUT OPERATING CONDITIONS .....	44
4.5.7	TEST RESULTS (FOR CCK).....	45
4.5.8	TEST RESULTS (FOR OFDM).....	49
4.5.9	BAND EDGES MEASUREMENT .....	53
4.5.10	LIMITS OF BAND EDGES MEASUREMENT.....	53
4.5.11	TEST INSTRUMENTS.....	53
4.5.12	TEST PROCEDURE.....	53
4.5.13	DEVIATION FROM TEST STANDARD .....	53
4.5.14	EUT OPERATING CONDITION .....	54
4.5.15	TEST RESULTS (FOR CCK).....	54
4.5.16	TEST RESULTS (FOR OFDM).....	57
4.6	ANTENNA REQUIREMENT .....	60
4.6.1	STANDARD APPLICABLE .....	60
4.6.2	ANTENNA CONNECTED CONSTRUCTION .....	60
5	PHOTOGRAPHS OF THE TEST CONFIGURATION.....	61
6	INFORMATION ON THE TESTING LABORATORIES .....	63




# 1 CERTIFICATION

**PRODUCT :** 802.11g Wireless PC Card  
**BRAND NAME :** GLOBAL SUN  
(Refer to page 6 for the other brands)  
**MODEL NO. :** WL 01 2454 NM  
(Refer to page 6 for the other models)  
**TEST ITEM:** ENGINEERING SAMPLE  
**APPLICANT :** GLOBAL SUN TECHNOLOGY INC.  
**STANDARDS :** FCC Part 15, Subpart C (Section 15.247),  
ANSI C63.4-1992

We, **Advance Data Technology Corporation**, hereby certify that one sample of the designation has been tested in our facility from November 27, 2003 to December 02, 2003. The test record, data evaluation and Equipment Under Test(EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions herein specified.

**PREPARED BY:**  , **DATE:** February 5, 2004  
Stephanie Hung

**APPROVED BY:**  , **DATE:** February 5, 2004  
Ellis Wu /  
Technical Manager



## 2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

<b>APPLIED STANDARD: FCC Part 15, Subpart C</b>			
<b>Standard Section</b>	<b>Test Type and Limit</b>	<b>Result</b>	<b>REMARK</b>
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit Minimum passing margin is -16.15 dB at 0.173 MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit
15.247(c)	Transmitter Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit Minimum passing margin is -2.14 dB at 2200.00 MHz
15.247(d)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit
15.247(c)	Band Edge Measurement Limit: 20 dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit

**NOTE:** The information of measurement uncertainty is available upon the customer's request.



### 3 GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

<b>PRODUCT</b>	802.11g Wireless PC Card
<b>MODEL NO.</b>	WL 01 2454 NM
<b>POWER SUPPLY</b>	3.3Vdc from host equipment
<b>MODULATION TYPE</b>	DBPSK,DQPSK,CCK,16QAM,64QAM
<b>RADIO TECHNOLOGY</b>	DSSS, OFDM
<b>TRANSFER RATE</b>	802.11b:11/5.5/2/1Mbps 802.11g: 54/48/36/24/18/12/9/6Mbps
<b>FREQUENCY RANGE</b>	2412MHz ~ 2462MHz
<b>NUMBER OF CHANNEL</b>	11
<b>OUTPUT POWER</b>	17.39dBm
<b>ANTENNA TYPE</b>	Printed antenna with 0dBi gain
<b>DATA CABLE</b>	NA
<b>I/O PORTS</b>	NA
<b>ASSOCIATED DEVICES</b>	NA

**NOTE:**

1. The EUT complies with IEEE 802.11g draft standards, and backwards compatible with IEEE 802.11b products.
2. This is a duplicate report of RF921127R01, and the only difference is changing the product name, model, brand and the applicant.
3. The models as below are identical to each other except for their brand and model due to marketing requirement.

<b>Brand</b>	<b>Model</b>	<b>Remark</b>
GLOBAL SUN	WL 01 2454 NM	
ORIGO	WLL-3210M	OEM model
PLANET	WL-3561	OEM model
AOpen	AOI-812	OEM model
Trust	Speedshare Pro Wireless PC-Card	OEM model
Level One	WPC-0301	OEM model
PLANEX/PCI	GW-NS54GM	OEM model
Etherwan Systems Inc.	EWP-0202-G	OEM model

4. For more detailed features description, please refer to the manufacturer's specifications or User's Manual.



### 3.2 DESCRIPTION OF TEST MODES

Eleven channels are provided to this EUT.

Channel	Frequency	Channel	Frequency
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

**NOTE:**

1. Below 1 GHz, the channel 1, 6, and 11 were pre-tested in chamber. The channel 11, worst case one, was chosen for final test.
2. Above 1 GHz, the channel 1, 6, and 11 were tested individually.
3. Transfer rate of 11Mbps with CCK technique and 6Mbps with OFDM technique, the worst case, were chosen for final test.

### 3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a 802.11g Wireless PC Card. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C. (15.247)**

**ANSI C63.4 : 1992**

All test items have been performed and recorded as per the above standards.

**NOTE:** The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



### 3.4 DESCRIPTION OF SUPPORT UNITS


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK	Dell	PP01L	TW-09C748-12800-16M-5064	FCC DoC Approved
2	MODEM	ACEEX	1414	980020503	IFAXDM1414
3	PRINTER	EPSON	LQ-300+	DCGY017096	FCC DoC Approved

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	1.2 m braid shielded wire, terminated with DB25 and DB9 connector via metallic frame, w/o core.
3	1.2m braid shielded wire, terminated with DB25 and Centronics connector via metallic frame, w/o core

**NOTE:** All power cords of the above support units are non shielded (1.8m).

### 3.5 CONFIGURATION OF SYSTEM UNDER TEST







## 4 TEST TYPES AND RESULTS

### 4.1 CONDUCTED EMISSION MEASUREMENT

#### 4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
  2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
  3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

#### 4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED ON
ROHDE & SCHWARZ Test Receiver	ESCS 30	838251/021	Jan. 04, 2005
ROHDE & SCHWARZ Artificial Mains Network (for EUT)	ESH3-Z5	100218	Dec. 09, 2004
ROHDE & SCHWARZ Artificial Mains Network (for peripherals)	ESH3-Z5	100219	Dec. 09, 2004
ROHDE & SCHWARZ Artificial Mains Network (for peripherals)	ESH3-Z5	100220	Dec. 09, 2004
*ROHDE & SCHWARZ 4-wire ISN	ENY41	837032/016	Nov. 19, 2004
*ROHDE & SCHWARZ 2-wire ISN	ENY22	837497/016	Nov. 19, 2004
Software	Cond-V2M3	NA	NA
RF cable (JYEBAO)	5D-FB	Cable-C10.01	May 01, 2004
SUHNER Terminator (For ROHDE & SCHWARZ LISN)	65BNC-5001	E1-010770	Mar. 24, 2004
SUHNER Terminator (For ROHDE & SCHWARZ LISN)	65BNC-5001	E1-010773	Apr. 06, 2004

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
  2. “\*”: These equipment are used for conducted telecom port test only (if tested).
  3. The test was performed in ADT Shielded Room No. 10.
  4. The VCCI Site Registration No. is C-1312.




#### 4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels under limit 20dB of the prescribed limits could not be reported.

#### 4.1.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.1.5 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
  2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

#### 4.1.6 EUT OPERATING CONDITIONS

- a. Plug the EUT a notebook computer system placed on a testing table.
- b. The computer system ran a test program to enable EUT under transmission/receiving condition continuously at specific channel frequency.
- c. The computer system sent "H" messages to its screen.
- d. The computer system sent "H" messages to modem.
- e. The computer system sent "H" messages to printer, and the printer prints them on paper.
- f. Repeated c~e.




4.1.7 TEST RESULTS

<b>EUT</b>	802.11g Wireless PC Card	<b>MODEL</b>	WL 01 2454 NM
<b>MODE</b>	Channel 1	<b>6dB BANDWIDTH</b>	9 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Line (L)
<b>ENVIRONMENTAL CONDITIONS</b>	20deg. C, 70%RH, 991 hPa	<b>TESTED BY:</b> Jamison Chan	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.173	0.06	48.59	-	48.65	-	64.79	54.79	-16.15	-
2	0.232	0.06	40.85	-	40.91	-	62.38	52.38	-21.47	-
3	0.295	0.06	35.64	-	35.70	-	60.40	50.40	-24.70	-
4	0.408	0.06	33.70	-	33.76	-	57.69	47.69	-23.93	-
5	3.910	0.22	28.11	-	28.33	-	56.00	46.00	-27.67	-
6	17.859	0.61	23.88	-	24.49	-	60.00	50.00	-35.51	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.






<b>EUT</b>	802.11g Wireless PC Card	<b>MODEL</b>	WL 01 2454 NM
<b>MODE</b>	Channel 1	<b>6dB BANDWIDTH</b>	9 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Neutral (N)
<b>ENVIRONMENTAL CONDITIONS</b>	20deg. C, 70%RH, 991 hPa	<b>TESTED BY:</b> Jamison Chan	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.173	0.05	48.24	-	48.29	-	64.79	54.79	-16.50	-
2	0.236	0.05	38.36	-	38.41	-	62.24	52.24	-23.83	-
3	0.287	0.05	29.49	-	29.54	-	60.62	50.62	-31.08	-
4	4.078	0.21	26.59	-	26.80	-	56.00	46.00	-29.20	-
5	5.184	0.24	16.10	-	16.34	-	60.00	50.00	-43.66	-
6	18.492	0.50	23.43	-	23.93	-	60.00	50.00	-36.07	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.






<b>EUT</b>	802.11g Wireless PC Card	<b>MODEL</b>	WL 01 2454 NM
<b>MODE</b>	Channel 6	<b>6dB BANDWIDTH</b>	9 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Line (L)
<b>ENVIRONMENTAL CONDITIONS</b>	20deg. C, 70%RH, 991 hPa	<b>TESTED BY:</b> Jamison Chan	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.177	0.06	47.89	-	47.95	-	64.61	54.61	-16.66	-
2	0.232	0.06	40.77	-	40.83	-	62.38	52.38	-21.55	-
3	0.291	0.06	36.74	-	36.80	-	60.51	50.51	-23.71	-
4	0.818	0.13	24.01	-	24.14	-	56.00	46.00	-31.86	-
5	3.563	0.21	26.66	-	26.87	-	56.00	46.00	-29.13	-
6	16.590	0.59	26.35	-	26.94	-	60.00	50.00	-33.06	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.






<b>EUT</b>	802.11g Wireless PC Card	<b>MODEL</b>	WL 01 2454 NM
<b>MODE</b>	Channel 6	<b>6dB BANDWIDTH</b>	9 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Neutral (N)
<b>ENVIRONMENTAL CONDITIONS</b>	20deg. C, 70%RH, 991 hPa	<b>TESTED BY:</b> Jamison Chan	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.177	0.05	47.50	-	47.55	-	64.61	54.61	-17.06	-
2	0.232	0.05	39.03	-	39.08	-	62.38	52.38	-23.30	-
3	0.291	0.05	34.40	-	34.45	-	60.51	50.51	-26.06	-
4	0.466	0.06	29.08	-	29.14	-	56.58	46.58	-27.44	-
5	4.027	0.21	27.76	-	27.97	-	56.00	46.00	-28.03	-
6	16.883	0.50	24.46	-	24.96	-	60.00	50.00	-35.04	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.






<b>EUT</b>	802.11g Wireless PC Card	<b>MODEL</b>	WL 01 2454 NM
<b>MODE</b>	Channel 11	<b>6dB BANDWIDTH</b>	9 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Line (L)
<b>ENVIRONMENTAL CONDITIONS</b>	20deg. C, 70%RH, 991 hPa	<b>TESTED BY:</b> Jamison Chan	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.177	0.06	47.95	-	48.01	-	64.61
2	0.236	0.06	40.08	-	40.14	-	62.24	52.24	-22.10	-
3	0.291	0.06	36.32	-	36.38	-	60.51	50.51	-24.13	-
4	0.412	0.06	32.19	-	32.25	-	57.61	47.61	-25.36	-
5	4.094	0.22	29.88	-	30.10	-	56.00	46.00	-25.90	-
6	22.750	0.78	24.25	-	25.03	-	60.00	50.00	-34.97	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.








<b>EUT</b>	802.11g Wireless PC Card	<b>MODEL</b>	WL 01 2454 NM
<b>MODE</b>	Channel 11	<b>6dB BANDWIDTH</b>	9 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Neutral (N)
<b>ENVIRONMENTAL CONDITIONS</b>	20deg. C, 70%RH, 991 hPa	<b>TESTED BY:</b> Jamison Chan	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.177	0.05	47.58	-	47.63	-	64.61	54.61	-16.98	-
2	0.232	0.05	38.79	-	38.84	-	62.38	52.38	-23.54	-
3	0.291	0.05	34.54	-	34.59	-	60.51	50.51	-25.92	-
4	0.466	0.06	28.88	-	28.94	-	56.58	46.58	-27.64	-
5	3.801	0.20	31.11	-	31.31	-	56.00	46.00	-24.69	-
6	18.527	0.50	22.08	-	22.58	-	60.00	50.00	-37.42	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.





## 4.2 RADIATED EMISSION MEASUREMENT

### 4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



## 4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED ON
* HP Spectrum Analyzer	8594E	3911A07465	July 07, 2004
* HP Preamplifier	8447D	2432A03504	June 10, 2004
* HP Preamplifier	8449B	3008A01292	Aug. 11, 2004
SCHAFFNER Tunable Dipole Antenna	VHBA 9123	459	Jun. 26, 2004
SCHWARZBECK Tunable Dipole Antenna	UHA 9105	977	
* ROHDE & SCHWARZ TEST RECEIVER	ESMI	839013/007 839379/002	Feb. 13, 2004
*Schwarzbeck Antenna	VULB9168	137	Apr. 03, 2004
* SCHWARZBECK Horn Antenna	BBHA9120-D1	D130	June 30, 2004
*ADT. Turn Table	TT100	0306	NA
*ADT. Tower	AT100	0306	NA
*Software	ADT_Radiated_V5.14	NA	NA
*TIMES RF cable	LL142	CABLE-CH6-01	Apr. 30, 2004

- NOTE:**
1. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.
  2. "\*" = These equipment are used for the final measurement.
  3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
  4. The test was performed in ADT Chamber No. 6.



#### 4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


**NOTE:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.

#### 4.2.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

#### 4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6



## 4.2.7 TEST RESULTS

<b>EUT</b>	802.11g Wireless PC Card	<b>MODEL</b>	WL 01 2454 NM
<b>MODE</b>	Channel 11	<b>FREQUENCY RANGE</b>	Below 1000 MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Quasi-Peak
<b>ENVIRONMENTAL CONDITIONS</b>	20 deg. C, 65 % RH, 991 hPa	<b>TESTED BY:</b> Jun Wu	

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	177.74	33.61 QP	43.50	-9.89	1.50 H	82	20.91	12.7
2	210.78	33.77 QP	43.50	-9.73	1.75 H	100	22.04	11.73
3	261.32	37.11 QP	43.50	-8.89	1.00 H	268	23.42	13.69
4	300.20	37.88 QP	43.50	-8.12	1.00 H	286	22.79	15.10
5	457.66	40.33 QP	43.50	-5.67	1.75 H	283	20.92	19.41
6	702.59	34.84 QP	43.50	-11.16	1.00 H	307	10.79	24.05
7	836.71	36.35 QP	43.50	-9.65	1.50 H	325	10.35	26.00
8	881.42	37.95 QP	43.50	-8.05	1.25 H	139	11.19	26.77

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	76.65	10.16 QP	40.00	-5.36	1.00 V	358	24.48	10.16
2	210.78	11.73 QP	43.50	-10.00	1.75 V	187	21.77	11.73
3	261.32	13.69 QP	46.00	-10.68	1.75 V	172	21.63	13.69
4	455.71	19.38 QP	46.00	-3.18	1.00 V	322	23.44	19.38
5	792.00	25.58 QP	46.00	-10.71	1.00 V	226	9.72	25.58
6	836.71	26.00 QP	46.00	-9.15	1.50 V	262	10.85	26.00
7	881.42	26.77 QP	46.00	-7.41	1.50 V	265	11.82	26.77
8	914.47	27.30 QP	46.00	-8.49	1.00 V	334	10.20	27.30

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.



4.2.8 TEST RESULTS (For CCK)

<b>EUT</b>	802.11g Wireless PC Card	<b>MODEL</b>	WL 01 2454 NM
<b>MODE</b>	Channel 1	<b>FREQUENCY RANGE</b>	1~25 GHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>ENVIRONMENTAL CONDITIONS</b>	20 deg. C, 65 % RH, 991 hPa	<b>TESTED BY:</b> Jun Wu	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2200.00	55.04 PK	74.00	-18.96	1.09 H	2	25.11	29.93
1	2200.00	50.32 AV	54.00	-3.68	1.09 H	2	20.39	29.93
2	2390.00	52.68 PK	74.00	-21.32	1.09 H	2	21.93	30.75
3	*2412.00	108.89 PK			1.09 H	2	78.00	30.84
3	*2412.00	100.62 AV			1.09 H	2	69.78	30.84
4	2784.00	47.80 PK	74.00	-26.20	1.00 H	15	16.01	31.79
5	4824.00	58.05 PK	74.00	-15.95	1.27 H	360	21.79	36.26
5	4824.00	46.79 AV	54.00	-7.21	1.27 H	360	10.53	36.26
6	7234.00	59.11 PK	74.00	-14.89	1.37 H	19	16.86	42.25
6	7234.00	45.89 AV	54.00	-8.11	1.37 H	19	3.64	42.25

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2200.00	59.94 PK	74.00	-14.06	1.54 V	247	30.01	29.93
<b>1</b>	<b>2200.00</b>	<b>51.86 AV</b>	<b>54.00</b>	<b>-2.14</b>	<b>1.54 V</b>	<b>247</b>	<b>21.93</b>	<b>29.93</b>
2	2390.00	53.58 PK	74.00	-20.42	1.54 V	247	22.83	30.75
2	2390.00	45.53 AV	54.00	-8.47	1.54 V	247	14.78	30.75
3	*2412.00	109.56 PK			1.54 V	247	78.72	30.84
3	*2412.00	101.40 AV			1.54 V	247	70.56	30.84
4	2784.00	49.43 PK	74.00	-24.57	1.00 V	230	17.64	31.79
5	4874.00	60.52 PK	74.00	-13.48	1.19 V	200	22.16	24.18
5	4874.00	48.71 AV	54.00	-5.29	1.19 V	200	12.37	36.34
6	7227.00	57.71 PK	74.00	-16.29	1.45 V	272	15.47	42.24
6	7227.00	45.03 AV	54.00	-8.97	1.45 V	272	2.79	42.24

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* ” : Fundamental frequency
  6. The other emission levels were very low against the limit.



<b>EUT</b>	802.11g Wireless PC Card	<b>MODEL</b>	WL 01 2454 NM
<b>MODE</b>	Channel 6	<b>FREQUENCY RANGE</b>	1~25 GHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>ENVIRONMENTAL CONDITIONS</b>	20 deg. C, 65 % RH, 991 hPa	<b>TESTED BY:</b> Jun Wu	

<b>ANTENNA POLARITY &amp; TEST DISTANCE: HORIZONTAL AT 3 M</b>								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	109.70 PK			1.07 H	354	78.75	30.95
1	*2437.00	97.40 AV			1.07 H	354	66.45	30.95
2	4874.00	57.27 PK	74.00	-16.73	1.36 H	173	20.93	36.34
2	4874.00	41.86 AV	54.00	-12.14	1.36 H	173	5.52	36.34
3	7361.00	52.37 PK	74.00	-21.63	1.42 H	214	9.90	42.47

<b>ANTENNA POLARITY &amp; TEST DISTANCE: VERTICAL AT 3 M</b>								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	111.02 PK			1.51 V	246	80.07	30.95
1	*2437.00	103.13 AV			1.51 V	246	72.18	30.95
2	2810.00	48.73 PK	74.00	-25.27	1.05 V	185	16.87	31.86
3	4874.00	60.89 PK	74.00	-13.11	1.17 V	202	24.55	36.34
3	4874.00	49.01 AV	54.00	-4.99	1.17 V	202	12.67	36.34

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “ : Fundamental frequency
  6. The other emission levels were very low against the limit.





<b>EUT</b>	802.11g Wireless PC Card	<b>MODEL</b>	WL 01 2454 NM
<b>MODE</b>	Channel 11	<b>FREQUENCY RANGE</b>	1~25 GHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>ENVIRONMENTAL CONDITIONS</b>	20 deg. C, 65 % RH, 991 hPa	<b>TESTED BY:</b> Jun Wu	

<b>ANTENNA POLARITY &amp; TEST DISTANCE: HORIZONTAL AT 3 M</b>								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2200.00	57.13 PK	74.00	-16.87	1.08 H	10	27.20	29.93
1	2200.00	49.75 AV	54.00	-4.25	1.08 H	10	19.82	29.93
2	*2462.00	105.41 PK			1.08 H	10	74.35	31.06
2	*2462.00	98.05 AV			1.08 H	10	66.99	31.06
3	2483.50	48.54 PK	74.00	-25.46	1.08 H	10	17.39	31.15
4	2836.00	51.65 PK	74.00	-22.35	1.32 H	23	19.69	31.96
5	4924.00	55.08 PK	74.00	-18.92	1.68 H	241	18.66	36.42
5	4924.00	41.38 AV	54.00	-12.62	1.68 H	241	4.96	36.42

<b>ANTENNA POLARITY &amp; TEST DISTANCE: VERTICAL AT 3 M</b>								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2200.00	58.86 PK	74.00	-15.14	1.46 V	247	28.93	29.93
1	2200.00	51.33 AV	54.00	-2.67	1.46 V	247	21.40	29.93
2	*2462.00	107.16 PK			1.46 V	247	76.10	31.06
2	*2462.00	99.69 AV			1.46 V	247	68.63	31.06
3	2483.50	50.77 PK	74.00	-23.23	1.46 V	247	-19.62	31.15
4	2836.00	50.79 PK	74.00	-23.21	1.13 V	235	18.83	31.96
5	4924.00	55.68 PK	74.00	-18.32	1.34 V	193	19.26	36.42
5	4924.00	39.28 AV	54.00	-14.72	1.34 V	193	2.86	36.42
6	7385.00	55.23 PK	74.00	-18.77	1.25 V	263	12.71	42.51
6	7385.00	42.03 AV	54.00	-11.97	1.25 V	263	-0.49	42.51

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “ : Fundamental frequency
  6. The other emission levels were very low against the limit.



4.2.9 TEST RESULTS (For OFDM)

<b>EUT</b>	802.11g Wireless PC Card	<b>MODEL</b>	WL 01 2454 NM
<b>MODE</b>	Channel 1	<b>FREQUENCY RANGE</b>	1~25 GHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>ENVIRONMENTAL CONDITIONS</b>	20 deg. C, 65 % RH, 991 hPa	<b>TESTED BY:</b> Jun Wu	

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2200.00	56.07 PK	74.00	-17.93	1.25 H	106	26.14	29.93
1	2200.00	46.84 AV	54.00	-7.16	1.25 H	106	16.91	29.93
2	2390.00	48.18 PK	74.00	-25.82	1.25 H	106	17.43	30.75
3	*2412.00	100.31 PK			1.25 H	106	69.47	30.84
3	*2412.00	91.12 AV			1.25 H	106	60.28	30.84
4	4824.00	50.12 PK	74.00	-23.88	1.53 H	177	13.87	36.26

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2200.00	49.84 PK	74.00	-24.16	1.00 V	343	19.91	29.93
2	2390.00	42.01 PK	74.00	-31.99	1.00 V	343	11.26	30.75
3	*2412.00	94.72 PK			1.00 V	343	63.88	30.84
3	*2412.00	89.01 AV			1.00 V	343	58.17	30.84
4	4824.00	53.32 PK	74.00	-20.68	1.20 V	188	17.07	36.26
4	4824.00	38.32 AV	54.00	-15.68	1.20 V	188	2.07	36.26

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* ” : Fundamental frequency
  6. The other emission levels were very low against the limit.



<b>EUT</b>	802.11g Wireless PC Card	<b>MODEL</b>	WL 01 2454 NM
<b>MODE</b>	Channel 6	<b>FREQUENCY RANGE</b>	1~25 GHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>ENVIRONMENTAL CONDITIONS</b>	20 deg. C, 65 % RH, 991 hPa	<b>TESTED BY:</b> Jun Wu	

<b>ANTENNA POLARITY &amp; TEST DISTANCE: HORIZONTAL AT 3 M</b>								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	105.90 PK			1.10 H	350	74.95	30.95
1	*2437.00	96.86 AV			1.10 H	350	65.91	30.95
2	2992.00	43.36 PK	74.00	-30.64	1.18 H	235	10.78	32.58
3	4874.00	51.40 PK	74.00	-22.60	1.44 H	32	15.06	36.34
3	4874.00	37.31 AV	54.00	-16.69	1.44 H	32	0.97	36.34

<b>ANTENNA POLARITY &amp; TEST DISTANCE: VERTICAL AT 3 M</b>								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	106.33 PK			1.46 V	250	75.38	30.95
1	*2437.00	97.29 AV			1.46 V	250	66.34	30.95
2	2992.00	46.76 PK	74.00	-27.24	1.48 V	247	14.18	32.58
3	4874.00	55.07 PK	74.00	-18.93	1.20 V	195	18.73	36.34
3	4874.00	39.00 AV	54.00	-15.00	1.20 V	195	2.66	36.34
4	7302.00	56.84 PK	74.00	-17.16	1.33 V	241	14.47	42.37
4	7302.00	42.31 AV	54.00	-11.69	1.33 V	241	-0.06	42.37

**REMARKS:**

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ \* “ : Fundamental frequency
6. The other emission levels were very low against the limit.



<b>EUT</b>	802.11g Wireless PC Card	<b>MODEL</b>	WL 01 2454 NM
<b>MODE</b>	Channel 11	<b>FREQUENCY RANGE</b>	1~25 GHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>ENVIRONMENTAL CONDITIONS</b>	20 deg. C, 65 % RH, 991 hPa	<b>TESTED BY:</b> Jun Wu	

<b>ANTENNA POLARITY &amp; TEST DISTANCE: HORIZONTAL AT 3 M</b>								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2200.00	57.42 PK	74.00	-16.58	1.07 H	360	27.49	29.93
1	2200.00	47.89 AV	54.00	-6.11	1.07 H	360	17.96	29.93
2	*2462.00	100.68 PK			1.07 H	360	69.62	31.06
2	*2462.00	91.23 AV			1.07 H	360	60.17	31.06
3	2483.50	51.60 PK	74.00	-22.40	1.07 H	360	20.45	31.15
3	2483.50	42.07 AV	54.00	-11.93	1.07 H	360	10.92	31.15
4	4924.00	50.15 PK	74.00	-23.85	1.21 H	162	13.73	36.42

<b>ANTENNA POLARITY &amp; TEST DISTANCE: VERTICAL AT 3 M</b>								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2200.00	58.92 PK	74.00	-15.08	1.51 V	244	28.99	29.93
1	2200.00	49.39 AV	54.00	-4.61	1.51 V	244	19.46	29.93
2	*2462.00	102.14 PK			1.51 V	244	71.08	31.06
2	*2462.00	92.57 AV			1.51 V	244	61.51	31.06
3	2483.50	53.10 PK	74.00	-20.90	1.51 V	244	21.95	31.15
3	2483.50	43.57 AV	54.00	-10.43	1.51 V	244	12.42	31.15
4	4924.00	51.48 PK	74.00	-22.52	1.33 V	193	15.06	36.42
4	4924.00	37.58 AV	54.00	-16.42	1.33 V	193	1.16	36.42

**REMARKS:**

- 1.Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
- 2.Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
- 3.The other emission levels were very low against the limit.
- 4.Margin value = Emission level – Limit value.
- 5.“ \* “ : Fundamental frequency
- 6.The other emission levels were very low against the limit.



### 4.3 6dB BANDWIDTH MEASUREMENT

#### 4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

#### 4.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated On
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2004

**NOTE:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


#### 4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 kHz RBW and 100 kHz VBW. The 6 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6 dB.

#### 4.3.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.3.5 TEST SETUP



#### 4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.




## 4.3.7 TEST RESULTS (For CCK)

<b>EUT</b>	802.11g Wireless PC Card	<b>MODEL</b>	WL 01 2454 NM
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>ENVIRONMENTAL CONDITIONS</b>	20deg. C, 62%RH, 991 hPa
<b>TESTED BY:</b> Stanely Hsu			

<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>6dB BANDWIDTH (MHz)</b>	<b>MINIMUM LIMIT (MHz)</b>	<b>PASS/FAIL</b>
1	2412	9.56	0.5	PASS
6	2437	9.48	0.5	PASS
11	2462	8.20	0.5	PASS




CH1








CH6





CH11






## 4.3.8 TEST RESULTS (For OFDM)

<b>EUT</b>	802.11g Wireless PC Card	<b>MODEL</b>	WL 01 2454 NM
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>ENVIRONMENTAL CONDITIONS</b>	20deg. C, 62%RH, 991 hPa
<b>TESTED BY:</b> Stanely Hsu			

<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>6dB BANDWIDTH (MHz)</b>	<b>MINIMUM LIMIT (MHz)</b>	<b>PASS/FAIL</b>
1	2412	16.08	0.5	PASS
6	2437	15.84	0.5	PASS
11	2462	15.84	0.5	PASS




CH1






CH6





CH11





#### 4.4 MAXIMUM PEAK OUTPUT POWER

##### 4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

##### 4.4.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated On
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2004
R&S SIGNAL GENERATOR	SMP04	100011	May 28, 2004
TEKTRONIX OSCILLOSCOPE	TDS 220	B048470	Mar. 05, 2004
NARDA DETECTOR	4503A	FSCM99899	NA

**NOTE:**

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA..



#### 4.4.3 TEST PROCEDURES

1. A detector was used on the output port of the EUT. An oscilloscope was used to read the response of the detector.
2. Replaced the EUT by the signal generator . The center frequency of the S.G was adjusted to the center frequency of the measured channel.
3. Adjusted the power to have the same reading on oscilloscope. Record the power level.

#### 4.4.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.4.5 TEST SETUP



#### 4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6.





## 4.4.7 TEST RESULTS (For CCK)

<b>EUT</b>	802.11g Wireless PC Card	<b>MODEL</b>	WL 01 2454 NM
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>ENVIRONMENTAL CONDITIONS</b>	20deg. C, 62%RH, 991 hPa
<b>TESTED BY:</b> Stanely Hsu			

<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>PEAK POWER OUTPUT (dBm)</b>	<b>PEAK POWER LIMIT (dBm)</b>	<b>PASS/FAIL</b>
1	2412	17.39	30	PASS
6	2437	16.60	30	PASS
11	2462	16.61	30	PASS



## 4.4.8 TEST RESULTS (For OFDM)

<b>EUT</b>	802.11g Wireless PC Card	<b>MODEL</b>	WL 01 2454 NM
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>ENVIRONMENTAL CONDITIONS</b>	20deg. C, 62%RH, 991 hPa
<b>TESTED BY:</b> Stanely Hsu			

<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>PEAK POWER OUTPUT (dBm)</b>	<b>PEAK POWER LIMIT (dBm)</b>	<b>PASS/FAIL</b>
1	2412	16.62	30	PASS
6	2437	16.64	30	PASS
11	2462	17.37	30	PASS



## 4.5 POWER SPECTRAL DENSITY MEASUREMENT

### 4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

### 4.5.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated On
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2003

**NOTE:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


#### 4.5.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3 kHz RBW and 30 kHz VBW, set sweep time=span/3kHz. The power spectral density was measured and recorded. The sweep time is allowed to be longer than span/3KHz for a full response of the mixer in the spectrum analyzer.

#### 4.5.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.5.5 TEST SETUP



#### 4.5.6 EUT OPERATING CONDITIONS

Same as 4.3.6




## 4.5.7 TEST RESULTS (For CCK)

<b>EUT</b>	802.11g Wireless PC Card	<b>MODEL</b>	WL 01 2454 NM
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>ENVIRONMENTAL CONDITIONS</b>	20deg. C, 62%RH, 991 hPa
<b>TESTED BY:</b> Stanely Hsu			

<b>CHANNEL NUMBER</b>	<b>CHANNEL FREQUENCY (MHz )</b>	<b>RF POWER LEVEL IN 3 KHz BW (dBm)</b>	<b>MAXIMUM LIMIT (dBm)</b>	<b>PASS/FAIL</b>
1	2412	-8.62	8	PASS
6	2437	-9.06	8	PASS
11	2462	-10.26	8	PASS




CH1






CH6





CH11








## 4.5.8 TEST RESULTS (For OFDM)

<b>EUT</b>	802.11g Wireless PC Card	<b>MODEL</b>	WL 01 2454 NM
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>ENVIRONMENTAL CONDITIONS</b>	20deg. C, 62%RH, 991 hPa
<b>TESTED BY:</b> Stanely Hsu			

<b>CHANNEL NUMBER</b>	<b>CHANNEL FREQUENCY (MHz )</b>	<b>RF POWER LEVEL IN 3 KHz BW (dBm)</b>	<b>MAXIMUM LIMIT (dBm)</b>	<b>PASS/FAIL</b>
1	2412	-20.34	8	PASS
6	2437	-19.51	8	PASS
11	2462	-18.66	8	PASS




CH1






CH6





CH11





#### 4.5.9 BAND EDGES MEASUREMENT

#### 4.5.10 LIMITS OF BAND EDGES MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100KHz Resolution Bandwidth).

#### 4.5.11 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated On
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2003

**NOTE:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

#### 4.5.12 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

#### 4.5.13 DEVIATION FROM TEST STANDARD

No deviation



#### 4.5.14 EUT OPERATING CONDITION

Same as Item 4.3.6


#### 4.5.15 TEST RESULTS (For CCK)

The spectrum plots are attached on the following 2 pages. D2 line indicates the highest level, D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(C).

**NOTE:**

The band edge emission plot on the following first page shows 49.87dB delta between carrier maximum power and local maximum emission in restrict band (2.3199GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.8 is 101.40dBuV/m, so the maximum field strength in restrict band is  $101.40 - 49.87 = 51.53$ dBuV/m which is under 54 dBuV/m limit.

The band edge emission plot on the following second page shows 49.64dB delta between carrier maximum power and local maximum emission in restrict band (2.4880GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.8 is 99.69dBuV/m, so the maximum field strength in restrict band is  $99.69 - 49.64 = 50.05$ dBuV/m which is under 54 dBuV/m limit.










#### 4.5.16 TEST RESULTS (For OFDM)


The spectrum plots are attached on the following 2 pages. D2 line indicates the highest level, D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(C).

**NOTE:**

The band edge emission plot on the following first page shows 37.64dB delta between carrier maximum power and local maximum emission in restrict band (2.3539GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.9 is 91.12dBuV/m, so the maximum field strength in restrict band is  $91.12 - 37.64 = 53.48$  dBuV/m which is under 54 dBuV/m limit.

The band edge emission plot on the following second page shows 39.19dB delta between carrier maximum power and local maximum emission in restrict band (2.4841GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.9 is 92.57dBuV/m, so the maximum field strength in restrict band is  $92.57 - 39.19 = 53.38$  dBuV/m which is under 54 dBuV/m limit.







## **4.6 ANTENNA REQUIREMENT**

### **4.6.1 STANDARD APPLICABLE**

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### **4.6.2 ANTENNA CONNECTED CONSTRUCTION**

The maximum Gain antenna used in this product is Printed antenna without antenna connector. And the maximum Gain of these antennas is 0dBi.

## 5 PHOTOGRAPHS OF THE TEST CONFIGURATION

### CONDUCTED EMISSION TEST



### RADIATED EMISSION TEST





## 6 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025, Guide 25 or EN 45001:

<b>USA</b>	FCC, NVLAP, UL
<b>Germany</b>	TUV Rheinland
<b>Japan</b>	VCCI
<b>New Zealand</b>	MoC
<b>Norway</b>	NEMKO
<b>Canada</b>	INDUSTRY CANADA
<b>R.O.C.</b>	CNLA, BSMI

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

[www.adt.com.tw/index.5/phtml](http://www.adt.com.tw/index.5/phtml). If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab:**

Tel: 886-2-26052180

Fax: 886-2-26052943

**Hsin Chu EMC/RF Lab:**

Tel: 886-3-5935343

Fax: 886-3-5935342

**Hwa Ya EMC/RF/Safety Lab:**

Tel: 886-3-3185781

Fax: 886-3-3185050

**Linko RF & Telecom Lab.**

Tel: 886-3-3270910

Fax: 886-3-3270892

**Email:** [service@mail.adt.com.tw](mailto:service@mail.adt.com.tw)

**Web Site:** [www.adt.com.tw](http://www.adt.com.tw)

The address and road map of all our labs can be found in our web site also.