## Maximum Public Exposure to RF (MPE) CFR 15.247 (i), CFR 1.1310 (e)

The maximum exposure level to the public from the RF power of the EUT shall not exceed a power density,  $\mathbf{S}$  as per the respective limits in Table 1 below, at a distance, d, of 20 cm (Mobile condition) from the EUT.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
	Limits for General Po	opulation/Uncontrolled	Exposure	
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

## TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

f = frequency in MHz \* = Plane-wave equivalent power density

Therefore, for:

## MPE for 2400 MHz – 2483.5 MHz for BT:

Limit: 1.0 mW/cm<sup>2</sup> Peak Power (dBm) = 8.07 dBm (From UST rpt 18-0327) Peak Power (Watts) = 0.0064 W Gain of Transmit Antenna =  $3.2 dB_i$  =2.09, numeric(Highest Gain Antenna) d = Distance = 20 cm = 0.2 m

**S** = (PG/  $4\pi d^2$ ) = EIRP/4A = 0.0064(2.09)/4\* $\pi$ \*0.2\*0.2 = 0.0134/0.5030 = 0.0266 W/m<sup>2</sup> = (0.0266 W/m<sup>2</sup>) (1m<sup>2</sup>/W) (0.1 mW/cm<sup>2</sup>) = 0.00266 mW/cm<sup>2</sup>

which is << less than S = 1.0 mW/cm<sup>2</sup>

RF Exposure Evaluation – IC

According to RSS-102, 2.5.2 Exemption Limits for Routine Evaluation

At or above 300 MHz and below 6 GHz and the source based time averaged maximum EIRP of the device is equal to or less than  $1.31 \times 10^{-2} \times f^{0.6834}$  in Watts (adjusted for tune up tolerance where applicable), where f= frequency in MHz

For 2.4 GHz Band:

Limit=  $1.31 \times 10^{-2} \times 2440^{0.6834} = 2.7$  Watts

Max EIRP for WiFi = 8.0 dBm + 3.2 dB = 11.2 dBm = 13.2 mW << 2700 mW