



FCC Test Report

APPLICANT : Palm, Inc.
EQUIPMENT : Phone
BRAND NAME : Palm
MODEL NAME : P100UNA
FCC ID : O8F-CASG
STANDARD : 47 CFR Part 2, 22(H), 24(E)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)
Tx/Rx FREQUENCY RANGE : GSM850 : 824.2 ~ 848.8 MHz /
869.2 ~ 893.8 MHz
GSM1900 : 1850.2 ~ 1909.8 MHz /
1930.2 ~ 1989.8 MHz
WCDMA Band V : 826.4 ~ 846.6 MHz /
871.4 ~ 891.6 MHz
WCDMA Band II : 1852.4 ~ 1907.6 MHz /
1932.4 ~ 1987.6 MHz
MAX. ERP/EIRP POWER : GSM850 (GPRS 8) : 1.11 W
GSM850 (EDGE 8) : 0.32 W
GSM1900 (GSM) : 1.35 W
GSM1900 (EDGE 8) : 0.68 W
WCDMA Band V (WCDMA) : 0.14 W
WCDMA Band II (HSDPA) : 0.28 W
EMISSION DESIGNATOR : GSM : 248KGXW
EDGE : 248KG7W
WCDMA : 4M20F9W

The product sample received on Oct. 23, 2008 and completely tested on Aug. 24, 2009. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.4-2003 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:

Roy Wu / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant.....	5
1.2 Manufacturer	5
1.3 Feature of Equipment Under Test.....	6
1.4 Testing Site.....	8
1.5 Applied Standards	8
1.6 Ancillary Equipment List.....	8
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	9
2.1 Test Mode.....	9
2.2 Connection Diagram of Test System	10
3 TEST RESULT	11
3.1 Conducted Output Power Measurement.....	11
3.2 Effective Radiated Power and Effective Isotropic Radiated Power Measurement	14
3.3 Occupied Bandwidth Measurement	20
3.4 Band Edge Measurement.....	39
3.5 Conducted Emission Measurement	46
3.6 Field Strength of Spurious Radiation Measurement	62
3.7 Frequency Stability Measurement.....	104
4 LIST OF MEASURING EQUIPMENT	108
5 UNCERTAINTY OF EVALUATION	109
6 CERTIFICATION OF TAF ACCREDITATION	110
APPENDIX A. PHOTOGRAPHS OF EUT	
APPENDIX B. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG8O2323-06	Rev. 01	Initial issue of report	Aug. 25, 2009

SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result
3.1	§2.1046	N/A	Conducted Output Power	N/A	PASS
3.2	§22.913(a)(2)	RSS-132(4.4) SRSP-503(5.1.3)	Effective Radiated Power	< 7 Watts for FCC (<6.3 Watts for IC)	PASS
3.2	§24.232(c)	RSS-133 (6.4) SRSP-510(5.1.2)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS
3.3	§2.1049 §22.917(a) §24.238(a)	N/A	Occupied Bandwidth	N/A	PASS
3.4	§2.1051 §22.917(a) §24.238(a)	RSS-132 (4.5.1) RSS-133 (6.5.1)	Band Edge Measurement	< 43+10log ₁₀ (P[Watts])	PASS
3.5	§2.1051 §22.917(a) §24.238(a)	RSS-132 (4.5.1) RSS-133 (6.5.1)	Conducted Emission	< 43+10log ₁₀ (P[Watts])	PASS
3.6	§2.1053 §22.917(a) §24.238(a)	RSS-132 (4.5.1) RSS-133 (6.5.1)	Field Strength of Spurious Radiation	< 43+10log ₁₀ (P[Watts])	PASS
3.7	§2.1055 §22.355 §24.235	RSS-132(4.3) RSS-133(6.3)	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS



1 General Description

1.1 Applicant

Palm, Inc.

950 W Maude Avenue, Sunnyvale, CA 94085

1.2 Manufacturer

Palm, Inc.

950 W Maude Avenue, Sunnyvale, CA 94085



1.3 Feature of Equipment Under Test

Product Feature & Specification	
Equipment	Phone
Brand Name	Palm
Model Name	P100UNA
FCC ID	O8F-CASG
Tx Frequency	GSM850 : 824 MHz ~ 849 MHz GSM1900 : 1850 MHz ~ 1910 MHz WCDMA Band V : 824 MHz ~ 849 MHz WCDMA Band II : 1850 MHz ~ 1910 MHz
Rx Frequency	GSM850 : 869 MHz ~ 894 MHz GSM1900 : 1930 MHz ~ 1990 MHz WCDMA Band V : 869 MHz ~ 894 MHz WCDMA Band II : 1930 MHz ~ 1990 MHz
Maximum Output Power to Antenna	GSM850 : 32.87 dBm GSM1900 : 29.69 dBm WCDMA Band V : 23.18 dBm WCDMA Band II : 23.45 dBm
Maximum ERP/EIRP	GSM850 (GPRS 8) : 1.11 W (30.44 dBm) GSM850 (EDGE 8) : 0.32 W (24.99 dBm) GSM1900 (GSM) : 1.35 W (31.30 dBm) GSM1900 (EDGE 8) : 0.68 W (28.35 dBm) WCDMA Band V (WCDMA) : 0.14 W (21.41 dBm) WCDMA Band II (HSDPA) : 0.28 W (24.54 dBm)
Antenna Type	Monopole antenna
Type of Modulation	GSM / GPRS : GMSK EDGE : 8PSK WCDMA : QPSK HSDPA : QPSK / 16QAM
Type of Emission	GSM : 248KGXW EDGE : 248KG7W WCDMA : 4M20F9W
EUT Stage	Identical Prototype

Remark:

1. For other wireless features of this EUT, the test report will be issued separately.
2. This test report recorded only product characteristics and test results of PCS Licensed Transmitter Held to Ear (PCE).

List of Accessory:

Specification of Accessory		
AC Adapter 1	Brand Name	Palm
	Part Number	157-10108-00
	Power Rating	I/P:100-240Vac, 50-60Hz, 0.2A; O/P: 5Vdc, 1000mA
AC Adapter 2	Brand Name	Palm
	Part Number	157-10124-00
	Power Rating	I/P:100-240Vac, 50-60Hz, 0.2A; O/P: 5Vdc, 1000mA
Inductive Charger	Brand Name	Palm
	Part Number	157-10123-00
	Power Rating	I/P: 5Vdc, 1000mA
Inductive back cover	Brand Name	Palm
	Part Number	180-10704-00
Battery	Brand Name	Palm
	Type Number	157-10119-00
	Power Rating	3.7Vdc, 1150mAh
	Type	Li-ion
Earphone	Brand Name	Palm
	Part Number	180-10632-00
	Signal Line Type	1.2 meter non-shielded cable without ferrite core
USB Cable	Brand Name	Palm
	Part Number	180-10646-00
	Signal Line Type	1.5 meter shielded cable without ferrite core

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. For accessories equipped with this EUT, please refer to the appendix of the external photo.

1.4 Testing Site

Test Site	SPORTON INTERNATIONAL INC.		
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978		
Test Site No.	Sporton Site No.		FCC/IC Registration No.
	TH02-HY	03CH07-HY	TW1022/4086B-1

1.5 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ Preliminary Guidance for Receiving Applications for Certification of 3G Device. May 9, 2006.
- ♦ 47 CFR Part 2, 22(H), 24(E)
- ♦ ANSI C63.4-2003
- ♦ ANSI / TIA / EIA-603-C-2004
- ♦ IC RSS-132 Issue 2
- ♦ IC RSS-133 Issue 5

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B (DoC), recorded in a separate test report.

1.6 Ancillary Equipment List

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU200	N/A	N/A	Unshielded, 1.8 m

2 Test Configuration of Equipment Under Test

2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.

Frequency range investigated for radiated emission is as follows:

1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V.
2. 30MHz to 19000 MHz for GSM1900 and WCDMA Band II.


Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	■ GPRS 8 Link ■ EDGE 8 Link ■ GPRS 8 Link + BT Ch39 ■ GPRS 8 Link + 802.11b Ch11	■ GPRS 8 Link ■ EDGE 8 Link
GSM 1900	■ GSM Link ■ EDGE 8 Link	■ GSM Link ■ EDGE 8 Link
WCDMA Band V	■ WCDMA Link	■ WCDMA Link
WCDMA Band II	■ HSDPA Link	■ HSDPA Link

Note: The maximum power levels are GPRS multi-slot class 8 mode (GSM850) and GSM mode (GSM1900) for GMSK, EDGE multi-slot class 8 mode (GSM850 and GSM1900) for 8PSK, WCDMA mode (WCDMA Band V) and HSDPA mode (WCDMA Band II) for QPSK, only these modes were used for all tests. The power tables are listed as follows:

Conducted Power (dBm)						
Mode	Band Channel	GSM 850			GSM 1900	
		128	189	251	512	810
GSM		32.86	32.80	32.73	29.69	29.61
GPRS 8		32.87	32.79	32.73	29.62	29.56
GPRS 10		29.81	29.73	29.64	29.60	29.51
GPRS 12		27.33	27.22	27.11	28.07	27.95
EGPRS 8		27.42	27.34	27.19	26.26	26.12
EGPRS 10		27.38	27.32	27.19	26.24	26.14
EGPRS 12		26.92	26.80	26.72	26.14	26.05

Conducted Power (dBm)							
Mode	Band	WCDMA Band V			WCDMA Band II		
	Channel	4132	4182	4233	9262	9400	9538
RMC 12.2K		22.63	22.97	23.18	23.41	23.16	22.86
HSDPA	Subtest-1	22.63	22.95	23.14	23.17	22.94	22.80
	Subtest-2	22.58	23.02	23.11	23.45	22.95	22.59
	Subtest-3	22.37	22.68	22.78	23.10	22.89	22.65
	Subtest-4	22.28	22.66	22.86	22.93	22.51	22.12

2.2 Connection Diagram of Test System



3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to base station.
2. Set EUT at maximum power through base station.
3. Select lowest, middle, and highest channels for each band and different modulation.

3.1.4 Test Setup





3.1.5 Test Result of Conducted Output Power

Cellular Band					
Modes		Channel	Frequency (MHz)	Conducted Power	
				(dBm)	(Watts)
GPRS 8		128 (Low)	824.2	32.87	1.94
		189 (Mid)	836.4	32.79	1.90
		251 (High)	848.8	32.73	1.87
EDGE 8		128 (Low)	824.2	27.42	0.55
		189 (Mid)	836.4	27.34	0.54
		251 (High)	848.8	27.19	0.52
WCDMA Band V	12.2k bps	4132 (Low)	826.4	22.63	0.18
		4182 (Mid)	836.4	22.97	0.20
		4233 (High)	846.6	23.18	0.21
	HSDPA Subtest-1	4132 (Low)	826.4	22.63	0.18
		4182 (Mid)	836.4	22.95	0.20
		4233 (High)	846.6	23.14	0.21
	HSDPA Subtest-2	4132 (Low)	826.4	22.58	0.18
		4182 (Mid)	836.4	23.02	0.20
		4233 (High)	846.6	23.11	0.20
	HSDPA Subtest-3	4132 (Low)	826.4	22.37	0.17
		4182 (Mid)	836.4	22.68	0.19
		4233 (High)	846.6	22.78	0.19
	HSDPA Subtest-4	4132 (Low)	826.4	22.28	0.18
		4182 (Mid)	836.4	22.66	0.18
		4233 (High)	846.6	22.86	0.19



PCS Band					
Modes		Channel	Frequency (MHz)	Conducted Power	
				(dBm)	(Watts)
GSM		512 (Low)	1850.2	29.69	0.93
		661 (Mid)	1880.0	29.61	0.91
		810 (High)	1909.8	29.63	0.92
EDGE 8		512 (Low)	1850.2	26.26	0.42
		661 (Mid)	1880.0	26.12	0.41
		810 (High)	1909.8	26.15	0.41
WCDMA Band II	12.2k bps	9262 (Low)	1852.4	23.41	0.22
		9400 (Mid)	1880.0	23.16	0.21
		9538 (High)	1907.6	22.86	0.19
	HSDPA Subtest-1	9262 (Low)	1852.4	23.17	0.21
		9400 (Mid)	1880.0	22.94	0.20
		9538 (High)	1907.6	22.80	0.19
	HSDPA Subtest-2	9262 (Low)	1852.4	23.45	0.22
		9400 (Mid)	1880.0	22.95	0.20
		9538 (High)	1907.6	22.59	0.18
	HSDPA Subtest-3	9262 (Low)	1852.4	23.10	0.20
		9400 (Mid)	1880.0	22.89	0.19
		9538 (High)	1907.6	22.65	0.18
	HSDPA Subtest-4	9262 (Low)	1852.4	22.93	0.20
		9400 (Mid)	1880.0	22.51	0.18
		9538 (High)	1907.6	22.12	0.16

3.2 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

3.2.1 Description of the ERP/EIRP Measurement

ERP/EIRP is measured by substitution method according to ANSI / TIA / EIA-603-C-2004. The ERP of mobile transmitters must not exceed 7 Watts and the EIRP of mobile transmitters are limited to 2 Watts.


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The EUT was placed on a turntable with 1.0 meter height in a fully anechoic chamber.
2. The EUT was set at 1.2 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiated power.
4. The height of the receiving antenna is adjusted to look for the maximum ERP/EIRP.
5. Taking the record of maximum ERP/EIRP.
6. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
7. The conducted power at the terminal of the dipole antenna is measured.
8. Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna.
9. $ERP/EIRP = P_s + E_t - E_s + G_s = P_s + R_t - R_s + G_s$
 P_s (dBm) : Input power to substitution antenna.
 G_s (dBi or dBd) : Substitution antenna Gain.
 $E_t = R_t + AF$
 $E_s = R_s + AF$
 AF (dB/m) : Receive antenna factor
 R_t : The highest received signal in spectrum analyzer for EUT.
 R_s : The highest received signal in spectrum analyzer for substitution antenna.

3.2.4 Test Setup



3.2.5 Test Result of ERP

GSM850 (GPRS 8) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-31.02	-48.12	0.00	-1.08	16.02	0.04
836.40	-30.92	-48.28	0.00	-0.93	16.43	0.04
848.80	-30.65	-48.35	0.00	-0.76	16.94	0.05
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-17.51	-47.97	0.00	-1.08	29.38	0.87
836.40	-17.28	-48.01	0.00	-0.93	29.80	0.95
848.80	-16.85	-48.05	0.00	-0.76	30.44	1.11

GSM850 (EDGE 8) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-37.33	-48.12	0.00	-1.08	9.71	0.01
836.40	-37.29	-48.28	0.00	-0.93	10.06	0.01
848.80	-36.85	-48.35	0.00	-0.76	10.74	0.01
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-23.18	-47.97	0.00	-1.08	23.71	0.23
836.40	-22.84	-48.01	0.00	-0.93	24.24	0.27
848.80	-22.30	-48.05	0.00	-0.76	24.99	0.32



WCDMA Band V (WCDMA) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
826.40	-41.24	-48.12	0.00	-1.08	5.80	0.00
836.40	-40.25	-48.28	0.00	-0.93	7.10	0.01
846.60	-40.78	-48.35	0.00	-0.76	6.81	0.00
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
826.40	-26.76	-47.97	0.00	-1.08	20.13	0.10
836.40	-25.67	-48.01	0.00	-0.93	21.41	0.14
846.60	-26.01	-48.05	0.00	-0.76	21.28	0.13

3.2.6 Test Result of EIRP

GSM1900 (GSM) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-26.55	-51.88	0.00	1.96	27.29	0.54
1880.00	-27.23	-52.99	0.00	2.00	27.76	0.60
1909.80	-28.24	-54.28	0.00	1.98	28.02	0.63
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-23.00	-52.13	0.00	1.96	31.09	1.29
1880.00	-23.87	-53.17	0.00	2.00	31.30	1.35
1909.80	-24.92	-54.13	0.00	1.98	31.19	1.32

GSM1900 (EDGE 8) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-29.59	-51.88	0.00	1.96	24.25	0.27
1880.00	-30.83	-52.99	0.00	2.00	24.16	0.26
1909.80	-31.73	-54.28	0.00	1.98	24.53	0.28
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-26.32	-52.13	0.00	1.96	27.77	0.60
1880.00	-26.82	-53.17	0.00	2.00	28.35	0.68
1909.80	-27.79	-54.13	0.00	1.98	28.32	0.68



WCDMA Band II (HSDPA) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1852.40	-32.82	-51.88	0.00	1.96	21.02	0.13
1880.00	-35.77	-52.99	0.00	2.00	19.22	0.08
1907.60	-36.49	-54.28	0.00	1.98	19.77	0.09
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1852.40	-29.55	-52.13	0.00	1.96	24.54	0.28
1880.00	-31.63	-53.17	0.00	2.00	23.54	0.23
1907.60	-32.78	-54.13	0.00	1.98	23.33	0.22

3.3 Occupied Bandwidth Measurement

3.3.1 Description of Occupied Bandwidth Measurement

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The 99% and 26 dB occupied bandwidth (BW) of the middle channel for the highest RF powers were measured.
3. The RBW was replaced by 10 kHz, due to the spectrum analyzer IF-Filter including an excess of the limit. A worst case correction factor of $10 \log (1\% \text{ BW/measurement RBW})$ was implemented.

3.3.4 Test Setup






3.3.5 Test Result (Plots) of Occupied Bandwidth


Band :	GSM 850	Power Stage :	High
Test Mode :	GPRS 8 Link		

99% Occupied Bandwidth Plot on Channel 128



Date: 17.APR.2009 18:51:44


26dB Bandwidth Plot on Channel 128



Date: 17.APR.2009 18:50:39




99% Occupied Bandwidth Plot on Channel 189



Date: 17.APR.2009 18:52:32


26dB Bandwidth Plot on Channel 189



Date: 17.APR.2009 18:50:04




99% Occupied Bandwidth Plot on Channel 251



Date: 17.APR.2009 18:53:10

26dB Bandwidth Plot on Channel 251




Date: 17.APR.2009 18:49:22




Band :	GSM 850	Power Stage :	High
Test Mode :	EDGE 8 Link		

99% Occupied Bandwidth Plot on Channel 128



Date: 17.APR.2009 23:48:25


26dB Bandwidth Plot on Channel 128



Date: 17.APR.2009 23:45:44




99% Occupied Bandwidth Plot on Channel 189



Date: 17.APR.2009 23:47:58


26dB Bandwidth Plot on Channel 189



Date: 17.APR.2009 23:46:18




99% Occupied Bandwidth Plot on Channel 251



Date: 17.APR.2009 23:47:21

26dB Bandwidth Plot on Channel 251




Date: 17.APR.2009 23:46:46




Band :	GSM 1900	Power Stage :	High
Test Mode :	GSM Link		

99% Occupied Bandwidth Plot on Channel 512



Date: 17.APR.2009 20:14:40


26dB Bandwidth Plot on Channel 512



Date: 17.APR.2009 20:11:25




99% Occupied Bandwidth Plot on Channel 661



Date: 17.APR.2009 20:14:00


26dB Bandwidth Plot on Channel 661



Date: 17.APR.2009 20:12:02




99% Occupied Bandwidth Plot on Channel 810



Date: 17.APR.2009 20:13:14

26dB Bandwidth Plot on Channel 810




Date: 17.APR.2009 20:12:36




Band :	GSM 1900	Power Stage :	High
Test Mode :	EDGE 8 Link		

99% Occupied Bandwidth Plot on Channel 512



Date: 17.APR.2009 23:05:01


26dB Bandwidth Plot on Channel 512



Date: 17.APR.2009 23:02:04




99% Occupied Bandwidth Plot on Channel 661



Date: 17.APR.2009 23:04:26


26dB Bandwidth Plot on Channel 661



Date: 17.APR.2009 23:02:38




99% Occupied Bandwidth Plot on Channel 810



Date: 17.APR.2009 23:03:58

26dB Bandwidth Plot on Channel 810




Date: 17.APR.2009 23:03:16




Band :	WCDMA Band V	Power Stage :	High
Test Mode :	WCDMA Link		

99% Occupied Bandwidth Plot on Channel 4132



Date: 17.APR.2009 21:40:12


26dB Bandwidth Plot on Channel 4132



Date: 17.APR.2009 21:38:21




99% Occupied Bandwidth Plot on Channel 4182



Date: 17.APR.2009 21:40:45


26dB Bandwidth Plot on Channel 4182



Date: 17.APR.2009 21:38:50




99% Occupied Bandwidth Plot on Channel 4233



Date: 17.APR.2009 21:41:13

26dB Bandwidth Plot on Channel 4233




Date: 17.APR.2009 21:39:22




Band :	WCDMA Band II	Power Stage :	High
Test Mode :	HSDPA Link		

99% Occupied Bandwidth Plot on Channel 9262



Date: 17.APR.2009 20:56:31


26dB Bandwidth Plot on Channel 9262



Date: 17.APR.2009 20:53:59




99% Occupied Bandwidth Plot on Channel 9400



Date: 17.APR.2009 20:56:04


26dB Bandwidth Plot on Channel 9400



Date: 17.APR.2009 20:54:30




99% Occupied Bandwidth Plot on Channel 9538



Date: 17.APR.2009 20:55:32

26dB Bandwidth Plot on Channel 9538



Date: 17.APR.2009 20:55:03

3.4 Band Edge Measurement

3.4.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

3.4.2 Measuring Instruments


See list of measuring instruments of this test report.

3.4.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The band edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly BW/100.

3.4.4 Test Setup

<Conducted Band Edge >






3.4.5 Test Result (Plots) of Conducted Band Edge


Band :	GSM850	Power Stage :	High
Test Mode :	GPRS 8 Link		

Lower Band Edge Plot on Channel 128



Date: 17.APR.2009 19:25:57

Higher Band Edge Plot on Channel 251




Date: 17.APR.2009 19:30:04




Band :	GSM850	Power Stage :	High
Test Mode :	EDGE 8 Link		

Lower Band Edge Plot on Channel 128



Date: 17.APR.2009 23:50:35

Higher Band Edge Plot on Channel 251




Date: 17.APR.2009 23:54:06




Band :	GSM1900	Power Stage :	High
Test Mode :	GSM Link		

Lower Band Edge Plot on Channel 512



Date: 17.APR.2009 20:17:42

Higher Band Edge Plot on Channel 810




Date: 17.APR.2009 20:21:57




Band :	GSM1900	Power Stage :	High
Test Mode :	EDGE 8 Link		

Lower Band Edge Plot on Channel 512



Date: 17.APR.2009 23:10:58

Higher Band Edge Plot on Channel 810




Date: 17.APR.2009 23:09:55




Band :	WCDMA Band V	Power Stage :	High
Test Mode :	WCDMA Link		

Lower Band Edge Plot on Channel 4132



Date: 17.APR.2009 21:43:04


Higher Band Edge Plot on Channel 4233




Date: 17.APR.2009 22:26:35



Band :	WCDMA Band II	Power Stage :	High
Test Mode :	HSDPA Link		

Lower Band Edge Plot on Channel 9262

Date: 17.APR.2009 21:01:44

Higher Band Edge Plot on Channel 9538

Date: 17.APR.2009 21:05:35

3.5 Conducted Emission Measurement

3.5.1 Description of Conducted Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.


3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Test Procedures


1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The middle channel for the highest RF power within the transmitting frequency was measured.
3. The conducted spurious emission for the whole frequency range was taken.

3.5.4 Test Setup




3.5.5 Test Result (Plots) of Conducted Emission

Band :	GSM850	Channel :	CH189
Test Mode :	GPRS 8 Link		


Conducted Emission Plot between 30M ~ 1GHz


Date: 17.APR.2009 19:39:59

Conducted Emission Plot between 1GHz ~ 3GHz



Date: 17.APR.2009 19:44:09

Conducted Emission Plot between 3GHz ~ 7GHz



Date: 17.APR.2009 19:46:08

Conducted Emission Plot between 7GHz ~ 9GHz




Date: 17.APR.2009 19:47:04




Band :	GSM850	Channel :	CH189
Test Mode :	EDGE 8 Link		

Conducted Emission Plot between 30M ~ 1GHz



Date: 17.APR.2009 23:41:00


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 17.APR.2009 23:42:19




Conducted Emission Plot between 3GHz ~ 7GHz



Date: 17.APR.2009 23:43:11

Conducted Emission Plot between 7GHz ~ 9GHz




Date: 17.APR.2009 23:43:53




Band :	GSM1900	Channel :	CH661
Test Mode :	GSM Link		

Conducted Emission Plot between 30M ~ 1GHz



Date: 17.APR.2009 20:02:10


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 17.APR.2009 20:03:55




Conducted Emission Plot between 3G ~ 7GHz



Date: 17.APR.2009 20:04:52


Conducted Emission Plot between 7G ~ 13.6G



Date: 17.APR.2009 23:28:36



Conducted Emission Plot between 13.6GH ~ 19.1GHz




Date: 17.APR.2009 20:09:13




Band :	GSM1900	Channel :	CH661
Test Mode :	EDGE 8 Link		

Conducted Emission Plot between 30M ~ 1GHz



Date: 17.APR.2009 23:17:50


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 17.APR.2009 23:20:44




Conducted Emission Plot between 3GHz ~ 7GHz



Date: 17.APR.2009 23:21:48


Conducted Emission Plot between 7GHz ~ 13.6GHz



Date: 17.APR.2009 23:25:15



Conducted Emission Plot between 13.6GHz ~ 19.1GHz




Date: 17.APR.2009 23:25:54




Band :	WCDMA Band V	Channel :	CH4182
Test Mode :	WCDMA Link		

Conducted Emission Plot between 30M ~ 1GHz



Date: 17.APR.2009 22:41:02


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 17.APR.2009 22:35:09




Conducted Emission Plot between 3GHz ~ 7GHz



Date: 17.APR.2009 21:33:20

Conducted Emission Plot between 7GHz ~ 9GHz




Date: 17.APR.2009 21:34:01




Band :	WCDMA Band II	Channel :	CH9400
Test Mode :	HSDPA Link		

Conducted Emission Plot between 30M ~ 1GHz



Date: 17.APR.2009 21:12:58


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 17.APR.2009 22:46:44




Conducted Emission Plot between 3GH ~ 7GHz



Date: 17.APR.2009 21:20:37


Conducted Emission Plot between 7GHz ~ 13.6GHz



Date: 17.APR.2009 23:31:23



Conducted Emission Plot between 13.6GHz ~ 19.1GHz



Date: 17.APR.2009 21:22:12

3.6 Field Strength of Spurious Radiation Measurement

3.6.1 Description of Field Strength of Spurious Radiated Measurement

The radiated spurious emission was measured by substitution method according to ANSI / TIA / EIA-603-C-2004. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.


3.6.2 Measuring Instruments

See list of measuring instruments of this test report.

3.6.3 Test Procedures


1. The EUT was placed on a rotatable wooden table with 0.8 meter about ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. Emission level (dBm) = output power + substitution Gain.

3.6.4 Test Setup



3.6.5 Test Result of Field Strength of Spurious Radiated


Band :	GSM850	Temperature :	22~24°C
Test Mode :	GPRS 8 Link Ch128	Relative Humidity :	42~45%
Test Engineer :	Elvis Chen	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1645	-40.83	-13	-27.83	-49.52	-41.01	3.1	5.43	H	Pass
2470	-44.07	-13	-31.07	-51.38	-44.06	3.89	6.03	H	Pass
3298	-29.37	-13	-16.37	-38.24	-30.93	4.16	7.87	H	Pass
4115	-41.44	-13	-28.44	-52.62	-43.41	4.88	9.00	H	Pass
4935	-42.36	-13	-29.36	-55.74	-44.75	5.09	9.63	H	Pass
5770	-46.21	-13	-33.21	-61.68	-48.92	5.54	10.40	H	Pass
6590	-40.14	-13	-27.14	-58.8	-43.19	5.88	11.08	H	Pass
7415	-31.58	-13	-18.58	-52.64	-35.34	6.17	12.08	H	Pass
8250	-31.15	-13	-18.15	-52.53	-34.74	7.16	12.90	H	Pass




Band :	GSM850	Temperature :	22~24°C
Test Mode :	GPRS 8 Link Ch128	Relative Humidity :	42~45%
Test Engineer :	Elvis Chen	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1645	-42.44	-13	-29.44	-49.55	-42.62	3.1	5.43	V	Pass
2470	-47.87	-13	-34.87	-57.28	-47.86	3.89	6.03	V	Pass
3298	-31.64	-13	-18.64	-43.43	-33.2	4.16	7.87	V	Pass
4115	-41.15	-13	-28.15	-54.16	-43.12	4.88	9.00	V	Pass
4935	-48.97	-13	-35.97	-60.75	-51.36	5.09	9.63	V	Pass
5770	-52.37	-13	-39.37	-65.73	-55.08	5.54	10.40	V	Pass
6590	-45.93	-13	-32.93	-62.17	-48.98	5.88	11.08	V	Pass
7415	-32.68	-13	-19.68	-52.7	-36.44	6.17	12.08	V	Pass
8250	-32.03	-13	-19.03	-53.4	-35.62	7.16	12.90	V	Pass




Band :	GSM850	Temperature :	22~24°C
Test Mode :	GPRS 8 Link Ch189	Relative Humidity :	42~45%
Test Engineer :	Elvis Chen	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1669	-46.16	-13	-33.16	-54.36	-46.01	3.39	5.39	H	Pass
2509	-43.80	-13	-30.80	-51.71	-44.06	3.71	6.12	H	Pass
3346	-29.21	-13	-16.21	-39.16	-31.93	3.13	8.00	H	Pass
4175	-40.57	-13	-27.57	-53.9	-44.41	3.01	9.00	H	Pass
5015	-45.78	-13	-32.78	-60.18	-50.75	2.61	9.73	H	Pass
5850	-43.58	-13	-30.58	-60.3	-47.45	4.38	10.40	H	Pass
6690	-42.50	-13	-29.50	-61.41	-46.28	5.22	11.15	H	Pass
7530	-29.49	-13	-16.49	-50.9	-33.34	6.22	12.22	H	Pass
8370	-30.44	-13	-17.44	-52.63	-35.74	5.59	13.04	H	Pass




Band :	GSM850	Temperature :	22~24°C
Test Mode :	GPRS 8 Link Ch189	Relative Humidity :	42~45%
Test Engineer :	Elvis Chen	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1669	-41.77	-13	-28.77	-49.1	-41.62	3.39	5.39	V	Pass
2509	-41.60	-13	-28.60	-52.64	-41.86	3.71	6.12	V	Pass
3346	-28.48	-13	-15.48	-41.73	-31.20	3.13	8.00	V	Pass
4175	-45.28	-13	-32.28	-58.54	-49.12	3.01	9.00	V	Pass
5015	-48.84	-13	-35.84	-62.84	-53.81	2.61	9.73	V	Pass
5850	-47.92	-13	-34.92	-62.44	-51.79	4.38	10.40	V	Pass
6690	-42.04	-13	-29.04	-63.26	-45.82	5.22	11.15	V	Pass
7530	-25.59	-13	-12.59	-46.54	-29.44	6.22	12.22	V	Pass
8370	-27.32	-13	-14.32	-50.29	-32.62	5.59	13.04	V	Pass




Band :	GSM850	Temperature :	22~24°C
Test Mode :	GPRS 8 Link Ch251	Relative Humidity :	42~45%
Test Engineer :	Elvis Chen	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1693	-46.83	-13	-33.83	-54.56	-47.01	3.02	5.35	H	Pass
2545	-41.75	-13	-28.75	-50.33	-42.06	3.73	6.19	H	Pass
3394	-34.94	-13	-21.94	-44.61	-36.93	3.98	8.12	H	Pass
4235	-43.40	-13	-30.40	-54.3	-45.41	4.84	9.00	H	Pass
5090	-52.33	-13	-39.33	-63.63	-54.64	5.36	9.82	H	Pass
5935	-44.03	-13	-31.03	-59.33	-46.45	5.83	10.40	H	Pass
6790	-45.33	-13	-32.33	-63.85	-48.45	5.96	11.23	H	Pass
7635	-30.60	-13	-17.60	-51.96	-34.34	6.42	12.31	H	Pass
8490	-33.78	-13	-20.78	-52.7	-35.74	9.07	13.18	H	Pass




Band :	GSM850	Temperature :	22~24°C
Test Mode :	GPRS 8 Link Ch251	Relative Humidity :	42~45%
Test Engineer :	Elvis Chen	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1693	-46.44	-13	-33.44	-52.84	-46.62	3.02	5.35	V	Pass
2545	-42.55	-13	-29.55	-53.66	-42.86	3.73	6.19	V	Pass
3397	-31.21	-13	-18.21	-43.58	-33.2	3.98	8.12	V	Pass
4235	-47.11	-13	-34.11	-58.71	-49.12	4.84	9.00	V	Pass
5090	-51.91	-13	-38.91	-63.25	-54.22	5.36	9.82	V	Pass
5935	-48.60	-13	-35.60	-61.67	-51.02	5.83	10.40	V	Pass
6790	-46.43	-13	-33.43	-62.74	-49.55	5.96	11.23	V	Pass
7635	-25.70	-13	-12.70	-46.54	-29.44	6.42	12.31	V	Pass
8490	-29.66	-13	-16.66	-49.23	-31.62	9.07	13.18	V	Pass




Band :	GSM850	Temperature :	22~24°C
Test Mode :	EDGE 8 Link Ch128	Relative Humidity :	42~45%
Test Engineer :	Elvis Chen	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1645	-42.83	-13	-29.83	-51.41	-43.01	3.1	5.43	H	Pass
2470	-50.07	-13	-37.07	-56.33	-50.06	3.89	6.03	H	Pass
3298	-32.37	-13	-19.37	-41.75	-33.93	4.16	7.87	H	Pass
4115	-43.44	-13	-30.44	-54.48	-45.41	4.88	9.00	H	Pass
4935	-43.36	-13	-30.36	-56.25	-45.75	5.09	9.63	H	Pass
5770	-46.28	-13	-33.28	-61.75	-48.99	5.54	10.40	H	Pass
6590	-44.10	-13	-31.10	-62.28	-47.15	5.88	11.08	H	Pass
7415	-34.58	-13	-21.58	-55.08	-38.34	6.17	12.08	H	Pass
8250	-36.15	-13	-23.15	-56.76	-39.74	7.16	12.90	H	Pass




Band :	GSM850	Temperature :	22~24°C
Test Mode :	EDGE 8 Link Ch128	Relative Humidity :	42~45%
Test Engineer :	Elvis Chen	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1645	-52.44	-13	-39.44	-57.46	-52.62	3.1	5.43	V	Pass
2470	-43.87	-13	-30.87	-54.35	-43.86	3.89	6.03	V	Pass
3298	-34.64	-13	-21.64	-46.34	-36.2	4.16	7.87	V	Pass
4115	-45.15	-13	-32.15	-57.56	-47.12	4.88	9.00	V	Pass
7415	-35.05	-13	-22.05	-53.5	-37.44	5.09	9.63	V	Pass
8250	-42.91	-13	-29.91	-60.36	-45.62	5.54	10.40	V	Pass




Band :	GSM850	Temperature :	22~24°C
Test Mode :	EDGE 8 Link Ch189	Relative Humidity :	42~45%
Test Engineer :	Elvis Chen	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1669	-52.16	-13	-39.16	-58.53	-52.01	3.39	5.39	H	Pass
2509	-45.80	-13	-32.80	-53.85	-46.06	3.71	6.12	H	Pass
3346	-34.21	-13	-21.21	-44.7	-36.93	3.13	8.00	H	Pass
4175	-48.65	-13	-35.65	-59.87	-52.49	3.01	9.00	H	Pass
5015	-49.12	-13	-36.12	-63.08	-54.09	2.61	9.73	H	Pass
5850	-47.58	-13	-34.58	-64.21	-51.45	4.38	10.40	H	Pass
6690	-45.21	-13	-32.21	-64.12	-48.99	5.22	11.15	H	Pass
7530	-32.49	-13	-19.49	-53.15	-36.34	6.22	12.22	H	Pass
8370	-35.44	-13	-22.44	-57.23	-40.74	5.59	13.04	H	Pass




Band :	GSM850	Temperature :	22~24°C
Test Mode :	EDGE 8 Link Ch189	Relative Humidity :	42~45%
Test Engineer :	Elvis Chen	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1669	-48.77	-13	-35.77	-54.01	-48.62	3.39	5.39	V	Pass
2509	-44.60	-13	-31.60	-55.24	-44.86	3.71	6.12	V	Pass
3346	-34.48	-13	-21.48	-47.47	-37.2	3.13	8.00	V	Pass
4175	-46.28	-13	-33.28	-59.8	-50.12	3.01	9.00	V	Pass
7530	-30.47	-13	-17.47	-51.89	-35.44	2.61	9.73	V	Pass
8370	-35.75	-13	-22.75	-56.23	-39.62	4.38	10.40	V	Pass




Band :	GSM850	Temperature :	22~24°C
Test Mode :	EDGE 8 Link Ch251	Relative Humidity :	42~45%
Test Engineer :	Elvis Chen	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1693	-53.83	-13	-40.83	-59.83	-54.01	3.02	5.35	H	Pass
2545	-46.75	-13	-33.75	-54.68	-47.06	3.73	6.19	H	Pass
3394	-38.94	-13	-25.94	-47.51	-40.93	3.98	8.12	H	Pass
4235	-48.40	-13	-35.40	-58.16	-50.41	4.84	9.00	H	Pass
5935	-48.47	-13	-35.47	-63.54	-50.78	5.36	9.82	H	Pass
6790	-47.99	-13	-34.99	-65.54	-50.41	5.83	10.40	H	Pass
7635	-35.22	-13	-22.22	-54.75	-38.34	5.96	11.23	H	Pass
8490	-33.00	-13	-20.00	-54.04	-36.74	6.42	12.31	H	Pass




Band :	GSM850	Temperature :	22~24°C
Test Mode :	EDGE 8 Link Ch251	Relative Humidity :	42~45%
Test Engineer :	Elvis Chen	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1693	-51.44	-13	-38.44	-57.04	-51.62	3.02	5.35	V	Pass
2545	-44.55	-13	-31.55	-55.14	-44.86	3.73	6.19	V	Pass
3397	-36.21	-13	-23.21	-48.7	-38.2	3.98	8.12	V	Pass
4235	-51.69	-13	-38.69	-62.09	-53.7	4.84	9.00	V	Pass
7635	-32.13	-13	-19.13	-51.39	-34.44	5.36	9.82	V	Pass
8490	-37.20	-13	-24.20	-56.35	-39.62	5.83	10.40	V	Pass



Band :	GSM850	Temperature :	22~24°C
Test Mode :	GPRS 8 Link Ch128 + BT Ch39	Relative Humidity :	42~45%
Test Engineer :	Elvis Chen	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY
Condition : FCC PART22/24 HF-EIRP(080306) HORIZONTAL
Project : FG802323

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1669	-48.90	-13	-35.90	-56.07	-48.75	3.39	5.39	H	Pass
2509	-43.69	-13	-30.69	-51.39	-43.95	3.71	6.12	H	Pass
3346	-31.80	-13	-18.80	-41.93	-34.52	3.13	8.00	H	Pass
4175	-45.72	-13	-32.72	-57.34	-49.56	3.01	9.00	H	Pass
5015	-41.85	-13	-28.85	-57.18	-46.82	2.61	9.73	H	Pass
6690	-45.27	-13	-32.27	-63.92	-49.05	5.22	11.15	H	Pass
7530	-33.27	-13	-20.27	-53.9	-37.12	6.22	12.22	H	Pass
8370	-34.41	-13	-21.41	-56.4	-39.71	5.59	13.04	H	Pass




Band :	GSM850	Temperature :	22~24°C
Test Mode :	GPRS 8 Link Ch189 + BT Ch39	Relative Humidity :	42~45%
Test Engineer :	Elvis Chen	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1669	-42.63	-13	-29.63	-49.23	-42.48	3.39	5.39	V	Pass
2509	-43.46	-13	-30.46	-54.43	-43.72	3.71	6.12	V	Pass
3346	-32.79	-13	-19.79	-45.78	-35.51	3.13	8.00	V	Pass
4175	-45.09	-13	-32.09	-58.79	-48.93	3.01	9.00	V	Pass
5015	-48.70	-13	-35.70	-62.69	-53.67	2.61	9.73	V	Pass
6690	-42.68	-13	-29.68	-64.35	-46.46	5.22	11.15	V	Pass
7530	-26.73	-13	-13.73	-47.23	-30.58	6.22	12.22	V	Pass
8370	-33.17	-13	-20.17	-55.64	-38.47	5.59	13.04	V	Pass




Band :	GSM850	Temperature :	22~24°C
Test Mode :	GPRS 8 Link Ch189 + 11b Ch11	Relative Humidity :	42~45%
Test Engineer :	Elvis Chen	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1669	-48.17	-13	-35.17	-55.54	-48.02	3.39	5.39	H	Pass
2509	-43.60	-13	-30.60	-51.23	-43.86	3.71	6.12	H	Pass
3346	-32.93	-13	-19.93	-43.02	-35.65	3.13	8.00	H	Pass
4175	-44.65	-13	-31.65	-56.91	-48.49	3.01	9.00	H	Pass
5015	-43.34	-13	-30.34	-58.2	-48.31	2.61	9.73	H	Pass
5850	-45.71	-13	-32.71	-62.68	-49.58	4.38	10.40	H	Pass
6690	-42.64	-13	-29.64	-61.67	-46.42	5.22	11.15	H	Pass
7530	-30.81	-13	-17.81	-51.75	-34.66	6.22	12.22	H	Pass
8370	-37.21	-13	-24.21	-58.42	-42.51	5.59	13.04	H	Pass




Band :	GSM850	Temperature :	22~24°C
Test Mode :	GPRS 8 Link Ch189 + 11b Ch11	Relative Humidity :	42~45%
Test Engineer :	Elvis Chen	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1669	-40.89	-13	-27.89	-47.94	-40.74	3.39	5.39	V	Pass
2509	-43.50	-13	-30.50	-54.44	-43.76	3.71	6.12	V	Pass
3346	-32.47	-13	-19.47	-45.49	-35.19	3.13	8.00	V	Pass
4175	-42.31	-13	-29.31	-56.56	-46.15	3.01	9.00	V	Pass
5015	-49.12	-13	-36.12	-63.08	-54.09	2.61	9.73	V	Pass
5850	-48.93	-13	-35.93	-63.41	-52.8	4.38	10.40	V	Pass
6690	-44.14	-13	-31.14	-65.89	-47.92	5.22	11.15	V	Pass
7530	-29.04	-13	-16.04	-49.46	-32.89	6.22	12.22	V	Pass
8370	-32.49	-13	-19.49	-55.21	-37.79	5.59	13.04	V	Pass



Band :	GSM1900	Temperature :	22~24°C
Test Mode :	GSM Link Ch512	Relative Humidity :	42~45%
Test Engineer :	Elvis Chen	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY
Condition : FCC PART22/24 HF-EIRP(080306) HORIZONTAL
Project : FG 802323

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3696	-46.25	-13	-33.25	-60.6	-50.37	4.52	8.64	H	Pass
5552	-30.74	-13	-17.74	-53.64	-35.94	5.2	10.40	H	Pass
7396	-30.85	-13	-17.85	-56.47	-36.88	6.02	12.05	H	Pass
9248	-22.01	-13	-9.01	-49.98	-27.70	7.46	13.15	H	Pass
11092	-22.77	-13	-9.77	-58.43	-27.28	8.85	13.36	H	Pass
12948	-20.89	-13	-7.89	-54.75	-25.7	8.36	13.17	H	Pass
14804	-27.38	-13	-14.38	-58.49	-32.8	8.46	13.88	H	Pass
16650	-17.76	-13	-4.76	-53.8	-21.5	9.82	13.56	H	Pass




Band :	GSM1900	Temperature :	22~24°C
Test Mode :	GSM Link Ch512	Relative Humidity :	42~45%
Test Engineer :	Elvis Chen	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3696	-39.76	-13	-26.76	-57.65	-43.88	4.52	8.64	V	Pass
5552	-36.70	-13	-23.70	-58.01	-41.90	5.2	10.40	V	Pass
7396	-29.95	-13	-16.95	-54.60	-35.98	6.02	12.05	V	Pass
9248	-20.81	-13	-7.81	-50.87	-26.50	7.46	13.15	V	Pass
11092	-22.37	-13	-9.37	-58.38	-26.88	8.85	13.36	V	Pass
12948	-28.79	-13	-15.79	-59.41	-33.60	8.36	13.17	V	Pass
14804	-33.58	-13	-20.58	-60.84	-39.00	8.46	13.88	V	Pass
16650	-23.66	-13	-10.66	-58.57	-27.40	9.82	13.56	V	Pass




Band :	GSM1900	Temperature :	22~24°C
Test Mode :	GSM Link Ch661	Relative Humidity :	42~45%
Test Engineer :	Elvis Chen	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-40.69	-13	-27.69	-56.4	-45.37	4.03	8.71	H	Pass
5636	-32.41	-13	-19.41	-55.8	-38.94	3.87	10.40	H	Pass
7520	-26.49	-13	-13.49	-52.43	-32.88	5.83	12.22	H	Pass
9396	-25.54	-13	-12.54	-54.01	-32.70	6.02	13.18	H	Pass
11280	-20.47	-13	-7.47	-56.29	-25.28	8.48	13.29	H	Pass
13156	-21.41	-13	-8.41	-54.12	-26.7	8.13	13.42	H	Pass
15033	-32.76	-13	-19.76	-60.03	-37.8	8.78	13.82	H	Pass
16917	-18.21	-13	-5.21	-50.72	-19.7	12.33	13.82	H	Pass




Band :	GSM1900	Temperature :	22~24°C
Test Mode :	GSM Link Ch661	Relative Humidity :	42~45%
Test Engineer :	Elvis Chen	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-35.20	-13	-22.20	-54.29	-39.88	4.03	8.71	V	Pass
5636	-30.37	-13	-17.37	-54.15	-36.90	3.87	10.40	V	Pass
7520	-21.59	-13	-8.59	-47.73	-27.98	5.83	12.22	V	Pass
9396	-24.34	-13	-11.34	-56.06	-31.50	6.02	13.18	V	Pass
11280	-18.78	-13	-5.78	-54.99	-23.59	8.48	13.29	V	Pass
13156	-26.11	-13	-13.11	-58.61	-31.4	8.13	13.42	V	Pass
15033	-32.86	-13	-19.86	-60.99	-37.9	8.78	13.82	V	Pass
16917	-22.71	-13	-9.71	-57.64	-24.2	12.33	13.82	V	Pass




Band :	GSM1900	Temperature :	22~24°C
Test Mode :	GSM Link Ch810	Relative Humidity :	42~45%
Test Engineer :	Elvis Chen	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3812	-38.37	-13	-25.37	-54.29	-42.37	4.78	8.78	H	Pass
5728	-34.20	-13	-21.20	-55.92	-38.94	5.66	10.40	H	Pass
7636	-23.85	-13	-10.85	-50.69	-29.88	6.28	12.31	H	Pass
9552	-29.71	-13	-16.71	-56.41	-35.70	7.2	13.19	H	Pass
11456	-23.65	-13	-10.65	-58.93	-28.28	8.59	13.22	H	Pass
13364	-28.89	-13	-15.89	-59.23	-33.2	9.4	13.71	H	Pass
17190	-17.07	-13	-4.07	-56.34	-22.1	8.88	13.91	H	Pass




Band :	GSM1900	Temperature :	22~24°C
Test Mode :	GSM Link Ch810	Relative Humidity :	42~45%
Test Engineer :	Elvis Chen	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3812	-34.88	-13	-21.88	-53.36	-38.88	4.78	8.78	V	Pass
5728	-40.16	-13	-27.16	-60.86	-44.90	5.66	10.40	V	Pass
7636	-21.95	-13	-8.95	-47.28	-27.98	6.28	12.31	V	Pass
9552	-25.51	-13	-12.51	-55.72	-31.50	7.2	13.19	V	Pass
11456	-22.25	-13	-9.25	-58.1	-26.88	8.59	13.22	V	Pass
13364	-35.49	-13	-22.49	-64.33	-39.8	9.4	13.71	V	Pass




Band :	GSM1900	Temperature :	22~24°C
Test Mode :	EDGE 8 Link Ch512	Relative Humidity :	42~45%
Test Engineer :	Elvis Chen	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3696	-49.26	-13	-36.26	-62.51	-53.38	4.52	8.64	H	Pass
5552	-31.66	-13	-18.66	-53.9	-36.86	5.2	10.40	H	Pass
7396	-30.07	-13	-17.07	-55.86	-36.1	6.02	12.05	H	Pass
9248	-27.26	-13	-14.26	-54.21	-32.95	7.46	13.15	H	Pass
11092	-23.35	-13	-10.35	-56.45	-27.86	8.85	13.36	H	Pass
12948	-22.69	-13	-9.69	-54.27	-27.5	8.36	13.17	H	Pass
14804	-33.08	-13	-20.08	-60.35	-38.5	8.46	13.88	H	Pass
16650	-18.06	-13	-5.06	-54.26	-21.8	9.82	13.56	H	Pass




Band :	GSM1900	Temperature :	22~24°C
Test Mode :	EDGE 8 Link Ch512	Relative Humidity :	42~45%
Test Engineer :	Elvis Chen	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3696	-36.80	-13	-23.80	-54.92	-40.92	4.52	8.64	V	Pass
5552	-35.65	-13	-22.65	-57.387	-40.85	5.2	10.40	V	Pass
7396	-31.02	-13	-18.02	-55.8	-37.05	6.02	12.05	V	Pass
9248	-24.05	-13	-11.05	-54.21	-29.74	7.46	13.15	V	Pass
11092	-22.56	-13	-9.56	-54.84	-27.07	8.85	13.36	V	Pass
12948	-28.29	-13	-15.29	-59.49	-33.1	8.36	13.17	V	Pass
14804	-35.28	-13	-22.28	-61.1	-40.7	8.46	13.88	V	Pass
16650	-24.06	-13	-11.06	-58.85	-27.8	9.82	13.56	V	Pass



Band :	GSM1900	Temperature :	22~24°C
Test Mode :	EDGE 8 Link Ch661	Relative Humidity :	42~45%
Test Engineer :	Elvis Chen	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY
Condition : FCC PART22/24 HF-EIRP(080306) HORIZONTAL
Project : FG 802323

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-41.69	-13	-28.69	-57.88	-46.37	4.03	8.71	H	Pass
5636	-26.41	-13	-13.41	-50.36	-32.94	3.87	10.40	H	Pass
7520	-25.49	-13	-12.49	-51.51	-31.88	5.83	12.22	H	Pass
9396	-25.54	-13	-12.54	-53.86	-32.70	6.02	13.18	H	Pass
11280	-23.51	-13	-10.51	-59.13	-28.32	8.48	13.29	H	Pass
13156	-22.91	-13	-9.91	-54.11	-28.2	8.13	13.42	H	Pass
15033	-39.96	-13	-26.96	-62.43	-45	8.78	13.82	H	Pass
16917	-20.31	-13	-7.31	-52.34	-21.8	12.33	13.82	H	Pass




Band :	GSM1900	Temperature :	22~24°C
Test Mode :	EDGE 8 Link Ch661	Relative Humidity :	42~45%
Test Engineer :	Elvis Chen	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-34.20	-13	-21.20	-53.18	-38.88	4.03	8.71	V	Pass
5636	-32.37	-13	-19.37	-56.12	-38.90	3.87	10.40	V	Pass
7520	-21.59	-13	-8.59	-47.33	-27.98	5.83	12.22	V	Pass
9396	-24.34	-13	-11.34	-55.93	-31.50	6.02	13.18	V	Pass
11280	-21.30	-13	-8.30	-57.61	-26.11	8.48	13.29	V	Pass
13156	-25.76	-13	-12.76	-58.99	-31.05	8.13	13.42	V	Pass
15033	-37.46	-13	-24.46	-62.92	-42.5	8.78	13.82	V	Pass
16917	-28.31	-13	-15.31	-60.62	-29.8	12.33	13.82	V	Pass




Band :	GSM1900	Temperature :	22~24°C
Test Mode :	EDGE 8 Link Ch810	Relative Humidity :	42~45%
Test Engineer :	Elvis Chen	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3812	-39.37	-13	-26.37	-55.13	-43.37	4.78	8.78	H	Pass
5728	-35.20	-13	-22.20	-56.54	-39.94	5.66	10.40	H	Pass
7636	-26.85	-13	-13.85	-53.36	-32.88	6.28	12.31	H	Pass
9552	-32.71	-13	-19.71	-59.06	-38.70	7.2	13.19	H	Pass
11456	-21.65	-13	-8.65	-57.84	-26.28	8.59	13.22	H	Pass
13364	-28.19	-13	-15.19	-58.91	-32.5	9.4	13.71	H	Pass
17190	-17.07	-13	-4.07	-56.45	-22.1	8.88	13.91	H	Pass



Band :	GSM1900	Temperature :	22~24°C
Test Mode :	EDGE 8 Link Ch810	Relative Humidity :	42~45%
Test Engineer :	Elvis Chen	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY
Condition : FCC PART22/24 HF-EIRP(080306) VERTICAL
Project : FG 8O2323

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3812	-35.88	-13	-22.88	-54.09	-39.88	4.78	8.78	V	Pass
5728	-44.16	-13	-31.16	-63.38	-48.90	5.66	10.40	V	Pass
7636	-23.95	-13	-10.95	-49.33	-29.98	6.28	12.31	V	Pass
9552	-27.51	-13	-14.51	-57.02	-33.50	7.2	13.19	V	Pass
11456	-21.25	-13	-8.25	-57.74	-25.88	8.59	13.22	V	Pass
13364	-36.69	-13	-23.69	-65.12	-41	9.4	13.71	V	Pass




Band :	WCDMA Band V	Temperature :	22~24°C
Test Mode :	WCDMA Link Ch4132	Relative Humidity :	42~45%
Test Engineer :	Elvis Chen	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1654	-51.08	-13	-38.08	-57.11	-51.26	3.1	5.43	H	Pass



Band :	WCDMA Band V	Temperature :	22~24°C
Test Mode :	WCDMA Link Ch4132	Relative Humidity :	42~45%
Test Engineer :	Elvis Chen	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY
Condition : FCC PART22/24 HF-EIRP(080306) VERTICAL
Project : FG 802323

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1645	-57.75	-13	-44.75	-60.69	-57.93	3.1	5.43	V	Pass
2482	-53.36	-13	-40.36	-62.33	-53.35	3.89	6.03	V	Pass




Band :	WCDMA Band V	Temperature :	22~24°C
Test Mode :	WCDMA Link Ch4182	Relative Humidity :	42~45%
Test Engineer :	Elvis Chen	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1669	-51.16	-13	-38.16	-57.78	-51.01	3.39	5.39	H	Pass
2506	-55.03	-13	-42.03	-61.85	-55.29	3.71	6.12	H	Pass




Band :	WCDMA Band V	Temperature :	22~24°C
Test Mode :	WCDMA Link Ch4182	Relative Humidity :	42~45%
Test Engineer :	Elvis Chen	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1669	-58.77	-13	-45.77	-61.33	-58.62	3.39	5.39	V	Pass
2506	-51.20	-13	-38.20	-60.41	-51.46	3.71	6.12	V	Pass




Band :	WCDMA Band V	Temperature :	22~24°C
Test Mode :	WCDMA Link Ch4233	Relative Humidity :	42~45%
Test Engineer :	Elvis Chen	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1693	-49.05	-13	-36.05	-55.67	-49.23	3.02	5.35	H	Pass
2533	-49.75	-13	-36.75	-56.73	-50.06	3.73	6.19	H	Pass




Band :	WCDMA Band V	Temperature :	22~24°C
Test Mode :	WCDMA Link Ch4233	Relative Humidity :	42~45%
Test Engineer :	Elvis Chen	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1690	-56.63	-13	-43.63	-59.89	-56.81	3.02	5.35	V	Pass
2533	-49.55	-13	-36.55	-59.97	-49.86	3.73	6.19	V	Pass




Band :	WCDMA Band II	Temperature :	22~24°C
Test Mode :	HSDPA Link Ch9262	Relative Humidity :	42~45%
Test Engineer :	Elvis Chen	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
7408	-37.85	-13	-24.85	-62.19	-43.88	6.02	12.05	H	Pass
9268	-33.01	-13	-20.01	-59.52	-38.70	7.46	13.15	H	Pass




Band :	WCDMA Band II	Temperature :	22~24°C
Test Mode :	HSDPA Link Ch9262	Relative Humidity :	42~45%
Test Engineer :	Elvis Chen	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
7412	-35.95	-13	-22.95	-60.05	-41.98	6.02	12.05	V	Pass
9268	-28.81	-13	-15.81	-58.74	-34.50	7.46	13.15	V	Pass




Band :	WCDMA Band II	Temperature :	22~24°C
Test Mode :	HSDPA Link Ch9400	Relative Humidity :	42~45%
Test Engineer :	Elvis Chen	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
7520	-37.39	-13	-24.39	-62.19	-43.78	5.83	12.22	H	Pass
9392	-35.44	-13	-22.44	-61.84	-42.60	6.02	13.18	H	Pass




Band :	WCDMA Band II	Temperature :	22~24°C
Test Mode :	HSDPA Link Ch9400	Relative Humidity :	42~45%
Test Engineer :	Elvis Chen	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
7508	-34.49	-13	-21.49	-59.16	-40.88	5.83	12.22	V	Pass
9392	-31.64	-13	-18.64	-62.29	-38.80	6.02	13.18	V	Pass




Band :	WCDMA Band II	Temperature :	22~24°C
Test Mode :	HSDPA Link Ch9538	Relative Humidity :	42~45%
Test Engineer :	Elvis Chen	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
5728	-46.00	-13	-33.00	-64.94	-50.74	5.66	10.40	H	Pass
7620	-37.65	-13	-24.65	-62.09	-43.68	6.28	12.31	H	Pass
9540	-38.51	-13	-25.51	-63.6	-44.50	7.2	13.19	H	Pass



Band :	WCDMA Band II	Temperature :	22~24°C
Test Mode :	HSDPA Link Ch9538	Relative Humidity :	42~45%
Test Engineer :	Elvis Chen	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH07-HY
Condition : FCC PART22/24 HF-EIRP(080306) VERTICAL
Project : FG 802323

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
5728	-46.06	-13	-33.06	-64.74	-50.80	5.66	10.40	V	Pass
7620	-31.55	-13	-18.55	-56.22	-37.58	6.28	12.31	V	Pass
9540	-35.41	-13	-22.41	-63.75	-41.40	7.2	13.19	V	Pass

3.7 Frequency Stability Measurement

3.7.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.7.2 Measuring Instruments

See list of measuring instruments of this test report.


3.7.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized for three hours. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.
4. If the EUT can not be turned on at -30°C , the testing lowest temperature will be raised in 10°C step until the EUT can be turned on.

3.7.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the base station.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

3.7.5 Test Setup



3.7.6 Test Result of Temperature Variation

Band :	GSM 850	Channel :	189
Limit (ppm) :	2.5		

Temperature (°C)	GPRS 8		EDGE 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
-30	N/A	N/A	N/A	N/A	PASS
-20	N/A	N/A	N/A	N/A	
-10	-35	-0.04	-16	-0.02	
0	-28	-0.03	-17	-0.02	
10	-22	-0.03	31	0.04	
20	16	0.02	39	0.05	
30	-20	-0.02	-30	-0.04	
40	-31	-0.04	29	0.03	
50	-20	-0.02	18	0.02	

Remark: The operational condition of EUT is -10 to 50°C which was declared by manufacturer.

Band :	GSM 1900	Channel :	661
Limit (ppm) :	2.5		

Temperature (°C)	GSM		EDGE 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
-30	N/A	N/A	N/A	N/A	PASS
-20	N/A	N/A	N/A	N/A	
-10	-40	-0.02	-35	-0.02	
0	-38	-0.02	-56	-0.03	
10	-41	-0.02	27	0.01	
20	-25	-0.01	31	0.02	
30	-67	-0.04	-32	-0.02	
40	-64	-0.03	-36	-0.02	
50	-34	-0.02	-62	-0.03	

Remark: The operational condition of EUT is -10 to 50°C which was declared by manufacturer.

Band :	WCDMA Band V	Channel :	4182
Limit (ppm) :	2.5		

Temperature (°C)	WCDMA		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	N/A	N/A	PASS
-20	N/A	N/A	
-10	25	0.03	
0	27	0.03	
10	-13	-0.02	
20	12	0.01	
30	-28	-0.03	
40	16	0.02	
50	-26	-0.03	

Remark: The operational condition of EUT is -10 to 50°C which was declared by manufacturer.

Band :	WCDMA Band II	Channel :	9400
Limit (ppm) :	2.5		

Temperature (°C)	HSDPA		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	N/A	N/A	PASS
-20	N/A	N/A	
-10	-44	-0.02	
0	-55	-0.03	
10	-45	-0.02	
20	-27	-0.01	
30	-45	-0.02	
40	38	0.02	
50	-45	-0.02	

Remark: The operational condition of EUT is -10 to 50°C which was declared by manufacturer.

3.7.7 Test Result of Voltage Variation

Band & Channel	Mode	Voltage (Volt)	Freq. Dev. (Hz)	Deviation (ppm)	Limit (ppm)	Result
GSM 850 CH189	GPRS 8	3.8	-41	-0.05	2.5	PASS
		BEP	-23	-0.03		
		4.2	-22	-0.03		
	EDGE 8	3.8	-18	-0.02		
		BEP	-27	-0.03		
		4.2	-11	-0.01		
GSM 1900 CH661	GSM	3.8	-35	-0.02		
		BEP	-57	-0.03		
		4.2	-30	-0.02		
	EDGE 8	3.8	-26	-0.01		
		BEP	-39	-0.02		
		4.2	-23	-0.01		
WCDMA Band V CH4182	WCDMA	3.8	22	0.03		
		BEP	-19	-0.02		
		4.2	-20	-0.02		
WCDMA Band II CH9400	HSDPA	3.8	-47	-0.02		
		BEP	-35	-0.02		
		4.2	-29	-0.02		

Note:

1. Normal Voltage = 3.8V.
2. Battery End Point (BEP) = 3.4 V.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Due Date	Remark
System Simulator	R&S	CMU200	105934	N/A	Nov. 08, 2008	Nov. 07, 2009	Conducted (TH02-HY)
Spectrum Analyzer	R&S	FSP40	100055	9kHz~40GHz	Jun. 26, 2008	Jun. 25, 2009	Conducted (TH02-HY)
Thermal Chamber	TEN BILLION	TTH-D35P	TBN-930701	N/A	Aug. 01, 2008	Jul. 31, 2009	Conducted (TH02-HY)
Bilog Antenna	SCHAFFNER	CBL6111C	2726	30MHz~1GHz	Nov. 20, 2008	Nov. 19, 2009	Radiation (03CH07-HY)
Spectrum Analyzer	R&S	FSP	101067	9kHz~30GHz	Dec. 02, 2008	Dec. 01, 2009	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	75962	1G~18GHz	Aug. 13, 2008	Aug. 12, 2009	Radiation (03CH07-HY)
Pre Amplifier	Agilent	8449B	3008A02362	1G~26.5GHz	Dec. 17, 2008	Dec. 16, 2009	Radiation (03CH07-HY)
Pre Amplifier	COM-POWER	PA-103A	161241	10~1000MHz. 32dB.GAIN	Mar. 27, 2009	Mar. 26, 2010	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	66584	1G~18GHz	Aug. 06, 2008	Aug. 05, 2009	Radiation (03CH07-HY)
SHF-EHF Horn	SCHWARZBECK	BBHA 9170	BBHA917025 1	15G - 40GHz	Oct. 16, 2008	Oct. 15, 2009	Radiation (03CH07-HY)
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz~30 MHz	May 22, 2008	May 21, 2010	Radiation (03CH07-HY)
System Simulator	R&S	CMU200	116457	N/A	Jun. 04, 2008	Jun. 03, 2009	System Simulator

5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Contribution	Uncertainty of x_i		$u(x_i)$
	dB	Probability Distribution	
Receiver reading	0.41	Normal(k=2)	0.21
Antenna factor calibration	0.83	Normal(k=2)	0.42
Cable loss calibration	0.25	Normal(k=2)	0.13
Pre Amplifier Gain calibration	0.27	Normal(k=2)	0.14
RCV/SPA specification	2.50	Rectangular	0.72
Antenna Factor Interpolation for Frequency	1.00	Rectangular	0.29
Site imperfection	1.43	Rectangular	0.83
Mismatch	+0.39/-0.41	U-shaped	0.28
Combined standard uncertainty Uc(y)	1.27		
Measuring uncertainty for a level of confidence of 95% U=2Uc(y)	2.54		

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Contribution	Uncertainty of x_i		$u(x_i)$	C_i	$C_i * u(x_i)$
	dB	Probability Distribution			
Receiver reading	±0.10	Normal(k=1)	0.10	1	0.10
Antenna factor calibration	±1.70	Normal(k=2)	0.85	1	0.85
Cable loss calibration	±0.50	Normal(k=2)	0.25	1	0.25
Receiver Correction	±2.00	Rectangular	1.15	1	1.15
Antenna Factor Directional	±1.50	Rectangular	0.87	1	0.87
Site imperfection	±2.80	Triangular	1.14	1	1.14
Mismatch Receiver VSWR $\Gamma_1 = 0.197$ Antenna VSWR $\Gamma_2 = 0.194$ Uncertainty = $20 \log(1 - \Gamma_1 * \Gamma_2)$	+0.34/-0.35	U-shaped	0.244	1	0.244
Combined standard uncertainty Uc(y)	2.36				
Measuring uncertainty for a level of confidence of 95% U=2Uc(y)	4.72				

6 Certification of TAF Accreditation



Certificate No. : L1190-090318

財團法人全國認證基金會
Taiwan Accreditation Foundation

Certificate of Accreditation

This is to certify that

Sporton International Inc.
EMC & Wireless Communications Laboratory
No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,
Taiwan, R.O.C.

is accredited in respect of laboratory

Accreditation Criteria	: ISO/IEC 17025:2005
Accreditation Number	: 1190
Originally Accredited	: December 15, 2003
Effective Period	: January 10, 2007 to January 09, 2010
Accredited Scope	: Testing Field, see described in the Appendix
Specific Accreditation Program	: Accreditation Program for Designated Testing Laboratory for Commodities Inspection Accreditation Program for Telecommunication Equipment Testing Laboratory Accreditation Program for BSMI Mutual Recognition Arrangement with Foreign Authorities



Jay-San Chen
President, Taiwan Accreditation Foundation
Date : March 18, 2009

Pl, total 19 pages

The Appendix forms an integral part of this Certificate, which shall be invalid when use without the Appendix



Appendix A. Photographs of EUT

Please refer to Sporton report number EP8O2323 as below.