

FCC Test Report

APPLICANT : Palm, Inc.
EQUIPMENT : Phone
BRAND NAME : Palm
MODEL NAME : P100UNA
FCC ID : O8F-CASG
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : Digital Transmission System (DTS)

The product sample received on Oct. 23, 2008 and completely tested on Apr. 29, 2009. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.4-2003 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:



Roy Wu / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION.....	5
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Feature of Equipment Under Test.....	5
1.4 Testing Site.....	7
1.5 Applied Standards	7
1.6 Ancillary Equipment List	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	8
2.1 RF Output Power.....	8
2.2 Test Mode.....	9
2.3 Connection Diagram of Test System.....	10
2.4 RF Utility	10
3 TEST RESULT	11
3.1 Number of Channel Measurement	11
3.2 20dB and 99% Bandwidth Measurement.....	13
3.3 Hopping Channel Separation Measurement	26
3.4 Dwell Time Measurement.....	29
3.5 Peak Output Power Measurement	31
3.6 Band Edges Measurement.....	34
3.7 Power Spectral Density Measurement	38
3.8 Spurious Emission Measurement.....	45
3.9 AC Conducted Emission Measurement.....	50
3.10 Radiated Emission Measurement.....	56
3.11 Antenna Requirements.....	67
4 LIST OF MEASURING EQUIPMENT.....	68
5 UNCERTAINTY OF EVALUATION.....	69
6 CERTIFICATION OF TAF ACCREDITATION	71
APPENDIX A. PHOTOGRAPHS OF EUT	
APPENDIX B. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR8O2323A	Rev. 01	Initial issue of report	Apr. 30, 2009

SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	15.247(b)(1)	A8.4(2)	Number of Channels	$\geq 15\text{Chs}$	Pass	
3.2	15.247(a)(1)	A8.1(a)	20dB Bandwidth	NA	Pass	-
3.2	-	Gen 4.4.1	99% Bandwidth	-	Pass	-
3.3	15.247(a)(1)	A8.1(b)	Channel Separation	$\geq 2/3$ of 20dB BW	Pass	-
3.4	15.247(a)(1)	A8.1(d)	Dwell Time of Each Channel	$\leq 0.4\text{sec}$ in 31.6sec period	Pass	-
3.5	15.247(a)(1)	A8.1(b)	Peak Output Power	$\leq 1\text{W}$	Pass	-
3.6	15.247(d)	A8.5	Frequency Band Edges	$\leq 20\text{dBc}$	Pass	-
3.7	15.247(f)	A8.3(2)	Power Spectral Density	$< 8\text{dBm}/3\text{kHz}$	Pass	
3.8	15.247(d)	A8.5	Spurious Emission	$< 20\text{ dBc}$	Pass	-
3.9	15.207	Gen 7.2.2	AC Conducted Emission	15.207(a)	Pass	Under limit 4.50 dB at 0.446 MHz
3.10	15.247(d)	A8.5	Transmitter Radiated Emission	15.209(a) & 15.247(d)	Pass	Under limit 5.62 dB at 30.00 MHz
3.11	15.203 & 15.247(b)	A8.4	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

Palm, Inc.

950 W Maude Avenue, Sunnyvale, CA 94085

1.2 Manufacturer

Palm, Inc.

950 W Maude Avenue, Sunnyvale, CA 94085

1.3 Feature of Equipment Under Test

Product Feature & Specification	
Equipment	Phone
Brand Name	Palm
Model Name	P100UNA
FCC ID	O8F-CASG
Tx/Rx Frequency Range	2400 MHz ~ 2483.5 MHz
Number of Channels	79
Carrier Frequency of Each Channel	2402+n*1 MHz; n=0~78
Channel Spacing	1 MHz
Maximum Output Power to Antenna	Bluetooth (1Mbps) : 3.83 dBm (2.415 mW) Bluetooth EDR (2Mbps) : 1.07dBm (1.279 mW) Bluetooth EDR (3Mbps) : 1.63dBm (1.455 mW)
Antenna Type	stamped metal monopole antenna
Antenna Connector Type	N/A
Type of Modulation	Bluetooth (1Mbps) : GFSK Bluetooth EDR (2Mbps) : $\pi/4$ -DQPSK Bluetooth EDR (3Mbps) : 8-DPSK
EUT Stage	Identical Prototype

List of Accessory:

Specification of Accessory		
AC Adapter 1	Brand Name	Palm
	Part Number	157-10108-00
	Power Rating	I/P: 100-240Vac, 50-60Hz, 0.2A; O/P: 5Vdc, 1000mA
AC Adapter 2	Brand Name	Palm
	Part Number	157-10124-00
	Power Rating	I/P: 100-240Vac, 50-60Hz, 0.2A; O/P: 5Vdc, 1000mA
Inductive Charger	Brand Name	Palm
	Part Number	157-10123-00
	Power Rating	I/P: 5Vdc, 1000mA
Inductive back cover	Brand Name	Palm
	Part Number	180-10704-00
Battery	Brand Name	Palm
	Type Number	157-10119-00
	Power Rating	3.7Vdc, 1150mAh
	Type	Li-ion
Earphone	Brand Name	Palm
	Part Number	180-10632-00
	Signal Line Type	1.2 meter non-shielded cable without ferrite core
USB Cable	Brand Name	Palm
	Part Number	180-10646-00
	Signal Line Type	1.5 meter shielded cable without ferrite core

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. For accessories equipped with this EUT, please refer to the appendix of the external photo.
3. For other wireless features of this EUT, test report will be issued separately.
4. This test report recorded only product characteristics and test results of Digital Spread Spectrum (DTS).

1.4 Testing Site

Test Site	SPORTON INTERNATIONAL INC.		
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-3273456 / FAX: +886-3-3284978		
Test Site No.	Sporton Site No.		FCC/IC Registration No.
	CO05-HY	03CH07-HY	TW1022/4086B-1

1.5 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC Public Notice DA 00-705
- ANSI C63.4-2003
- IC RSS-210 Issue 7

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B (DoC), recorded in a separate test report.

1.6 Ancillary Equipment List

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Earphone	Nokia	BH-100	PYA1YH	N/A	N/A
2.	WLAN AP	D-Link	DIR-628	KA2DIR628A2	N/A	Unshielded, 1.8m

2 Test Configuration of Equipment Under Test

2.1 RF Output Power

Preliminary tests were performed in different data rate and recorded the RF output power in the following table:

Channel	Frequency	Bluetooth RF Output Power		
		Data Rate / Modulation		
		GFSK	$\pi/4$ -DQPSK	8-DPSK
		1Mbps	2Mbps	3Mbps
Ch00	2402MHz	3.23 dBm	0.90 dBm	1.07 dBm
Ch39	2441MHz	3.83 dBm	1.07 dBm	1.63 dBm
Ch78	2480MHz	3.32 dBm	0.52 dBm	1.20 dBm

Remark:

1. The data rate 1Mbps was set for all the test cases, due to the highest RF output power.
2. The EUT is programmed to transmit signal continuously for all testing.

2.2 Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2003 and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).


Pre-scanned tests were conducted to determine the final configuration from all possible combinations.

The following tables are showing the test modes as the worst cases and recorded in this report.


Test Cases			
Test Item	Data Rate / Modulation		
	Bluetooth 1Mbps GFSK	Bluetooth EDR 2Mbps $\pi/4$ -DQPSK	Bluetooth EDR 3Mbps 8-DPSK
Conducted TCs	■ Mode 1: CH00_2402 MHz ■ Mode 2: CH39_2441 MHz ■ Mode 3: CH78_2480 MHz ■ Mode 4: 802.11b CH11 + BT CH39	■ Mode 4: CH00_2402 MHz ■ Mode 5: CH39_2441 MHz ■ Mode 6: CH78_2480 MHz	■ Mode 7: CH00_2402 MHz ■ Mode 8: CH39_2441 MHz ■ Mode 9: CH78_2480 MHz
Radiated TCs	■ Mode 1: CH00_2402 MHz + Back cover A + Earphone + USB Cable + Adapter 2 ■ Mode 2: CH39_2441 MHz + Back cover A + Earphone + USB Cable + Adapter 2 ■ Mode 3: CH78_2480 MHz + Back cover A + Earphone + USB Cable + Adapter 2 ■ Mode 4: 802.11b CH11 + BT CH39 + Back cover A + Earphone + USB Cable + Adapter 2	N/A	N/A
AC Conducted Emission	■ Mode 1: WLAN Link + BT Link + MPEG4 + Back cover B + USB Cable + Adapter 1 + Earphone + Charging dock		
Remark:			
1. The worst case of radiated emission was Bluetooth 1Mbps mode; only the test data of this mode was reported. 2. Back cover A stands for standard specification; Back cover B stands for inductive specification.			

2.3 Connection Diagram of Test System

<Conducted Emission>



<Radiated Emission>



2.4 RF Utility

For Bluetooth function, the programmed RF Utility “Compliance” is installed in EUT to provide channel selection, data rate and the application type. The RF Utility can send transmitting signal for all testing.

3 Test Result

3.1 Number of Channel Measurement

3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedure

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The modulation types of EUT are irrelevant to number of hopping channels deviation.
4. The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:
Span = the frequency band of operation; $RBW \geq 1\%$ of the span; $VBW \geq RBW$; Sweep = auto;
Detector function = peak; Trace = max hold.
5. The number of hopping frequency used is defined as the device has the numbers of total channel.


3.1.4 Test Setup



3.1.5 Test Result of Number of Hopping Frequency

Test Mode :	Mode 1~3	Temperature :	22~23°C
Test Engineer :	Eric Hum	Relative Humidity :	42~43%
Number of Hopping Channels (Channel)		Limits (Channel)	Pass/Fail
79		> 15	Pass

Number of Hopping Channel Plot on Channel 00 - 78



Date: 14.APR.2009 21:39:32

3.2 20dB and 99% Bandwidth Measurement

3.2.1 Limit of 20dB Bandwidth

N/A


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The EUT should be transmitting at its maximum data rate as the worst cases.
4. Use the following spectrum analyzer settings:
Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel;
RBW $\geq$ 1% of the 20 dB bandwidth; VBW $\geq$ RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
5. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

3.2.4 Test Setup






3.2.5 Test Result of 20dB Bandwidth

Test Mode :	Mode 1, 2, 3	Temperature :	22~23°C
Test Engineer :	Eric Hum	Relative Humidity :	42~43%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	0.820
39	2441	0.826
78	2480	0.822


20 dB Bandwidth Plot on Channel 00



Date: 14.APR.2009 17:55:58




20 dB Bandwidth Plot on Channel 39



Date: 14.APR.2009 17:56:39

20 dB Bandwidth Plot on Channel 78




Date: 14.APR.2009 17:57:16



Test Mode :	Mode 4, 5, 6	Temperature :	22~23°C
Test Engineer :	Eric Hum	Relative Humidity :	42~43%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.204
39	2441	1.212
78	2480	1.216


20 dB Bandwidth Plot on Channel 00



Date: 14.APR.2009 19:31:49




20 dB Bandwidth Plot on Channel 39



Date: 14.APR.2009 19:32:20

20 dB Bandwidth Plot on Channel 78




Date: 14.APR.2009 19:31:22



Test Mode :	Mode 7, 8, 9	Temperature :	22~23°C
Test Engineer :	Eric Hum	Relative Humidity :	42~43%


Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.204
39	2441	1.212
78	2480	1.212

20 dB Bandwidth Plot on Channel 00

Date: 14.APR.2009 19:36:12




20 dB Bandwidth Plot on Channel 39



Date: 14.APR.2009 19:35:50

20 dB Bandwidth Plot on Channel 78




Date: 14.APR.2009 19:37:45

3.2.6 Test Result of 99% Occupied Bandwidth

Test Mode :	Mode 1, 2, 3	Temperature :	22~23°C
Test Engineer :	Eric Hum	Relative Humidity :	42~43%

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
00	2402	0.772
39	2441	0.786
78	2480	0.786


99% Bandwidth Plot on Channel 00



Date: 14.APR.2009 19:43:48




99% Occupied Bandwidth Plot on Channel 39



Date: 14.APR.2009 19:44:31

99% Occupied Bandwidth Plot on Channel 78




Date: 14.APR.2009 19:45:13



Test Mode :	Mode 4, 5, 6	Temperature :	22~23°C
Test Engineer :	Eric Hum	Relative Humidity :	42~43%

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
00	2402	1.156
39	2441	1.160
78	2480	1.156


99% Bandwidth Plot on Channel 00



Date: 14.APR.2009 19:40:50




99% Occupied Bandwidth Plot on Channel 39



Date: 14.APR.2009 19:41:16

99% Occupied Bandwidth Plot on Channel 78




Date: 14.APR.2009 19:41:54



Test Mode :	Mode 7, 8, 9	Temperature :	22~23°C
Test Engineer :	Eric Hum	Relative Humidity :	42~43%


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
00	2402	1.144
39	2441	1.140
78	2480	1.140

99% Bandwidth Plot on Channel 00

Date: 14.APR.2009 19:43:19




99% Occupied Bandwidth Plot on Channel 39



Date: 14.APR.2009 19:39:20

99% Occupied Bandwidth Plot on Channel 78



Date: 14.APR.2009 19:38:31

3.3 Hopping Channel Separation Measurement

3.3.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.


3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

1. Please refer FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The EUT should be transmitting at its maximum data rate as the worst cases.
4. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels; $RBW \geq 1\%$ of the span;
 $VBW \geq RBW$; Sweep = auto; Detector function = peak; Trace = max hold.
5. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

3.3.4 Test Setup






3.3.5 Test Result of Hopping Channel Separation

Test Mode :	Mode 1, 2, 3	Temperature :	22~23°C
Test Engineer :	Eric Hum	Relative Humidity :	42~43%

Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.004	0.547	Pass
39	2441	1.000	0.551	Pass
78	2480	1.004	0.548	Pass


Channel Separation Plot on Channel 00 - 01



Date: 14.APR.2009 20:00:11




Channel Separation Plot on Channel 39 - 40



Date: 14.APR.2009 20:04:10

Channel Separation Plot on Channel 77 - 78



Date: 14.APR.2009 20:13:55

3.4 Dwell Time Measurement

3.4.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

3.4.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The EUT should be transmitting at its maximum data rate as the worst cases.
4. The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:
Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW $\geq$ RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
5. Use the marker-delta function to calculate the dwell time.

3.4.4 Test Setup



3.4.5 Test Result of Dwell Time

Test Mode :	Mode 2	Temperature :	22~23°C
Test Engineer :	Eric Hum	Relative Humidity :	42~43%


Package Mode	Average Hopping Channel	Package Transfer Time (usec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
DH5	3.400	3108.000	0.334	0.4	Pass

Remark:

1. Dwell Time=79(channels) x 0.4(s) x average hopping channel x package transfer time
2. 79 channels come from the Hopping Channel number.
3. Average Hopping Channel = hops/sweep time
4. t: Package Transfer Time(us)




DH5 Dwell Time (One Pulse) Plot on Channel 39



Date: 14.APR.2009 18:12:41

DH5 Dwell Time (Count Pulses) Plot on Channel 39



Date: 14.APR.2009 18:19:25

3.5 Peak Output Power Measurement

3.5.1 Limit of Peak Output Power

Frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels: 1W (30 dBm).


3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the peak power meter by a low loss cable.

3.5.4 Test Setup




3.5.5 Test Result of Peak Output Power

Test Mode :	Mode 1, 2, 3	Temperature :	22~23℃	
Test Engineer :	Eric Hum	Relative Humidity :	42~43%	

Channel	Frequency (MHz)	RF Power (dBm)		
		GFSK	Max. Limits (dBm)	Pass/Fail
		1 Mbps		
00	2402	3.23	30	Pass
39	2441	3.83	30	Pass
78	2480	3.32	30	Pass




Peak Output Power Plot on Channel 00



Date: 14.APR.2009 17:04:58


Peak Output Power Plot on Channel 39



Date: 14.APR.2009 17:09:01



Peak Output Power Plot on Channel 78



Date: 14.APR.2009 17:15:16

3.6 Band Edges Measurement

3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.6.2 Measuring Instruments

See list of measuring instruments of this test report.

3.6.3 Test Procedures

1. The testing follows the guidelines in ANSI C63.4-2003 and FCC Public Notice DA 00-705 Measurement Guidelines.
2. RF antenna conducted test: Set RBW = 100 kHz, Video bandwidth (VBW) > RBW, scan up through 10th harmonic. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW. Note: If the device complies with the use of power option 2 the attenuation under this paragraph shall be 30 dB instead of 20 dB.
3. Radiated emission test: Applies to band edge emissions that fall in the restricted bands listed in FCC Section 15.205. The maximum permitted average field strength is listed in FCC Section 15.209. A pre-amp is necessary for this measurement. For measurements above 1 GHz, set RBW = 1MHz, VBW = 10 Hz, Sweep: Auto. If the emission is pulsed, modify the unit for continuous operation; use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation. See FCC Section 15.35(b) and (c).

3.6.4 Test Setup



3.6.5 Test Result of Radiated Band Edges

Test Mode :	Mode 1	Temperature :	23~27°C
Test Channel :	00	Relative Humidity :	40~43%
		Test Engineer :	Kar Wang

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2389.99	56.04	-17.96	74.00	52.95	32.02	5.46	34.38	100	346	Peak
2389.99	36.52	-17.48	54.00	33.43	32.02	5.46	345.38	100	346	Average

Remark:

<Delta Marker>

Delta marker at 1% RBW of span = $38.10 + 3.20 = 41.30$ dB (can be referred to section 3.6.6)

Peak band edge at 2389.99 MHz (RBW = VBW = 1MHz) = $97.34 \text{ dBuV/m} - 41.30 \text{ dB} = 56.04 \text{ dBuV/m}$

Duty factor = $20 \times \log ((\text{Package Transfer Times(ms)} \times \text{Avg Hopping Channel}) / 100 \text{ ms})$

$$= 20 \times \log ((3.108 \times 3.4) / 100) = -19.5208$$

Average band edge = Peak band edge + Duty factor = $56.04 \text{ dBuV/m} + (-19.5208) = 36.52 \text{ dBuV/m}$

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2387.90	58.70	-15.30	74.00	55.61	32.02	5.46	34.38	100	57	Peak
2387.90	39.18	-14.82	54.00	36.09	32.02	5.46	34.38	100	57	Average

Remark:

<Delta Marker>

Delta marker at 1% RBW of span = $38.10 + 3.20 = 41.30$ dB (can be referred to section 3.6.6)

Peak band edge at 2387.99 MHz (RBW = VBW = 1MHz) = $100 \text{ dBuV/m} - 41.30 \text{ dB} = 58.70 \text{ dBuV/m}$

Duty factor = $20 \times \log ((\text{Package Transfer Times(ms)} \times \text{Avg Hopping Channel}) / 100 \text{ ms})$

$$= 20 \times \log ((3.108 \times 3.4) / 100) = -19.5208$$

Average band edge = Peak band edge + Duty factor = $58.70 \text{ dBuV/m} + (-19.5208) = 39.18 \text{ dBuV/m}$

Test Mode :	Mode 3	Temperature :	23~27°C
Test Channel :	78	Relative Humidity :	40~43%
		Test Engineer :	Kar Wang

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.50	51.02	-22.98	74.00	47.95	32.09	5.38	34.40	161	354	Peak
2483.50	31.50	-22.50	54.00	28.43	32.09	5.38	34.40	161	354	Average

Remark:

<Delta Marker>

Delta marker at 1% RBW of span = $46.49 - 0.20 = 46.29$ dB (can be referred to section 3.6.6)

Peak band edge at 2483.50 MHz (RBW = VBW = 1MHz) = $97.31 \text{ dBuV/m} - 46.29 \text{ dB} = 51.02 \text{ dBuV/m}$

Duty factor = $20 \times \log ((\text{Package Transfer Times(ms)} \times \text{Avg Hopping Channel}) / 100 \text{ ms})$

$$= 20 \times \log ((3.108 \times 3.4) / 100) = -19.5208$$

Average band edge = Peak band edge + Duty factor = $51.02 \text{ dBuV/m} + (-19.5208) \text{ dB} = 31.50 \text{ dBuV/m}$

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.50	53.53	-20.47	74.00	50.46	32.09	5.38	34.40	100	237	Peak
2483.50	34.01	-19.99	54.00	30.94	32.09	5.38	34.40	100	237	Average

Remark:

<Delta Marker>

Delta marker at 1% RBW of span = $46.49 - 0.20 = 46.29$ dB (can be referred to section 3.6.6)

Peak band edge at 2483.50 MHz (RBW = VBW = 1MHz) = $99.82 \text{ dBuV/m} - 46.29 \text{ dB} = 53.53 \text{ dBuV/m}$


Duty factor = $20 \times \log ((\text{Package Transfer Times(ms)} \times \text{Avg Hopping Channel}) / 100 \text{ ms})$

$$= 20 \times \log ((3.108 \times 3.4)/100) = -19.5208$$


Average band edge = Peak band edge + Duty factor = $53.53 \text{ dBuV/m} + (-19.5208) \text{ dB} = 34.01 \text{ dBuV/m}$

**3.6.6 Test Result of Conducted Band Edges**

Test Mode :	Mode 1 and 3	Temperature :	22~23°C
Test Channel :	00 and 78	Relative Humidity :	42~43%
		Test Engineer :	Eric Hum

Low Band Edge Plot on Channel 00

Date: 14.APR.2009 17:59:26

High Band Edge Plot on Channel 78

Date: 14.APR.2009 18:01:13

3.7 Power Spectral Density Measurement

3.7.1 Limit of Power Spectral Density Measurement

The peak power spectral density shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.


3.7.2 Measuring Instruments

See list of measuring instruments of this test report.

3.7.3 Test Procedure

1. The transmitter output was connected to spectrum analyzer directly.
2. The spectrum analyzer's resolution bandwidth was set RBW at 3kHz and VBW at 30kHz of the fundamental frequency. Set the sweep time=span/3kHz.
3. The power spectral density was measured and recorded.
4. The sweep time is allowed to be longer than span/3kHz for a full response of the mixer in the spectrum analyzer.


3.7.4 Test Setup



**3.7.5 Test Result**

Test Mode :	Mode 1, 2, 3	Temperature :	22~23°C
Test Engineer :	Eric Hum	Relative Humidity :	42~43%


Channel	Frequency (MHz)	Power Spectral Density (dBm)	Max. Limits (dBm)	Pass/Fail
00	2402	-7.83	8	Pass
39	2441	-6.89	8	Pass
78	2480	-7.62	8	Pass

Power Spectral Density Plot on Channel 00

Date: 23.APR.2009 20:45:45




Power Spectral Density Plot on Channel 39



Date: 23.APR.2009 20:54:57

Power Spectral Density Plot on Channel 78




Date: 23.APR.2009 21:04:06



Test Mode :	Mode 4, 5, 6	Temperature :	22~23°C
Test Engineer :	Eric Hum	Relative Humidity :	42~43%

Channel	Frequency (MHz)	Power Spectral Density (dBm)	Max. Limits (dBm)	Pass/Fail
00	2402	-10.48	8	Pass
39	2441	-10.15	8	Pass
78	2480	-10.41	8	Pass


Power Spectral Density Plot on Channel 00



Date: 23.APR.2009 21:13:53




Power Spectral Density Plot on Channel 39



Date: 23.APR.2009 21:23:06

Power Spectral Density Plot on Channel 78




Date: 23.APR.2009 21:32:05



Test Mode :	Mode 7, 8, 9	Temperature :	22~23°C
Test Engineer :	Eric Hum	Relative Humidity :	42~43%


Channel	Frequency (MHz)	Power Spectral Density (dBm)	Max. Limits (dBm)	Pass/Fail
00	2402	-12.20	8	Pass
39	2441	-11.51	8	Pass
78	2480	-12.28	8	Pass

Power Spectral Density Plot on Channel 00

Date: 23.APR.2009 21:41:54




Power Spectral Density Plot on Channel 39



Date: 23.APR.2009 21:51:25

Power Spectral Density Plot on Channel 78



Date: 23.APR.2009 22:00:45

3.8 Spurious Emission Measurement

3.8.1 Limit of Spurious Emission Measurement

All harmonics/spurs must be at least 20 dB down from the highest emission level within the authorized band.


3.8.2 Measuring Instruments

See list of measuring instruments of this test report.

3.8.3 Test Procedure


1. The transmitter output was connected to the spectrum analyzer via a low lose cable.
2. Set RBW = 100 kHz, Video bandwidth (VBW) $\geq$ RBW, scan up through 10th harmonic. All harmonics/spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.

3.8.4 Test Setup




**3.8.5 Test Result**

Test Mode :	Mode 1	Temperature :	22~23°C
Test Channel :	00	Relative Humidity :	42~43%
		Test Engineer :	Eric Hum

Conducted Spurious Emission Plot between 9k-3G


Date: 15.APR.2009 17:50:26

Conducted Spurious Emission Plot between 1G-25G


Date: 15.APR.2009 17:50:51



Test Mode :	Mode 2	Temperature :	22~23°C
Test Channel :	39	Relative Humidity :	42~43%
		Test Engineer :	Eric Hum

Conducted Spurious Emission Plot between 9k-3G


Date: 15.APR.2009 17:51:28

Conducted Spurious Emission Plot between 1G-25G


Date: 15.APR.2009 17:52:04



Test Mode :	Mode 3	Temperature :	22~23°C
Test Channel :	78	Relative Humidity :	42~43%
		Test Engineer :	Eric Hum

Conducted Spurious Emission Plot between 9k-3G


Date: 15.APR.2009 17:53:42

Conducted Spurious Emission Plot between 1G-25G


Date: 15.APR.2009 17:54:14



Test Mode :	Mode 4	Temperature :	22~23°C
Test Channel :	802.11b CH11 + BT CH39	Relative Humidity :	42~43%
		Test Engineer :	Eric Hum

Conducted Spurious Emission Plot between 9k-3G

Date: 29.APR.2009 22:50:02

Conducted Spurious Emission Plot between 1G-25G

Date: 29.APR.2009 22:51:20

3.9 AC Conducted Emission Measurement

3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.9.2 Measuring Instruments

See list of measuring instruments of this test report.

3.9.3 Test Procedures


1. Please follow the guidelines in ANSI C63.4-2003.
2. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN).
4. All the support units are connecting to the other LISN.
5. The LISN provides 50 ohm coupling impedance for the measuring instrument.
6. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
7. Both sides of AC line were checked for maximum conducted interference.
8. The frequency range from 150 kHz to 30 MHz was searched.
9. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.9.4 Test Setup



3.9.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	23~27°C
Test Engineer :	Cona Huang	Relative Humidity :	40~43%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	WLAN Link + BT Link + MPEG4 + Back cover B + USB Cable + Adapter 1 + Earphone + Charging dock		
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		




Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.222000	55.8	Off	L1	19.3	6.9	62.7
0.294000	55.0	Off	L1	19.3	5.4	60.4
0.374000	52.8	Off	L1	19.4	5.6	58.4
0.446000	52.4	Off	L1	19.3	4.5	56.9
0.526000	51.0	Off	L1	19.3	5.0	56.0
0.598000	50.7	Off	L1	19.4	5.3	56.0
0.670000	50.7	Off	L1	19.4	5.3	56.0
0.734000	49.4	Off	L1	19.4	6.6	56.0
0.838000	47.3	Off	L1	19.5	8.7	56.0
0.958000	47.8	Off	L1	19.4	8.2	56.0
1.142000	46.3	Off	L1	19.4	9.7	56.0
1.390000	44.4	Off	L1	19.4	11.6	56.0

Final Result 2

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.222000	42.4	Off	L1	19.3	10.3	52.7
0.294000	41.2	Off	L1	19.3	9.2	50.4
0.374000	39.4	Off	L1	19.4	9.0	48.4
0.446000	39.7	Off	L1	19.3	7.2	46.9
0.526000	37.9	Off	L1	19.3	8.1	46.0
0.598000	38.1	Off	L1	19.4	7.9	46.0
0.670000	38.0	Off	L1	19.4	8.0	46.0
0.734000	37.2	Off	L1	19.4	8.8	46.0
0.838000	34.9	Off	L1	19.5	11.1	46.0
0.958000	36.7	Off	L1	19.4	9.3	46.0
1.142000	35.0	Off	L1	19.4	11.0	46.0
1.390000	33.8	Off	L1	19.4	12.2	46.0

Test Mode :	Mode 1	Temperature :	23~27°C
Test Engineer :	Cona Huang	Relative Humidity :	40~43%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	WLAN Link + BT Link + MPEG4 + Back cover B + USB Cable + Adapter 1 + Earphone + Charging dock		
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		


Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	59.1	Off	N	19.4	6.9	66.0
0.222000	55.9	Off	N	19.3	6.8	62.7
0.302000	53.4	Off	N	19.3	6.8	60.2
0.374000	52.6	Off	N	19.4	5.8	58.4
0.438000	51.6	Off	N	19.4	5.5	57.1
0.526000	50.8	Off	N	19.3	5.2	56.0
0.590000	50.3	Off	N	19.3	5.7	56.0
0.670000	50.1	Off	N	19.4	5.9	56.0
0.750000	48.9	Off	N	19.4	7.1	56.0
0.966000	47.1	Off	N	19.4	8.9	56.0
1.190000	47.6	Off	N	19.5	8.4	56.0
1.430000	46.5	Off	N	19.4	9.5	56.0
1.670000	44.2	Off	N	19.5	11.8	56.0

Final Result 2

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	44.2	Off	N	19.4	11.8	56.0
0.222000	41.3	Off	N	19.3	11.4	52.7
0.302000	37.4	Off	N	19.3	12.8	50.2
0.374000	38.3	Off	N	19.4	10.1	48.4
0.438000	36.3	Off	N	19.4	10.8	47.1
0.526000	36.1	Off	N	19.3	9.9	46.0
0.590000	36.8	Off	N	19.3	9.2	46.0
0.670000	36.7	Off	N	19.4	9.3	46.0
0.750000	35.3	Off	N	19.4	10.7	46.0
0.966000	34.2	Off	N	19.4	11.8	46.0
1.190000	39.8	Off	N	19.5	6.2	46.0
1.430000	39.9	Off	N	19.4	6.1	46.0

3.10 Radiated Emission Measurement

3.10.1 Limit of Radiated Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.10.2 Measuring Instruments


See list of measuring instruments of this test report.

3.10.3 Test Procedures


1. The testing follows the guidelines in FCC Public Notice DA 00-705 Measurement Guidelines.
2. Use the following spectrum analyzer settings:
Span = wide enough to fully capture the emission being measured; RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
3. Follow the guidelines in ANSI C63.4-2003 with respect to maximizing the emission by rotating the EUT, measuring the emission for three EUT orthogonal planes, and adjusting the measurement antenna height and polarization. A pre-amp and a high pass filter are used for this test in order to get the good signal level.

3.10.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions above 30MHz



3.10.5 Test Results of Radiated Emissions (9kHz ~ 30MHz)

Temperature	23~27°C	Humidity	40~43%
Test Engineer	Kar Wang		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.



3.10.6 Test Result of Radiated Emission (30MHz ~ 25GHz)

Test Mode :	Mode 1	Temperature :	23~27°C
Test Channel :	00	Relative Humidity :	40~43%
Test Engineer :	Kar Wang	Polarization :	Horizontal
Remark :	#9 and #10 are Fundamental Signals which can be ignored.		



Site : 03CH07-HY
Condition : FCC CLASS-B 3m SHF-EHF HORN HORIZONTAL
Project : FR 802323
Mode : Mode 1


	Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	30.81	26.34	-13.66	40.00	38.03	19.36	0.65	31.70	---	---	Peak
2	130.17	22.25	-21.25	43.50	40.25	12.30	1.37	31.67	---	---	Peak
3	258.42	29.37	-16.63	46.00	45.23	13.68	1.94	31.48	---	---	Peak
4	363.00	32.38	-13.62	46.00	45.74	15.51	2.41	31.27	---	---	Peak
5	394.50	34.74	-11.26	46.00	47.14	16.28	2.53	31.21	100	109	Peak
6	425.30	34.00	-12.00	46.00	45.60	16.87	2.70	31.17	---	---	Peak
7	2389.99	56.04	-17.96	74.00	52.95	32.02	5.46	34.38	100	346	Peak
8	2389.99	36.52	-17.48	54.00	33.43	32.02	5.46	34.38	100	346	Average
9 X	2402.00	97.34			94.25	32.03	5.44	34.38	100	346	Peak
10 X	2402.00	83.89			80.80	32.02	5.46	34.38	100	346	Average
11	2484.00	44.20	-29.80	74.00	41.13	32.09	5.38	34.40	100	346	Peak
12	2484.00	32.07	-21.93	54.00	29.00	32.09	5.38	34.40	100	346	Average
13	8937.00	54.12	-19.88	74.00	43.14	36.05	10.32	35.39	100	218	Peak
14	8937.00	42.04	-11.96	54.00	31.06	36.05	10.32	35.39	100	218	Average



FCC Test Report

Report No. : FR802323A

Test Mode :	Mode 1	Temperature :	23~27°C
Test Channel :	00	Relative Humidity :	40~43%
Test Engineer :	Kar Wang	Polarization :	Vertical
Remark :	#9 and #10 are Fundamental Signals which can be ignored.		



Site : 03CH07-HY
Condition : FCC CLASS-B 3m SHF-EHF HORN VERTICAL
Project : FR 802323
Mode : Mode 1


	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	Ant	Table	
	MHz	dBuV/m	Limit	Line	Level	Loss	Factor	Pos	Pos	Remark
			dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	30.81	32.70	-7.30	40.00	44.39	19.36	0.65	31.70	100	206 Peak
2	35.94	27.60	-12.40	40.00	41.99	16.62	0.69	31.70	---	---
3	47.01	30.46	-9.54	40.00	50.98	10.40	0.78	31.70	---	---
4	394.50	29.02	-16.98	46.00	41.42	16.28	2.53	31.21	---	---
5	425.30	29.84	-16.16	46.00	41.45	16.87	2.70	31.17	---	---
6	458.20	27.95	-18.05	46.00	38.83	17.44	2.82	31.14	---	---
7	2387.90	58.70	-15.30	74.00	55.61	32.02	5.46	34.38	100	57 Peak
8	2387.90	39.18	-14.82	54.00	36.09	32.02	5.46	34.38	100	57 Average
9 X	2402.00	100.00			96.91	32.03	5.44	34.38	100	57 Peak
10 @	2402.00	86.22			83.13	32.02	5.46	34.38	100	57 Average
11	2500.00	44.05	-29.95	74.00	40.98	32.10	5.37	34.40	100	57 Peak
12	2500.00	32.04	-21.96	54.00	28.97	32.10	5.37	34.40	100	57 Average
13	7101.00	54.22	-19.78	74.00	43.75	35.50	10.01	35.04	100	251 Peak
14	7101.00	42.11	-11.89	54.00	31.64	35.50	10.01	35.04	100	251 Average



FCC Test Report

Report No. : FR8O2323A


Test Mode :	Mode 2	Temperature :	23~27°C
Test Channel :	39	Relative Humidity :	40~43%
Test Engineer :	Kar Wang	Polarization :	Horizontal
Remark :	#9 and #10 are Fundamental Signals which can be ignored.		



Site : 03CH07-HY
Condition : FCC CLASS-B 3m SHF-EHF HORN HORIZONTAL
Project : FR 802323
Mode : Mode 2

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	Ant	Table	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	30.54	28.78	-11.22	40.00	40.48	19.36	0.65	31.70	---	Peak
2	37.29	21.64	-18.36	40.00	37.17	15.46	0.71	31.70	---	Peak
3	130.98	23.77	-19.73	43.50	41.79	12.28	1.37	31.67	---	Peak
4	394.50	35.31	-10.69	46.00	47.71	16.28	2.53	31.21	100	251 Peak
5	425.30	35.16	-10.84	46.00	46.76	16.87	2.70	31.17	---	Peak
6	511.40	33.98	-12.02	46.00	43.75	18.35	2.97	31.09	---	Peak
7	2332.00	45.34	-28.66	74.00	42.23	31.96	5.51	34.37	109	311 Peak
8	2332.00	33.23	-20.77	54.00	30.12	31.96	5.51	34.37	109	311 Average
9 X	2441.00	97.75			94.66	32.06	5.41	34.39	109	311 Peak
10 X	2441.00	84.31			81.23	32.06	5.41	34.39	109	311 Average
11	2492.00	44.49	-29.51	74.00	41.42	32.10	5.37	34.40	109	311 Peak
12	2492.00	32.28	-21.72	54.00	29.21	32.10	5.37	34.40	109	311 Average
13	7026.00	54.24	-19.76	74.00	43.65	35.50	10.09	35.01	100	128 Peak
14	7026.00	41.88	-12.12	54.00	31.29	35.50	10.09	35.01	100	128 Average

Test Mode :	Mode 2	Temperature :	23~27°C
Test Channel :	39	Relative Humidity :	40~43%
Test Engineer :	Kar Wang	Polarization :	Vertical
Remark :	#9 and #10 are Fundamental Signals which can be ignored.		



Site : 03CH07-HY
Condition : FCC CLASS-B 3m SHF-EHF HORN VERTICAL
Project : FR 802323
Mode : Mode 2


	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	Ant	Table	
	MHz	dBuV/m	Limit	Line	Level	Loss	Factor	Pos	Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	30.00	32.49	-7.51	40.00	43.65	19.90	0.64	31.70	100	106 Peak
2	35.94	27.55	-12.45	40.00	41.94	16.62	0.69	31.70	---	---
3	44.85	22.56	-17.44	40.00	41.94	11.60	0.72	31.70	---	---
4	363.00	27.97	-18.03	46.00	41.34	15.51	2.41	31.27	---	---
5	394.50	27.16	-18.84	46.00	39.56	16.28	2.53	31.21	---	---
6	425.30	28.71	-17.29	46.00	40.31	16.87	2.70	31.17	---	---
7	2324.00	45.42	-28.58	74.00	42.30	31.96	5.51	34.37	150	51 Peak
8	2324.00	33.43	-20.57	54.00	30.32	31.96	5.51	34.37	150	51 Average
9 X	2441.00	101.52			98.44	32.06	5.41	34.39	150	51 Peak
10 @	2441.00	87.64			84.56	32.06	5.41	34.39	150	51 Average
11	2484.00	46.08	-27.92	74.00	43.01	32.09	5.38	34.40	150	51 Peak
12	2484.00	32.72	-21.28	54.00	29.65	32.09	5.38	34.40	150	51 Average
13	8865.00	54.05	-19.95	74.00	43.14	35.99	10.30	35.37	100	345 Peak
14	8865.00	41.97	-12.03	54.00	31.05	35.99	10.30	35.37	100	345 Average



FCC Test Report

Report No. : FR802323A

Test Mode :	Mode 3	Temperature :	23~27°C
Test Channel :	78	Relative Humidity :	40~43%
Test Engineer :	Kar Wang	Polarization :	Horizontal
Remark :	#9 and #10 are Fundamental Signals which can be ignored.		



Site : 03CH07-HY
Condition : FCC CLASS-B 3m SHF-EHF HORN HORIZONTAL
Project : FR 802323
Mode : Mode 3


	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	30.81	25.80	-14.20	40.00	37.49	19.36	0.65	31.70	---	---	Peak
2	132.06	22.64	-20.86	43.50	40.67	12.26	1.37	31.67	---	---	Peak
3	253.02	25.94	-20.06	46.00	42.37	13.13	1.93	31.49	---	---	Peak
4	363.00	33.53	-12.47	46.00	46.89	15.51	2.41	31.27	---	---	Peak
5	394.50	34.32	-11.68	46.00	46.72	16.28	2.53	31.21	---	---	Peak
6	425.30	35.34	-10.66	46.00	46.94	16.87	2.70	31.17	100	85	Peak
7	2374.00	44.82	-29.18	74.00	41.72	32.00	5.47	34.38	161	354	Peak
8	2374.00	32.80	-21.20	54.00	29.70	32.00	5.47	34.38	161	354	Average
9 X	2480.00	97.31			94.23	32.09	5.38	34.40	161	354	Peak
10 X	2480.00	83.94			80.87	32.09	5.38	34.40	161	354	Average
11	2483.50	51.02	-22.98	74.00	47.95	32.09	5.38	34.40	161	354	Peak
12	2483.50	31.50	-22.50	54.00	28.43	32.09	5.38	34.40	161	354	Average
13	8913.00	54.20	-19.80	74.00	43.25	36.02	10.31	35.38	100	167	Peak
14	8913.00	42.11	-11.89	54.00	31.16	36.02	10.31	35.38	100	167	Average



FCC Test Report

Report No. : FR8O2323A

Test Mode :	Mode 3	Temperature :	23~27°C
Test Channel :	78	Relative Humidity :	40~43%
Test Engineer :	Kar Wang	Polarization :	Vertical
Remark :	#9 and #10 are Fundamental Signals which can be ignored.		



Site : 03CH07-HY
Condition : FCC CLASS-B 3m SHF-EHF HORN VERTICAL
Project : FR 8O2323
Mode : Mode 3


	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	Ant	Table	Remark
	MHz	dBuV/m	Limit	Line	Level	Factor	Loss	Factor	Pos	
			dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1 !	30.00	34.38	-5.62	40.00	45.54	19.90	0.64	31.70	100	218 Peak
2	36.21	27.80	-12.20	40.00	42.19	16.62	0.69	31.70	---	---
3	45.66	22.60	-17.40	40.00	42.36	11.20	0.74	31.70	---	---
4	360.90	26.18	-19.82	46.00	39.60	15.46	2.40	31.28	---	---
5	393.80	27.06	-18.94	46.00	39.49	16.26	2.52	31.21	---	---
6	424.60	28.05	-17.95	46.00	39.67	16.85	2.70	31.18	---	---
7	2326.00	45.70	-28.30	74.00	42.59	31.96	5.51	34.37	100	237 Peak
8	2326.00	32.82	-21.18	54.00	29.71	31.96	5.51	34.37	100	237 Average
9 X	2480.00	99.82			96.74	32.09	5.38	34.40	100	237 Peak
10 @	2480.00	85.89			82.82	32.09	5.38	34.40	100	237 Average
11	2483.50	53.53	-20.47	74.00	50.46	32.09	5.38	34.40	100	237 Peak
12	2483.50	34.01	-19.99	54.00	30.94	32.09	5.38	34.40	100	237 Average
13	8385.00	54.27	-19.73	74.00	43.80	35.68	10.10	35.30	100	292 Peak
14	8385.00	42.01	-11.99	54.00	31.54	35.68	10.10	35.30	100	292 Average



FCC Test Report

Report No. : FR8O2323A


Test Mode :	Mode 4	Temperature :	23~27°C
Test Channel :	802.11b CH11 + BT CH39	Relative Humidity :	40~43%
Test Engineer :	Kar Wang	Polarization :	Horizontal
Remark :	#9 ~ #12 are Fundamental Signals which can be ignored.		



Site : 03CH07-HY
Condition : 3m SHF-EHF HORN HORIZONTAL
Project : FR 802323
Mode : Mode 10

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	Ant	Table	Remark
	MHz	dBuV/m	Limit	Line	Level	Loss	Factor	Pos	Pos	
			dB	dBuV/m	dBuV	dB	dB	cm	deg	
1	32.97	24.26	-15.74	40.00	37.01	18.28	0.66	31.70	100	36 Peak
2	44.04	21.54	-18.46	40.00	40.37	12.14	0.72	31.70	---	Peak
3	95.34	23.26	-20.24	43.50	43.97	9.85	1.14	31.70	---	Peak
4	623.40	22.26	-23.74	46.00	30.13	19.78	3.33	30.98	---	Peak
5	855.80	25.86	-20.14	46.00	29.58	22.99	3.98	30.70	---	Peak
6	937.00	27.04	-18.96	46.00	29.45	24.02	4.23	30.66	---	Peak
7	2388.09	47.51	-26.49	74.00	44.42	32.02	5.46	34.38	100	4 Peak
8	2388.09	34.57	-19.43	54.00	31.48	32.02	5.46	34.38	100	4 Average
9 X	2441.00	100.34			97.26	32.06	5.41	34.39	100	4 Peak
10 X	2441.00	88.63			85.55	32.06	5.41	34.39	100	4 Average
11 X	2462.00	102.80			99.72	32.07	5.40	34.39	100	49 Peak
12 @	2462.00	92.42			89.34	32.07	5.40	34.39	100	49 Average
13	2483.50	67.22	-6.78	74.00	64.15	32.09	5.38	34.40	100	4 Peak
14	2483.50	46.02	-7.98	54.00	42.95	32.09	5.38	34.40	100	4 Average
15	8322.00	53.85	-20.15	74.00	43.43	35.67	10.06	35.30	100	281 Peak
16	8322.00	40.65	-13.35	54.00	30.22	35.67	10.06	35.30	100	281 Average

Test Mode :	Mode 4	Temperature :	23~27°C
Test Channel :	802.11b CH11 + BT CH39	Relative Humidity :	40~43%
Test Engineer :	Kar Wang	Polarization :	Vertical
Remark :	#9 ~ #12 are Fundamental Signals which can be ignored.		



Site : 03CH07-HY
Condition : 3m SHF-EHF HORN VERTICAL
Project : FR 8O2323
Mode : Mode 10

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	Ant	Table	Remark
	MHz	dBuV/m	Limit	Line	Level	Loss	Factor	Pos	Pos	
			dB	dBuV/m	dBuV	dB	dB	cm	deg	
1	34.05	26.10	-13.90	40.00	39.39	17.74	0.67	31.70	---	Peak
2	43.77	26.23	-13.77	40.00	45.07	12.14	0.72	31.70	100	57 Peak
3	155.82	23.41	-20.09	43.50	42.22	11.34	1.49	31.64	---	Peak
4	788.60	25.11	-20.89	46.00	30.14	21.88	3.82	30.72	---	Peak
5	859.30	26.26	-19.74	46.00	29.98	22.98	4.00	30.70	---	Peak
6	940.50	27.55	-18.45	46.00	29.83	24.14	4.24	30.66	---	Peak
7	2389.61	46.13	-27.87	74.00	43.04	32.02	5.46	34.38	158	120 Peak
8	2389.61	33.02	-20.98	54.00	29.93	32.02	5.46	34.38	158	120 Average
9 X	2441.00	94.72			91.64	32.06	5.41	34.39	100	135 Peak
10 X	2441.00	83.24			80.16	32.06	5.41	34.39	100	135 Average
11 X	2462.00	101.73			98.65	32.07	5.40	34.39	158	120 Peak
12 @	2462.00	91.05			87.97	32.07	5.40	34.39	158	120 Average
13	2483.50	62.64	-11.36	74.00	59.57	32.09	5.38	34.40	158	120 Peak
14	2483.50	39.63	-14.37	54.00	36.56	32.09	5.38	34.40	158	120 Average
15	8898.00	53.81	-20.19	74.00	42.87	36.02	10.31	35.38	100	182 Peak
16	8898.00	40.52	-13.48	54.00	29.57	36.02	10.31	35.38	100	182 Average

3.11 Antenna Requirements

3.11.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi.

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.11.2 Antenna Connected Construction

The antennas type used in this product is stamped metal monopole antenna without connector and it is considered to meet antenna requirement.

3.11.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100055	9kHz~40GHz	Jun. 26, 2008	Jun. 25, 2009	Conducted (TH02-HY)
Power Meter	Agilent	E4416A	GB412923 44	N/A	Feb. 19, 2009	Feb. 18, 2010	Conducted (TH02-HY)
Power Sensor	Agilent	E9327A	US404415 48	N/A	Feb. 19, 2009	Feb. 18, 2010	Conducted (TH02-HY)
EMI Receiver	R&S	ESCS 30	100356	9kHz~2.75GHz	Aug. 01, 2008	Jul. 31, 2009	Conduction (CO05-HY)
Two-LISN	R&S	ENV216	11-100081	9kHz~30MHz	Nov. 26, 2008	Nov. 25, 2009	Conduction (CO05-HY)
Two-LISN	R&S	ENV216	11-100080	9kHz~30MHz	Nov. 26, 2008	Nov. 25, 2009	Conduction (CO05-HY)
AC Power Source	APC	APC-1000W	N/A	N/A	N/A	N/A	Conduction (CO05-HY)
Bilog Antenna	SCHAFFNER	CBL6111C	2726	30MHz~1GHz	Nov. 20, 2008	Nov. 19, 2009	Radiation (03CH07-HY)
Spectrum Analyzer	R&S	FSP	101067	9kHz~30GHz	Dec. 02, 2008	Dec. 01, 2009	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	75962	1G~18GHz	Aug. 13, 2008	Aug. 12, 2009	Radiation (03CH07-HY)
SHF-EHF Horn	SCHWARZBECK	BBHA 9170	BBHA9170 251	15G - 40GHz	Oct. 16, 2008	Oct. 15, 2009	Radiation (03CH07-HY)
Pre Amplifier	Agilent	8449B	3008A023 62	1G~26.5GHz	Dec. 17, 2008	Dec. 16, 2009	Radiation (03CH07-HY)
Pre Amplifier	COM-POWER	PA-103A	161241	10~1000MHz. 32dB.GAIN	Mar. 27, 2009	Mar. 26, 2010	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	66584	1G~18GHz	Aug. 06, 2008	Aug. 05, 2009	Radiation (03CH07-HY)
Loop Antenna	R&S	HFH2-Z2	860004/00 1	9 kHz~30 MHz	May 22, 2008	May 21, 2010	Radiation (03CH07-HY)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Contribution	Uncertainty of x_i		$u(x_i)$
	dB	Probability Distribution	
Receiver reading	0.10	Normal(k=2)	0.05
Cable loss	0.10	Normal(k=2)	0.05
AMN insertion loss	2.50	Rectangular	0.63
Receiver Spec	1.50	Rectangular	0.43
Site imperfection	1.39	Rectangular	0.80
Mismatch	+0.34/-0.35	U-shape	0.24
Combined standard uncertainty Uc(y)	1.13		
Measuring uncertainty for a level of confidence of 95% U=2Uc(y)	2.26		

Uncertainty of Radiated Emission Measurement (30MHz ~ 1000MHz)

Contribution	Uncertainty of x_i		$u(x_i)$
	dB	Probability Distribution	
Receiver reading	0.41	Normal(k=2)	0.21
Antenna factor calibration	0.83	Normal(k=2)	0.42
Cable loss calibration	0.25	Normal(k=2)	0.13
Pre Amplifier Gain calibration	0.27	Normal(k=2)	0.14
RCV/SPA specification	2.50	Rectangular	0.72
Antenna Factor Interpolation for Frequency	1.00	Rectangular	0.29
Site imperfection	1.43	Rectangular	0.83
Mismatch	+0.39/-0.41	U-shaped	0.28
Combined standard uncertainty Uc(y)	1.27		
Measuring uncertainty for a level of confidence of 95% U=2Uc(y)	2.54		

Uncertainty of Radiated Emission Measurement (1GHz ~ 40GHz)

Contribution	Uncertainty of x_i		$u(x_i)$	C_i	$C_i * u(x_i)$
	dB	Probability Distribution			
Receiver reading	± 0.10	Normal(k=1)	0.10	1	0.10
Antenna factor calibration	± 1.70	Normal(k=2)	0.85	1	0.85
Cable loss calibration	± 0.50	Normal(k=2)	0.25	1	0.25
Receiver Correction	± 2.00	Rectangular	1.15	1	1.15
Antenna Factor Directional	± 1.50	Rectangular	0.87	1	0.87
Site imperfection	± 2.80	Triangular	1.14	1	1.14
Mismatch Receiver VSWR $\Gamma_1 = 0.197$ Antenna VSWR $\Gamma_2 = 0.194$ Uncertainty = $20 \log(1 - \Gamma_1 * \Gamma_2)$	+0.34/-0.35	U-shaped	0.244	1	0.244
Combined standard uncertainty $U_c(y)$	2.36				
Measuring uncertainty for a level of confidence of 95% $U = 2U_c(y)$	4.72				

6 Certification of TAF Accreditation


財團法人全國認證基金會
Taiwan Accreditation Foundation

Certificate No. : L1190-090318

Certificate of Accreditation

This is to certify that

Sporton International Inc.
EMC & Wireless Communications Laboratory
No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,
Taiwan, R.O.C.

is accredited in respect of laboratory

Accreditation Criteria	: ISO/IEC 17025:2005
Accreditation Number	: 1190
Originally Accredited	: December 15, 2003
Effective Period	: January 10, 2007 to January 09, 2010
Accredited Scope	: Testing Field, see described in the Appendix
Specific Accreditation Program	: Accreditation Program for Designated Testing Laboratory for Commodities Inspection Accreditation Program for Telecommunication Equipment Testing Laboratory Accreditation Program for BSMI Mutual Recognition Arrangement with Foreign Authorities


Jay-San Chen
President, Taiwan Accreditation Foundation
Date : March 18, 2009

P1, total 19 pages

The Appendix forms an integral part of this Certificate, which shall be invalid when use without the Appendix



Appendix A. Photographs of EUT

Please refer to Sporton report number EP8O2323 as below.