

Test Laboratory: Compliance Certification Services

CDMA PCS Band

DUT: Palm; Type: NA; Serial: NA

Communication System: CDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV2 - 1012; ; Calibrated: 2/9/2009

- Sensor-Surface: 0mm (Fix Surface)

- Electronics: DAE3 Sn427; Calibrated: 10/20/2008

- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA; Serial:NA

- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Point scan/z (axial) scan at point with noise/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 34.4

Measure Window Start: 0ms

Measure Window Length: 1000ms

BWC applied: 0 dB

Device Reference Point: 0.000, 0.000, -6.30 mm

Category	Telephone parameters WD signal quality [(signal+noise)-to-noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB


Cursor:

ABM1/ABM2 = 43.7 dB

ABM1 = 10.8 dB A/m

BWC Factor = 0 dB

Location: -8.3, 2, 3.7 mm



Test Laboratory: Compliance Certification Services

CDMA PCS Band

DUT: Palm; Type: NA; Serial: NA

Communication System: CDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV2 - 1012; ; Calibrated: 2/9/2009

- Sensor-Surface: 0mm (Fix Surface)

- Electronics: DAE3 Sn427; Calibrated: 10/20/2008

- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA; Serial:NA

- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Point scan/x (longitudinal) scan at point with noise/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 34.4

Measure Window Start: 0ms

Measure Window Length: 1000ms

BWC applied: 0 dB

Device Reference Point: 0.000, 0.000, -6.30 mm

Category	Telephone parameters WD signal quality [(signal+noise)-to-noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB


Cursor:

ABM1/ABM2 = 32.0 dB

ABM1 = 8.93 dB A/m

BWC Factor = 0 dB

Location: -10.5, -2.2, 3.7 mm



Test Laboratory: Compliance Certification Services

CDMA PCS Band

DUT: Palm; Type: NA; Serial: NA

Communication System: CDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV2 - 1012; ; Calibrated: 2/9/2009

- Sensor-Surface: 0mm (Fix Surface)

- Electronics: DAE3 Sn427; Calibrated: 10/20/2008

- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA; Serial:NA

- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Point scan/y (transversal) scan at point with noise/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 34.4

Measure Window Start: 0ms

Measure Window Length: 1000ms

BWC applied: 0 dB

Device Reference Point: 0.000, 0.000, -6.30 mm

Category	Telephone parameters WD signal quality [(signal+noise)-to-noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB


Cursor:

ABM1/ABM2 = 47.5 dB

ABM1 = 3.09 dB A/m

BWC Factor = 0 dB

Location: -0.2, 2, 3.7 mm



Test Laboratory: Compliance Certification Services

CDMA Cell Band

DUT: Palm; Type: NA; Serial: NA

Communication System: CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV2 - 1012; ; Calibrated: 2/9/2009

- Sensor-Surface: 0mm (Fix Surface)

- Electronics: DAE3 Sn427; Calibrated: 10/20/2008

- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA; Serial:NA

- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Point scan/z (axial) scan at point with noise/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 38.2

Measure Window Start: 0ms

Measure Window Length: 1000ms

BWC applied: 0.343005 dB

Device Reference Point: 0.000, 0.000, -6.30 mm

Category	Telephone parameters WD signal quality [(signal+noise)-to-noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB


Cursor:

ABM1/ABM2 = 46.4 dB

ABM1 comp = 15.8 dB A/m

BWC Factor = 0.343005 dB

Location: -6.2, -4.2, 3.7 mm



Test Laboratory: Compliance Certification Services

CDMA Cell Band

DUT: Palm; Type: NA; Serial: NA

Communication System: CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV2 - 1012; ; Calibrated: 2/9/2009

- Sensor-Surface: 0mm (Fix Surface)

- Electronics: DAE3 Sn427; Calibrated: 10/20/2008

- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA; Serial:NA

- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Point scan/x (longitudinal) scan at point with noise/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 38.2

Measure Window Start: 0ms

Measure Window Length: 1000ms

BWC applied: 0.343005 dB

Device Reference Point: 0.000, 0.000, -6.30 mm

Category	Telephone parameters WD signal quality [(signal+noise)-to-noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB


Cursor:

ABM1/ABM2 = 31.9 dB

ABM1 comp = 7.48 dB A/m

BWC Factor = 0.343005 dB

Location: -14.5, -2.2, 3.7 mm



Test Laboratory: Compliance Certification Services

CDMA Cell Band

DUT: Palm; Type: NA; Serial: NA

Communication System: CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV2 - 1012; ; Calibrated: 2/9/2009

- Sensor-Surface: 0mm (Fix Surface)

- Electronics: DAE3 Sn427; Calibrated: 10/20/2008

- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA; Serial:NA

- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Point scan/y (transversal) scan at point with noise/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 38.2

Measure Window Start: 0ms

Measure Window Length: 1000ms

BWC applied: 0.343005 dB

Device Reference Point: 0.000, 0.000, -6.30 mm

Category	Telephone parameters WD signal quality [(signal+noise)-to-noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB

Cursor:

ABM1/ABM2 = 43.7 dB

ABM1 comp = 6.95 dB A/m

BWC Factor = 0.343005 dB

Location: -2.2, 4.2, 3.7 mm

