



EMC Test Data

Client:	Handspring	Job Number:	J44013
Model:	Shea	T-Log Number:	T44028
		Proj Eng:	Mark Briggs
Contact:	David Waitt		
Spec:	FCC 24E and ETS 300 342-3	Class:	N/A

Radiated Emissions

Test Specifics

Objective: The objective of this test session is to perform engineering evaluation testing of the EUT with respect to the specification listed above.

Date of Test: 7/2/2001 Config. Used:
Test Engineer: jmartinez Config Change:
Test Location: SVOATS #3 EUT Voltage: 120V/60Hz

General Test Configuration

The EUT and all local support equipment were located on the turntable for radiated spurious emissions testing.

For radiated emissions testing the measurement antenna was located 3 meters from the EUT. For any Spurious emission more than 20-dB of the field strength limit, substitution was performed. If the Spurious emissions are 20-dB below the field strength limit, substitution does not have to be performed.

Ambient Conditions: Temperature: 27.2°C
Rel. Humidity: 20%

Summary of Results

Run #	Test Performed	Limit	Result	Margin
1a	RE, 1 - 20 GHz - Spurious Emissions	24.238(a)	Pass	-11.3 dB @ 13080 MHz
1b	Output Power	24.232(b)	Pass	29.5 dBm

Modifications Made During Testing:

No modifications were made to the EUT during testing

Deviations From The Standard

No deviations were made from the requirements of the standard.



EMC Test Data

Client:	Handspring	Job Number:	J44013
Model:	Shea	T-Log Number:	T44028
		Proj Eng:	Mark Briggs
Contact:	David Waitt		
Spec:	FCC 24E and ETS 300 342-3	Class:	N/A

Run #1a: Radiated Spurious Emissions, 1-20 GHz, Transmit Frequency 1869.89 MHz

	H	V
Fundamental emission level @ 3m in 1MHz RBW:	126.35	127.62
-13 dBm converted to dB μ V/m @ 3 Meters ^{note 1:}	82.2	dB μ V/m

Frequency	Level	Pol	Pt. 24	Detector	Azimuth	Height	Comments
MHz	dB μ V/m	v/h	Limit	Margin	Pk/QP/Avg	degrees	meters
3739.000	55.3	V	82.2	-26.9	Pk	90	1.3
5609.000	63.3	V	82.2	-18.9	Pk	90	1.1
7479.000	67.1	V	82.2	-15.1	Pk	180	1.1
9349.000	63.1	V	82.2	-19.1	Pk	280	1.0
11219.00	66.0	V	82.2	-16.2	Pk	280	1.0
13088.00	66.9	V	82.2	-15.3	Pk	128	1.1
3739.000	55.1	H	82.2	-27.2	Pk	87	1.4
5609.000	66.3	H	82.2	-15.9	Pk	180	1.0
7479.000	66.4	H	82.2	-15.8	Pk	125	1.0
9349.000	63.5	H	82.2	-18.7	Pk	126	1.0
11219.00	65.6	H	82.2	-16.6	Pk	190	1.0

Note 1: No other Spurious emission detected above the 5th harmonic within 20-dB of the limit.

Note 2:



EMC Test Data

Client:	Handspring	Job Number:	J44013
Model:	Shea	T-Log Number:	T44028
		Proj Eng:	Mark Briggs
Contact:	David Waitt		
Spec:	FCC 24E and ETS 300 342-3	Class:	N/A

Substitution Method for Spurious emission 20-dB from the limit. Taken from Run# 1a

Frequency	Level	Pol	Pin	Gain	Substitution ^{Note 1}		Limit	Margin	Comment
					EIRP	ERP			
MHz	dB μ V/m	v/h	dBm	dBi	dBm	dBm	dBm	dB	
3739.000	56.5	v	-50.0	8.1	-41.9	-44.0	-13	-31.0	
5609.000	64.3	v	-43.0	8.9	-34.1	-36.2	-13	-23.2	
7479.000	67.1	v	-40.5	9.2	-31.3	-33.4	-13	-20.4	
9349.000	64.2	v	-45.0	9.0	-36.0	-38.1	-13	-25.1	
11219.00	67.6	v	-40.0	10.6	-29.4	-31.5	-13	-18.5	
13088.00	68.0	v	-34.0	11.8	-22.2	-24.3	-13	-11.3	
3739.000	56.3	h	-52.0	8.1	-43.9	-46.0	-13	-33.0	
5609.000	66.9	h	-41.5	8.9	-32.6	-34.7	-13	-21.7	
7479.000	66.6	h	-40.0	9.2	-30.8	-32.9	-13	-19.9	
9349.000	65.2	h	-43.0	9.0	-34.0	-36.1	-13	-23.1	
11219.00	69.7	h	-39.0	10.6	-28.4	-30.5	-13	-17.5	

Note 1: Pin is the power input (dBm) to the substitution antenna to obtain the field strength recorded from the EUT. G is the gain (dBi) for the substitution antenna. ERP is the effective radiated power (Pin + GdBi - 2.2) from the substitution antenna. EIRP is calculated as follows (Pin+GdBi)

Run #1b: Output Power (Substitution Method)

Frequency	Level	Pol	Pin	Gain	Substitution ^{Note 1}		Comment
					EIRP	ERP	
MHz	dB μ V/m	v/h	dBm	dBi	dBm	dBm	
1869.00	127.6	v	24.6	7.0	31.6	29.5	Note 1 and 2
1869.00	126.4	h	19.9	7.0	26.9	24.7	Note 1 and 2

Note 1: Field Strength = Measured - reduced by dB = S.A. level that will be measured. The reduced by dB was then added to the signal generators (Pin) level to get the correct output power and then added the Gain (dBi) of the antenna.

Note 2: Pin is the power input (dBm) to the substitution antenna to obtain the field strength recorded from the EUT. G is the gain (dBi) for the substitution antenna. ERP is the effective radiated power (Pin + GdBi - 2.2) from the substitution antenna. EIRP is calculated as follows (Pin+GdBi)