



TEST REPORT

KCTL Inc. 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr		Report No.: KR20-SRF0092-A Page (1) of (8)	
1. Client <ul style="list-style-type: none"> ◦ Name : ShinHeung Precision Co., Ltd. ◦ Address : 53, Je3gongdan3-gil, Seoun-myeon, Anseong-si, Gyeonggi-do, Korea ◦ Date of Receipt : 2019-10-04 			
2. Use of Report : Certification			
3. Name of Product and Model : KIOSK / SK-161			
4. Manufacturer and Country of Origin : ShinHeung Precision Co., Ltd. / Korea			
5. FCC ID : O8HSK-161			
6. Date of Test : 2019-11-15 to 2019-11-21			
7. Test Standards : 47 CFR Part 1.1310			
8. Test Results : Refer to the test result in the test report			
Affirmation	Tested by	Technical Manager	
	Name : Euijung Kim	 (Signature)	 (Signature)
			2020-03-05
<h2>KCTL Inc.</h2>			
As a test result of the sample which was submitted from the client, this report does not guarantee the whole product quality. This test report should not be used and copied without a written agreement by KCTL Inc.			

Report revision history

Date	Revision	Page No
2020-03-04	Initial report	-
2020-03-05	Updated	8

This report shall not be reproduced except in full, without the written approval of KCTL Inc. This document may be altered or revised by KCTL Inc. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KCTL Inc. will constitute fraud and shall nullify the document. This test report is a general report that does not use the KOLAS accreditation mark and is not related to KOLAS accreditation.

Note. The report No. KR20-SRF0092 is superseded by the report No. KR20-SRF0092-A.



CONTENTS

1.	General information	4
2.	Device information	4
2.1.	Information about derivative model	5
2.2.	Frequency/channel operations.....	5
3.	Measurement uncertainty	6
4.	RF Exposure.....	7
4.1.	Test results.....	8



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR20-SRF0092-A

Page (4) of (8)



1. General information

Client : ShinHeung Precision Co., Ltd.
Address : 53, Je3gongdan3-gil, Seoun-myeon, Anseong-si, Gyeonggi-do, Korea
Manufacturer : ShinHeung Precision Co., Ltd.
Address : 53, Je3gongdan3-gil, Seoun-myeon, Anseong-si, Gyeonggi-do, Korea
Laboratory : KCTL Inc.
Address : 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea
Accreditations : FCC Site Designation No: KR0040, FCC Site Registration No: 687132
VCCI Registration No. : R-20080, G-20078, C-20059, T-20056
Industry Canada Registration No. : 8035A
KOLAS No.: KT231

2. Device information

Equipment under test : KIOSK
Model : SK-161
Derivative Model : SK-361, SK-561
Modulation technique : WIFI(802.11a/b/g/n)_DSSS, OFDM
Power source : AC 120 V
Antenna specification : Dipole Antenna
Antenna gain : 3.42 dBi
Operation temperature : 21 °C
Software version : Windows 10 Enterprise 2016 LTSC
Hardware version : VER1.0
Frequency range & Number of channels
2 412 MHz ~ 2 462 MHz : WIFI(802.11b/g/n_HT20)_11 ch
2 422 MHz ~ 2 452 MHz : WIFI(802.11n_HT40)_09 ch

2.1. Information about derivative model

The difference between basic model and derivative models is:

Derivative models are for the different buyer code.

2.2. Frequency/channel operations

This device contains the following capabilities:

802.11b/g/n(HT20/40)

Ch.	Frequency (MHz)
301	2 412
⋮	⋮
06	2 437
⋮	⋮
11	2 462

Table 2.2.1. 802.11b/g/n(HT20) mode

Ch.	Frequency (MHz)
03	2 422
⋮	⋮
06	2 442
⋮	⋮
09	2 452

Table 2.2.2. 802.11n HT40 mode

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR20-SRF0092-A

Page (6) of (8)



3. Measurement uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013.

All measurement uncertainty values are shown with a coverage factor of $k=2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded uncertainty (\pm)
Conducted RF power	1.76 dB



4. RF Exposure

FCC

Regulation

This document is prepared to show compliance with the RF Exposure requirements as required in §1.1310 of the FCC rules and Regulations.

The limit for Maximum Permissible Exposure (MPE), specified in FCC §1.1310, is listed in Table 1-1. According to FCC §1.1310: the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b).

Table 1 – Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength [V/m]	Magnetic Field Strength [A/m]	Power Density [mW/cm ²]	Averaging Time [minute]
(A) Limits for Occupational / Controlled Exposure				
0.3 ~ 3.0	614	1.63	*100	6
3.0 ~ 30	1842/f	4.89/f	*900/f ²	6
30 ~ 300	61.4	0.163	1.0	6
300 ~ 1 500	/	/	f/300	6
1 500 ~ 15 000	/	/	5	6
(B) Limits for General Population / Uncontrolled Exposure				
0.3 ~ 1.34	614	1.63	*100	30
1.34 ~ 30	824/f	2.19/f	*180/f ²	30
30 ~ 300	27.5	0.073	0.2	30
300 ~ 1 500	/	/	f/1 500	30
1 500 ~ 15 000	/	/	1.0	30

f=frequency in MHz, * = plane-wave equivalent power density

Per the guidance of KDB 680106, the E-field and H-field limits shown in the table above are extended down to 100 kHz

4.1. Test results

FCC

MPE (Maximum Permissible Exposure) Prediction

Predication of MPE limit at a given distance: Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2 \quad (\Rightarrow R = \sqrt{PG/4\pi S})$$

S = power density [mW/cm²]

P = Power input to antenna [mW]

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna [cm]

RF Exposure Compliance Issue

The information should be included in the user's manual:

This appliance and its antenna must not be co-located or operation is conjunction with any other antenna or transmitter. A minimum separation distance of 20 cm must be maintained between the antenna and the person for this appliance to satisfy the RF exposure requirements.

Note.

1. The power density P_d (5th column) at a distance of 20 cm calculated from the friis transmission Formula is far below the limit of 1 mW/cm².

2. Unequal antenna gains, with equal transmit powers. For antenna gains given by G₁, G₂, ..., G_N dBi (i) If transmit signals are correlated, then

Directional gain = 10 log[(10G₁/20 + 10G₂/20 + ... + 10G_N/20)/2/NANT] dB i [Note the "20"s in the denominator of each exponent and the square of the sum of terms; the object is to combine the signal levels coherently.]

Calculation Result of RF exposure

Maximum tune-up tolerance

-WLAN (2.4 GHz)

Mode	Frequency [MHz]	Max Tune-up Power [dBm]	Max Tune-up Power [mW]	Ant Gain [dBi]	Ant Gain [mW]	Power density at 20 cm [mW/cm ²]	Limit [mW/cm ²]
802.11 b	2 462	16.50	44.67	3.42	2.20	0.019 53	1.000 00

End of test report