

TecNet International Inc.

1420 N.W. Vivion Road Suite 109 Kansas City Missouri United States

§1.1307 and §2.1093-RF EXPOSURE EVULATION

1.1 Limit

§ 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b).

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

LIVITS FOR WAXIMOW I ERWISSIBLE EXI OSURE (WILE)				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm2)	Average Time (minutes)
(A) Limits for Occupational/Control Exposures				
30 - 300	61.4	0.163	1.0	6
300 - 1500			f/300	6
(B) Limits for General Population/Uncontrolled Exposure				
30 - 300	27.5	0.073	0.2	30
300 - 1500			f/1500	30

Note: f is frequency in MHz

1.2 Method of Measurements

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi \cdot r^2} = \frac{EIRP}{4\pi \cdot r^2}$$

Where,

P: power input to the antenna in mW

EIRP: Equivalent (effective) isotropic radiated power.

S: power density mW/cm2

G: numeric gain of antenna relative to isotropic radiator

r: distance to centre of radiation in cm

$$r = \sqrt{\frac{PG}{4\pi \cdot S}} = \sqrt{\frac{EIRP}{4\pi \cdot S}}$$

FCC radio frequency exposure limits may be exceeded at distances closer than r cm from the antenna of this device.

1.3 Evaluation of RF Exposure Compliance Requirements

Maximum RF Power conducted, P [dBm] = 46.04

Maximum Antenna Gain, G[dBi] = 0

Maximum EIRP, P [dBm] = 46.04

User-based time-average for PTT = 50%

Peak EIRP = 47.01 dBm + 0 dBi = 47.02 dBm = 40,180 mWatts (worst case)

Average EIRP = 50% * EIRP = 20,090 mWatts

MPE Limit for Occupational/Controlled Exposure, S [mW/cm2] = 1.0

MPE Limit for General Population/Uncontrolled Exposure, S [mW/cm2] = 0.2

Calculation of Minimum RF Safety Distance Limits:

Calculated RF Safety Distance for Occupational/Controlled Exposure,

r [cm] = 39.98

Calculated RF Safety Distance for General Population/Uncontrolled Exposure,

r [cm] = 89.40

Results: Manufacturer declares RF Safety Distance of 40 cm for Occupational/Controlled Exposure and 90 cm for General Population/Uncontrolled Exposure which met the FCC Limits. Please refer to Users Manual for details of RF Exposure Information.