FCC ID: 09C-WL560 Issued on Aug. 05, 2004

5.10. RF Exposure

5.10.1. Limit For Maximum Permissible Exposure (MPE)

This product can be classified as mobile device, so the 20cm separation distance warning is required.

In this section, the power density at 20cm location is calculated to examine if it is lower than the limit.

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm²)	Averaging Time E ², H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm²)	Averaging Time E ², H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

F = frequency in MHz

SPORTON International Inc.

TEL: 886-2-2696-2468 FAX: 886-2-2696-2255 Page No. : 112 of 116
Issued Date : Aug. 05, 2004

Report No.: F453118

^{*}Plane-wave equivalent power density

FCC ID: 09C-WL560 Issued on Aug. 05, 2004

5.10.2. MPE Calculation Method

$$E (V/m) = \frac{\sqrt{30 \times P \times G}}{d}$$
 Power Density: $Pd \text{ (mW/cm}^2\text{)} = \frac{E^2}{377}$

 $\mathbf{E} = \text{Electric field} \quad (V/m)$

P = Peak RF output power (mW)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=2.5cm, as well as the gain of the used antenna, the RF power density can be obtained.

TEL: 886-2-2696-2468 FAX: 886-2-2696-2255 Report No.: F453118



FCC ID: O9C-WL560 Issued on Aug. 05, 2004

5.10.3. Calculated Result and Limit

Only the mode with maximum Gain was calculated (${\sf Mode\ 1}$).

Normal Mode

Channel No.	Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm²)	Limit of Power Density (S) (mW/cm²)
Channel 22	5	3.16	23.65	231.7395	0.1459	1

Turbo Mode

Channel No.	Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm²)	Limit of Power Density (S) (mW/cm²)
Channel 03	5	3.16	18.5000	70.7946	0.0446	1

TEL: 886-2-2696-2468 FAX: 886-2-2696-2255 Page No. : 114 of 116
Issued Date : Aug. 05, 2004

Report No.: F453118