

Technical Description

This device is a Bridging kit - 802.11a operates in 5GHz with OFDM technique. The transmitter rate could be 1/2/5.5/6/9/11/12/18/24/36/48/54Mbps, and the maximum data rate could be up to 108Mbps in turbo mode. The transmitter of the EUT is powered by POE (Power over Ethernet). The antenna The antennas used in this product are as below:

No.	Model	Antnnna Type	2.4/ 5GHz Antenna Gain	Connector Type
1	3CWE591 (Z1996)	High gain omni antenna	6/ 8 dBi	N Female
2	3CWE598 (Z1997)	Medium gain panel antenna	8/ 10 dBi	N Female
3	3CWE596	High gain panel antenna	18/ 20 dBi	N Female

Under normal use condition, the user has to keep at least 20 cm separation distance between radiator and the body of the user.

For more detailed instruction, please refer to the user's manual.

FCC 15.407(c) states : The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals.

Applicants shall include in their application for equipment authorization a description of hoe this requirement is met.

Data transmission is always initiated by software, which is then pass down through the MAC, through the digital and analog baseband, and finally to the RF chip. Several special packets (ACKs, CTS, PSPoll, etc...) are initiated by the MAC. There are the only ways the digital baseband portion will turn on the RF transmitter, which it then turns off at the end of the packet. Therefore, the transmitter will be on only while one of the aforementioned packets are being transmitted.