

FASTRACK M1213: ALLGON 1140.27 ANTENNA SPECIFICATION

Electrical and Mechanical data for MiniMag & Sputnik magnet mount antenna



Electrical

■ Frequency	1140.4 1140.14 1140.24; 1140.27 1140.26	890-960 MHz 1700-2500 MHz 824-894/1850-1990 MHz 890-960/1710-1880 MHz
■ Impedance	Nominal 50 Ω	
■ Polarization	linear vertical	
■ VSWR	1140.4 1140.14 1140.24; 1140.27; 1140.26	1.7:1 @ BW 8% 2:1 @ BW 8% 2:1 @ BW 8%
■ Gain	1140.14; 1140.26; 1140.27 1140.4; 1140.24	0 dBd 3 dBd (low band)/0 dBd (high band)
■ Max Power	10 W	

Mechanical

■ Dimension	Base	27 x 20 (ØxH) mm
■ Height with radiator	1140.4 1140.14 1140.24 1140.26; 1140.27	270 mm 16.5 mm 300 mm 53 mm
■ Weight	1140.4 1140.14 1140.24 1140.26; 1140.27 1150.2; 1150.3	63 g 59 g 73 g 59 g 74 g (incl Sputnik)
■ Material	Base: ABS	
■ Colour	Black	

Environmental

■ Temperature	Storage: -40°C +80°C Operating: -25°C +70°C
---------------	------------------------------------------------

Other

■ Cable	Mini Low Loss 2.5 m
■ Connector	FME (female)
■ ISO9001 Certified	

Sizarteq reserves the right to change specifications without prior notice.