



# PCTEST Engineering Laboratory, Inc.

6660-B Dobbin Road • Columbia, MD 21045 • U.S.A.

TEL (410) 290-6652 • FAX (410) 290-6654

<http://www.pctestlab.com>



## CERTIFICATE OF COMPLIANCE FCC Part 24 & 22 Certification

WAVECOM, INC.  
4810 Eastgate Mall, 2<sup>nd</sup> Floor  
San Diego, CA 92121  
Attn: Kye Cheung, Director of Marketing

Dates of Tests: Sept. 25-26, 2002  
Test Report S/N: 22/24.220925529.09E  
Test Site: PCTEST Lab, Columbia MD

FCC ID

**09EQ23X8001**

APPLICANT

**WAVECOM, INC.**

Classification: Licensed Portable Transmitter Held to Ear (PCE)  
FCC Rule Part(s): §24(E), §22.901(d); §2  
EUT Type: Dual-Band CDMA Wireless Module  
Model: *WISMO QUIK Q2338*  
Tx Frequency Range: 824.70 – 848.31MHz (CDMA) / 1851.25MHz – 1908.75MHz (PCS CDMA)  
Rx Frequency Range: 869.70 – 893.31MHz (CDMA) / 1931.25MHz – 1988.75MHz (PCS CDMA)  
Max. RF Output Power: 0.247 W ERP CDMA (23.933 dBm) / 0.327 W EIRP PCS CDMA (25.151 dBm)  
Max. SAR Measurement: 0.252W/kg CDMA Head SAR; 0.0380W/kg CDMA Body SAR;  
0.597W/kg PCS CDMA Head SAR; 0.0405W/kg PCS CDMA Body SAR  
Emission Designator(s): 1M25F9W (CDMA)

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

*PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.*

**Alfred Cirwithian**  
Vice President Engineering





PCTEST™ PT. 22/24 REPORT	FCC CERTIFICATION			Reviewed By: Quality Manager
Test Report S/N: 22/24.220925529.09E	Test Dates: SEPT. 25-26, 2002	EUT Type: Dual-Band CDMA Wireless Module	FCC ID: 09EQ23X8001	Page 1 of 24



## TABLE OF CONTENTS

---

<b>ATTACHMENT A:</b>	<b>COVER LETTER(S)</b>	
<b>ATTACHMENT B:</b>	<b>ATTESTATION STATEMENT(S)</b>	
<b>ATTACHMENT C:</b>	<b>TEST REPORT</b>	
1.1	SCOPE	3
2.1	INTRODUCTION	4
3.1	INSERTS	5
4.1	DESCRIPTION OF TESTS	6-8
5.1	EFFECTIVE RADIATED POWER OUTPUT	9
6.1	EQUIVALENT ISOTROPIC RADIATED POWER	10
7.1	RADIATED MEASUREMENTS	11-16
8.1	FREQUENCY STABILITY	17-20
9.1	PLOTS OF EMISSIONS	21
10.1	LIST OF TEST EQUIPMENT	22
11.1	SAMPLE CALCULATIONS	23
12.1	CONCLUSION	24
<b>ATTACHMENT D:</b>	<b>TEST PLOTS</b>	
<b>ATTACHMENT E:</b>	<b>FCC ID LABEL / LOCATION</b>	
<b>ATTACHMENT F:</b>	<b>TEST SETUP PHOTOGRAPHS</b>	
<b>ATTACHMENT G:</b>	<b>EXTERNAL PHOTOGRAPHS</b>	
<b>ATTACHMENT H:</b>	<b>INTERNAL PHOTOGRAPHS</b>	
<b>ATTACHMENT I:</b>	<b>BLOCK DIAGRAM(S)</b>	
<b>ATTACHMENT J:</b>	<b>SCHEMATIC DIAGRAM(S)</b>	
<b>ATTACHMENT K:</b>	<b>OPERATIONAL / CIRCUIT DESCRIPTION</b>	
<b>ATTACHMENT L:</b>	<b>PARTS LIST/TUNE UP PROCEDURE</b>	
<b>ATTACHMENT M:</b>	<b>USER'S MANUAL</b>	
<b>ATTACHMENT N:</b>	<b>SAR MEASUREMENT REPORT</b>	
<b>ATTACHMENT O:</b>	<b>SAR TEST DATA</b>	
<b>ATTACHMENT P:</b>	<b>SAR TEST SETUP PHOTOGRAPHS</b>	
<b>ATTACHMENT Q:</b>	<b>DIPOLE VALIDATION</b>	
<b>ATTACHMENT R:</b>	<b>PROBE CALIBRATION</b>	

PCTEST™ PT. 22/24 REPORT	 <b>FCC CERTIFICATION</b> 			Reviewed By: Quality Manager
Test Report S/N: 22/24.220925529.09E	Test Dates: SEPT. 25-26, 2002	EUT Type: Dual-Band CDMA Wireless Module	FCC ID: 09EQ23X8001	Page 2 of 24

# MEASUREMENT REPORT





## 1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.

## §2.1033 General Information

**Applicant Name:** WAVECOM, Inc.  
**Address:** 4810 Eastgate Mall, 2<sup>nd</sup> Floor  
 San Diego, CA 92121  
**Attention:** Kye Cheung, Director of Marketing

- FCC ID: 09EQ23X8001
- Model: WISMO Quik Q2338
- Quantity: Quantity production is planned
- Emission Designators: 1M25F9W (CDMA)
- Tx Freq. Range: 824.70 – 848.31 MHz (CDMA)  
1851.25 – 1908.75 MHz (PCS CDMA)
- Rx Freq. Range: 869.70 – 893.31 MHz (CDMA)  
1931.25 – 1988.75 MHz (PCS CDMA)
- Max. Power Rating: 0.247 W ERP CDMA (23.933 dBm)  
0.327 W EIRP PCS CDMA (25.151 dBm)
- FCC Classification(s): Licensed Portable Tx Held to Ear (PCE)
- Equipment (EUT) Type: Dual-Band CDMA Wireless Module
- Modulation(s): CDMA
- Frequency Tolerance:  $\pm 0.00025\%$  (2.5 ppm)
- FCC Rule Part(s): § 24(E), §22.901(d)
- Dates of Tests: Sept. 25-26, 2002
- Place of Tests: PCTEST Lab, Columbia, MD U.S.A.
- Test Report S/N: 22/24.220925529.09E

PCTEST™ PT. 22/24 REPORT	 <b>FCC CERTIFICATION</b> 			Reviewed By: Quality Manager
Test Report S/N: 22/24.220925529.09E	Test Dates: SEPT. 25-26, 2002	EUT Type: Dual-Band CDMA Wireless Module	FCC ID: 09EQ23X8001	Page 3 of 24

## 2.1 INTRODUCTION




Figure 1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area.

These measurement tests were conducted at **PCTEST Engineering Laboratory, Inc.** facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49'38" W longitude. The facility is 1.5 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4 on October 19, 1992.

### Measurement Procedure

The radiated and spurious measurements were made outdoors at a 3-meter test range (see Figure2). The equipment under test is placed on a wooden turntable 3-meters from the receive antenna.

The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.




Figure 2. Diagram of 3-meter outdoor test range

PCTEST™ PT. 22/24 REPORT	FCC CERTIFICATION		wavecom®	Reviewed By: Quality Manager
Test Report S/N: 22/24.220925529.09E	Test Dates: SEPT. 25-26, 2002	EUT Type: Dual-Band CDMA Wireless Module	FCC ID: 09EQ23X8001	Page 4 of 24

## 3.1 INSERTS

---

### **Function of Active Devices (Confidential)**

The Function of active devices are shown in Attachment K.

### **Block & Schematic Diagrams (Confidential)**

The block diagrams are shown in Attachment I, and the schematic diagrams are shown in Attachment J.

### **Operating Instructions**

The instruction manual is shown in Attachment M.

### **Parts List & Tune-Up Procedure (Confidential)**



The parts list & tune-up procedure is shown in Attachment L.

### **Description of Freq. Stabilization Circuit (Confidential)**

The description of frequency stabilization circuit is shown in Attachment K.

### **Description for Suppression of Spurious Radiation, for Limiting Modulation, and Harmonic Suppresion Circuits (Confidential)**

The description of suppression stabilization circuits is shown in Attachment K.

PCTEST™ PT. 22/24 REPORT	 FCC CERTIFICATION 			Reviewed By: Quality Manager
Test Report S/N: 22/24.220925529.09E	Test Dates: SEPT. 25-26, 2002	EUT Type: Dual-Band CDMA Wireless Module	FCC ID: 09EQ23X8001	Page 5 of 24



## 4.1 DESCRIPTION OF TESTS

### 4.2 Occupied Bandwidth Emission Limits

- (a) On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log(P)$  dB.
- (b) Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.
- (c) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the licensee's frequency block edges, both upper and lower, as the design permits.
- (d) The measurement of emission power can be expressed in peak or average values, provided they are expressed in the same parameters as the transmitter power.

BLOCK	Freq. Range (MHz) Transmitter (Tx)	Freq. Range (MHz) Receiver (Rx)
A	1850 - 1865	1930 - 1945
B	1870 - 1885	1950 - 1965
C	1895 - 1910	1975 - 1990
D	1865 - 1870	1945 - 1950
E	1885 - 1890	1965 - 1970
F	1890 - 1895	1970 - 1975

Table 1. Broadband PCS Service Frequency Blocks.

PCTEST™ PT. 22/24 REPORT	 <b>FCC CERTIFICATION</b> 			Reviewed By: Quality Manager
Test Report S/N: 22/24.220925529.09E	Test Dates: SEPT. 25-26, 2002	EUT Type: Dual-Band CDMA Wireless Module	FCC ID: 09EQ23X8001	Page 6 of 24

## 4.1 DESCRIPTION OF TESTS (CONTINUED)

---

### **4.3 Spurious and Harmonic Emissions at Antenna Terminal**

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to 10 GHz. The transmitter is modulated with a 2500Hz tone at a level of 16dB greater than that required to provide 50% modulation.



At the input terminals of the spectrum analyzer, an isolator (RF circulator with one port terminated with 50 ohms) and an 870 MHz to 890 MHz bandpass filter is connected between the test transceiver (for conducted tests) or the receive antenna (for radiated tests) and the analyzer. The rejection of the bandpass filter to signals in the 825 – 845 MHz range is adequate to limit the transmit energy from the test transceiver which appears to a level which will allow the analyzer to measure signals less than –90dBm. Calibration of the test receiver is performed in the 870 – 890 MHz range to insure accuracy to allow variation in the bandpass filter insertion loss to be calibrated.

### **4.4 Frequencies**

At the input terminals of the spectrum analyzer, an isolator (RF pad) and a high-pass filter are connected between the test transceiver (for conducted tests) or the receive antenna (for radiated tests) and the analyzer. The high-pass filter (signals below 1.6 GHz) is to limit the fundamental frequency from interfering with the measurement of low-level spurious and harmonic emissions and to ensure that the preamplifier is not saturated.

### **4.5 Radiation Spurious and Harmonic Emissions**

Radiation and harmonic emissions are measured outdoors at our 3-meter test range. The equipment under test is placed on a wooden turntable 3-meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer reading. This level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST™ PT. 22/24 REPORT	 <b>FCC CERTIFICATION</b> 			Reviewed By: Quality Manager
Test Report S/N: 22/24.220925529.09E	Test Dates: SEPT. 25-26, 2002	EUT Type: Dual-Band CDMA Wireless Module	FCC ID: 09EQ23X8001	Page 7 of 24

## 5.0 Frequency Stability/Temperature Variation.

The frequency stability of the transmitter is measured by:



- a.) **Temperature:** The temperature is varied from -30°C to +60°C using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the voltage normally at the input to the device or at the power supply terminals if cables are not normally supplied.

*Specification – The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within  $\pm 0.00025$  ( $\pm 2.5$  ppm) of the center frequency.*

### **Time Period and Procedure:**

1. The carrier frequency of the transmitter and the individual oscillators is measured at room temperature (25°C to 27°C to provide a reference).
2. The equipment is subjected to an overnight “soak” at -30°C without any power applied.
3. After the overnight “soak” at 30°C (usually 14-16 hours), the equipment is turned on in a “standby” condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter and the individual oscillators is made within a three minute interval after applying power to the transmitter.
4. Frequency measurements are made at 10°C interval up to room temperature. At least a period of one and one half-hour is provided to allow stabilization of the equipment at each temperature level.
5. Again the transmitter carrier frequency and the individual oscillators is measured at room temperature to begin measurement of the upper temperature levels.
6. Frequency measurements are at 10 intervals starting at 30°C up to +50°C allowing at least two hours at each temperature for stabilization. In all measurements the frequency is measured within three minutes after re-applying power to the transmitter.
7. The artificial load is mounted external to the temperature chamber.

**NOTE: The EUT is tested down to the battery endpoint.**

PCTEST™ PT. 22/24 REPORT	 <b>FCC CERTIFICATION</b> 			Reviewed By: Quality Manager
Test Report S/N: 22/24.220925529.09E	Test Dates: SEPT. 25-26, 2002	EUT Type: Dual-Band CDMA Wireless Module	FCC ID: 09EQ23X8001	Page 8 of 24

## 5.1 Test Data

### 5.2 Effective Radiated Power Output



#### A. POWER: High (CDMA Mode)

Freq. Tuned (MHz)	REF. LEVEL (dBm)	POL (H/V)	ERP (W)	ERP (dBm)
824.70	-17.400	V	0.24450	23.883
835.89	-17.500	V	0.24733	23.933
848.31	-17.700	V	0.24394	23.873

#### NOTES:

Effective Radiated Power Output Measurements by Substitution  
Method according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the dipole is measured. The ERP is recorded.

PCTEST™ PT. 22/24 REPORT	 <b>FCC CERTIFICATION</b> 			Reviewed By: Quality Manager
Test Report S/N: 22/24.220925529.09E	Test Dates: SEPT. 25-26, 2002	EUT Type: Dual-Band CDMA Wireless Module	FCC ID: 09EQ23X8001	Page 9 of 24

## 6.1 Test Data

### 6.2 Equivalent Isotropic Radiated Power (E.I.R.P.)

Radiated measurements at 3 meters

Supply Voltage: 3.7 VDC



Modulation: PCS CDMA

FREQ. (MHz)	REF. LEVEL (dBm)	POL (H/V)	Azimuth (o angle)	EIRP (dBm)	EIRP (W)
1851.25	-18.000	V	60	25.081	0.322
1880.00	-18.100	V	60	25.151	0.327
1908.75	-18.300	V	60	25.121	0.325

#### NOTES:

Equivalent Isotropic Radiated Power Measurements by Substitution  
Method according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A Horn antenna was substituted in place of the EUT. This Horn antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the Horn antenna is measured. The difference between the gain of the horn and an isotropic antenna is taken into consideration and the EIRP is recorded.

PCTEST™ PT. 22/24 REPORT	 FCC CERTIFICATION			Reviewed By: Quality Manager
Test Report S/N: 22/24.220925529.09E	Test Dates: SEPT. 25-26, 2002	EUT Type: Dual-Band CDMA Wireless Module	FCC ID: 09EQ23X8001	Page 10 of 24

## 7.1 Test Data

### 7.2 CELLULAR CDMA Radiated Measurements

#### Field Strength of SPURIOUS Radiation



OPERATING FREQUENCY: 824.70 MHz  
 CHANNEL: 1013 (Low)  
 MEASURED OUTPUT POWER: 23.933 dBm = 0.247 W  
 MODULATION SIGNAL: CDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  36.93 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1649.40	-52.58	6.10	-46.48	V	70.4
2474.10	-52.28	6.70	-45.58	V	69.5
3298.80	-62.88	6.80	-56.08	V	80.0

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method  
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST™ PT. 22/24 REPORT	 <b>FCC CERTIFICATION</b> 			Reviewed By: Quality Manager
Test Report S/N: 22/24.220925529.09E	Test Dates: SEPT. 25-26, 2002	EUT Type: Dual-Band CDMA Wireless Module	FCC ID: 09EQ23X8001	Page 11 of 24

## 7.1 Test Data (Continued)

### 7.3 CELLULAR CDMA Radiated Measurements

#### Field Strength of SPURIOUS Radiation



OPERATING FREQUENCY: 835.89 MHz  
 CHANNEL: 0363 (Mid)  
 MEASURED OUTPUT POWER: 23.933 dBm = 0.247 W  
 MODULATION SIGNAL: CDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  36.93 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1671.78	-52.88	6.10	-46.78	V	70.7
2507.67	-51.88	6.70	-45.18	V	69.1
3343.56	-64.38	6.80	-57.58	V	81.5

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method  
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST™ PT. 22/24 REPORT	 <b>FCC CERTIFICATION</b> 			Reviewed By: Quality Manager
Test Report S/N: 22/24.220925529.09E	Test Dates: SEPT. 25-26, 2002	EUT Type: Dual-Band CDMA Wireless Module	FCC ID: 09EQ23X8001	Page 12 of 24

## 7.1 Test Data (Continued)

### 7.4 CELLULAR CDMA Radiated Measurements

#### Field Strength of SPURIOUS Radiation



OPERATING FREQUENCY: 848.31 MHz  
 CHANNEL: 0777 (High)  
 MEASURED OUTPUT POWER: 23.933 dBm = 0.247 W  
 MODULATION SIGNAL: CDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  36.93 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1696.62	-51.98	6.10	-45.88	V	69.8
2544.93	-51.78	6.70	-45.08	V	69.0
3393.24	-62.38	6.80	-55.58	V	79.5

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method  
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST™ PT. 22/24 REPORT	 <b>FCC CERTIFICATION</b> 		Reviewed By: Quality Manager
Test Report S/N: 22/24.220925529.09E	Test Dates: SEPT. 25-26, 2002	EUT Type: Dual-Band CDMA Wireless Module	FCC ID: 09EQ23X8001
Page 13 of 24			

## 7.1 Test Data (Continued)

### 7.5 PCS CDMA Radiated Measurements

#### Field Strength of SPURIOUS Radiation



OPERATING FREQUENCY: 1851.25 MHz  
 CHANNEL: 0025 (Low)  
 MEASURED OUTPUT POWER: 25.151 dBm = 0.327 W  
 MODULATION SIGNAL: CDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  38.15 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
3702.50	-44.33	8.70	-35.63	V	60.8
5553.75	-43.43	9.70	-33.73	V	58.9
7405.00	-61.93	9.90	-52.03	V	77.2

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method  
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST™ PT. 22/24 REPORT	 <b>FCC CERTIFICATION</b> 		Reviewed By: Quality Manager
Test Report S/N: 22/24.220925529.09E	Test Dates: SEPT. 25-26, 2002	EUT Type: Dual-Band CDMA Wireless Module	FCC ID: 09EQ23X8001
© 2002 PCTEST ENGINEERING LABORATORY, INC.			Page 14 of 24

## 7.1 Test Data (Continued)

### 7.6 PCS CDMA Radiated Measurements

#### Field Strength of SPURIOUS Radiation



OPERATING FREQUENCY: 1880.00 MHz  
 CHANNEL: 0600 (Mid)  
 MEASURED OUTPUT POWER: 25.151 dBm = 0.327 W  
 MODULATION SIGNAL: CDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  38.15 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
3760.00	-43.53	8.70	-34.83	V	60.0
5640.00	-43.03	9.70	-33.33	V	58.5
7520.00	-61.03	9.90	-51.13	V	76.3

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method  
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST™ PT. 22/24 REPORT	 <b>FCC CERTIFICATION</b> 		Reviewed By: Quality Manager
Test Report S/N: 22/24.220925529.09E	Test Dates: SEPT. 25-26, 2002	EUT Type: Dual-Band CDMA Wireless Module	FCC ID: 09EQ23X8001
© 2002 PCTEST ENGINEERING LABORATORY, INC.			Page 15 of 24

## 7.1 Test Data (Continued)

### 7.7 PCS CDMA Radiated Measurements

#### Field Strength of SPURIOUS Radiation



OPERATING FREQUENCY: 1908.75 MHz  
 CHANNEL: 1175 (High)  
 MEASURED OUTPUT POWER: 25.151 dBm = 0.327 W  
 MODULATION SIGNAL: CDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  38.15 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
3817.50	-44.53	8.70	-35.83	V	61.0
5726.25	-43.33	9.70	-33.63	V	58.8
7635.00	-61.93	9.90	-52.03	V	77.2

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method  
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST™ PT. 22/24 REPORT	 <b>FCC CERTIFICATION</b> 			Reviewed By: Quality Manager
Test Report S/N: 22/24.220925529.09E	Test Dates: SEPT. 25-26, 2002	EUT Type: Dual-Band CDMA Wireless Module	FCC ID: 09EQ23X8001	Page 16 of 24

## 8.1 Test Data

### 8.2 FREQUENCY STABILITY (CDMA)



OPERATING FREQUENCY: 835,890,004 Hz

CHANNEL: 363

REFERENCE VOLTAGE: 4.0 VDC


DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm



VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQ. (Hz)	Deviation (%)
100 %	4.00	+ 20 (Ref)	835,890,004	0.000000
100 %		- 30	835,889,920	0.000010
100 %		- 20	835,889,929	0.000009
100 %		- 10	835,889,920	0.000010
100 %		0	835,889,962	0.000005
100 %		+ 10	835,889,937	0.000008
100 %		+ 20	835,890,004	0.000000
100 %		+ 25	835,889,962	0.000005
100 %		+ 30	835,889,987	0.000002
100 %		+ 40	835,890,029	-0.000003
100 %		+ 50	835,890,071	-0.000008
100 %		+ 60	835,890,088	-0.000010
85 %	3.17	+ 20	835,890,004	0.000000
115 %	4.60	+ 20	835,890,004	0.000000
BATT. ENDPOINT	2.94	+ 20	835,890,004	0.000000

PCTEST™ PT. 22/24 REPORT	 <b>FCC CERTIFICATION</b> 			Reviewed By: Quality Manager
Test Report S/N: 22/24.220925529.09E	Test Dates: SEPT. 25-26, 2002	EUT Type: Dual-Band CDMA Wireless Module	FCC ID: 09EQ23X8001	Page 17 of 24

## 8.1 Test Data (Continued)

### 8.3 FREQUENCY STABILITY (CDMA)



PCTEST™ PT. 22/24 REPORT	 <b>FCC CERTIFICATION</b>			Reviewed By: Quality Manager
Test Report S/N: 22/24.220925529.09E	Test Dates: SEPT. 25-26, 2002	EUT Type: Dual-Band CDMA Wireless Module	FCC ID: 09EQ23X8001	Page 18 of 24

## 8.1 Test Data (Continued)

### 8.4 FREQUENCY STABILITY (PCS CDMA)



OPERATING FREQUENCY: 1,880,000,003 Hz

CHANNEL: 600

REFERENCE VOLTAGE: 4.0 VDC


DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm



VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQ. (Hz)	Deviation (%)
100 %	4.00	+ 20 (Ref)	1,880,000,003	0.000000
100 %		- 30	1,879,999,834	0.000009
100 %		- 20	1,879,999,853	0.000008
100 %		- 10	1,879,999,815	0.000010
100 %		0	1,879,999,909	0.000005
100 %		+ 10	1,879,999,890	0.000006
100 %		+ 20	1,880,000,003	0.000000
100 %		+ 25	1,879,999,909	0.000005
100 %		+ 30	1,879,999,965	0.000002
100 %		+ 40	1,880,000,116	-0.000006
100 %		+ 50	1,880,000,153	-0.000008
100 %		+ 60	1,880,000,191	-0.000010
85 %	3.17	+ 20	1,880,000,003	0.000000
115 %	4.60	+ 20	1,880,000,003	0.000000
BATT. ENDPOINT	2.94	+ 20	1,880,000,003	0.000000

PCTEST™ PT. 22/24 REPORT	 <b>FCC CERTIFICATION</b> 			Reviewed By: Quality Manager
Test Report S/N: 22/24.220925529.09E	Test Dates: SEPT. 25-26, 2002	EUT Type: Dual-Band CDMA Wireless Module	FCC ID: 09EQ23X8001	Page 19 of 24

## 8.1 Test Data (Continued)

### 8.5 FREQUENCY STABILITY (PCS CDMA)





PCTEST™ PT. 22/24 REPORT	<div><div><b>PCTEST</b> <small>Engineering Excellence, Inc.</small></div><div><b>FCC CERTIFICATION</b></div><div><b>wavecom</b><sup>SM</sup></div></div>			Reviewed By: Quality Manager
Test Report S/N: 22/24.220925529.09E	Test Dates: SEPT. 25-26, 2002	EUT Type: Dual-Band CDMA Wireless Module	FCC ID: 09EQ23X8001	Page 20 of 24

## 9.1 PLOT(S) OF EMISSIONS

---



(SEE ATTACHMENT D)

PCTEST™ PT. 22/24 REPORT	 <b>FCC CERTIFICATION</b> 			Reviewed By: Quality Manager
Test Report S/N: 22/24.220925529.09E	Test Dates: SEPT. 25-26, 2002	EUT Type: Dual-Band CDMA Wireless Module	FCC ID: 09EQ23X8001	Page 21 of 24

## 10.1 TEST EQUIPMENT

Type	Model	Cal. Due Date	S/N
Microwave Spectrum Analyzer	HP 8566B (100Hz-22GHz)	08/15/03	3638A08713
Microwave Spectrum Analyzer	HP 8566B (100Hz-22GHz)	04/17/03	2542A11898
Spectrum Analyzer/Tracking Gen.	HP 8591A (100Hz-1.8GHz)	08/10/03	3144A02458
Signal Generator*	HP 8640B (500Hz-1GHz)	06/03/03	2232A19558
Signal Generator*	HP 8640B (500Hz-1GHz)	06/03/03	1851A09816
Signal Generator*	Rohde & Schwarz (0.1-1000MHz)	09/11/03	894215/012
Ailtech/Eaton Receiver	NM 37/57A-SL (30-1000MHz)	04/12/03	0792-03271
Ailtech/Eaton Receiver	NM 37/57A (30-1000MHz)	03/11/03	0805-03334
Ailtech/Eaton Receiver	NM 17/27A (0.1-32MHz)	09/17/03	0608-03241
Quasi-Peak Adapter	HP 85650A	08/15/03	2043A00301
Ailtech/Eaton Adapter	CCA-7 CISPR/ANSI QP Adapter	03/11/03	0194-04082
Gigatronics Universal Power Meter	8657A		1835256
Gigatronics Power Sensor	80701A (0.05-18GHz)		1833460
Signal Generator	HP 8648D (9kHz-4GHz)		3613A00315
Amplifier Research	5SIG4 (5W, 800MHz-4.2GHz)		22322
Network Analyzer	HP 8753E (30kHz-3GHz)		JP38020182
Audio Analyzer	HP 8903B		3011A09025
Modulation Analyzer	HP 8901A		2432A03467
Power Meter	HP 437B		3125U24437
Power Sensor	HP 8482H (30μW-3W)		2237A02084
Harmonic/Flicker Test System	HP 6841A (IEC 555-2/3)		3531A00115
Broadband Amplifier (2)	HP 8447D		1145A00470, 1937A03348
Broadband Amplifier	HP 8447F		2443A03784
Horn Antenna	EMCO Model 3115 (1-18GHz)		9704-5182
Horn Antenna	EMCO Model 3115 (1-18GHz)		9205-3874
Horn Antenna	EMCO Model 3116 (18-40GHz)		9203-2178
Biconical Antenna (4)	Eaton 94455/Eaton 94455-1/Singer 94455-1/Compliance Design 1295, 1332, 0355		0608, 1103, 1104
Log-Spiral Antenna (3)	Ailtech/Eaton 93490-1		
Roberts Dipoles	Compliance Design (1 set)		
Ailtech Dipoles	DM-105A (1 set)		33448-111
EMCO LISN (6)	3816/2		1079
Microwave Preamplifier 40dB Gain	HP 83017A (0.5-26.5GHz)		3123A00181
Microwave Cables	MicroCoax (1.0-26.5GHz)		
Ailtech/Eaton Receiver	NM37/57A-SL		0792-03271
Spectrum Analyzer	HP 8594A		3051A00187
Spectrum Analyzer (2)	HP 8591A		3034A01395, 3108A02053
Microwave Survey Meter	Holaday Model 1501 (2.450GHz)		80931
Digital Thermometer	Extech Instruments 421305		426966
Attenuator	HP 8495A (0-70dB) DC-4GHz		
Bi-Directional Coax Coupler	Narda 3020A (50-1000MHz)		
Shielded Screen Room	RF Lindgren Model 26-2/2-0		6710 (PCT270)
Shielded Semi-Anechoic Chamber	Ray Proof Model S81		R2437 (PCT278)
Environmental Chamber	Associated Systems Model 1025 (Temperature/Humidity)		PCT285

\* Calibration traceable to the National Institute of Standards and Technology (NIST).

PCTEST™ PT. 22/24 REPORT	 <b>FCC CERTIFICATION</b> 			Reviewed By: Quality Manager
Test Report S/N: 22/24.220925529.09E	Test Dates: SEPT. 25-26, 2002	EUT Type: Dual-Band CDMA Wireless Module	FCC ID: 09EQ23X8001	Page 22 of 24

## 11.1 SAMPLE CALCULATIONS

---

### A. Emission Designator

Emission Designator = 1M25F9W

CDMA BW = 1.25 MHz

F = Frequency Modulation

9 = Composite Digital Info



W = Combination (Audio/Data)

(Measured at the 99.75% power bandwidth)

### B. Spurious Radiated Emission - PCS Band

Example: Channel 25 PCS Mode 2<sup>nd</sup> Harmonic (3702.50 MHz)



The receive analyzer reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the receive analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3702.50 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm - (-24.80) = 50.3 dBc

PCTEST™ PT. 22/24 REPORT	 FCC CERTIFICATION 			Reviewed By: Quality Manager
Test Report S/N: 22/24.220925529.09E	Test Dates: SEPT. 25-26, 2002	EUT Type: Dual-Band CDMA Wireless Module	FCC ID: 09EQ23X8001	Page 23 of 24

## 12.1 CONCLUSION

---

The data collected shows that the **WAVECOM Dual-Band CDMA Wireless Module FCC ID: 09EQ23X8001** complies with all the requirements of Parts 2, 22, and 24 of the FCC rules.

PCTEST™ PT. 22/24 REPORT	 <b>FCC CERTIFICATION</b> 			Reviewed By: Quality Manager
Test Report S/N: 22/24.220925529.09E	Test Dates: SEPT. 25-26, 2002	EUT Type: Dual-Band CDMA Wireless Module	FCC ID: 09EQ23X8001	Page 24 of 24