

INTERTEK TESTING SERVICES

RF Exposure

The equipment under test (EUT) is an RC Shark operating at 2.4G Band. The EUT can be powered by DC 3.0V (2 x 1.5V AAA batteries). For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna

Modulation Type: GFSK

Antenna Gain: 0dBi

The nominal conducted output power specified: -6.0 dBm (± 3 dB)

The nominal radiated output power (e.i.r.p) specified: -6.0 dBm (± 3 dB)

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 90.0 dB μ V/m at 3m in the frequency 2465MHz

The EIRP = [(FS*D) ^2 / 30] mW = -5.23dBm

which is within the production variation.

The Minimum peak radiated emission for the EUT is 86.9 dB μ V/m at 3m in the frequency 2420MHz

The EIRP = [(FS*D) ^2 / 30] mW = -8.33dBm

which is within the production variation.

The maximum conducted output power specified is -3.0dBm= 0.501mW

The source- based time-averaging conducted output power =0.501* Duty cycle mW <0.501 mW(Duty cycle <100%)

The SAR Exclusion Threshold Level:

$$\begin{aligned} P_{th}(\text{mW}) &= \text{ERP}_{20\text{cm}} * (d/20\text{cm})^x \quad (X = -\log_{10} \left(\frac{60}{\text{ERP}_{20\text{cm}} \sqrt{f}} \right)) \\ &= 3060 * (0.5/20)^{1.9} \text{ mW} \\ &= 2.72 \text{ mW} \end{aligned}$$

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 1.23188ms

Effective period of the cycle = 130.43 μ s x1 = 0.13043ms

DC =0.13043ms / 1.23188ms =0.1059 or 10.59%