



RF Exposure Evaluation Report

APPLICANT : Spireon Inc
EQUIPMENT : GPS tracker
BRAND NAME : Flex2-M
MODEL NAME : Flex2-M
FCC ID : O9YFLF2M
STANDARD : 47 CFR Part 2.1091
FCC KDB 447498 D01 v06

We, Sporton International (Kunshan) Inc., would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and FCC KDB 447498 D01 v06, and pass the limit. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.



Reviewed by: Rose Wang / Supervisor



Approved by: Kat Yin / Manager



Sporton International (Kunshan) Inc.

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China



Table of Contents

1. ADMINISTRATION DATA	4
1.1. Testing Laboratory	4
2. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	5
3. MAXIMUM RF TUNE UP POWER AMONG PRODUCTION UNITS	6
4. RF EXPOSURE LIMIT INTRODUCTION	7
5. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION	8
5.1. Standalone Power Density Calculation	8

**Revision History**

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA050828	Rev. 01	Initial issue of report	Jul. 21, 2020



1. Administration Data

1.1. Testing Laboratory

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Testing Laboratory		
Test Firm	Sporton International (Kunshan) Inc.	
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958	
Test Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CN1257	314309

Applicant	
Company Name	Spireon Inc
Address	9724 Kingston Pike, Suite 800 Knoxville, TN37922, United States

Manufacturer	
Company Name	Asiatelco Technologies Co.
Address	#289 Bisheng Road, Building-8, 3F, Zhangjiang Hi-Tech Park, Pudong, Shanghai 201204, China



2. Description of Equipment Under Test (EUT)

Product Feature & Specification	
EUT Type	GPS tracker
Brand Name	Flex2-M
Model Name	Flex2-M
FCC ID	O9YFLF2M
IMEI Code	865284042582605
Wireless Technology and Frequency Range	LTE Band 2: 1850.7 MHz ~ 1909.3 MHz LTE Band 4: 1710.7 MHz ~ 1754.3 MHz LTE Band 12: 699.7 MHz ~ 715.3 MHz LTE Band 13: 779.5 MHz ~ 784.5 MHz LTE Band 25: 1850.7 MHz ~ 1914.3 MHz
Mode	LTE Category M1: QPSK, 16QAM
HW Version	2.0.0
SW Version	B1
EUT Stage	Identical Prototype
Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.	

Comments and Explanations:

1. The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.
2. The maximum RF output tune up power, antenna gain also the safe distance used for evaluate RF exposure were declared by manufacturer.



3. Maximum RF Tune Up Power among production units

<LTE>

Mode		Maximum Average power(dBm)
LTE	Band 2	24.50
	Band 4	24.50
	Band 12	24.00
	Band 13	24.00
	Band 25	24.50

4. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna



5. Radio Frequency Radiation Exposure Evaluation

5.1. Standalone Power Density Calculation

Band	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Maximum EIRP (W)	Average EIRP (mW)	Power Density at 20cm (mW/cm ²)	Limit (mW/cm ²)	Power Density / Limit
LTE Band 2	1850.7	1.77	24.50	26.27	0.42	423.64	0.084	1.000	0.084
LTE Band 4	1710.7	1.41	24.50	25.91	0.39	389.94	0.078	1.000	0.078
LTE Band 12	699.7	1.06	24.00	25.06	0.32	320.63	0.064	0.466	0.137
LTE Band 13	779.5	0.68	24.00	24.68	0.29	293.76	0.058	0.520	0.113
LTE Band 25	706.5	1.77	24.50	26.27	0.42	423.64	0.084	1.000	0.084

Note: For conservativeness, the lowest frequency of each band is used to determine the MPE limit of that band.

Conclusion:

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.