



# RF TEST REPORT

<b>Applicant</b>	Spireon Inc
<b>FCC ID</b>	O9YFLF3L
<b>Product</b>	GPS tracker
<b>Model</b>	Flex2-L
<b>Report No.</b>	R2109A0848-R1V1
<b>Issue Date</b>	November 1, 2021

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC CFR47 Part 2 (2020)/ FCC CFR 47 Part 22H (2020)**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Prepared by: Peng Tao

Approved by: Kai Xu

---

## TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000



# TABLE OF CONTENT

- 1. Test Laboratory .....5
  - 1.1. Notes of the Test Report ..... 5
  - 1.2. Test facility..... 5
  - 1.3. Testing Location ..... 5
- 2. General Description of Equipment under Test.....6
  - 2.1. Applicant and Manufacturer Information .....6
  - 2.2. General Information..... 6
- 3. Applied Standards .....7
- 4. Test Configuration.....8
- 5. Test Case Results.....9
  - 5.1. RF Power Output and Effective Radiated Power .....9
  - 5.2. Radiates Spurious Emission ..... 11
- 6. Main Test Instruments ..... 15
- ANNEX A: The EUT Appearance .....16
- ANNEX B: Test Setup Photos ..... 17



Version	Revision description	Issue Date
Rev.0	Initial issue of report.	October 19, 2021
Rev.1	Update description in Page 4.	November 1, 2021

Note: This revised report (Report No. R2109A0848-R1V1) supersedes and replaces the previously issued report (Report No. R2109A0848-R1). Please discard or destroy the previously issued report and dispose of it accordingly.



### Summary of measurement results

No.	Test Case	Clause in FCC rules	Verdict
1	RF Power Output and Effective Radiated Power	2.1046 22.913(a)(5)	PASS
2	Occupied Bandwidth	2.1049	Refer to the module report. (Report No: RTWK160719001-00)
3	Band Edge Compliance	2.1051 / 22.917(a)	Refer to the module report. (Report No: RTWK160719001-00)
4	Peak-to-Average Power Ratio	22.913(d)/ KDB 971168 D01(5.7)	Refer to the module report. (Report No: RTWK160719001-00)
5	Frequency Stability	2.1055 / 22.355	Refer to the module report. (Report No: RTWK160719001-00)
6	Spurious Emissions at Antenna Terminals	2.1051 / 22.917(a)	Refer to the module report. (Report No: RTWK160719001-00)
7	Radiates Spurious Emission	2.1053 / 22.917 (a)	PASS
Date of Testing: October 3, 2021			
Date of Sample Received: September 23, 2021			
Note: PASS: The EUT complies with the essential requirements in the standard. FAIL: The EUT does not comply with the essential requirements in the standard. All indications of Pass/Fail in this report are opinions expressed by TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.			

**The report only tests the RF Power Output and Effective Isotropic Radiated Power and Radiates Spurious Emission. Other test items are subject to the module test report. (Report No: R1805A0226-R1V3) and the module RF test report refers to the original Module report. (Report No: RTWK160719001-00).**



## 1. Test Laboratory

### 1.1. Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

### 1.2. Test facility

#### **FCC (Designation number: CN1179, Test Firm Registration Number: 446626)**

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

#### **A2LA (Certificate Number: 3857.01)**

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform measurement.

### 1.3. Testing Location

Company: TA Technology (Shanghai) Co., Ltd.  
Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong  
City: Shanghai  
Post code: 201201  
Country: P. R. China  
Contact: Xu Kai  
Telephone: +86-021-50791141/2/3  
Fax: +86-021-50791141/2/3-8000  
Website: <http://www.ta-shanghai.com>  
E-mail: [xukai@ta-shanghai.com](mailto:xukai@ta-shanghai.com)

## 2. General Description of Equipment under Test

### 2.1. Applicant and Manufacturer Information

Applicant	Spireon Inc
Applicant address	9724 Kingston Pike, Suite 800 Knoxville
Manufacturer	Asiatelco Technologies Co
Manufacturer address	#289 Bisheng Road, Building-8, 3F, Zhangjiang Hi-Tech Park, Pudong, Shanghai 201204, China

### 2.2. General Information

EUT Description			
Model	Flex2-L		
IMEI	861836059908801		
Hardware Version	P3.0.0		
Software Version	B1		
Power Supply	Battery		
Antenna Type	Internal Antenna		
Antenna Gain	1.2 dBi		
Test Mode(s)	WCDMA Band V;		
Test Modulation	(WCDMA) BPSK, QPSK, 16QAM;		
Maximum E.R.P.	WCDMA Band V:	21.69 dBm	
Rated Power Supply Voltage	12V		
Operating Voltage	Minimum: 8V    Maximum: 30V		
Operating Temperature	Lowest: -30°C    Highest: +70°C		
Extreme Temperature	Lowest: 0°C    Highest: +45°C		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	WCDMA Band V	824 ~ 849	869 ~ 894
EUT Accessory			
Battery	Manufacturer: Expecell Group, Inc. Model: LIP-2S2PLx18650LT-PTC25		
Note: 1. The EUT is sent from the applicant to TA and the information of the EUT is declared by the applicant.			



### 3. Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**Test standards:**

**FCC CFR 47 Part 22H (2020)**

**ANSI C63.26 (2015)**

**Reference standard:**

**FCC CFR47 Part 2 (2020)**

**KDB 971168 D01 Power Meas License Digital Systems v03r01**

## 4. Test Configuration

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes. EUT stand-up position (Z axis), lie-down position (X, Y axis). Receiver antenna polarization (horizontal and vertical), the worst emission was found in position (Z axis, horizontal polarization) and the worst case was recorded.

All mode and data rates and positions and RB size and modulations were investigated.

Subsequently, only the worst case emissions are reported.

The following testing in WCDMA is set based on the maximum RF Output Power.

Test modes are chosen to be reported as the worst case configuration below:

Test items	Modes/Modulation
	WCDMA Band V
RF Power Output and Effective Radiated power	RMC HSDPA/HSUPA DC-HSDPA
Occupied Bandwidth	RMC
Band Edge Compliance	RMC
Peak-to-Average Power Ratio	RMC
Frequency Stability	RMC
Spurious Emissions at Antenna Terminals	RMC
Radiates Spurious Emission	RMC



## 5. Test Case Results

### 5.1. RF Power Output and Effective Radiated Power

#### Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

#### Methods of Measurement

During the process of the testing, The EUT was connected to the Base Station Simulator with a known loss. The EUT is controlled by the Base Station Simulator test set to ensure max power transmission with proper modulation.


ERP can then be calculated as follows:

$$\text{EIRP (dBm)} = \text{Output Power (dBm)} - \text{Losses (dB)} + \text{Antenna Gain (dBi)}$$

where:dBd refers to gain relative to an ideal dipole.

$$\text{EIRP (dBm)} = \text{ERP (dBm)} + 2.15 \text{ (dB)}.$$

#### Test Setup



#### Limits

No specific RF power output requirements in part 2.1046.

Rule Part 22.913(a)(5) specifies that "Mobile/portable stations are limited to 7 watts ERP".

Limit	≤ 7 W (38.45 dBm)
-------	-------------------

#### Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 2$ ,  $U = 0.4 \text{ dB}$  for RF power output,  $k = 2$ ,  $U = 1.19 \text{ dB}$  for ERP.



## Test Results

WCDMA Band V		Maximum Output Power (dBm)			ERP (dBm)		
		Channel 4132	Channel 4183	Channel 4233	Channel 4132	Channel 4183	Channel 4233
		826.4 (MHz)	836.6 (MHz)	846.6 (MHz)	826.4 (MHz)	836.6 (MHz)	846.6 (MHz)
<b>RMC</b>		22.64	22.59	22.58	21.69	21.64	21.63
<b>HSDPA</b>	Sub - Test 1	22.10	22.01	22.02	21.15	21.06	21.07
	Sub - Test 2	22.09	22.03	21.99	21.14	21.08	21.04
	Sub - Test 3	21.56	21.53	21.51	20.61	20.58	20.56
	Sub - Test 4	21.57	21.54	21.49	20.62	20.59	20.54
<b>HSUPA</b>	Sub - Test 1	22.06	22.00	21.97	21.11	21.05	21.02
	Sub - Test 2	21.05	20.98	20.96	20.10	20.03	20.01
	Sub - Test 3	21.52	21.46	21.45	20.57	20.51	20.50
	Sub - Test 4	20.98	20.95	20.93	20.03	20.00	19.98
	Sub - Test 5	21.99	21.93	21.91	21.04	20.98	20.96
<b>DC-HSDPA</b>	Sub - Test 1	21.98	21.95	21.92	21.03	21.00	20.97
	Sub - Test 2	21.97	21.94	21.91	21.02	20.99	20.96
	Sub - Test 3	21.55	21.43	21.42	20.60	20.48	20.47
	Sub - Test 4	21.54	21.42	21.41	20.59	20.47	20.46

## 5.2. Radiates Spurious Emission

### Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

### Method of Measurement


1. The testing follows FCC KDB 971168 v03r01 Section 5.8 and ANSI C63.26 (2015).
2. Below 1GHz: The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H). Above 1GHz: (Note: the FCC's permission to use 1.5m as an alternative per TCBC Conf call of Dec. 2, 2014.) The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).
3. A loop antenna, A log-periodic antenna or horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
4. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=100kHz,VBW=300kHz, and the maximum value of the receiver should be recorded as (Pr).
5. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (PMea) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (PMea) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
6. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (Pcl) ,the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAg) should be recorded after test.
7. The measurement results are obtained as described below:  
Power(EIRP)=PMea- PAg - Pcl + Ga  
The measurement results are amend as described below:  
Power(EIRP)=PMea- Pcl + Ga
8. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dB) and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP

= EIRP-2.15dB.


The modulation mode and RB allocation refer to section 5.1, using the maximum output power configuration.

**Test setup**


**9KHz ~ 30MHz**



**30MHz ~ 1GHz**



**Above 1GHz**



Note: Area side:2.4mX3.6m



## Limits

Rule Part 22.917(a) specifies that “The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log (P)$  dB.”

Limit	-13 dBm
-------	---------

## Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 1.96$ ,  $U = 3.55$  dB.

**Test Result**

Sweep the whole frequency band through the range from 9kHz to the 10th harmonic of the carrier, the emissions below the noise floor will not be recorded in the report.

## WCDMA Band V CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1673.20	-64.76	1.70	8.70	Horizontal	-59.91	-13.00	46.91	0
3	2509.80	-62.36	2.30	12.00	Horizontal	-54.81	-13.00	41.81	90
4	3346.40	-66.39	2.70	12.70	Horizontal	-58.54	-13.00	45.54	90
5	4183.00	-63.65	3.00	12.50	Horizontal	-56.30	-13.00	43.30	0
6	5019.60	-59.63	3.40	12.50	Horizontal	-52.68	-13.00	39.68	180
7	5856.20	-58.57	3.40	12.80	Horizontal	-51.32	-13.00	38.32	270
8	6692.80	-59.57	4.10	11.50	Horizontal	-54.32	-13.00	41.32	45
9	7529.40	-53.85	4.20	12.20	Horizontal	-48.00	-13.00	35.00	90
10	8366.00	-54.69	4.30	12.50	Horizontal	-48.64	-13.00	35.64	90

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.



## 6. Main Test Instruments

Name	Manufacturer	Type	Serial Number	Calibration Date	Expiration Date
Base Station Simulator	R&S	CMW500	150415	2021-05-15	2022-05-14
Signal Analyzer	R&S	FSV3030	101411	2020-12-13	2021-12-12
Horn Antenna	R&S	HF907	102723	2020-08-11	2023-08-10
Horn Antenna	ETS-Lindgren	3160-09	00102643	2018-06-20	2023-06-19
Software	R&S	EMC32	9.26.0	/	/

\*\*\*\*\*END OF REPORT \*\*\*\*\*



## **ANNEX A: The EUT Appearance**

The EUT Appearance are submitted separately.





## **ANNEX B: Test Setup Photos**

The Test Setup Photos are submitted separately.