

## FCC Test Report

### (PART 27)

**Report No.:** RF190415C07-2

**FCC ID:** O9YJKS3

**Test Model:** JKS3A

**Series Model:** ATS100M-YZ-V, ATS100M-YZ-S, JKS3B, ATS100M-Y-V, ATS100M-Y-S, JKS3C, ATS100M-Z-V, ATS100M-Z-S, JKS3D, ATS100M-V, ATS100M-S  
(Refer to section 3.1 for detail)

**Received Date:** Apr. 15, 2019

**Test Date:** May 03 ~ May 31, 2019

**Issued Date:** Jun. 11, 2019

**Applicant:** Spireon Inc

**Address:** 9724 Kingstone Pike, suite 800, Knoxville, Tennessee, USA, 37922

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan  
( R.O.C )

**Test Location:** No. 19, Hwa Ya 2nd Rd, Wen Hwa Vil, Kwei Shan Dist., Taoyuan City  
33383, Taiwan (R.O.C)

**FCC Registration /  
Designation Number:** 788550 / TW0003



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies

## Table of Contents

<b>Release Control Record</b> .....	<b>4</b>
<b>1 Certificate of Conformity</b> .....	<b>5</b>
<b>2 Summary of Test Results</b> .....	<b>6</b>
2.1 Measurement Uncertainty .....	7
2.2 Test Site and Instruments .....	8
<b>3 General Information</b> .....	<b>10</b>
3.1 General Description of EUT .....	10
3.2 Configuration of System under Test .....	12
3.2.1 Description of Support Units .....	12
3.3 Test Mode Applicability and Tested Channel Detail .....	12
3.4 EUT Operating Conditions .....	16
3.5 General Description of Applied Standards .....	16
<b>4 Test Types and Results</b> .....	<b>17</b>
4.1 Output Power Measurement .....	17
4.1.1 Limits of Output Power Measurement .....	17
4.1.2 Test Procedures .....	17
4.1.3 Test Setup .....	18
4.1.4 Test Results .....	19
4.2 Modulation Characteristics Measurement .....	35
4.2.1 Limits of Modulation Characteristics .....	35
4.2.2 Test Setup .....	35
4.2.3 Test Procedure .....	35
4.2.4 Test Results .....	36
4.3 Frequency Stability Measurement .....	37
4.3.1 Limits of Frequency Stability Measurement .....	37
4.3.2 Test Procedure .....	37
4.3.3 Test Setup .....	37
4.3.4 Test Results .....	38
4.4 Occupied Bandwidth Measurement .....	46
4.4.1 Limits of Occupied Bandwidth Measurement .....	46
4.4.2 Test Procedure .....	46
4.4.3 Test Setup .....	46
4.4.4 Test Result .....	47
4.5 Band Edge Measurement .....	51
4.5.1 Limits of Band Edge Measurement .....	51
4.5.2 Test Setup .....	51
4.5.3 Test Procedures .....	51
4.5.4 Test Results .....	52
4.6 Peak to Average Ratio .....	62
4.6.1 Limits of Peak to Average Ratio Measurement .....	62
4.6.2 Test Setup .....	62
4.6.3 Test Procedures .....	62
4.6.4 Test Results .....	63
4.7 Conducted Spurious Emissions .....	67
4.7.1 Limits of Conducted Spurious Emissions Measurement .....	67
4.7.2 Test Setup .....	67
4.7.3 Test Procedure .....	67
4.7.4 Test Results .....	68
4.8 Radiated Emission Measurement .....	81
4.8.1 Limits of Radiated Emission Measurement .....	81
4.8.2 Test Procedure .....	81
4.8.3 Deviation from Test Standard .....	81
4.8.4 Test Setup .....	82

4.8.5 Test Results .....	83
<b>5 Pictures of Test Arrangements.....</b>	<b>109</b>
<b>Appendix – Information of the Testing Laboratories .....</b>	<b>110</b>

### Release Control Record

Issue No.	Description	Date Issued
RF190415C07-2	Original Release	Jun. 11, 2019

## 1 Certificate of Conformity

**Product:** GPS Tracker

**Brand:** Spireon

**Test Model:** JKS3A

**Series Model:** ATS100M-YZ-V, ATS100M-YZ-S, JKS3B, ATS100M-Y-V, ATS100M-Y-S, JKS3C, ATS100M-Z-V, ATS100M-Z-S, JKS3D, ATS100M-V, ATS100M-S (Refer to section 3.1 for detail)

**Sample Status:** Engineering Sample


**Applicant:** Spireon Inc

**Test Date:** May 03 ~ May 31, 2019

**Standards:** FCC Part 27, Subpart F, L

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

**Prepared by :** , **Date:** Jun. 11, 2019  
Lena Wang / Specialist

**Approved by :** , **Date:** Jun. 11, 2019  
Dylan Chiou / Project Engineer

## 2 Summary of Test Results

Applied Standard: FCC Part 27 & Part 2 (LTE 4)			
FCC Clause	Test Item	Result	Remarks
2.1046 27.50(d)(4)	Maximum Peak Output Power	Pass	Meet the requirement of limit.
2.1047	Modulation Characteristics	Pass	Meet the requirement.
2.1055 27.54	Frequency Stability	Pass	Meet the requirement of limit.
2.1049	Occupied Bandwidth	Pass	Meet the requirement of limit.
27.50(d)(5)	Peak to Average Ratio	Pass	Meet the requirement of limit.
27.53(h)	Band Edge Measurements	Pass	Meet the requirement of limit.
2.1051 27.53(h)	Conducted Spurious Emissions	Pass	Meet the requirement of limit.
2.1053 27.53(h)	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -19.02 dB at 6980.00 MHz.

Applied Standard: FCC Part 27 & Part 2 (LTE 13)			
FCC Clause	Test Item	Result	Remarks
2.1046 27.50(b)(10)	Maximum Peak Output Power	Pass	Meet the requirement of limit.
2.1047	Modulation Characteristics	Pass	Meet the requirement.
2.1055 27.54	Frequency Stability	Pass	Meet the requirement of limit.
2.1049	Occupied Bandwidth	Pass	Meet the requirement of limit.
---	Peak to Average Ratio	Pass	Meet the requirement of limit.
27.53(c)(2)(4)	Band Edge Measurements	Pass	Meet the requirement of limit.
2.1051 27.53(c)(2)&(f)	Conducted Spurious Emissions	Pass	Meet the requirement of limit.
2.1053 27.53(c)(2)&(f)	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -5.61 dB at 1564.00 MHz.

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

## 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) ( $\pm$ )
Radiated Emissions up to 1 GHz	9 kHz ~ 30 MHz	3.04 dB
	30 MHz ~ 200 MHz	2.93 dB
	200 MHz ~ 1000 MHz	2.95 dB
Radiated Emissions above 1 GHz	1 GHz ~ 18 GHz	2.26 dB
	18 GHz ~ 40 GHz	1.94 dB

## 2.2 Test Site and Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver Agilent	N9038A	MY51210203	Mar. 18, 2019	Mar. 17, 2020
Spectrum Analyzer Agilent	N9010A	MY52220314	Dec. 13, 2018	Dec. 12, 2019
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Apr. 15, 2019	Apr. 14, 2020
Spectrum Analyzer ROHDE & SCHWARZ	FSW26	102023	Oct. 11, 2018	Oct. 10, 2019
HORN Antenna SCHWARZBECK	BBHA 9120D	9120D-969	Nov. 25, 2018	Nov. 24, 2019
BILOG Antenna SCHWARZBECK	VULB9168	9168-472	Nov. 23, 2018	Nov. 22, 2019
Horn Antenna SCHWARZBECK	BBHA 9170	148	Nov. 25, 2018	Nov. 24, 2019
Fixed Attenuator Mini-Circuits	MDCS18N-10	MDCS18N-10-01	Apr. 15, 2019	Apr. 14, 2020
MXG Vector signal generator Agilent	N5182B	MY53050430	Nov. 19, 2018	Nov. 18, 2019
Preamplifier EMCI	EMC 012645	980115	Oct. 12, 2018	Oct. 11, 2019
Preamplifier EMCI	EMC 184045	980116	Oct. 12, 2018	Oct. 11, 2019
Preamplifier EMCI	EMC 330H	980112	Oct. 12, 2018	Oct. 11, 2019
RF Coaxial Cable HUBER+SUHNNER	EMC104-SM-SM- 8000&3000	140811+170717	Oct. 12, 2018	Oct. 11, 2019
RF Coaxial Cable HUBER+SUHNNER	SUCOFLEX 104	EMC104-SM-SM- 1000(140807)	Oct. 12, 2018	Oct. 11, 2019
RF Coaxial Cable Worken	8D-FB	Cable-Ch10-01	Oct. 12, 2018	Oct. 11, 2019
Boresight Antenna Fixture	FBA-01	FBA-SIP01	NA	NA
Software BV ADT	E3 6.120103	NA	NA	NA
Antenna Tower MF	MFA-440H	NA	NA	NA
Turn Table MF	MFT-201SS	NA	NA	NA
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA
LTE Wireless Communication Test Set Keysight	E7515A	MY57270629	Feb. 22, 2019	Feb. 22, 2020
Radio Communication Analyzer Anritsu	MT8820C	6201300640	Aug. 16, 2017	Aug. 15, 2019
Temperature & Humidity Chamber	GTH-120-40-CP-AR	MAA1306-019	Sep. 05, 2018	Sep. 04, 2019
DC Power Supply Topward	33010D	807748	NA	NA



- Note: 1. The calibration interval of the above test instruments is 12 / 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Chamber 10.

### 3 General Information

#### 3.1 General Description of EUT

<b>Product</b>	GPS Tracker	
<b>Brand</b>	Spireon	
<b>Test Model</b>	JKS3A	
<b>Series Model</b>	ATS100M-YZ-V, ATS100M-YZ-S, JKS3B, ATS100M-Y-V, ATS100M-Y-S, JKS3C, ATS100M-Z-V, ATS100M-Z-S, JKS3D, ATS100M-V, ATS100M-S	
<b>Status of EUT</b>	Engineering Sample	
<b>Power Supply Rating</b>	12 Vdc (adapter) 3.7 Vdc (battery)	
<b>Modulation Type</b>	LTE	QPSK, 16QAM
<b>Frequency Range</b>	LTE Band 4 (Channel Bandwidth: 1.4 MHz)	1710.7 ~ 1754.3 MHz
	LTE Band 4 (Channel Bandwidth: 3 MHz)	1711.5 ~ 1753.5 MHz
	LTE Band 4 (Channel Bandwidth: 5 MHz)	1712.5 ~ 1752.5 MHz
	LTE Band 4 (Channel Bandwidth: 10 MHz)	1715.0 ~ 1750.0 MHz
	LTE Band 4 (Channel Bandwidth: 15 MHz)	1717.5 ~ 1747.5 MHz
	LTE Band 4 (Channel Bandwidth: 20 MHz)	1720.0 ~ 1745.0 MHz
	LTE Band 13 (Channel Bandwidth: 5 MHz)	779.5 ~ 784.5 MHz
	LTE Band 13 (Channel Bandwidth: 10 MHz)	782.0 MHz
<b>Emission Designator</b>	LTE Band 4 (Channel Bandwidth: 1.4 MHz)	1M09G7D
	LTE Band 4 (Channel Bandwidth: 3 MHz)	1M09G7D
	LTE Band 4 (Channel Bandwidth: 5 MHz)	1M10G7D
	LTE Band 4 (Channel Bandwidth: 10 MHz)	1M09G7D
	LTE Band 4 (Channel Bandwidth: 15 MHz)	1M11G7D
	LTE Band 4 (Channel Bandwidth: 20 MHz)	1M10G7D
	LTE Band 13 (Channel Bandwidth: 5 MHz)	1M10G7D
	LTE Band 13 (Channel Bandwidth: 10 MHz)	1M09G7D
<b>Max. ERP Power</b>	LTE Band 13 (Channel Bandwidth: 5 MHz)	190.55 mW
	LTE Band 13 (Channel Bandwidth: 10 MHz)	201.84 mW
<b>Max. EIRP Power</b>	LTE Band 4 (Channel Bandwidth: 1.4 MHz)	319.89 mW
	LTE Band 4 (Channel Bandwidth: 3 MHz)	323.59 mW
	LTE Band 4 (Channel Bandwidth: 5 MHz)	328.85 mW
	LTE Band 4 (Channel Bandwidth: 10 MHz)	331.89 mW
	LTE Band 4 (Channel Bandwidth: 15 MHz)	335.74 mW
	LTE Band 4 (Channel Bandwidth: 20 MHz)	341.19 mW
<b>Antenna Type</b>	PIFA Antenna	
<b>Antenna Gain</b>	LTE Band 4	2.8 dBi
	LTE Band 13	1.8 dBi
<b>Accessory Device</b>	Refer to Note as below	
<b>Data Cable Supplied</b>	Refer to Note as below	

Note:

1. All models are listed as below. Model JKS3A is the representative for final test.


Brand	Model	Difference
Spireon	JKS3A	With Battery; With Buzzer
	ATS100M-YZ-V	
	ATS100M-YZ-S	
	JKS3B	With Battery; Without Buzzer
	ATS100M-Y-V	
	ATS100M-Y-S	
	JKS3C	Without Battery; With Buzzer
	ATS100M-Z-V	
	ATS100M-Z-S	
	JKS3D	Without Battery; Without Buzzer
	ATS100M-V	
ATS100M-S		

2. The EUT uses following adapter. (For support unit only)

Brand	Chanel Well Technology
Model	CAP012121
Input Power	100-240 Vac, 47~63 Hz, 0.35 A
Output Power	12 Vdc, 1.0 A
Power Line	2.25m non-shuelded DC power cable without core

3. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.

### 3.2 Configuration of System under Test



#### 3.2.1 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Product	Brand	Model No.	Serial No.	FCC ID
1.	Radio Communication Analyzer	ANRITSU	MT8821C	6201502978	N/A
2.	Adapter	Chanel Well Technology	CAP012121	N/A	N/A

No.	Signal Cable Description Of The Above Support Units
1.	N/A
2.	2.25m

Note:

1. All power cords of the above support units are non-shielded (1.8m).
2. Items 1 acted as communication partners to transfer data.
3. Items 2 was provided by client.

### 3.3 Test Mode Applicability and Tested Channel Detail

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis, and antenna ports

The worst case was found when positioned as the table below. Following channel(s) was (were) selected for the final test as listed below:

Band	ERP / EIRP	Radiated Emission
LTE Band 4	X-plane	Y-axis
LTE Band 13	X-plane	Y-axis

### LTE Band 4

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
-	EIRP	19957 to 20393	19957, 20175, 20393	1.4 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		19965 to 20385	19965, 20175, 20385	3 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		19975 to 20375	19975, 20175, 20375	5 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20000 to 20350	20000, 20175, 20350	10 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20025 to 20325	20025, 20175, 20325	15 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20050 to 20300	20050, 20175, 20300	20 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
-	Modulation Characteristics	20050 to 20300	20175	20 MHz	QPSK, 16QAM	6 RB / 0 RB Offset
-	Frequency Stability	19957 to 20393	19957, 20393	1.4 MHz	QPSK	1 RB / 0 RB Offset
		19965 to 20385	19965, 20385	3 MHz	QPSK	1 RB / 0 RB Offset
		19975 to 20375	19975, 20375	5 MHz	QPSK	1 RB / 0 RB Offset
		20000 to 20350	20000, 20350	10 MHz	QPSK	1 RB / 0 RB Offset
		20025 to 20325	20025, 20325	15 MHz	QPSK	1 RB / 0 RB Offset
		20050 to 20300	20050, 20300	20 MHz	QPSK	1 RB / 0 RB Offset
-	Occupied Bandwidth	19957 to 20393	19957, 20175, 20393	1.4 MHz	QPSK, 16QAM	6 RB / 0 RB Offset
		19965 to 20385	19965, 20175, 20385	3 MHz	QPSK, 16QAM	15 RB / 0 RB Offset
		19975 to 20375	19975, 20175, 20375	5 MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		20000 to 20350	20000, 20175, 20350	10 MHz	QPSK, 16QAM	50 RB / 0 RB Offset
		20025 to 20325	20025, 20175, 20325	15 MHz	QPSK, 16QAM	75 RB / 0 RB Offset
		20050 to 20300	20050, 20175, 20300	20 MHz	QPSK, 16QAM	100 RB / 0 RB Offset
-	Peak to Average Ratio	19957 to 20393	19957, 20175, 20393	1.4 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		19965 to 20385	19965, 20175, 20385	3 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		19975 to 20375	19975, 20175, 20375	5 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20000 to 20350	20000, 20175, 20350	10 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20025 to 20325	20025, 20175, 20325	15 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20050 to 20300	20050, 20175, 20300	20 MHz	QPSK, 16QAM	1 RB / 0 RB Offset

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode		
-	Band Edge	19957 to 20393	19957	1.4 MHz	QPSK	1 RB / 0 RB Offset 6 RB / 0 RB Offset		
			20393	1.4 MHz	QPSK	1 RB / 5 RB Offset 6 RB / 0 RB Offset		
		19965 to 20385	19965	3 MHz	QPSK	1 RB / 0 RB Offset 15 RB / 0 RB Offset		
			20385	3 MHz	QPSK	1 RB / 14 RB Offset 15 RB / 0 RB Offset		
		19975 to 20375	19975	5 MHz	QPSK	1 RB / 0 RB Offset 25 RB / 0 RB Offset		
			20375	5 MHz	QPSK	1 RB / 24 RB Offset 25 RB / 0 RB Offset		
		20000 to 20350	20000	10 MHz	QPSK	1 RB / 0 RB Offset 50 RB / 0 RB Offset		
			20350	10 MHz	QPSK	1 RB / 49 RB Offset 50 RB / 0 RB Offset		
		20025 to 20325	20025	15 MHz	QPSK	1 RB / 0 RB Offset 75 RB / 0 RB Offset		
			20325	15 MHz	QPSK	1 RB / 74 RB Offset 75 RB / 0 RB Offset		
		20050 to 20300	20050	20 MHz	QPSK	1 RB / 0 RB Offset 100 RB / 0 RB Offset		
			20300	20 MHz	QPSK	1 RB / 99 RB Offset 100 RB / 0 RB Offset		
		-	Conducted Emission	19957 to 20393	19957, 20175, 20393	1.4 MHz	QPSK	1 RB / 0 RB Offset
				19965 to 20385	19965, 20175, 20385	3 MHz	QPSK	1 RB / 0 RB Offset
				19975 to 20375	19975, 20175, 20375	5 MHz	QPSK	1 RB / 0 RB Offset
				20000 to 20350	20000, 20175, 20350	10 MHz	QPSK	1 RB / 0 RB Offset
				20025 to 20325	20025, 20175, 20325	15 MHz	QPSK	1 RB / 0 RB Offset
				20050 to 20300	20050, 20175, 20300	20 MHz	QPSK	1 RB / 0 RB Offset
-	Radiated Emission	19957 to 20393	19957, 20175, 20393	1.4 MHz	QPSK	1 RB / 0 RB Offset		
		19975 to 20375	19975, 20175, 20375	5 MHz	QPSK	1 RB / 0 RB Offset		
		20050 to 20300	20050, 20175, 20300	20 MHz	QPSK	1 RB / 0 RB Offset		

**Note:**

1. This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.
2. For radiated emission above 1 GHz, according to 3GPP 36.521 Section 6.6.3.1.4, choose the lowest, 5 MHz & highest channel bandwidth for final test.

### LTE Band 13

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
-	ERP	23205 to 23255	23205, 23230, 23255	5 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		23230	23230	10 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
-	Modulation Characteristics	23230	23230	10 MHz	QPSK, 16QAM	6 RB / 0 RB Offset
-	Frequency Stability	23205 to 23255	23205, 23255	5 MHz	QPSK	1 RB / 0 RB Offset
		23230	23230	10 MHz	QPSK	1 RB / 0 RB Offset
-	Occupied Bandwidth	23205 to 23255	23205, 23230, 23255	5 MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		23230	23230	10 MHz	QPSK, 16QAM	50 RB / 0 RB Offset
-	Peak to Average Ratio	23205 to 23255	23205, 23230, 23255	5 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		23230	23230	10 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
-	Band Edge	23205 to 23255	23205	5 MHz	QPSK	1 RB / 0 RB Offset 25 RB / 0 RB Offset
			23255	5 MHz	QPSK	1 RB / 24 RB Offset 25 RB / 0 RB Offset
		23230	23230	10 MHz	QPSK	1 RB / 0 RB Offset 50 RB / 0 RB Offset
			23230	10 MHz	QPSK	1 RB / 49 RB Offset 50 RB / 0 RB Offset

**Note:**

1. This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.
2. For radiated emission above 1 GHz, according to 3GPP 36.521 Section 6.6.3.1.4, choose the lowest, 5 MHz & highest channel bandwidth for final test.

**Test Condition:**

Test Item	Environmental Conditions	Input Power	Tested By
ERP / EIRP	25 deg. C, 65 % RH	3.7 Vdc	Thomas Wei
Modulation Characteristics	25 deg. C, 65 % RH	3.7 Vdc	Getaz Yang
Frequency Stability	25 deg. C, 65 % RH	3.7 Vdc	Getaz Yang
Occupied Bandwidth	25 deg. C, 65 % RH	3.7 Vdc	Getaz Yang
Band Edge	25 deg. C, 65 % RH	3.7 Vdc	Getaz Yang
Peak to Average Ratio	25 deg. C, 65 % RH	3.7 Vdc	Getaz Yang
Conducted Emission	25 deg. C, 65 % RH	3.7 Vdc	Getaz Yang
Radiated Emission	25 deg. C, 65 % RH	120 Vac, 60 Hz	Tim-Chen, Getaz Yang

### **3.4 EUT Operating Conditions**

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

### **3.5 General Description of Applied Standards**

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC 47 CFR Part 2**

**FCC 47 CFR Part 27**

**KDB 971168 D01 Power Meas License Digital Systems v03r01**

**ANSI/TIA/EIA-603-E 2016**

**ANSI 63.26-2015**

**Note:** All test items have been performed and recorded as per the above standards.



## 4 Test Types and Results

### 4.1 Output Power Measurement

#### 4.1.1 Limits of Output Power Measurement

Fixed, mobile, and portable (hand-held) stations operating in the 1710–1755 MHz band and mobile and portable stations operating in the 1695-1710 MHz and 1755-1780 MHz bands are limited to 1 watt EIRP.

Portable stations (hand-held devices) operating in the 746-757 MHz, 776-788 MHz and 805-806 MHz band are limited to 3 watts ERP

Portable stations (hand-held device) operating in the 600 MHz uplink band and the 698-746 MHz band, and fixed and mobile stations in the 600 MHz uplink band are limited to 3 watts ERP.

#### 4.1.2 Test Procedures

##### **EIRP / ERP Measurement:**

- a. All measurements were done at low, middle and high operational frequency range. RBW and VBW is 10 MHz for LTE mode.
- b. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8 m (below or equal 1 GHz) and/or 1.5 m (above 1 GHz) height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.
- c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a tx cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to “Read Value” of step b. Record the power level of S.G.
- d.  $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$ . E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole,  $E.R.P \text{ power} = E.I.R.P \text{ power} - 2.15 \text{ dB}$ .


##### **Conducted Power Measurement:**

- a. The EUT was set up for the maximum power with LTE link data modulation and link up with simulator.
- b. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.


4.1.3 Test Setup

**EIRP / ERP Measurement:**

**<Radiated Emission below or equal 1 GHz>**




**<Radiated Emission above 1 GHz>**



For the actual test configuration, please refer to the attached file (Test Setup Photo).

**Conducted Power Measurement:**



4.1.4 Test Results

**Conducted Output Power (dBm)**

eMTC	Band 4	Region(s) :	FCC	Power :	Class 3	23	Tolerance :	2.7
------	--------	-------------	-----	---------	---------	----	-------------	-----

maximum :	24.22
-----------	-------

BW(MHz):	1.4
----------	-----

Test Frequency ID	N <sub>UL</sub>	Frequency of Uplink [MHz]	N <sub>DL</sub>	Frequency of Downlink [MHz]	Test Configuration				Initial of Power		EUT	
					Modulation	RB Size	RB Offset	Narrowband Index	Cell power (dBm/15kHz)	power (dBm)		
Low Range	19957	1710.7	1957	2110.7	QPSK	1	0	0	-85	23.02		
					QPSK	1	5	0	-85	23.11		
					QPSK	3	3	0	-85	23.05		
					QPSK	6	0	0	-85	23.06		
					16QAM	1	0	0	-85	23.09		
					16QAM	1	5	0	-85	23.27		
					16QAM	3	0	0	-85	23.12		
Mid Range	20175	1732.5	2175	2132.5	QPSK	1	0	0	-85	23.51		
					QPSK	1	5	0	-85	23.31		
					QPSK	3	3	0	-85	23.28		
					QPSK	6	0	0	-85	23.25		
					16QAM	1	0	0	-85	23.21		
					16QAM	1	5	0	-85	23.15		
					16QAM	3	0	0	-85	23.47		
High Range	20393	1754.3	2393	2154.3	16QAM	5	0	0	-85	23.53		
					QPSK	1	0	0	-85	23.11		
					QPSK	1	5	0	-85	23.36		
					QPSK	3	3	0	-85	23.29		
					QPSK	6	0	0	-85	23.25		
					16QAM	1	0	0	-85	23.34		
					16QAM	1	5	0	-85	23.12		
High Range	20393	1754.3	2393	2154.3	16QAM	3	0	0	-85	23.11		
					16QAM	5	0	0	-85	23.12		
					16QAM	5	0	0	-85	23.12		

BW(MHz):	3
----------	---

Test Frequency ID	N <sub>UL</sub>	Frequency of Uplink [MHz]	N <sub>DL</sub>	Frequency of Downlink [MHz]	Test Configuration				Initial of Power		EUT	
					Modulation	RB Size	RB Offset	Narrowband Index	Cell power (dBm/15kHz)	power (dBm)		
Low Range	19965	1711.5	1965	2111.5	QPSK	1	0	0	-85	23.1		
					QPSK	1	5	0	-85	23.24		
					QPSK	1	0	1	-85	23.24		

					QPSK	1	5	1	-85	23.15
					QPSK	3	3	0	-85	23.27
					QPSK	3	3	1	-85	23.35
					QPSK	6	0	0	-85	23.15
					QPSK	6	0	1	-85	23.39
					16QAM	1	0	0	-85	23.14
					16QAM	1	5	0	-85	23.39
					16QAM	1	0	1	-85	23.31
					16QAM	1	5	1	-85	23.33
					16QAM	3	0	0	-85	23.37
					16QAM	3	3	1	-85	23.22
					16QAM	5	0	0	-85	23.64
					16QAM	5	0	1	-85	23.56
Mid Range	20175	1732.5	2175	2132.5	QPSK	1	0	0	-85	23.72
					QPSK	1	5	0	-85	23.29
					QPSK	1	0	1	-85	23.6
					QPSK	1	5	1	-85	23.43
					QPSK	3	3	0	-85	23.37
					QPSK	3	3	1	-85	23.47
					QPSK	6	0	0	-85	23.18
	QPSK	6	0	1	-85	23.21				
	16QAM	1	0	0	-85	23.19				
	16QAM	1	5	0	-85	23.27				
	16QAM	1	0	1	-85	23.53				
	16QAM	1	5	1	-85	23.1				
	16QAM	3	0	0	-85	23.54				
	16QAM	3	3	1	-85	23.37				
High Range	20385	1753.5	2385	1915	16QAM	5	0	0	-85	23.73
					16QAM	5	0	1	-85	23.63
					QPSK	1	0	0	-85	23.4
					QPSK	1	5	0	-85	23.37
					QPSK	1	0	1	-85	23.25
					QPSK	1	5	1	-85	23.43
					QPSK	3	3	0	-85	23.23
	QPSK	3	3	1	-85	23.55				
	QPSK	6	0	0	-85	23.53				
	QPSK	6	0	1	-85	23.54				
	16QAM	1	0	0	-85	23.04				
	16QAM	1	5	0	-85	23.26				
	16QAM	1	0	1	-85	22.92				
	16QAM	1	5	1	-85	22.92				

				16QAM	3	0	0	-85	23
				16QAM	3	3	1	-85	23.28
				16QAM	5	0	0	-85	23.37
				16QAM	5	0	1	-85	23.45

BW(MHz): 5

Test Frequency ID	N <sub>UL</sub>	Frequency of Uplink [MHz]	N <sub>DL</sub>	Frequency of Downlink [MHz]	Test Configuration				Initial of Power	
					Modulation	RB Size	RB Offset	Narrowband Index	Cell power (dBm/15kHz)	power (dBm)
Low Range	19975	1712.5	1975	2112.5	QPSK	1	0	0	-85	23.33
					QPSK	1	5	0	-85	23.31
					QPSK	1	0	1	-85	23.36
					QPSK	1	5	1	-85	23.26
					QPSK	1	0	3	-85	23.45
					QPSK	1	5	3	-85	23.52
					QPSK	3	0	0	-85	23.39
					QPSK	3	3	3	-85	23.48
					QPSK	6	0	0	-85	23.36
					QPSK	6	0	1	-85	23.42
					QPSK	6	0	3	-85	23.52
					16QAM	1	0	0	-85	23.34
					16QAM	1	5	0	-85	23.4
					16QAM	1	0	1	-85	23.45
					16QAM	1	5	1	-85	23.7
					16QAM	1	0	3	-85	23.76
					16QAM	1	5	3	-85	23.45
					16QAM	3	0	0	-85	23.41
					16QAM	3	3	3	-85	23.57
					16QAM	5	0	0	-85	23.51
16QAM	5	0	1	-85	23.43					
16QAM	5	0	3	-85	23.48					
Mid Range	20175	1732.5	2175	2132.5	QPSK	1	0	0	-85	23.91
					QPSK	1	5	0	-85	23.36
					QPSK	1	0	1	-85	23.41
					QPSK	1	5	1	-85	23.34
					QPSK	1	0	3	-85	23.64
					QPSK	1	5	3	-85	23.24
					QPSK	3	0	0	-85	23.58
					QPSK	3	3	3	-85	23.51
					QPSK	6	0	0	-85	23.81

High Range	20375	1752.5	2375	2152.5	QPSK	6	0	1	-85	23.66
					QPSK	6	0	3	-85	23.5
					16QAM	1	0	0	-85	23.43
					16QAM	1	5	0	-85	23.52
					16QAM	1	0	1	-85	23.36
					16QAM	1	5	1	-85	23.71
					16QAM	1	0	3	-85	23.3
					16QAM	1	5	3	-85	23.77
					16QAM	3	0	0	-85	23.72
					16QAM	3	3	3	-85	23.37
					16QAM	5	0	0	-85	23.25
					16QAM	5	0	1	-85	23.37
					16QAM	5	0	3	-85	23.19
					QPSK	1	0	0	-85	23.21
					QPSK	1	5	0	-85	23.31
	QPSK	1	0	1	-85	23.4				
	QPSK	1	5	1	-85	23.52				
	QPSK	1	0	3	-85	23.41				
	QPSK	1	5	3	-85	23.34				
	QPSK	3	0	0	-85	23.3				
	QPSK	3	3	3	-85	23.41				
	QPSK	6	0	0	-85	23.32				
	QPSK	6	0	1	-85	23.29				
	QPSK	6	0	3	-85	23.36				
	16QAM	1	0	0	-85	23.5				
	16QAM	1	5	0	-85	23.29				
	16QAM	1	0	1	-85	23.62				
	16QAM	1	5	1	-85	23.32				
	16QAM	1	0	3	-85	23.29				
	16QAM	1	5	3	-85	23.12				
16QAM	3	0	0	-85	23.21					
16QAM	3	3	3	-85	23.14					
16QAM	5	0	0	-85	23.22					
16QAM	5	0	1	-85	23.37					
16QAM	5	0	3	-85	23.47					

BW(MHz): 10

NUL		NbL		Test Configuration	Initial of Power	EUT
-----	--	-----	--	--------------------	------------------	-----

Test Frequency ID		Frequency of Uplink [MHz]		Frequency of Downlink [MHz]	Modulation	RB Size	RB Offset	Narrowband Index	Cell power (dBm/15kHz)	power (dBm)
Low Range	20000	1715	2000	2115	QPSK	1	0	0	-85	23.38
					QPSK	1	5	0	-85	23.45
					QPSK	1	0	3	-85	23.52
					QPSK	1	5	3	-85	23.39
					QPSK	1	0	7	-85	23.54
					QPSK	1	5	7	-85	23.66
					QPSK	4	0	0	-85	23.38
					QPSK	4	2	7	-85	23.62
					QPSK	6	0	0	-85	23.5
					QPSK	6	0	7	-85	23.6
					16QAM	1	0	0	-85	23.61
					16QAM	1	5	0	-85	23.57
					16QAM	1	0	3	-85	23.59
					16QAM	1	5	3	-85	23.53
					16QAM	1	0	7	-85	23.9
					16QAM	1	5	7	-85	23.86
					16QAM	4	2	0	-85	23.6
					16QAM	4	2	7	-85	23.57
16QAM	5	0	0	-85	23.76					
16QAM	5	0	7	-85	23.67					
Mid Range	20175	1732.5	2175	2132.5	QPSK	1	0	0	-85	24.01
					QPSK	1	5	0	-85	23.68
					QPSK	1	0	3	-85	23.49
					QPSK	1	5	3	-85	23.46
					QPSK	1	0	7	-85	23.55
					QPSK	1	5	7	-85	23.48
					QPSK	4	0	0	-85	23.77
					QPSK	4	2	7	-85	23.36
					QPSK	6	0	0	-85	23.67
					QPSK	6	0	7	-85	23.6
					16QAM	1	0	0	-85	23.87
					16QAM	1	5	0	-85	23.86
					16QAM	1	0	3	-85	23.68
					16QAM	1	5	3	-85	23.63
					16QAM	1	0	7	-85	23.64
16QAM	1	5	7	-85	23.5					
16QAM	4	2	0	-85	23.8					
16QAM	4	2	7	-85	23.48					

High Range	20350	1750	2350	2150	16QAM	5	0	0	-85	23.81
					16QAM	5	0	7	-85	23.75
					QPSK	1	0	0	-85	23.41
					QPSK	1	5	0	-85	23.47
					QPSK	1	5	7	-85	23.3
					QPSK	1	0	3	-85	23.18
					QPSK	1	5	3	-85	23.27
					QPSK	1	0	7	-85	23.45
					QPSK	4	0	0	-85	23.55
					QPSK	4	2	7	-85	23.62
					QPSK	6	0	0	-85	23.56
					QPSK	6	0	7	-85	23.55
					16QAM	1	0	0	-85	23.46
					16QAM	1	5	0	-85	23.5
					16QAM	1	0	3	-85	23.49
					16QAM	1	5	3	-85	23.39
					16QAM	1	0	7	-85	23.5
					16QAM	1	5	7	-85	23.66
					16QAM	4	2	0	-85	23.46
					16QAM	4	2	7	-85	23.73
16QAM	5	0	0	-85	23.44					
16QAM	5	0	7	-85	23.42					

BW(MHz): 15

Test Frequency ID	N <sub>UL</sub>	Frequency of Uplink [MHz]	N <sub>DL</sub>	Frequency of Downlink [MHz]	Test Configuration				Initial of Power		EUT	
					Modulation	RB Size	RB Offset	Narrowband Index	Cell power (dBm/15kHz)	power (dBm)		
Low Range	20025	1717.5	2025	2117.5	QPSK	1	0	0	-85	23.48		
					QPSK	1	5	0	-85	23.58		
					QPSK	1	0	5	-85	23.6		
					QPSK	1	5	5	-85	23.55		
					QPSK	1	0	11	-85	23.67		
					QPSK	1	5	11	-85	23.77		
					QPSK	3	0	0	-85	23.53		
					QPSK	3	3	11	-85	23.76		
					QPSK	6	0	0	-85	23.6		
					QPSK	6	0	11	-85	23.68		
					16QAM	1	0	0	-85	23.71		
					16QAM	1	5	0	-85	23.67		



					16QAM	1	0	5	-85	23.69
					16QAM	1	5	5	-85	23.69
					16QAM	1	0	11	-85	23.97
					16QAM	1	5	11	-85	23.96
					16QAM	3	0	0	-85	23.74
					16QAM	3	3	11	-85	23.64
					16QAM	5	0	0	-85	23.87
					16QAM	5	0	11	-85	23.77
Mid Range	20175	1732.5	2175	2132.5	QPSK	1	0	0	-85	24.12
					QPSK	1	5	0	-85	23.79
					QPSK	1	0	5	-85	23.62
					QPSK	1	5	5	-85	23.56
					QPSK	1	0	11	-85	23.61
					QPSK	1	5	11	-85	23.63
					QPSK	3	0	0	-85	23.86
					QPSK	3	3	11	-85	23.48
					QPSK	6	0	0	-85	23.9
					QPSK	6	0	11	-85	23.78
					16QAM	1	0	0	-85	24.08
					16QAM	1	5	0	-85	24.02
					16QAM	1	0	5	-85	23.82
					16QAM	1	5	5	-85	23.79
					16QAM	1	0	11	-85	23.75
					16QAM	1	5	11	-85	23.6
					16QAM	3	0	0	-85	23.9
					16QAM	3	3	11	-85	23.63
					16QAM	5	0	0	-85	24
					16QAM	5	0	11	-85	23.92
High Range	20325	1747.5	2325	2147.5	QPSK	1	0	0	-85	23.46
					QPSK	1	5	11	-85	23.54
					QPSK	1	0	5	-85	23.42
					QPSK	1	5	5	-85	23.34
					QPSK	1	0	11	-85	23.41
					QPSK	1	5	11	-85	23.53
					QPSK	3	0	0	-85	23.68
					QPSK	3	3	11	-85	23.76
					QPSK	6	0	0	-85	23.7
					QPSK	6	0	11	-85	23.58
					16QAM	1	0	0	-85	23.59
					16QAM	1	5	0	-85	23.59
					16QAM	1	0	5	-85	23.62

					16QAM	1	5	5	-85	23.58
					16QAM	1	0	11	-85	23.65
					16QAM	1	5	11	-85	23.79
					16QAM	3	0	0	-85	23.57
					16QAM	3	3	11	-85	23.85
					16QAM	5	0	0	-85	23.56
					16QAM	5	0	11	-85	23.58

BW(MHz): 20

Test Frequency ID	N <sub>UL</sub>	Frequency of Uplink [MHz]	N <sub>DL</sub>	Frequency of Downlink [MHz]	Test Configuration				Initial of Power		EUT	
					Modulation	RB Size	RB Offset	Narrowband Index	Cell power (dBm/15kHz)	power (dBm)		
Low Range	20050	1720	2050	2120	QPSK	1	0	0	-85	23.64		
					QPSK	1	5	0	-85	23.71		
					QPSK	1	0	7	-85	23.73		
					QPSK	1	5	7	-85	23.7		
					QPSK	1	0	15	-85	23.79		
					QPSK	1	5	15	-85	23.91		
					QPSK	3	0	0	-85	23.67		
					QPSK	3	3	15	-85	23.86		
					QPSK	6	0	0	-85	23.7		
					QPSK	6	0	15	-85	23.83		
					16QAM	1	0	0	-85	23.85		
					16QAM	1	5	0	-85	23.8		
					16QAM	1	0	7	-85	23.84		
					16QAM	1	5	7	-85	23.81		
					16QAM	1	0	15	-85	24.09		
					16QAM	1	5	15	-85	24.11		
					16QAM	3	0	0	-85	23.84		
					16QAM	3	3	15	-85	23.79		
16QAM	5	0	0	-85	24.03							
16QAM	5	0	15	-85	23.9							
Mid Range	20175	1732.5	2175	2132.5	QPSK	1	0	0	-85	24.22		
					QPSK	1	5	0	-85	23.91		
					QPSK	1	0	7	-85	23.73		
					QPSK	1	5	7	-85	23.7		
					QPSK	1	0	15	-85	23.77		
					QPSK	1	5	15	-85	23.74		
QPSK	3	0	0	-85	24.01							

					QPSK	3	3	15	-85	23.62
					QPSK	6	0	0	-85	23.99
					QPSK	6	0	15	-85	23.88
					16QAM	1	0	0	-85	24.17
					16QAM	1	5	0	-85	24.11
					16QAM	1	0	7	-85	23.92
					16QAM	1	5	7	-85	23.89
					16QAM	1	0	15	-85	23.87
					16QAM	1	5	15	-85	23.76
					16QAM	3	0	0	-85	24.05
					16QAM	3	3	15	-85	23.72
					16QAM	5	0	0	-85	24.11
					16QAM	5	0	15	-85	24.05
High Range	20300	1745	2300	2145	QPSK	1	0	0	-85	23.62
					QPSK	1	5	0	-85	23.7
					QPSK	1	0	7	-85	23.53
					QPSK	1	5	7	-85	23.43
					QPSK	1	0	15	-85	23.56
					QPSK	1	5	15	-85	23.68
					QPSK	3	0	0	-85	23.82
					QPSK	3	3	15	-85	23.89
					QPSK	6	0	0	-85	23.8
					QPSK	6	0	15	-85	23.74
					16QAM	1	0	0	-85	23.74
					16QAM	1	5	0	-85	23.73
					16QAM	1	0	7	-85	23.71
					16QAM	1	5	7	-85	23.68
					16QAM	1	0	15	-85	23.78
					16QAM	1	5	15	-85	23.89
					16QAM	3	0	0	-85	23.7
					16QAM	3	3	15	-85	24.01
					16QAM	5	0	0	-85	23.71
					16QAM	5	0	15	-85	23.73

eMTC	Band 13	Region(s):	FCC	Power:	Class 3	23	Tolerance:	2.7
------	---------	------------	-----	--------	---------	----	------------	-----

maximum:	23.53
----------	-------

BW(MHz):	5
----------	---

Test Frequency ID	N <sub>UL</sub>	Frequency of Uplink [MHz]	N <sub>DL</sub>	Frequency of Downlink [MHz]	Test Configuration				Initial of Power		EUT	
					Modulation	RB Size	RB Offset	Narrowband Index	Cell power (dBm/15kHz)	power (dBm)		
Low Range	23205	779.5	5205	748.5	QPSK	1	0	0	-85	23.32		
					QPSK	1	5	0	-85	23.12		
					QPSK	1	0	1	-85	23.15		
					QPSK	1	5	1	-85	23.11		
					QPSK	1	0	3	-85	23.31		
					QPSK	1	5	3	-85	23.22		
					QPSK	3	0	0	-85	22.16		
					QPSK	3	3	3	-85	22.11		
					QPSK	6	0	0	-85	22.24		
					QPSK	6	0	1	-85	22.45		
					QPSK	6	0	3	-85	22.32		
					16QAM	1	0	0	-85	23.41		
					16QAM	1	5	0	-85	23.23		
					16QAM	1	0	1	-85	23.28		
					16QAM	1	5	1	-85	23.27		
					16QAM	1	0	3	-85	23.21		
					16QAM	1	5	3	-85	23.15		
					16QAM	3	0	0	-85	22.45		
					16QAM	3	3	3	-85	22.24		
					16QAM	5	0	0	-85	21.67		
16QAM	5	0	1	-85	21.73							
16QAM	5	0	3	-85	21.72							
Mid Range	23230	782	5230	751	QPSK	1	0	0	-85	23.42		
					QPSK	1	5	0	-85	23.31		
					QPSK	1	0	1	-85	23.45		
					QPSK	1	5	1	-85	23.44		
					QPSK	1	0	3	-85	23.42		
					QPSK	1	5	3	-85	23.46		
					QPSK	3	0	0	-85	22.51		
					QPSK	3	3	3	-85	22.33		
					QPSK	6	0	0	-85	22.52		
					QPSK	6	0	1	-85	21.42		
					QPSK	6	0	3	-85	22.52		
					16QAM	1	0	0	-85	23.32		

High Range	23255	784.5	5255	753.5	16QAM	1	5	0	-85	23.39
					16QAM	1	0	1	-85	23.25
					16QAM	1	5	1	-85	23.41
					16QAM	1	0	3	-85	23.38
					16QAM	1	5	3	-85	23.29
					16QAM	3	0	0	-85	22.41
					16QAM	3	3	3	-85	22.45
					16QAM	5	0	0	-85	21.72
					16QAM	5	0	1	-85	21.62
					16QAM	5	0	3	-85	21.66
	23255	784.5	5255	753.5	QPSK	1	0	0	-85	22.93
					QPSK	1	5	0	-85	22.91
					QPSK	1	0	1	-85	22.92
					QPSK	1	5	1	-85	22.9
					QPSK	1	0	3	-85	23.05
					QPSK	1	5	3	-85	23.06
					QPSK	3	0	0	-85	21.98
					QPSK	3	3	3	-85	21.81
					QPSK	6	0	0	-85	21.84
					QPSK	6	0	1	-85	22.15
					QPSK	6	0	3	-85	22.07
					16QAM	1	0	0	-85	23.21
					16QAM	1	5	0	-85	22.98
					16QAM	1	0	1	-85	23.04
					16QAM	1	5	1	-85	21.99
					16QAM	1	0	3	-85	23.21
					16QAM	1	5	3	-85	22.71
					16QAM	3	0	0	-85	22.12
					16QAM	3	3	3	-85	22.15
					16QAM	5	0	0	-85	21.42
16QAM	5	0	1	-85	21.23					
16QAM	5	0	3	-85	21.52					

BW(MHz): 10

Test Frequency ID	NUL	Frequency of Uplink [MHz]	NBL	Frequency of Downlink [MHz]	Test Configuration				Initial of Power		EUT	
					Modulation	RB Size	RB Offset	Narrowband Index	Cell power (dBm/15kHz)	power (dBm)		
Mid Range	23230	782	5230	751	QPSK	1	0	0	-85	23.53		
					QPSK	1	5	0	-85	23.45		

				QPSK	1	0	3	-85	23.51
				QPSK	1	5	3	-85	23.48
				QPSK	1	0	7	-85	23.32
				QPSK	1	5	7	-85	23.23
				QPSK	4	0	0	-85	23.25
				QPSK	4	2	7	-85	23.39
				QPSK	6	0	0	-85	22.29
				QPSK	6	0	7	-85	22.34
				16QAM	1	0	0	-85	23.05
				16QAM	1	5	0	-85	22.85
				16QAM	1	0	3	-85	23.11
				16QAM	1	5	3	-85	23.14
				16QAM	1	0	7	-85	23.16
				16QAM	1	5	7	-85	23.15
				16QAM	4	2	0	-85	22.35
				16QAM	4	2	7	-85	22.56
				16QAM	5	0	0	-85	22.48
				16QAM	5	0	7	-85	22.81

**ERP Power (dBm)**

LTE Band 13							
Channel Bandwidth: 5 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
X	23205	779.5	-7.97	32.24	22.12	162.93	H
	23230	782.0	-7.22	32.17	22.80	190.55	
	23255	784.5	-7.94	32.11	22.02	159.22	
	23205	779.5	-13.43	32.43	16.85	48.42	V
	23230	782.0	-13.34	32.42	16.93	49.32	
	23255	784.5	-13.67	32.46	16.64	46.13	
Channel Bandwidth: 5 MHz / 16QAM							
X	23205	779.5	-8.77	32.24	21.32	135.52	H
	23230	782.0	-8.12	32.17	21.90	154.88	
	23255	784.5	-8.64	32.11	21.32	135.52	
	23205	779.5	-14.23	32.43	16.05	40.27	V
	23230	782.0	-14.24	32.42	16.03	40.09	
	23255	784.5	-14.37	32.46	15.94	39.26	

Note: ERP (dBm) = Reading (dBm) + Correction Factor (dB) – 2.15

LTE Band 13							
Channel Bandwidth: 10 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
X	23230	782.0	-6.97	32.17	23.05	201.84	H
	23230	782.0	-13.09	32.42	17.18	52.24	V
Channel Bandwidth: 10 MHz / 16QAM							
X	23230	782.0	-7.87	32.17	22.15	164.06	H
	23230	782.0	-13.89	32.42	16.38	43.45	V

Note: ERP (dBm) = Reading (dBm) + Correction Factor (dB) – 2.15

**EIRP Power (dBm)**

LTE Band 4							
Channel Bandwidth: 1.4 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
X	19957	1710.7	-11.59	36.45	24.86	306.20	H
	20175	1732.5	-11.75	36.80	25.05	319.89	
	20393	1754.3	-12.13	36.94	24.81	302.69	
	19957	1710.7	-17.09	37.28	20.19	104.47	V
	20175	1732.5	-17.25	37.63	20.38	109.14	
	20393	1754.3	-17.52	37.64	20.12	102.80	
Channel Bandwidth: 1.4 MHz / 16QAM							
X	19957	1710.7	-14.02	36.45	22.43	174.98	H
	20175	1732.5	-14.04	36.80	22.76	188.80	
	20393	1754.3	-14.41	36.94	22.53	179.06	
	19957	1710.7	-19.40	37.28	17.88	61.38	V
	20175	1732.5	-19.51	37.63	18.12	64.86	
	20393	1754.3	-19.85	37.64	17.79	60.12	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

LTE Band 4							
Channel Bandwidth: 3 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
X	19965	1711.5	-11.55	36.45	24.90	309.03	H
	20175	1732.5	-11.70	36.80	25.10	323.59	
	20385	1753.5	-12.10	36.94	24.84	304.79	
	19965	1711.5	-17.06	37.28	20.22	105.20	V
	20175	1732.5	-17.17	37.63	20.46	111.17	
	20385	1753.5	-17.56	37.64	20.08	101.86	
Channel Bandwidth: 3 MHz / 16QAM							
X	19965	1711.5	-12.89	36.45	23.56	226.99	H
	20175	1732.5	-13.06	36.80	23.74	236.59	
	20385	1753.5	-13.45	36.94	23.49	223.36	
	19965	1711.5	-18.43	37.28	18.85	76.74	V
	20175	1732.5	-18.58	37.63	19.05	80.35	
	20385	1753.5	-18.86	37.64	18.78	75.51	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)



LTE Band 4							
Channel Bandwidth: 5 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
X	19975	1712.5	-11.54	36.45	24.91	309.74	H
	20175	1732.5	-11.63	36.80	25.17	328.85	
	20375	1752.5	-12.02	36.94	24.92	310.46	
	19975	1712.5	-17.03	37.28	20.25	105.93	V
	20175	1732.5	-17.12	37.63	20.51	112.46	
	20375	1752.5	-17.47	37.64	20.17	103.99	
Channel Bandwidth: 5 MHz / 16QAM							
X	19975	1712.5	-12.79	36.45	23.66	232.27	H
	20175	1732.5	-12.94	36.80	23.86	243.22	
	20375	1752.5	-13.31	36.94	23.63	230.67	
	19975	1712.5	-18.20	37.28	19.08	80.91	V
	20175	1732.5	-18.37	37.63	19.26	84.33	
	20375	1752.5	-18.73	37.64	18.91	77.80	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

LTE Band 4							
Channel Bandwidth: 10 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
X	20000	1715.0	-11.65	36.64	24.99	315.50	H
	20175	1732.5	-11.59	36.80	25.21	331.89	
	20350	1750.0	-11.85	36.80	24.95	312.61	
	20000	1715.0	-17.13	37.44	20.31	107.40	V
	20175	1732.5	-17.09	37.63	20.54	113.24	
	20350	1750.0	-17.44	37.64	20.20	104.71	
Channel Bandwidth: 10 MHz / 16QAM							
X	20000	1715.0	-12.96	36.64	23.68	233.35	H
	20175	1732.5	-12.82	36.80	23.98	250.03	
	20350	1750.0	-13.12	36.80	23.68	233.35	
	20000	1715.0	-18.25	37.44	19.19	82.99	V
	20175	1732.5	-18.25	37.63	19.38	86.70	
	20350	1750.0	-18.67	37.64	18.97	78.89	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

LTE Band 4							
Channel Bandwidth: 15 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
X	20025	1717.5	-11.42	36.45	25.03	318.42	H
	20175	1732.5	-11.54	36.80	25.26	335.74	
	20325	1747.5	-11.90	36.94	25.04	319.15	
	20025	1717.5	-16.91	37.28	20.37	108.89	V
	20175	1732.5	-17.03	37.63	20.60	114.82	
	20325	1747.5	-17.36	37.64	20.28	106.66	
Channel Bandwidth: 15 MHz / 16QAM							
X	20025	1717.5	-12.50	36.45	23.95	248.31	H
	20175	1732.5	-12.69	36.80	24.11	257.63	
	20325	1747.5	-12.96	36.94	23.98	250.03	
	20025	1717.5	-18.00	37.28	19.28	84.72	V
	20175	1732.5	-18.12	37.63	19.51	89.33	
	20325	1747.5	-18.48	37.64	19.16	82.41	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

LTE Band 4							
Channel Bandwidth: 20 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
X	20050	1720.0	-11.34	36.45	25.11	324.34	H
	20175	1732.5	-11.47	36.80	25.33	341.19	
	20300	1745.0	-11.86	36.94	25.08	322.11	
	20050	1720.0	-16.83	37.28	20.45	110.92	V
	20175	1732.5	-16.96	37.63	20.67	116.68	
	20300	1745.0	-17.31	37.64	20.33	107.89	
Channel Bandwidth: 20 MHz / 16QAM							
X	20050	1720.0	-12.39	36.45	24.06	254.68	H
	20175	1732.5	-12.55	36.80	24.25	266.07	
	20300	1745.0	-12.92	36.94	24.02	252.35	
	20050	1720.0	-17.91	37.28	19.37	86.50	V
	20175	1732.5	-18.00	37.63	19.63	91.83	
	20300	1745.0	-18.37	37.64	19.27	84.53	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

## 4.2 Modulation Characteristics Measurement

### 4.2.1 Limits of Modulation Characteristics

N/A



### 4.2.2 Test Setup



### 4.2.3 Test Procedure

Connect the EUT to Communication Simulator via the antenna connector. The frequency band is set as EUT supported Modulation and Channels, the EUT output is matched with 50 ohm load, the waveform quality and constellation of the EUT was tested.

### 4.2.4 Test Results



### 4.3 Frequency Stability Measurement

#### 4.3.1 Limits of Frequency Stability Measurement


The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

#### 4.3.2 Test Procedure

- Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the  $\pm 0.5^\circ\text{C}$  during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

**Note:** The frequency error was recorded frequency error from the communication simulator.

#### 4.3.3 Test Setup



#### 4.3.4 Test Results

##### Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 4			
	Channel Bandwidth: 1.4 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
3.145	1710.700003	0.002	1754.300003	0.002
3.7	1710.700002	0.001	1754.300003	0.002
4.225	1710.700003	0.002	1754.300004	0.002

**Note:** The applicant defined the normal working voltage of the battery is from 3.7 Vdc to 4.225 Vdc.

##### Frequency Error vs. Temperature

Temp. (°C)	LTE Band 4			
	Channel Bandwidth: 1.4 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	1710.700003	0.002	1754.300001	0.001
-30	1710.700004	0.002	1754.300003	0.002
-20	1710.700003	0.001	1754.300003	0.002
-10	1710.700003	0.002	1754.300001	0.001
0	1710.700002	0.001	1754.300003	0.002
10	1710.699997	-0.002	1754.299999	-0.001
20	1710.699997	-0.002	1754.299999	-0.001
30	1710.699999	-0.001	1754.299999	-0.001
40	1710.699996	-0.002	1754.299998	-0.001
50	1710.699996	-0.002	1754.299998	-0.001
60	1710.699996	-0.002	1754.299998	-0.001
70	1710.699996	-0.002	1754.299997	-0.002
75	1710.699997	-0.002	1754.299997	-0.002

## Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 4			
	Channel Bandwidth: 3 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
3.145	1710.700004	0.002	1754.300003	0.002
3.7	1710.700003	0.002	1754.300002	0.001
4.225	1710.700002	0.001	1754.300004	0.002

**Note:** The applicant defined the normal working voltage of the battery is from 3.7 Vdc to 4.225 Vdc.

## Frequency Error vs. Temperature

Temp. (°C)	LTE Band 4			
	Channel Bandwidth: 3 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	1710.700004	0.002	1754.300003	0.002
-30	1710.700003	0.002	1754.300003	0.002
-20	1710.700002	0.001	1754.300003	0.002
-10	1710.700001	0.001	1754.300001	0.001
0	1710.700004	0.002	1754.300002	0.001
10	1710.699997	-0.002	1754.299998	-0.001
20	1710.699998	-0.001	1754.299999	-0.001
30	1710.699998	-0.001	1754.299998	-0.001
40	1710.699998	-0.001	1754.299999	-0.001
50	1710.699996	-0.002	1754.299997	-0.002
60	1710.699997	-0.002	1754.299998	-0.001
70	1710.699998	-0.001	1754.299997	-0.002
75	1710.699998	-0.001	1754.299997	-0.002

## Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 4			
	Channel Bandwidth: 5 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
3.145	1710.700003	0.002	1754.300002	0.001
3.7	1710.700003	0.002	1754.300003	0.001
4.225	1710.700003	0.002	1754.300003	0.002

**Note:** The applicant defined the normal working voltage of the battery is from 3.7 Vdc to 4.225 Vdc.

## Frequency Error vs. Temperature

Temp. (°C)	LTE Band 4			
	Channel Bandwidth: 5 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	1710.700001	0.001	1754.300001	0.001
-30	1710.700001	0.001	1754.300003	0.002
-20	1710.700001	0.001	1754.300004	0.002
-10	1710.700003	0.002	1754.300004	0.002
0	1710.700003	0.002	1754.300004	0.002
10	1710.699997	-0.002	1754.299996	-0.002
20	1710.699997	-0.002	1754.299999	-0.001
30	1710.699996	-0.002	1754.299996	-0.002
40	1710.699997	-0.002	1754.299997	-0.001
50	1710.699997	-0.002	1754.299996	-0.002
60	1710.699999	-0.001	1754.299998	-0.001
70	1710.699997	-0.002	1754.299999	-0.001
75	1710.699998	-0.001	1754.299996	-0.002



## Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 4			
	Channel Bandwidth: 10 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
3.145	1710.700003	0.002	1754.300004	0.002
3.7	1710.700001	0.001	1754.300003	0.002
4.225	1710.700001	0.001	1754.300001	0.001

**Note:** The applicant defined the normal working voltage of the battery is from 3.7 Vdc to 4.225 Vdc.

## Frequency Error vs. Temperature

Temp. (°C)	LTE Band 4			
	Channel Bandwidth: 10 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	1710.700001	0.001	1754.300001	0.001
-30	1710.700004	0.002	1754.300003	0.002
-20	1710.700002	0.001	1754.300002	0.001
-10	1710.700002	0.001	1754.300004	0.002
0	1710.700003	0.002	1754.300003	0.002
10	1710.699997	-0.002	1754.299997	-0.002
20	1710.699999	-0.001	1754.299996	-0.002
30	1710.699997	-0.002	1754.299996	-0.002
40	1710.699996	-0.002	1754.299999	-0.001
50	1710.699998	-0.001	1754.299998	-0.001
60	1710.699998	-0.001	1754.299998	-0.001
70	1710.699997	-0.002	1754.299997	-0.002
75	1710.699999	-0.001	1754.299998	-0.001

## Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 4			
	Channel Bandwidth: 15 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
3.145	1710.700003	0.002	1754.300002	0.001
3.7	1710.700002	0.001	1754.300003	0.002
4.225	1710.700003	0.002	1754.300004	0.002

**Note:** The applicant defined the normal working voltage of the battery is from 3.7 Vdc to 4.225 Vdc.

## Frequency Error vs. Temperature

Temp. (°C)	LTE Band 4			
	Channel Bandwidth: 15 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	1710.700001	0.001	1754.300004	0.002
-30	1710.700003	0.002	1754.300003	0.002
-20	1710.700004	0.002	1754.300004	0.002
-10	1710.700003	0.002	1754.300002	0.001
0	1710.700002	0.001	1754.300001	0.001
10	1710.699998	-0.001	1754.299998	-0.001
20	1710.699998	-0.001	1754.299996	-0.002
30	1710.699999	-0.001	1754.299999	-0.001
40	1710.699998	-0.001	1754.299996	-0.002
50	1710.699998	-0.001	1754.299996	-0.002
60	1710.699998	-0.001	1754.299999	-0.001
70	1710.699997	-0.002	1754.299999	-0.001
75	1710.699997	-0.002	1754.299997	-0.002

## Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 4			
	Channel Bandwidth: 20 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
3.145	1710.700002	0.001	1754.300002	0.001
3.7	1710.700002	0.001	1754.300002	0.001
4.225	1710.700003	0.002	1754.300003	0.002

**Note:** The applicant defined the normal working voltage of the battery is from 3.7 Vdc to 4.225 Vdc.

## Frequency Error vs. Temperature

Temp. (°C)	LTE Band 4			
	Channel Bandwidth: 20 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	1710.700004	0.002	1754.300003	0.002
-30	1710.700004	0.002	1754.300003	0.002
-20	1710.700002	0.001	1754.300001	0.001
-10	1710.700002	0.001	1754.300002	0.001
0	1710.700003	0.002	1754.300004	0.002
10	1710.699998	-0.001	1754.299999	-0.001
20	1710.699999	-0.001	1754.299998	-0.001
30	1710.699999	-0.001	1754.299998	-0.001
40	1710.699998	-0.001	1754.299997	-0.002
50	1710.699996	-0.002	1754.299997	-0.001
60	1710.699998	-0.001	1754.299997	-0.002
70	1710.699996	-0.002	1754.299999	-0.001
75	1710.699999	-0.001	1754.299997	-0.002

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 13			
	Channel Bandwidth: 5 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
3.145	779.500004	0.005	784.500003	0.003
3.7	779.500002	0.003	784.500003	0.004
4.225	779.500003	0.004	784.500003	0.004

**Note:** The applicant defined the normal working voltage of the battery is from 3.7 Vdc to 4.225 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 13			
	Channel Bandwidth: 5 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	779.500002	0.003	784.500003	0.004
-30	779.500002	0.002	784.500002	0.002
-20	779.500004	0.005	784.500002	0.003
-10	779.500003	0.003	784.500003	0.004
0	779.500002	0.003	784.500002	0.003
10	779.499996	-0.005	784.499997	-0.004
20	779.499999	-0.002	784.499996	-0.005
30	779.499997	-0.004	784.499996	-0.005
40	779.499999	-0.002	784.499998	-0.002
50	779.499998	-0.003	784.499998	-0.002
60	779.499997	-0.004	784.499998	-0.002
70	779.499999	-0.002	784.499998	-0.003
75	779.499997	-0.004	784.499996	-0.005

## Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 13	
	Channel Bandwidth: 10 MHz	
	Frequency (MHz)	Frequency Error (ppm)
3.145	779.500002	0.002
3.7	779.500003	0.003
4.225	779.500003	0.004

**Note:** The applicant defined the normal working voltage of the battery is from 3.7 Vdc to 4.225 Vdc.

## Frequency Error vs. Temperature

Temp. (°C)	LTE Band 13	
	Channel Bandwidth: 10 MHz	
	Frequency (MHz)	Frequency Error (ppm)
-40	779.500002	0.002
-30	779.500003	0.004
-20	779.500004	0.005
-10	779.500003	0.004
0	779.500003	0.004
10	779.499999	-0.001
20	779.499997	-0.003
30	779.499997	-0.004
40	779.499997	-0.004
50	779.499997	-0.003
60	779.499996	-0.005
70	779.499996	-0.005
75	779.499999	-0.001

## 4.4 Occupied Bandwidth Measurement


### 4.4.1 Limits of Occupied Bandwidth Measurement

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

### 4.4.2 Test Procedure

- The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
- Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

### 4.4.3 Test Setup




#### 4.4.4 Test Result

LTE Band 4					
Channel Bandwidth: 1.4 MHz					
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		26 dB Bandwidth (MHz)	
		QPSK	16QAM	QPSK	16QAM
19957	1710.7	1.0910	0.9120	1.252	1.106
20175	1732.5	1.0918	0.9129	1.250	1.098
20393	1754.3	1.0909	0.9132	1.253	1.103


Channel Bandwidth: 3 MHz					
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		26 dB Bandwidth (MHz)	
		QPSK	16QAM	QPSK	16QAM
19965	1711.5	1.0876	0.9219	1.372	1.187
20175	1732.5	1.0905	0.9213	1.335	1.187
20385	1753.5	1.0904	0.9162	1.354	1.147



LTE Band 4					
Channel Bandwidth: 5 MHz					
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		26 dB Bandwidth (MHz)	
		QPSK	16QAM	QPSK	16QAM
19975	1712.5	1.0874	0.9112	1.357	1.183
20175	1732.5	1.0973	0.9177	1.342	1.166
20375	1752.5	1.0910	0.9149	1.286	1.175

Channel Bandwidth: 10 MHz					
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		26 dB Bandwidth (MHz)	
		QPSK	16QAM	QPSK	16QAM
20000	1715.0	1.0939	0.9135	1.468	1.225
20175	1732.5	1.0886	0.9117	1.440	1.274
20350	1750.0	1.0918	0.9146	1.408	1.255






LTE Band 4					
Channel Bandwidth: 15 MHz					
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		26 dB Bandwidth (MHz)	
		QPSK	16QAM	QPSK	16QAM
20025	1717.5	1.1063	0.9237	1.517	1.321
20175	1732.5	1.1047	0.9244	1.453	1.343
20325	1747.5	1.1014	0.9275	1.504	1.287


Channel Bandwidth: 20 MHz					
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		26 dB Bandwidth (MHz)	
		QPSK	16QAM	QPSK	16QAM
20050	1720.0	1.0951	0.9178	1.455	1.365
20175	1732.5	1.0942	0.9175	1.452	1.374
20300	1745.0	1.0946	0.9174	1.405	1.369



LTE Band 13					
Channel Bandwidth: 5 MHz					
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		26 dB Bandwidth (MHz)	
		QPSK	16QAM	QPSK	16QAM
23205	779.5	1.0954	0.9207	1.300	1.153
23230	782.0	1.0962	0.9206	1.297	1.147
23255	784.5	1.0967	0.9205	1.297	1.147

Channel Bandwidth: 10 MHz					
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		26 dB Bandwidth (MHz)	
		QPSK	16QAM	QPSK	16QAM
23230	782.0	1.0939	0.9159	1.401	1.232



## 4.5 Band Edge Measurement

### 4.5.1 Limits of Band Edge Measurement

For ISED

For operations in the 698-787 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least  $43 + 10 \log (P)$  dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater.

However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.


For FCC

For operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least  $43 + 10 \log (P)$  dB.

On all frequencies between 763-775 MHz and 793-805 MHz, by a factor no less than  $65 + 10 \log (P)$  dB in a 6.25 kHz band segment, for mobile and portable stations.

For operations in the 1710–1755 MHz bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log (P)$  dB.


### 4.5.2 Test Setup




### 4.5.3 Test Procedures

- All measurements were done at low and high operational frequency range.
- 16 kHz and VB of the spectrum is 51 kHz (LTE Bandwidth 1.4 MHz).
- The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 16 kHz and VB of the spectrum is 51 kHz (LTE Bandwidth 3 MHz).
- The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 16 kHz and VB of the spectrum is 51 kHz (LTE Bandwidth 5 MHz).
- The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 16 kHz and VB of the spectrum is 51 kHz (LTE Bandwidth 10 MHz).
- The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 16 kHz and VB of the spectrum is 51 kHz (LTE Bandwidth 15 MHz).
- The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 16 kHz and VB of the spectrum is 51 kHz (LTE Bandwidth 20 MHz).
- Record the max. trace plot into the test report.


#### 4.5.4 Test Results





**LTE Band 4**  
**Channel Bandwidth: 3 MHz**





**LTE Band 4**  
**Channel Bandwidth: 5 MHz**



**LTE Band 4**  
**Channel Bandwidth: 10 MHz**






**LTE Band 4**  
**Channel Bandwidth: 15 MHz**






**LTE Band 4**  
**Channel Bandwidth: 20 MHz**






LTE Band 13

Channel Bandwidth: 10 MHz




### Emission Mask



For the 763 - 775 MHz and 793 - 805 MHz band, the FCC limit is  $65 + 10\log(P[\text{watt}])$  in a 6.25 kHz bandwidth. Since it was not possible to set the resolution bandwidth to 6.25 kHz with the available equipment, a bandwidth of 10 kHz was used instead to show compliance. By using a 10 kHz bandwidth on the spectrum analyzer.

$$10\log(10\text{kHz}/6.25\text{kHz}) = 2.04 \text{ dB}$$

$$\text{Limit line} = -35 \text{ dBm} + 2.04 \text{ dB} = -32.96 \text{ dBm}$$



For the 763 - 775 MHz and 793 - 805 MHz band, the FCC limit is  $65+10\log(P[\text{watt}])$  in a 6.25 kHz bandwidth. Since it was not possible to set the resolution bandwidth to 6.25 kHz with the available equipment, a bandwidth of 10 kHz was used instead to show compliance. By using a 10 kHz bandwidth on the spectrum analyzer.

$$10\log(10\text{kHz}/6.25\text{kHz}) = 2.04 \text{ dB}$$


$$\text{Limit line} = -35 \text{ dBm} + 2.04 \text{ dB} = -32.96 \text{ dBm}$$

## 4.6 Peak to Average Ratio

### 4.6.1 Limits of Peak to Average Ratio Measurement

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB.

### 4.6.2 Test Setup




### 4.6.3 Test Procedures


1. Set resolution/measurement bandwidth  $\geq$  signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1 %.

#### 4.6.4 Test Results

LTE Band 4							
Channel Bandwidth: 1.4 MHz				Channel Bandwidth: 3 MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
19957	1710.7	4.36	5.42	19965	1711.5	4.31	5.38
20175	1732.5	4.44	5.54	20175	1732.5	4.38	5.49
20393	1754.3	4.55	5.61	20385	1753.5	4.53	5.64




LTE Band 4							
Channel Bandwidth: 5 MHz				Channel Bandwidth: 10 MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
19975	1712.5	4.47	5.01	20000	1715.0	4.43	4.89
20175	1732.5	4.57	5.21	20175	1732.5	4.47	4.98
20375	1752.5	4.69	5.36	20350	1750.0	4.59	5.11






LTE Band 4							
Channel Bandwidth: 15 MHz				Channel Bandwidth: 20 MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
20025	1717.5	4.36	4.85	20050	1720.0	4.34	4.86
20175	1732.5	4.42	4.92	20175	1732.5	4.40	4.90
20325	1747.5	4.53	5.01	20300	1745.0	4.48	4.96



LTE Band 13							
Channel Bandwidth: 5 MHz				Channel Bandwidth: 10 MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
23205	779.5	4.74	5.18	23230	782.0	4.71	5.19
23230	782.0	4.74	5.17				
23255	784.5	4.67	5.12				




## 4.7 Conducted Spurious Emissions

### 4.7.1 Limits of Conducted Spurious Emissions Measurement

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log (P)$  dB. The limit of emission is equal to -13 dBm.

For operations in the 775-788 MHz, emissions in the band 1559-1610 MHz shall be limited to -70 dBW/MHz. The limit of emissions is equal to -40 dBm / MHz.


### 4.7.2 Test Setup




### 4.7.3 Test Procedure

- The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- Measuring frequency range is from 9 kHz to 1 GHz. 10 dB attenuation pad is connected with spectrum. RBW = 300 kHz and VBW = 1 MHz is used for conducted emission measurement.
- Measuring frequency range is from 1 GHz to 7 GHz / 8 GHz / 18 GHz. 10 dB attenuation pad is connected with spectrum. RBW = 1 MHz and VBW = 3 MHz is used for conducted emission measurement.


#### 4.7.4 Test Results




Note: The signal over the limit in 9 kHz is from spectrum analyzer.




Note: The signal over the limit in 9 kHz is from spectrum analyzer.




Note: The signal over the limit in 9 kHz is from spectrum analyzer.




Note: The signal over the limit in 9 kHz is from spectrum analyzer.




Note: The signal over the limit in 9 kHz is from spectrum analyzer.




Note: The signal over the limit in 9 kHz is from spectrum analyzer.




Note: The signal over the limit in 9 kHz is from spectrum analyzer.



Note: The signal over the limit in 9 kHz is from spectrum analyzer.




Note: The signal over the limit in 9 kHz is from spectrum analyzer.




Note: The signal over the limit in 9 kHz is from spectrum analyzer.







Note: The signal over the limit in 9 kHz is from spectrum analyzer.




Note: The signal over the limit in 9 kHz is from spectrum analyzer.




Note: The signal over the limit in 9 kHz is from spectrum analyzer.




Note: The signal over the limit in 9 kHz is from spectrum analyzer.




Note: The signal over the limit in 9 kHz is from spectrum analyzer.




Note: The signal over the limit in 9 kHz is from spectrum analyzer.




Note: The signal over the limit in 9 kHz is from spectrum analyzer.




Note: The signal over the limit in 9 kHz is from spectrum analyzer.




Note: The signal over the limit in 9 kHz is from spectrum analyzer.



Note: The signal over the limit in 9 kHz is from spectrum analyzer.



Note: The signal over the limit in 9 kHz is from spectrum analyzer.



Note: The signal over the limit in 9 kHz is from spectrum analyzer.



## 4.8 Radiated Emission Measurement

### 4.8.1 Limits of Radiated Emission Measurement

- a. The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log (P)$  dB. The limit of emission is equal to -13 dBm.
- b. For operations in the 775-788 MHz, emissions in the band 1559-1610 MHz shall be limited to -70 dBW/MHz. The limit of emissions is equal to -40 dBm.

### 4.8.2 Test Procedure

- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8 m (below or equal 1 GHz) and/or 1.5 m (above 1 GHz) height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step a. Record the power level of S.G.
- c.  $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$ .
- d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole,  $E.R.P \text{ power} = E.I.R.P \text{ power} - 2.15 \text{ dB}$ .


**Note:** The resolution bandwidth of spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz.

### 4.8.3 Deviation from Test Standard


No deviation.

#### 4.8.4 Test Setup

##### <Radiated Emission below or equal 1 GHz>



##### <Radiated Emission above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.8.5 Test Results

LTE Band 4

Channel Bandwidth: 1.4 MHz / QPSK


Low Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 3



Site : 966 Chamber 5  
 Condition: PART27 HORIZONTAL  
 Remak : Cat-M1 Band 4 QPSK\_1.4M Link\_L-CH  
 Tested by: Getaz Yang


	Freq	Level	Read	Limit	Over		
	MHz	dBm	Level	Line	Factor	Limit	Remark
			dBm	dBm	dB	dB	
1	3421.40	-52.25	-43.91	-13.00	-8.34	-39.25	Peak
2	5132.10	-37.19	-35.45	-13.00	-1.74	-24.19	Peak
3 pp	6842.80	-35.76	-38.07	-13.00	2.31	-22.76	Peak



## Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 4



Site : 966 Chamber 5  
 Condition: PART27 VERTICAL  
 Remark : Cat-M1 Band 4 QPSK\_1.4M Link\_L-CH  
 Tested by: Getaz Yang

	Freq	Level	Read Level	Limit	Line Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	3421.40	-50.35	-42.01	-13.00	-8.34	-37.35	Peak
2	5132.10	-43.27	-41.53	-13.00	-1.74	-30.27	Peak


## Middle Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 3



Site : 966 Chamber 5  
 Condition: PART27 HORIZONTAL  
 Remak : Cat-M1 Band 4 QPSK\_1.4M Link\_M-CH  
 Tested by: Getaz Yang

	Read	Limit	Over			
Freq	Level	Level	Line	Factor	Limit	Remark
MHz	dBm	dBm	dBm	dB	dB	
1	3465.00	-52.37	-44.49	-13.00	-7.88	-39.37 Peak
2	5197.50	-41.39	-39.32	-13.00	-2.07	-28.39 Peak
3 pp	6930.00	-33.38	-36.07	-13.00	2.69	-20.38 Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 4

Date: 05-20-2019



Site : 966 Chamber 5  
 Condition: PART27 VERTICAL  
 Remark : Cat-M1 Band 4 QPSK\_1.4M Link\_M-CH  
 Tested by: Getaz Yang

	Freq	Level	Read Level	Limit	Line Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	3465.00	-49.35	-41.47	-13.00	-7.88	-36.35	Peak
2	5197.50	-43.07	-41.00	-13.00	-2.07	-30.07	Peak
3	6930.00	-44.10	-46.79	-13.00	2.69	-31.10	Peak


## High Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 3



Site : 966 Chamber 5  
 Condition: PART27 HORIZONTAL  
 Remak : Cat-M1 Band 4 QPSK\_1.4M Link\_H-CH  
 Tested by: Getaz Yang

	Freq	Level	Read Level	Limit	Over	Factor	Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	dB	
1	3508.60	-52.29	-44.84	-13.00	-7.45	-39.29	Peak	
2	5262.90	-42.68	-40.16	-13.00	-2.52	-29.68	Peak	
3 pp	7017.20	-34.63	-37.82	-13.00	3.19	-21.63	Peak	




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 4

Date: 05-20-2019



Site : 966 Chamber 5  
 Condition: PART27 VERTICAL  
 Remark : Cat-M1 Band 4 QPSK\_1.4M Link\_H-CH  
 Tested by: Getaz Yang

	Freq	Level	Read Level	Limit	Line Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	3508.60	-48.67	-41.22	-13.00	-7.45	-35.67	Peak
2	5262.90	-46.51	-43.99	-13.00	-2.52	-33.51	Peak
3 pp	7017.20	-41.21	-44.40	-13.00	3.19	-28.21	Peak




Channel Bandwidth: 5 MHz / QPSK  
Low Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 3



Site : 966 Chamber 5  
Condition: PART27 HORIZONTAL  
Remak : Cat-M1 Band 4 QPSK\_5M Link\_L-CH  
Tested by: Getaz Yang

	Freq	Level	Read Level	Limit	Over	Factor	Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB		
1	3425.00	-53.15	-44.81	-13.00	-8.34	-40.15	Peak	
2	5137.50	-38.29	-36.55	-13.00	-1.74	-25.29	Peak	
3 pp	6850.00	-36.30	-38.61	-13.00	2.31	-23.30	Peak	




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 4

Date: 05-20-2019



Site : 966 Chamber 5  
 Condition: PART27 VERTICAL  
 Remark : Cat-M1 Band 4 QPSK\_5M Link\_L-CH  
 Tested by: Getaz Yang

	Freq	Level	Read Level	Limit	Line Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	3425.00	-50.95	-42.61	-13.00	-8.34	-37.95	Peak
2	5137.50	-42.10	-40.36	-13.00	-1.74	-29.10	Peak
3	6850.00	-43.17	-45.48	-13.00	2.31	-30.17	Peak


## Middle Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 3



Site : 966 Chamber 5  
 Condition: PART27 HORIZONTAL  
 Remak : Cat-M1 Band 4 QPSK\_5M Link\_M-CH  
 Tested by: Getaz Yang

	Freq	Level	Read Level	Limit	Over	Factor	Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	dB	
1	3465.00	-52.69	-44.81	-13.00	-7.88	-39.69	Peak	
2	5197.50	-40.80	-38.73	-13.00	-2.07	-27.80	Peak	
3 pp	6930.00	-36.85	-39.54	-13.00	2.69	-23.85	Peak	




## Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 4

Date: 05-20-2019



Site : 966 Chamber 5  
 Condition: PART27 VERTICAL  
 Remark : Cat-M1 Band 4 QPSK\_5M Link\_M-CH  
 Tested by: Getaz Yang

	Freq	Level	Read Level	Limit	Line Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	3465.00	-49.69	-41.81	-13.00	-7.88	-36.69	Peak
2	5197.50	-42.66	-40.59	-13.00	-2.07	-29.66	Peak
3	6930.00	-43.76	-46.45	-13.00	2.69	-30.76	Peak


## High Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 3



Site : 966 Chamber 5  
 Condition: PART27 HORIZONTAL  
 Remak : Cat-M1 Band 4 QPSK\_5M Link\_H-CH  
 Tested by: Getaz Yang

	Freq	Level	Read Level	Limit	Over	Factor	Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	dB	
1	3505.00	-53.24	-45.79	-13.00	-7.45	-40.24	Peak	
2	5257.50	-42.55	-40.03	-13.00	-2.52	-29.55	Peak	
3 pp	7010.00	-32.77	-35.96	-13.00	3.19	-19.77	Peak	




## Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 4

Date: 05-20-2019



Site : 966 Chamber 5  
 Condition: PART27 VERTICAL  
 Remark : Cat-M1 Band 4 QPSK\_5M Link\_H-CH  
 Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	3505.00	-51.53	-44.08	-13.00	-7.45	-38.53	Peak
2	5257.50	-47.56	-45.04	-13.00	-2.52	-34.56	Peak
3	7010.00	-42.28	-45.47	-13.00	3.19	-29.28	Peak


Channel Bandwidth: 20 MHz / QPSK  
Low Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 3



Site : 966 Chamber 5  
Condition: PART27 HORIZONTAL  
Remak : Cat-M1 Band 4 QPSK\_20M Link\_L-CH  
Tested by: Getaz Yang

	Freq	Level	Read Level	Limit	Line Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	3440.00	-53.29	-45.07	-13.00	-8.22	-40.29	Peak
2	5160.00	-39.64	-37.73	-13.00	-1.91	-26.64	Peak
3 pp	6880.00	-36.37	-38.85	-13.00	2.48	-23.37	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 4

Date: 05-20-2019



Site : 966 Chamber 5  
 Condition: PART27 VERTICAL  
 Remark : Cat-M1 Band 4 QPSK\_20M Link\_L-CH  
 Tested by: Getaz Yang

	Freq	Level	Read Level	Limit	Line Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	3440.00	-50.92	-42.70	-13.00	-8.22	-37.92	Peak
2	5160.00	-43.47	-41.56	-13.00	-1.91	-30.47	Peak




## Middle Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 3



Site : 966 Chamber 5  
 Condition: PART27 HORIZONTAL  
 Remak : Cat-M1 Band 4 QPSK\_20M Link\_M-CH  
 Tested by: Getaz Yang

	Freq	Level	Read Level	Limit	Over	Factor	Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	dB	
1	3465.00	-53.00	-45.12	-13.00	-7.88	-40.00	Peak	
2	5197.50	-38.11	-36.04	-13.00	-2.07	-25.11	Peak	
3 pp	6930.00	-32.08	-34.77	-13.00	2.69	-19.08	Peak	




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 4

Date: 05-20-2019



Site : 966 Chamber 5  
 Condition: PART27 VERTICAL  
 Remak : Cat-M1 Band 4 QPSK\_20M Link\_M-CH  
 Tested by: Getaz Yang

	Freq	Level	Read Level	Limit	Line Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	3465.00	-50.11	-42.23	-13.00	-7.88	-37.11	Peak
2	pp 5197.50	-42.78	-40.71	-13.00	-2.07	-29.78	Peak
3	6930.00	-42.96	-45.65	-13.00	2.69	-29.96	Peak

# High Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 5

Date: 05-20-2019



Site : 966 Chamber 5  
 Condition: PART27 HORIZONTAL  
 Remak : Cat-M1 Band 4 QPSK\_20M Link\_H-CH  
 Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Over Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	42.61	-46.86	-45.92	-13.00	-0.94	-33.86	Peak
2	95.96	-57.22	-46.44	-13.00	-10.78	-44.22	Peak
3	363.68	-70.09	-63.93	-13.00	-6.16	-57.09	Peak
4	527.61	-68.87	-65.23	-13.00	-3.64	-55.87	Peak
5	635.28	-65.18	-64.33	-13.00	-0.85	-52.18	Peak
6	903.97	-61.55	-62.22	-13.00	0.67	-48.55	Peak
7	3490.00	-53.04	-45.39	-13.00	-7.65	-40.04	Peak
8	5235.00	-42.00	-39.59	-13.00	-2.41	-29.00	Peak
9 pp	6980.00	-32.02	-35.08	-13.00	3.06	-19.02	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 6

Date: 05-20-2019



Site : 966 Chamber 5  
 Condition: PART27 VERTICAL  
 Remak : Cat-M1 Band 4 QPSK\_20M Link\_H-CH  
 Tested by: Getaz Yang

	Freq	Level	Read Level	Limit	Line Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	pp	31.94	-38.84	-38.24	-13.00	-0.60	-25.84 Peak
2		53.28	-49.77	-43.96	-13.00	-5.81	-36.77 Peak
3		94.99	-53.64	-42.80	-13.00	-10.84	-40.64 Peak
4		373.38	-69.96	-63.86	-13.00	-6.10	-56.96 Peak
5		604.24	-65.24	-64.48	-13.00	-0.76	-52.24 Peak
6		903.97	-62.24	-62.91	-13.00	0.67	-49.24 Peak
7		3490.00	-49.46	-41.81	-13.00	-7.65	-36.46 Peak
8		5235.00	-44.03	-41.62	-13.00	-2.41	-31.03 Peak
9		6980.00	-39.74	-42.80	-13.00	3.06	-26.74 Peak


LTE Band 13  
 Channel Bandwidth: 5 MHz / QPSK  
 Low Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 3



Site : 966 Chamber 5  
 Condition: PART27(B13) HORIZONTAL  
 Remak : Cat-M1 Band 13 QPSK\_5M Link\_L-CH  
 Tested by: tim-chen

	Freq	Level	Read Level	Limit	Over	Remark
	MHz	dBm	dBm	dBm	dB	dB
1 pp	1559.00	-50.85	-37.53	-40.00	-13.32	-10.85 Peak
2	2338.50	-40.40	-31.02	-13.00	-9.38	-27.40 Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 4

Date: 2019-05-31



Site : 966 Chamber 5  
 Condition: PART27(B13) VERTICAL  
 Remak : Cat-M1 Band 13 QPSK\_5M Link\_L-CH  
 Tested by: tim-chen

	Freq	Level	Read Level	Limit	Line Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	1559.00	-45.80	-32.48	-40.00	-13.32	-5.80	Peak
2	2338.50	-41.43	-32.05	-13.00	-9.38	-28.43	Peak

### Middle Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 5

Date: 2019-05-31



Site : 966 Chamber 5  
 Condition: PART27(B13) HORIZONTAL  
 Remak : Cat-M1 Band 13 QPSK\_5M Link\_M-CH  
 Tested by: tim-chen

	Freq	Level	Read Level	Limit	Line Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	pp 1564.00	-49.63	-36.29	-40.00	-13.34	-9.63	Peak
2	2346.00	-37.78	-28.34	-13.00	-9.44	-24.78	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 6

Date: 2019-05-31



Site : 966 Chamber 5  
 Condition: PART27(B13) VERTICAL  
 Remak : Cat-M1 Band 13 QPSK\_5M Link\_M-CH  
 Tested by: tim-chen

	Freq	Level	Read Level	Limit	Line Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	1564.00	-45.79	-32.45	-40.00	-13.34	-5.79	Peak
2	2346.00	-42.81	-33.37	-13.00	-9.44	-29.81	Peak



## High Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 3

Date: 2019-05-31



Site : 966 Chamber 5  
 Condition: PART27(B13) HORIZONTAL  
 Remak : Cat-M1 Band 13 QPSK\_5M Link\_H-CH  
 Tested by: tim-chen

	Freq	Level	Read Level	Limit	Line Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	pp 1569.00	-49.81	-36.46	-40.00	-13.35	-9.81	Peak
2	2353.50	-36.34	-26.83	-13.00	-9.51	-23.34	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 4

Date: 2019-05-31



Site : 966 Chamber 5  
 Condition: PART27(B13) VERTICAL  
 Remak : Cat-M1 Band 13 QPSK\_5M Link\_H-CH  
 Tested by: tim-chen

	Freq	Level	Read Level	Limit	Line Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	1569.00	-45.97	-32.62	-40.00	-13.35	-5.97	Peak
2	2353.50	-44.32	-34.81	-13.00	-9.51	-31.32	Peak


Channel Bandwidth: 10 MHz / QPSK  
Middle Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9



Site : 966 Chamber 5  
Condition: PART27(B13) HORIZONTAL  
Remak : Cat-M1 Band 13 QPSK\_10M Link\_M-CH  
Tested by: tim-chen

	Freq	Level	Read	Limit	Over		
	MHz	dBm	Level	Line	Factor	Limit	Remark
			dBm	dBm	dB	dB	
1	32.91	-49.79	-48.70	-13.00	-1.09	-36.79	Peak
2	55.22	-53.19	-46.85	-13.00	-6.34	-40.19	Peak
3	98.87	-58.53	-47.91	-13.00	-10.62	-45.53	Peak
4	232.73	-67.92	-61.22	-13.00	-6.70	-54.92	Peak
5	561.56	-66.97	-64.60	-13.00	-2.37	-53.97	Peak
6	958.29	-62.85	-64.96	-13.00	2.11	-49.85	Peak
7 pp	1564.00	-52.60	-39.26	-40.00	-13.34	-12.60	Peak
8	2346.00	-38.62	-29.18	-13.00	-9.44	-25.62	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2019-05-31



Site : 966 Chamber 5  
 Condition: PART27(B13) VERTICAL  
 Remak : Cat-M1 Band 13 QPSK\_10M Link\_M-CH  
 Tested by: tim-chen

	Freq	Level	Read Level	Limit	Line Factor	Over	Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	dB	
1	30.97	-39.54	-39.43	-13.00	-0.11	-26.54		Peak
2	54.25	-51.86	-45.79	-13.00	-6.07	-38.86		Peak
3	93.05	-55.35	-44.40	-13.00	-10.95	-42.35		Peak
4	243.40	-69.85	-63.58	-13.00	-6.27	-56.85		Peak
5	623.64	-65.45	-64.63	-13.00	-0.82	-52.45		Peak
6	964.11	-62.22	-64.53	-13.00	2.31	-49.22		Peak
7 pp	1564.00	-45.61	-32.27	-40.00	-13.34	-5.61		Peak
8	2346.00	-42.99	-33.55	-13.00	-9.44	-29.99		Peak

## 5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

## Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Lin Kou EMC/RF Lab**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF/Telecom Lab**

Tel: 886-3-6668565

Fax: 886-3-6668323

**Hwa Ya EMC/RF/Safety Lab**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---