



H.B. Compliance Solutions

Maximum Permissible Exposure Statement

For the

Microchip Technology Inc.

MRF24J40MC Transceiver Module

January 12, 2011

Prepared for:

Microchip Technology Inc.

2355 W. Chandler Blvd.

Chandler, Arizona 85224

Prepared By:

H.B. Compliance Solutions

3292 E. Mead Drive

Gilbert, Arizona 85298

Reviewed By:

A handwritten signature in black ink, appearing to read 'Hoosamuddin Bandukwala'.

Hoosamuddin Bandukwala



Cert # ATL-0062-E

Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where,

S = power density (mW/cm²)

P = output power at the antenna terminal (mW)

G = gain of transmit antenna (numeric)

R = distance from transmitting antenna (cm)

Maximum peak output power at antenna input terminal = 18.89 (dBm)

Maximum peak output power at antenna input terminal = 77.45 (mW)

Antenna gain (typical) = 5 (dBi)

Maximum antenna gain = 3.16 (numeric)

Prediction distance = 200 (cm)

Prediction frequency = 2405 (MHz)

MPE limit for uncontrolled exposure at prediction frequency = 1.0 (mW/cm²)

Power density at prediction frequency = 0.0486913 (mW/cm²)

To solve for the minimum mounting distance required;

$$R = \sqrt{PG/4\pi S}$$

$$R = \sqrt{77.45 \times 3.16 / 4\pi \times 0.0486913} = \underline{20 \text{ cm}} \text{ (Based on continuous transmission)}$$

END OF TEST REPORT