

## TABLE OF CONTENTS LIST

APPLICANT: J COMMUNICATIONS CO., LTD.

FCC ID: OAJJGG2002

TEST REPORT:

PAGE	1.....COVER SHEET - GENERAL INFORMATION & TECHNICAL DESCRIPTIVE
PAGE	2.....TECHNICAL DESCRIPTION CONTINUED
PAGE	3.....RF POWER OUTPUT
PAGE	4.....MODULATION CHARACTERISTICS
PAGE	5.....AUDIO FREQUENCY RESPONSE GRAPH
PAGE	6.....MODULATION LIMITING GRAPH - 300Hz
PAGE	7.....MODULATION LIMITING GRAPH - 1000Hz
PAGE	8.....MODULATION LIMITING GRAPH - 2500Hz
PAGE	9.....AUDIO LOW PASS FILTER GRAPH
PAGE	10.....OCCUPIED BANDWIDTH
PAGE	11.....OCCUPIED BANDWIDTH PLOT
PAGE	12.....OCCUPIED BANDWIDTH PLOT - CW
PAGE	13.....SPURIOUS EMISSIONS AT ANTENNA TERMINALS
PAGE	14.....UNWANTED RADIATION
PAGE	15.....METHOD OF MEASURING RADIATED SPURIOUS EMISSIONS
PAGE	16.....FREQUENCY STABILITY
PAGE	17-19..LIST OF TEST EQUIPMENT

EXHIBITS CONTAINING:

EXHIBIT 1.....	FCC ID LABEL SAMPLE
EXHIBIT 2.....	SKETCH OF LOCATION
EXHIBIT 3.....	EXTERNAL PHOTOGRAPHS
EXHIBIT 4.....	INTERNAL PHOTOGRAPHS
EXHIBIT 5.....	BLOCK DIAGRAM
EXHIBIT 6.....	SCHEMATICS
EXHIBIT 7.....	USER'S MANUAL
EXHIBIT 8.....	CIRCUIT DESCRIPTION
EXHIBIT 9.....	TUNING PROCEDURE
EXHIBIT 10.....	PARTS LIST
EXHIBIT 11.....	TEST SET UP PHOTO
EXHIBIT 12.....	SAR TEST REPORT

APPLICANT: J COMMUNICATIONS CO., LTD.

FCC ID: OAJJGG2002

REPORT #: J\Jcom\_OAJ\1198UT2\1198UT2TestReport.doc

TABLE OF CONTENTS

GENERAL INFORMATION REQUIRED  
FOR CERTIFICATION

2.1033(c)(1)(2) J COMMUNICATIONS CO., LTD. will manufacture the  
FCCID: OAJJGG2002 GMRS TRANSCEIVER in quantity,  
for use under FCC RULES PART 95.

J COMMUNICATIONS CO., LTD.  
124-4 OJEON-DONG,  
UIWANG-CITY, KYUNGKI-DO, KOREA

2.1033 (c) TECHNICAL DESCRIPTION

2.1033(c)(3) Instruction book. A draft copy of the instruction  
manual is included as EXHIBIT 7.

2.1033(c)(4) Type of Emission: 10K0F3E  
95.631

$$\begin{aligned} B_n &= 2M + 2DK \\ M &= 2500 \\ D &= 2500 \\ B_n &= 2(2500) + 2(2500) = 10.0K \end{aligned}$$

Authorized Bandwidth 20.0 kHz

2.1033(c)(5) Frequency Range: 1. 462.5625 9. 462.6250  
95.621 2. 462.5875 10. 462.6750  
3. 462.6125 11. 462.5500  
4. 462.6375 12. 462.6000  
5. 462.6625 13. 462.6500  
6. 462.6875 14. 462.6500  
7. 462.7125 15. 462.7250  
8. 462.5750

2.10311c)(6)(7) The Maximum Output Power Rating:  
HIGH: 1.0 Watts

2.1033(c)(8) DC Voltages and Current into Final Amplifier:  
FINAL AMPLIFIER ONLY

FOR HIGH POWER SETTING INPUT POWER: (6.9V)(.60A) = 4.14 WATTS

2.1033(c)(9) Tune-up procedure. The tune-up procedure is included  
as EXHIBIT # 9.

APPLICANT: J COMMUNICATIONS CO., LTD.

FCC ID: OAJJGG2002

REPORT #: J\Jcom\_OAJ\1198UT2\1198UT2TestReport.doc

Page 1 of 19

2.1033(c)(10) Complete Circuit Diagrams: The circuit diagram is included as EXHIBIT 6 of this report. The block diagrams are included as EXHIBIT 5 of this report.

2.1033(c)(11) A photograph or a drawing of the equipment identification label is included as exhibit No. 1.

2.1033(c)(12) Photographs(8"X10") of the equipment of sufficient clarity to reveal equipment construction and layout, including meters, labels for controls, including any view under shields. See exhibits 3-4.

2.1033(c)(13) Digital modulation is not allowed.

2.1033(c)(14) The data required by 2.1046 through 2.1057 is submitted below.


95.639 Power Output shall not exceed 50.0 Watts effective radiated power. There can be no provisions for increasing the power or varying the power.

95.649

2.1046(a) RF power is measured by the substitution method as outlined in TIA/EIA - 603. With a nominal battery voltage of 6.0 V, and the transmitter properly adjusted the RF output measures:

OUTPUT POWER: HIGH: 1.0 Watts ERP

2.1046(a) RF power output. The test procedure used was TIA/EIA-603 S2



2.1047(a)(b) Modulation characteristics:

AUDIO FREQUENCY RESPONSE

The audio frequency response was measured in accordance with TIA/EIA Specification 603. The audio frequency response curve is shown on the next page. The audio signal was fed into a dummy microphone circuit and into the microphone connector. The input required to produce 30 percent modulation level was measured. See Page 5 of report.

2.1047(b) Audio input versus modulation

The audio input level needed for a particular percentage of modulation was measured in accordance with TIA/EIA Specification 603. The audio input curves versus modulation are on the following pages. Curves are provided for audio input frequencies of 300, 1000, and 2500 Hz. See Pages 6,7 & 8 of report.

95.637

Post Limiter Filter Each GMRS transmitter, except a mobile station transmitter with a power of 2.5Watts or less, must be equipped with an audio low pass filter. At any frequency between 3 & 20 kHz the filter must have an attenuation of  $60\log(f/3)$  greater than the attenuation at 1KHz. See Page 9 of report.


APPLICANT: J COMMUNICATIONS CO., LTD.

FCC ID: OAJJGG2002

REPORT #: J\Jcom\_OAJ\1198UT2\1198UT2TestReport.doc


Page 4 of 19

**AUDIO FREQUENCY RESPONSE PLOT**




APPLICANT: J COMMUNICATIONS CO., LTD.  
FCC ID: OAJJGG2002  
REPORT #: J\Jcom\_OAJ\1198UT2\1198UT2TestReport.doc  
Page 5 of 19

MODULATION LIMITING PLOT - 300 Hz




APPLICANT: J COMMUNICATIONS CO., LTD.  
FCC ID: OAJGG2002  
REPORT #: J\Jcom\_OAJ\1198UT2\1198UT2TestReport.doc  
Page 6 of 19

MODULATION LIMITING PLOT - 1000 Hz



APPLICANT: J COMMUNICATIONS CO., LTD.  
FCC ID: OAJJGG2002  
REPORT #: J\Jcom\_OAJ\1198UT2\1198UT2TestReport.doc  
Page 7 of 19

MODULATION LIMITING PLOT (2500 Hz)



APPLICANT: J COMMUNICATIONS CO., LTD.  
FCC ID: OAJGG2002  
REPORT #: J\Jcom\_OAJ\1198UT2\1198UT2TestReport.doc  
Page 8 of 19


AUDIO LOW PASS FILTER PLOT

## Audio Lowpass Filter

Model : JGG-2002

Date : 02.11.14

Test By : H.S. Moon



APPLICANT: J COMMUNICATIONS CO., LTD.

FCC ID: OAJGG2002


REPORT #: J\Jcom\_OAJ\1198UT2\1198UT2TestReport.doc

Page 9 of 19


2.1049                    Occupied bandwidth:  
95.635(b)(1)(3)(7)

At least 25dB on any frequency removed from the center of the authorized bandwidth by more than 50% up to and including 100% of the authorized bandwidth. At least 35 dB on any frequency removed from the center of the authorized BW by more than 100% up to and including 250% of the authorized BW. At least  $43 + \log_{10}(TP)$  dB on any frequency removed from the center of the authorized bandwidth by more than 250%. See plots on the next 2 pages.

Occupied BW Test Equipment Setup




OCCUPIED BANDWIDTH PLOT



APPLICANT: J COMMUNICATIONS CO., LTD.  
FCC ID: OAJJGG2002  
REPORT #: J\Jcom\_OAJ\1198UT2\1198UT2TestReport.doc  
Page 11 of 19


OCCUPIED BANDWIDTH PLOT CW



APPLICANT: J COMMUNICATIONS CO., LTD.  
FCC ID: OAJJGG2002  
REPORT #: J\Jcom\_OAJ\1198UT2\1198UT2TestReport.doc  
Page 12 of 19

2.1051 Spurious emissions at antenna terminals (conducted):  
The following data shows the level of conducted spurious responses at the antenna terminal. The test procedure used was TIA/EIA 603 S2.2.13 with the exception that the emissions were recorded in dBc. The spectrum was scanned from 0.4 to at least the 10th harmonic of the fundamental.

Spurious Emissions at  
Antenna Terminals



Method of Measuring Conducted Spurious Emissions

2.1051 Spurious emissions at the Antenna Terminals

NAME OF TEST: SPURIOUS EMISSIONS AT ANTENNA TERMINALS

2.1051 Not Applicable, no antenna terminal allowed.

2.1053  
95.635(b)(7)

UNWANTED RADIATION:

The tabulated Data shows the results of the radiated field strength emissions test. The spectrum was scanned from 30 to at least the 10th harmonic of the fundamental. This test was conducted per ANSI C63.4-1992.

REQUIREMENTS: GMRS:  $43 + 10\log(1.0) = 43$  dB

TEST DATA:


EMISSION FREQUENCY MHz	ATTN dBc		MARGIN dB
		dBm	
462.64	0.00	30.0	0.00
925.28	50.3	-20.3	7.30
1387.91	72.7	-42.7	29.70
1850.55	76.4	-46.4	33.40
2313.19	67.3	-37.3	24.35
2775.83	72.9	-42.9	29.90
3238.46	69.7	-39.7	26.70
3701.10	64.5	-34.5	21.50
4163.74	64.7	-34.7	21.70
4626.38	65.7	-35.7	22.70

METHOD OF MEASUREMENT: The tabulated data shows the results of the radiated field strength emissions test. The spectrum was scanned from 30 to at least the tenth harmonic of the fundamental. This test was conducted per TIA/EIA STANDARD 603 using the substitution method. Measurements were made at the open field test site of TIMCO ENGINEERING, INC. located at 849 NW State Road 45, Newberry, FL 32669.

APPLICANT : J COMMUNICATIONS CO., LTD.

FCC ID : JGG-2002

Method of Measuring Radiated Spurious Emissions



Equipment placed 80 cm above ground  
on a rotatable platform.

\* Appropriate antenna raised from 1 to 4 M.

2.1055  
95.621(b)

Frequency stability:

Temperature and voltage tests were performed to verify that the frequency remains within the 0.0005%, 5 ppm specification limit. The test was conducted as follows: The transmitter was placed in the temperature chamber at 25 degrees C and allowed to stabilize for one hour. The transmitter was keyed ON for one minute during which four frequency readings were recorded at 15 second intervals. The worse case number was taken for temperature plotting. The assigned channel frequency was considered to be the reference frequency. The temperature was then reduced to -30 degrees C after which the transmitter was again allowed to stabilize for one hour. The transmitter was keyed ON for one minute, and again frequency readings were noted at 15 second intervals. The worst case number was recorded for temperature plotting. This procedure was repeated in 10 degree increments up to + 50 degrees C.

Readings were also taken at plus and minus 15% of the battery voltage of 6.0 VDC.

MEASUREMENT DATA:

Assigned Frequency (Ref. Frequency): 462.637 500

TEMPERATURE C	FREQUENCY MHz	PPM
REFERENCE_____	462.637 500	00.00
-30C_____	462.635 29	-4.78
-20C_____	462.637 300	-0.43
-10C_____	462.637 36	0.30
0C_____	462.637 89	0.84
10C_____	462.637 82	0.69
20C_____	462.637 42	-0.17
30C_____	462.636 89	-1.32
40C_____	462.636 93	-1.23
50C_____	462.636 900	-1.30

BATT. %	BATT. DATA	VOLTS	BATT. PPM
-15%	462.637 88	5.1	0.82
+15%	462.637 900	6.9	0.86

RESULTS OF MEASUREMENTS: The maximum frequency variation over the temperature range was -4.78 to 0.84 ppm. The maximum frequency variation with voltage was 0.82 to 0.86 ppm.

# EMC Equipment List

	DEVICE	MFGR	MODEL	SERNO	CAL/CHAR DATE	DUE DATE or STATUS
X	3-Meter OATS	TEI	N/A	N/A	Listed 12/22/99	12/22/02
	3/10-Meter OATS	TEI	N/A	N/A	Listed 3/26/01	3/26/04
	Receiver, Beige Tower Spectrum Analyzer (Tan)	HP	8566B Opt 462	3138A07786 3144A20661	CAL 8/31/01	8/31/03
	RF Preselector (Tan)	HP	85685A	3221A01400	CAL 8/31/01	8/31/03
	Quasi-Peak Adapter (Tan)	HP	85650A	3303A01690	CAL 8/31/01	8/31/03
X	Receiver, Blue Tower Spectrum Analyzer (Blue)	HP	8568B	2928A04729 2848A18049	CHAR 10/22/01	10/22/03
X	RF Preselector (Blue)	HP	85685A	2926A00983	CHAR 10/22/01	10/22/03
X	Quasi-Peak Adapter (Blue)	HP	85650A	2811A01279	CHAR 10/22/01	10/22/03
X	Biconnical Antenna	Electro-Metrics	BIA-25	1171	CAL 4/26/01	4/26/03
	Biconnical Antenna	Eaton	94455-1	1096	CAL 10/1/01	10/1/03
	Biconnical Antenna	Eaton	94455-1	1057	CHAR 3/15/00	3/15/02
	BiconiLog Antenna	EMCO	3143	9409-1043		
X	Log-Periodic Antenna	Electro-Metrics	LPA-25	1122	CAL 10/2/01	10/2/03
	Log-Periodic Antenna	Electro-Metrics	EM-6950	632	CHAR 10/15/01	10/15/03
	Log-Periodic Antenna	Electro-Metrics	LPA-30	409	CHAR 10/16/01	10/16/03
	Dipole Antenna Kit	Electro-Metrics	TDA-30/1-4	152	CAL 3/21/01	3/21/04
	Dipole Antenna Kit	Electro-Metrics	TDA-30/1-4	153	CHAR 11/24/00	11/24/03
	Double-Ridged Horn Antenna	Electro-Metrics	RGA -180	2319	CAL 12/19/01	12/19/03
	Horn Antenna	Electro-Metrics	EM-6961	6246	CAL 3/21/01	3/21/03
	Horn Antenna	ATM	19-443-6R	None	No Cal Required	
	Passive Loop Antenna	EMC Test Systems	EMCO 6512	9706-1211	CHAR 7/10/01	7/10/03
	Line Impedance Stabilization . . .	Electro-Metrics	ANS-25/2	2604	CAL 10/9/01	10/9/03

APPLICANT: J COMMUNICATIONS CO., LTD.

FCC ID: OAJJGG2002

REPORT #: J\Jcom\_OAJ\1198UT2\1198UT2TestReport.doc

Page 17 of 19

DEVICE	MFGR	MODEL	SERNO	CAL/CHAR DATE	DUE DATE or STATUS
Line Impedance Stabilization . . .	Electro-Metrics	EM-7820	2682	CAL 3/16/01	3/16/03
Termaline Wattmeter	Bird Electronic Corporation	611	16405	CAL 5/25/99	5/25/01
Termaline Wattmeter	Bird Electronic Corporation	6104	1926	CAL 12/12/01	12/12/03
Oscilloscope	Tektronix	2230	300572	CHAR 2/1/01	2/1/03
Temperature Chamber	Tenney Engineering	TTRC	11717-7	CHAR 1/22/02	1/22/04
AC Voltmeter	HP	400FL	2213A14499	CAL 10/9/01	10/9/03
AC Voltmeter	HP	400FL	2213A14261	CHAR 10/15/01	10/15/03
AC Voltmeter	HP	400FL	2213A14728	CHAR 10/15/01	10/15/03
X Digital Multimeter	Fluke	77	35053830	CHAR 1/8/02	1/8/04
Digital Multimeter	Fluke	77	43850817	CHAR 1/8/02	1/8/04
Digital Multimeter	HP	E2377A	2927J05849	CHAR 1/8/02	1/8/04
Multimeter	Fluke	FLUKE-77-3	79510405	CAL 9/26/01	9/26/03
Peak Power Meter	HP	8900C	2131A00545	CHAR 1/26/01	1/26/03
Digital Thermometer	Fluke	2166A	42032	CAL 1/16/02	1/16/04
Thermometer	Traulsen	SK-128		CHAR 1/22/02	1/22/04
X Temp/Humidity gauge	EXTech	44577F	E000901	CHAR 1/22/02	1/22/04
Frequency Counter	HP	5352B	2632A00165	CAL 11/28/01	11/28/03
Power Sensor	Agilent Technologies	84811A	2551A02705	CAL 1/26/01	1/26/03
Service Monitor	IFR	FM/AM 500A	5182	CAL 11/22/00	11/22/02
Comm. Serv. Monitor	IFR	FM/AM 1200S	6593	CAL 5/12/02	5/12/04
Signal Generator	HP	8640B	2308A21464	CAL 11/15/01	11/15/03
Modulation Analyzer	HP	8901A	3435A06868	CAL 9/5/01	9/5/03
Near Field Probe	HP	HP11940A	2650A02748	CHAR 2/1/01	2/1/03
BandReject Filter	Lorch Microwave	5BR4-2400/ 60-N	Z1	CHAR 3/2/01	3/2/03
BandReject Filter	Lorch Microwave	6BR6-2442/ 300-N	Z1	CHAR 3/2/01	3/2/03

APPLICANT: J COMMUNICATIONS CO., LTD.

FCC ID: OAJJGG2002

REPORT #: J\Jcom\_OAJ\1198UT2\1198UT2TestReport.doc

Page 18 of 19

DEVICE	MFGR	MODEL	SERNO	CAL/CHAR DATE	DUE DATE or STATUS
BandReject Filter	Lorch Microwave	5BR4-10525/ 900-S	Z1	CHAR 3/2/01	3/2/03
High Pas Filter	Microlab	HA-10N		CHAR 10/4/01	10/4/03
Audio Oscillator	HP	653A	832-00260	CHAR 3/1/01	3/1/03
Frequency Counter	HP	5382A	1620A03535	CHAR 3/2/01	3/2/03
Frequency Counter	HP	5385A	3242A07460	CHAR 12/11/01	12/11/03
Preamplifier	HP	8449B-H02	3008A00372	CHAR 3/4/01	3/4/03
Amplifier	HP	11975A	2738A01969	CHAR 3/1/01	3/1/03
Egg Timer	Unk			CHAR 8/31/01	8/31/03
Measuring Tape, 20M	Kraftixx	0631-20		CHAR 2/1/02	2/1/04
Measuring Tape, 7.5M	Kraftixx	7.5M PROFI		2/1/02	2/1/04
Coaxial Cable #51	Insulated Wire Inc.	NPS 2251-2880	Timco #51	CHAR 1/23/02	1/23/04
Coaxial Cable #64	Semflex Inc.	60637	Timco #64	CHAR 1/24/02	1/24/04
Coaxial Cable #65	General Cable Co.	E9917 RG233/U	Timco #65	CHAR 1/23/02	1/23/04
Coaxial Cable #106	Unknown	Unknown	Timco #106	CHAR 1/23/02	1/23/04

APPLICANT: J COMMUNICATIONS CO., LTD.

FCC ID: OAJJGG2002

REPORT #: J\Jcom\_OAJ\1198UT2\1198UT2TestReport.doc

Page 19 of 19