



BNetzA-CAB-02/21-102



RF Exposure Evaluation according to KDB 447498 D01 v06

Report identification number: 1-6942_23-01-08_TR1-R01_MPE_FCC

Certification numbers and labeling requirements	
FCC ID	OAYARS6A

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Document authorised:



Alexander Hnatovskiy
Lab Manager
Radio Labs



Eric Tuetmann
Testing Manager
Radio Labs

1. MPE at given distance (KDB 447498 D01 General RF Exposure Guidance v06)

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4\pi R^2$$

where: S = Power density
P = Power input to the antenna
G = Antenna gain
R = Distance to the center of radiation of the antenna
PG = Output Power including antenna gain

The table below is excerpted from Table 1B of 47 CFR 1.1310 titled "Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure"

Frequency Range (MHz)	Power Density (mW/cm ²)	Averaging Time (minutes)
300 -1500	f/1500	30
1500 - 100000	1.0	30

where f = Frequency (MHz)

2. EUT technologies

Declared minimum safety distance: **20 cm**

SRD Technology	Frequency [MHz]		Reference #	Output Power [dBm]			Power Density [mW/cm ²]		Share of Limit %
	f _{Min}	f _{Max}		P _{ERP}	P _{EIRP}	P _{RF Exp}	S _{Result}	S _{Limit}	
Radar	76000	77000	A	N/A	26.9	26.9	0.10	1.00	9.77%

Referenced Documents:

#	Results from:
A	Test Report 1-6942/23-01-03

3. Conclusion

This prediction demonstrates the following:
The power density levels for FCC at a distance of 20 cm are below the maximum levels allowed by regulations.

Conclusion: RF exposure evaluation is not required.