

RF Exposure Statement:

Page 1 of 1

Client: NovaComm Technologies Inc.
902A, #560 Shengxia Rd .ZJ InnoPark, Shanghai, China

Test item: Bluetooth Module

Identification: Mode name : NVC-MDC556

FCC Requirement

According to FCC 2.1091, mobile equipment must comply with the following applicable limit for maximum permissible exposure (MPE) specified in FCC 1.1310:

| Equipment Use | Frequency Range | Power Density [mW/cm ²] | Average Time [min] |
|--|-----------------|-------------------------------------|--------------------|
| General Population / Uncontrolled Exposure | 1.5 – 100GHz | 1 | 6 |

IC Requirement

According to RSS-102 (Issue 4), clause 2.5.2, no routine RF exposure evaluation is required if the transmitter power (e.i.r.p.) is below the following threshold:

| Frequency Range | SAR Limitation [W] |
|-----------------|--------------------|
| Above 1.5GHz | 5 |

Measurement Result

The maximum measured transmitter power is the following:

| Conducted Output Power P _{out} [mW] | Maximum Antenna Gain [dBi] | P _{out} EIRP [mW] | Power Density at 20cm [mW/cm ²] |
|--|----------------------------|----------------------------|---|
| 2.49 | 1 | 3.13 | 0.0006 |

Note:

The power density S in mW/cm² is calculated according to the Friis formula: $S = (P_{out} \cdot G) / (4\pi \cdot D^2)$, where
S = power density in mW/cm²

P_{out} = antenna conducted output power in mW

G = antenna gain in linear scale (here: 1dBi=10log(G))

D = distance between observation point and radiating structure in cm (here: 20cm)

Conclusion

The device complies with the FCC and IC RF exposure requirements since the maximum transmitter power density is below the FCC limit and the e.i.r.p. power is below the IC RF exposure evaluation exemption threshold.

Refer to test report 15062958 001 for more details.