Ringway Tech(Jiangsu) Co.,Ltd.

Bluetooth Receiver

Main Model: BT-1 Serial Model: N/A

September 17, 2014 Report No.: 14020924-FCC-H1



Modifications made to the product : None				
This Test Report is Issued Under the Authority of:				
Kevin Tian	Alex Lin			
Kevin Tian Compliance Engineer	Alex Liu Technical Manager			

This test report may be reproduced in full only. Test result presented in this test report is applicable to the representative sample only.

RF Exposure Evaluation Report

Report No.: 14020924-FCC-H1
Issue Date: September 17, 2014
Page: 2 of 9

www.siemic.com

Laboratory Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to <u>testing</u> and <u>certification</u>, SIEMIC provides initial design reviews and <u>compliance</u> <u>management</u> through out a project. Our extensive experience with <u>China</u>, <u>Asia Pacific</u>, <u>North America</u>, <u>European</u>, <u>and international</u> compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the <u>global markets</u>.

Accreditations for Conformity Assessment

Country/Region	Scope	
USA	EMC , RF/Wireless , Telecom	
Canada	EMC, RF/Wireless, Telecom	
Taiwan	EMC, RF, Telecom , Safety	
Hong Kong	RF/Wireless ,Telecom	
Australia	EMC, RF, Telecom , Safety	
Korea	EMI, EMS, RF , Telecom, Safety	
Japan	EMI, RF/Wireless, Telecom	
Singapore	EMC , RF , Telecom	
Europe	EMC, RF, Telecom , Safety	



Report No.: Issue Date: Page:

14020924-FCC-H1 September 17, 2014 3 of 9 www.siemic.com

This page has been left blank intentionally.

Report No.: 14020924-FCC-H1 Issue Date: September 17, 2014 Page: 4 of 9 www.siemic.com

CONTENTS

1	EXECUTIVE SUMMARY & EUT INFORMATION	5
2	TECHNICAL DETAILS	<i>6</i>
	MODIFICATION	
4	TEST SUMMARY	3
5	MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	. 9

Report No.: Issue Date: 14020924-FCC-H1 September 17, 2014 5 of 9

1 EXECUTIVE SUMMARY & EUT INFORMATION

The purpose of this test programme was to demonstrate compliance of the Ringway Tech(Jiangsu) Co.,Ltd., Bluetooth Receiver and model: BT-1 against the current Stipulated Standards. The Bluetooth Receiver has demonstrated compliance with the §15.247 (i), §2.1093.

EUT Information

EUT Description	Bluetooth Receiver
Main Model	BT-1
Serial Model	N/A
Antenna Gain	0dBi
Input Power	DC 3.6V ~ 4.2V By USB Power Supply
Classification Per Stipulated Test Standard	§15.247 (i), §2.1093

Report No.: Issue Date: Page: 14020924-FCC-H1 September 17, 2014 6 of 9 www.siemic.com

2 TECHNICAL DETAILS

	2 TECHNICAL DETAILS
Purpose	Compliance testing of Bluetooth Receiver with stipulated standard
Applicant / Client	Ringway Tech(Jiangsu) Co.,Ltd. No. 101 West Hanjiang Road, Changzhou,Jiangsu, China
Manufacturer	Ringway Tech(Jiangsu) Co.,Ltd. No. 101 West Hanjiang Road, Changzhou,Jiangsu, China
Laboratory performing the tests	SIEMIC (Nanjing-China) Laboratories NO.2-1,Longcang Dadao, Yuhua Economic Development Zone, Nanjing, China Tel: +86(25)86730128/86730129 Fax: +86(25)86730127 Email: China@siemic.com.cn
Test report reference number	14020924-FCC-H1
Date EUT received	September 10, 2014
Standard applied	§15.247 (i), §2.1093
Dates of test (from – to)	September 16 to September 17, 2014
No of Units :	#1
Equipment Category :	Spread Spectrum System/Device
Trade Name :	Artesia
RF Operating Frequency (ies)	Bluetooth: 2402-2480 MHz
Number of Channels	Bluetooth: 79CH
Modulation	Bluetooth: GFSK
Port	USB Port
FCC ID	OCDBT-1



Report No.: Issue Date: Page:

14020924-FCC-H1 September 17, 2014 7 of 9

www.siemic.com

MODIFICATION

NONE

Report No.: 14020924-FCC-H1
Issue Date: September 17, 2014
Page: 8 of 9

www.siemic.com

4 TEST SUMMARY

The product was tested in accordance with the following specifications.
All testing has been performed according to below product classification:

Test Results Summary

FCC Rules	Description of Test	Result
§15.247 (i), §2.1093	RF Exposure	Compliance

5 MEASUREMENTS, EXAMINATION AND DERIVED RESULTS

5.1 §15.247 (i) and §2.1093/ – RF Exposure

Standard Requirement:

According to §15.247 (i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f_{\text{(GHz)}}}] \le 3.0 \text{ for } 1\text{-g SAR and } \le 7.5 \text{ for } 10\text{-g extremity SAR,}^{16} \text{ where}$

- f_(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation¹⁷
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is ≤ 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

BT Mode:

One antenna is available for the EUT. The minimum separation distances is 5 mm.

The maximum average output power(turn-up power) in low channel of BT is-2.35dBm=0.58 mW

The calculation results= $0.58/5*\sqrt{2.402}=0.10<3$

The maximum average output power(turn-up power) in middle channel of BT is -3.81 dBm=0.42mW

The calculation results = $0.42/5*\sqrt{2.441}=0.13<3$

The maximum average output power(turn-up power) in high channel of BT is -5.16 dBm=0.30 mW

The calculation results= $0.30/5*\sqrt{2.480}=0.09<3$

According to KDB 447498, no stand-alone required for BT antenna, and no simultaneous SAR measurement is required.

Test Result: Pass