

# FCC REPORT

**Applicant:** SONOMA COMMUNICATIONS L.L.C.

**Address of Applicant:** 1159 SONORA CT STE 322 SUNNYVALE CA 94086 UNITED STATES

**Equipment Under Test (EUT)**

Product Name: MOBILE PHONE

Model No.: A1,A2,G1,G2,M1,M2,Q1,Q2

Trade mark: RCA

**FCC ID:** OCVRCAA1

**Applicable standards:** FCC CFR Title 47 Part 15 Subpart B

**Date of sample receipt:** 12 Dec., 2013

**Date of Test:** 13 Dec., to 02 Jan., 2014

**Date of report issued:** 03 Jan., 2013

**Test Result :** Pass \*

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

A blue circular stamp with the text "SHENZHEN ZHONGJIAN NANFANG TESTING CO., LTD." around the perimeter and "CCIS" in the center. A handwritten signature in blue ink is written over the stamp.

Bruce Zhang  
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

## 2 Version

Version No.	Date	Description
00	03 Jan.,2013	Original

**Prepared by:** Sera Xiang **Date:** 03 Jan.,2013  
**Report Clerk**

**Reviewed by:** Vincent Chen **Date:** 03 Jan.,2013  
**Project Engineer**

### 3 Contents

	Page
1 COVER PAGE .....	1
2 VERSION .....	2
3 CONTENTS .....	3
4 TEST SUMMARY .....	4
5 GENERAL INFORMATION .....	5
5.1 CLIENT INFORMATION .....	5
5.2 GENERAL DESCRIPTION OF E.U.T.....	5
5.3 TEST MODE .....	5
5.4 DESCRIPTION OF SUPPORT UNITS .....	6
5.5 LABORATORY FACILITY .....	6
5.6 LABORATORY LOCATION.....	6
5.7 TEST INSTRUMENTS LIST.....	7
6 TEST RESULTS AND MEASUREMENT DATA.....	8
6.1 CONDUCTED EMISSION .....	8
6.2 RADIATED EMISSION .....	11
7 TEST SETUP PHOTO .....	17
8 EUT CONSTRUCTIONAL DETAILS .....	19

## 4 Test Summary

Test Item	Section in CFR 47	Result
Conducted Emission	Part15.107	Pass
Radiated Emission	Part15.109	Pass

*Pass: The EUT complies with the essential requirements in the standard.*

## 5 General Information

### 5.1 Client Information

Applicant:	SONOMA COMMUNICATIONS L.L.C.
Address of Applicant:	1159 SONORA CT STE 322 SUNNYVALE CA 94086 UNITED STATES
Manufacturer/Factory:	SHENZHEN BAI LI YONG XING TECHNOLOGE CO.,LTD
Address of Manufacturer/ Factory:	#5A,BLOCK 10,XINQIAO SHAJING STREET,HENGMINGZHU INDUSTRIAL PARK,TONGFUYU INDUSTRIAL ZONE,BAOAN DISTRICT,SHENZHEN,CHINA

### 5.2 General Description of E.U.T.

Product Name:	MOBILE PHONE
Model No.:	A1,A2,G1,G2,M1,M2,Q1,Q2
Trade mark:	RCA
Power supply:	Rechargeable Li-ion Battery DC3.7V-1600mAh
AC adapter :	Model:RCA A1 Input:100-240V AC,50/60Hz 0.1A Output:5.0V DC MAX1000mA
Remark:	The Model: A1,A2,G1,G2,M1,M2,Q1 and Q2 are identical to the same PCB layout, interior structure and electrical circuit, with only difference being model name and their appearance for the commercial purpose.

### 5.3 Test Mode

Operating mode	Detail description
Donloading mode	Keep the EUT in Donloading mode
<p>The sample was placed 0.8m above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y &amp; Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.</p>	

## 5.4 Description of Support Units

Manufacturer	Description	Model	Serial Number	FCC ID/DoC
DELL	PC	OPTIPLEX745	N/A	DoC
DELL	MONITOR	E178FPC	N/A	DoC
DELL	KEYBOARD	SK-8115	N/A	DoC
DELL	MOUSE	MOC5UO	N/A	DoC
HP	Printer	CB495A	05257893	DoC
MERCURY	Wireless router	MW150R	12922104015	FCC ID

## 5.5 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC - Registration No.: 817957**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in out files. Registration 817957, February 27, 2012.

● **IC - Registration No.: 10106A-1**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

● **CNAS - Registration No.: CNAS L6048**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.

## 5.6 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.  
 Address: No.B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road,  
 Bao'an District, Shenzhen, Guangdong, China  
 Tel: 0755-23118282  
 Fax: 0755-23116366

## 5.7 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	SAEMC	9(L)*6(W)* 6(H)	CCIS0001	June 09 2013	June 08 2014
2	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	CCIS0005	May 25 2013	May 24 2014
3	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA9120D	CCIS0006	May 25 2013	May 24 2014
4	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
5	Coaxial Cable	CCIS	N/A	CCIS0016	Apr. 01 2013	Mar. 31 2014
6	Coaxial Cable	CCIS	N/A	CCIS0017	Apr. 01 2013	Mar. 31 2014
7	Coaxial cable	CCIS	N/A	CCIS0018	Apr. 01 2013	Mar. 31 2014
8	Coaxial Cable	CCIS	N/A	CCIS0019	Apr. 01 2013	Mar. 31 2014
9	Coaxial Cable	CCIS	N/A	CCIS0087	Apr. 01 2013	Mar. 31 2014
10	Amplifier(10kHz-1.3GHz)	HP	8447D	CCIS0003	Apr. 01 2013	Mar. 31 2014
11	Amplifier(1GHz-18GHz)	Compliance Direction Systems Inc.	PAP-1G18	CCIS0011	June 09 2013	June 08 2014
12	Pre-amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	Apr. 01 2013	Mar. 31 2014
13	Horn Antenna	ETS-LINDGREN	3160	GTS217	Mar. 30 2013	Mar. 29 2014
14	Printer	HP	HP LaserJet P1007	N/A	N/A	N/A
15	Positioning Controller	UC	UC3000	CCIS0015	N/A	N/A
16	Spectrum analyzer 9k-30GHz	Rohde & Schwarz	FSP	CCIS0023	May. 25 2013	May. 24 2014
17	EMI Test Receiver	Rohde & Schwarz	ESPI	CCIS0022	Apr 01 2013	Mar. 31 2014
18	Loop antenna	Laplace instrument	RF300	EMC0701	Aug. 12 2013	Aug. 11 2014
19	Universal radio communication tester	Rhode & Schwarz	CMU200	CCIS0069	May. 25 2013	May. 24 2014
20	Signal Analyzer	Rohde & Schwarz	FSIQ3	CCIS0088	May. 25 2013	May. 24 2014

Conducted Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongShuo Electron	11.0(L)x4.0(W)x3.0(H)	CCIS0061	June 09 2013	June 08 2014
2	EMI Test Receiver	Rohde & Schwarz	ESCI	CCIS0002	May 25 2013	May. 24 2014
3	LISN	CHASE	MN2050D	CCIS0074	Apr. 01 2013	Mar. 31 2014
4	Coaxial Cable	CCIS	N/A	CCIS0086	Apr. 01 2013	Mar. 31 2014

## 6 Test results and Measurement Data


### 6.1 Conducted Emission

Test Requirement:	FCC Part15 B Section 15.107														
Test Method:	ANSI C63.4:2003														
Test Frequency Range:	150kHz to 30MHz														
Class / Severity:	Class B														
Receiver setup:	RBW=9kHz, VBW=30kHz														
Limit:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBμV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>0.5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>	Frequency range (MHz)	Limit (dBμV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	0.5-30	60	50
Frequency range (MHz)	Limit (dBμV)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
0.5-30	60	50													
Test setup:	<p>Remark:  E.U.T: Equipment Under Test  LISN: Line Impedance Stabilization Network  Test table height=0.8m</p>														
Test procedure	<ol style="list-style-type: none"> <li>The E.U.T and simulators are connected to the main power through a line impedance stabilization network(L.I.S.N.). The provide a 50ohm/50uH coupling impedance for the measuring equipment.</li> <li>The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs).</li> <li>Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2003 on conducted measurement.</li> </ol>														
Test environment:	Temp.: 23 °C Humid.: 56% Press.: 1 01kPa														
Measurement Record:	Uncertainty: 3.28dB														
Test Instruments:	Refer to section 5.7 for details														
Test mode:	Refer to section 5.3 for details														
Test results:	Pass														



**Measurement data:**

Line:




Trace: 17

Site :  
 Condition : ICES-003 QP LISN LINE  
 Job No. : 565RF  
 EUT : Mobile Phone  
 Model : A1  
 Test Mode : Downloading Mode  
 Power Rating : AC 120V/60Hz  
 Environment : Temp: 23 °C Humi:56% Atmos:101KPa  
 Test Engineer: Garen

	Read	LISN	Cable	Limit	Over		
Freq	Level	Factor	Loss	Line	Limit	Remark	
MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.166	24.73	10.24	0.78	35.75	55.16	-19.41 Average
2	0.202	28.96	10.21	0.76	39.93	63.54	-23.61 QP
3	0.242	24.01	10.23	0.75	34.99	52.04	-17.05 Average
4	0.330	27.04	10.27	0.73	38.04	59.44	-21.40 QP
5	0.361	16.01	10.27	0.73	27.01	48.69	-21.68 Average
6	1.178	23.59	10.23	0.89	34.71	56.00	-21.29 QP
7	2.622	18.65	10.28	0.93	29.86	46.00	-16.14 Average
8	3.241	30.86	10.29	0.91	42.06	56.00	-13.94 QP
9	3.293	19.75	10.29	0.91	30.95	46.00	-15.05 Average
10	4.647	30.80	10.28	0.87	41.95	56.00	-14.05 QP
11	28.152	27.74	10.76	0.87	39.37	60.00	-20.63 QP
12	28.452	25.78	10.78	0.87	37.43	50.00	-12.57 Average

Neutral:



Trace: 19  
 Site :  
 Condition : ICES-003 QP LISN NEUTRAL  
 Job No. : 565RF  
 EUT : Mobile Phone  
 Model : A1  
 Test Mode : Downloading Mode  
 Power Rating : AC 120V/60Hz  
 Environment : Temp: 23 °C Humi:56% Atmos:101KPa  
 Test Engineer: Garen

	Read	LISN	Cable	Limit	Over		
Freq	Level	Factor	Loss	Line	Limit	Remark	
MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.242	21.56	10.23	0.75	32.54	52.04	-19.50 Average
2	0.346	27.91	10.25	0.73	38.89	59.05	-20.16 QP
3	0.361	17.29	10.25	0.73	28.27	48.69	-20.42 Average
4	0.398	26.23	10.26	0.72	37.21	57.90	-20.69 QP
5	2.554	29.89	10.27	0.94	41.10	56.00	-14.90 QP
6	2.664	19.45	10.27	0.93	30.65	46.00	-15.35 Average
7	3.310	30.03	10.28	0.91	41.22	56.00	-14.78 QP
8	3.985	20.19	10.28	0.89	31.36	46.00	-14.64 Average
9	4.647	28.10	10.27	0.87	39.24	56.00	-16.76 QP
10	14.907	23.73	10.23	0.90	34.86	50.00	-15.14 Average
11	15.388	27.18	10.24	0.90	38.32	60.00	-21.68 QP
12	28.603	25.18	10.78	0.87	36.83	50.00	-13.17 Average

Notes:

1. The following Quasi-Peak and Average measurements were performed on the EUT
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.

## 6.2 Radiated Emission


Test Requirement:	FCC Part15 B Section 15.109				
Test Method:	ANSI C63.4:2003				
Test Frequency Range:	30MHz to 6000MHz				
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120 kHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
Limit:	Frequency	Limit (dBuV/m @3m)		Remark	
	30MHz-88MHz	40.0		Quasi-peak Value	
	88MHz-216MHz	43.5		Quasi-peak Value	
	216MHz-960MHz	46.0		Quasi-peak Value	
	960MHz-1GHz	54.0		Quasi-peak Value	
Above 1GHz	54.0		Average Value		
	74.0		Peak Value		
Test setup:	Below 1GHz				
Above 1GHz	Above 1GHz				

<p>Test Procedure:</p>	<ol style="list-style-type: none"> <li>1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li> </ol>
<p>Test environment:</p>	<p>Temp.: 25 °C      Humid.: 55%      Press.: 1 01kPa</p>
<p>Measurement Record:</p>	<p>Uncertainty: 4.88dB</p>
<p>Test Instruments:</p>	<p>Refer to section 5.7 for details</p>
<p>Test mode:</p>	<p>Refer to section 5.3 for details</p>
<p>Test results:</p>	<p>Passed</p>

## Measurement Data

Below 1GHz


Horizontal:



Site : 3m chamber  
 Condition : FCC PART15 CLASS B 3m VULB9163(30M1G) HORIZONTAL  
 Job NO. : 565RF  
 EUT : Mobile phone  
 Model : A1  
 Test mode : PC mode  
 Power Rating : AC120V/60Hz  
 Environment : Temp:25.5°C Humi:55%  
 Test Engineer: Garen

	Read	Antenna	Cable	Preamp	Limit	Over	
Freq	Level	Factor	Loss	Factor	Level	Line	Limit Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	53.882	48.74	13.09	1.34	28.66	34.51	40.00 -5.49 QP
2	165.487	58.51	8.82	2.62	29.33	40.62	43.50 -2.88 QP
3	194.453	56.07	10.56	2.83	29.82	39.64	43.50 -3.86 QP
4	283.979	56.25	12.75	2.90	29.48	42.42	46.00 -3.58 QP
5	480.528	48.80	16.07	3.46	30.52	37.81	46.00 -8.19 QP
6	721.726	47.79	19.10	4.26	30.55	40.60	46.00 -5.40 QP

Vertical:




Site : 3m chamber  
 Condition : FCC PART15 CLASS B 3m VULB9163(30M1G) VERTICAL  
 Job NO. : 565RF  
 EUT : Mobile phone  
 Model : A1  
 Test mode : PC mode  
 Power Rating : AC120V/60Hz  
 Environment : Temp:25.5°C Humi:55%  
 Test Engineer: Garen

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	52.391	51.41	13.15	1.29	28.52	37.33	40.00	-2.67	QP
2	147.404	55.58	8.24	2.49	29.26	37.05	43.50	-6.45	QP
3	166.068	58.47	8.85	2.63	29.25	40.70	43.50	-2.80	QP
4	195.822	54.39	10.57	2.84	29.82	37.98	43.50	-5.52	QP
5	283.979	51.30	12.75	2.90	29.48	37.47	46.00	-8.53	QP
6	480.528	48.07	16.07	3.46	30.52	37.08	46.00	-8.92	QP



Above 1GHz


Horizontal:



Site : 3m chamber  
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) HORIZONTAL  
 Job NO. : 565RF  
 EUT : Mobile Phone  
 Model : A1  
 Test mode : PC mode  
 Power Rating : AC120V/60Hz  
 Environment : Temp:25.5°C Humi:55%  
 Test Engineer: Garen

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1200.526	55.22	25.02	3.50	40.89	42.85	74.00	-31.15	Peak
2	1200.526	46.26	25.02	3.50	40.89	33.89	54.00	-20.11	Average
3	1663.393	59.76	24.90	4.28	40.97	47.97	74.00	-26.03	Peak
4	1663.393	48.64	24.90	4.28	40.97	36.85	54.00	-17.15	Average
5	1954.468	63.05	25.93	4.79	40.88	52.89	74.00	-21.11	Peak
6	1954.468	49.26	25.93	4.79	40.88	39.10	54.00	-14.90	Average
7	2393.094	56.94	27.58	5.67	31.35	58.84	74.00	-15.16	Peak
8	2393.094	42.66	27.58	5.67	31.35	44.56	54.00	-9.44	Average

Vertical:



Site : 3m chamber  
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) VERTICAL  
 Job NO. : 565RF  
 EUT : Mobile Phone  
 Model : A1  
 Test mode : PC mode  
 Power Rating : AC120V/60Hz  
 Environment : Temp:25.5°C Humi:55%  
 Test Engineer: Garen

	Read	Antenna	Cable	Preamp	Level	Limit	Over	
-----	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
-----	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	-----
1	1329.615	54.09	25.65	3.63	40.92	42.45	74.00	-31.55 Peak
2	1329.615	41.62	25.65	3.63	40.92	29.98	54.00	-24.02 Average
3	1666.376	60.04	24.90	4.28	40.97	48.25	74.00	-25.75 Peak
4	1666.376	47.99	24.90	4.28	40.97	36.20	54.00	-17.80 Average
5	1989.803	60.57	26.06	4.82	40.85	50.60	74.00	-23.40 Peak
6	1989.803	45.69	26.06	4.82	40.85	35.72	54.00	-18.28 Average
7	2393.094	58.06	27.58	5.67	31.35	59.96	74.00	-14.04 Peak
8	2393.094	36.75	27.58	5.67	31.35	38.65	54.00	-15.35 Average