



FCC PART 15.247

TEST REPORT

For

Techwall Electronics Co., Ltd.

24/F, Tower 1, Tern Centre, 237 Queen's Road, Central, Hong Kong

FCC ID: OD9BC70PU

Report Type: Original Report	Product Name: Digital Baby Monitor
Report Number:	RDG171219004-00B
Report Date:	2018-07-12
Reviewed By:	Jerry Zhang EMC Manager <i>Jerry Zhang</i>
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan). This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA* or any agency of the Federal Government. * This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “*”

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE.....	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY.....	4
MEASUREMENT UNCERTAINTY.....	5
TEST FACILITY.....	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION.....	6
EUT EXERCISE SOFTWARE.....	6
EQUIPMENT MODIFICATIONS.....	6
SUPPORT CABLE LIST AND DETAILS.....	6
BLOCK DIAGRAM OF TEST SETUP.....	7
SUMMARY OF TEST RESULTS.....	8
FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE.....	9
APPLICABLE STANDARD.....	9
FCC §15.203 - ANTENNA REQUIREMENT.....	10
APPLICABLE STANDARD.....	10
ANTENNA CONNECTOR CONSTRUCTION.....	10
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS.....	11
APPLICABLE STANDARD.....	11
EUT SETUP.....	11
EMI TEST RECEIVER SETUP.....	11
TEST PROCEDURE.....	11
CORRECTED AMPLITUDE & MARGIN CALCULATION.....	12
TEST EQUIPMENT LIST AND DETAILS.....	12
TEST DATA.....	12
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	15
APPLICABLE STANDARD.....	15
EUT SETUP.....	15
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP.....	16
TEST PROCEDURE.....	16
TEST EQUIPMENT LIST AND DETAILS.....	16
CORRECTED AMPLITUDE & MARGIN CALCULATION.....	17
TEST DATA.....	17
FCC §15.247(a) (1) – CHANNEL SEPARATION TEST.....	22
APPLICABLE STANDARD.....	22
TEST EQUIPMENT LIST AND DETAILS.....	22
TEST PROCEDURE.....	22
TEST DATA.....	22
FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING.....	25
APPLICABLE STANDARD.....	25
TEST PROCEDURE.....	25
TEST EQUIPMENT LIST AND DETAILS.....	25

TEST DATA25

FCC §15.247(a) (1) (i) - QUANTITY OF HOPPING CHANNEL TEST28

 APPLICABLE STANDARD28

 TEST PROCEDURE28

 TEST EQUIPMENT LIST AND DETAILS.....28

 TEST DATA28

FCC §15.247(a) (1) (i) - TIME OF OCCUPANCY (DWELL TIME).....30

 APPLICABLE STANDARD30

 TEST PROCEDURE30

 TEST EQUIPMENT LIST AND DETAILS.....30

 TEST DATA30

FCC §15.247(b) (2) - PEAK OUTPUT POWER MEASUREMENT33

 APPLICABLE STANDARD33

 TEST PROCEDURE33

 TEST EQUIPMENT LIST AND DETAILS.....33

 TEST DATA33

FCC §15.247(d) - BAND EDGES TESTING34

 APPLICABLE STANDARD34

 TEST PROCEDURE34

 TEST EQUIPMENT LIST AND DETAILS.....34

 TEST DATA35

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product Type:		Digital Baby Monitor(Parent Unit)
EUT Name:		Digital Baby Monitor
EUT Model:		BC-70
FCC ID:		OD9BC70PU
Rated Input Voltage:		DC 5V from Adapter or DC3.7V from Li-ion Battery
Adapter Information	Model:	SW0500600-A04
	Input:	100-240V~50/60Hz Max. 200mA
	Output:	DC 5V, 600mA
External Dimension:		Length (63 mm)*Width (63 mm)*High (77 mm)
Serial Number:		171219004
EUT Received Date:		2017.12.19

Objective

This report is prepared on behalf of *Techwall Electronics Co., Ltd.* in accordance with Part 2, Subpart J, Part 15, Subparts A and C of the Federal Communications Commission's rules

The tests were performed in order to determine the EUT compliance with FCC Rules Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

Part of system submissions with FCC ID: OD9BC70BU, FCC ID: OD9BSM1.

Test Methodology

All measurements detailed in this Test Report were performed in accordance with ANSI C63.10-2013 "American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices".

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Measurement Uncertainty

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	30M~200MHz: 4.55 dB,200M~1GHz: 5.92 dB,1G~6GHz: 4.98 dB, 6G~18GHz: 5.89 dB,18G~26.5G:5.47 dB,26.5G~40G:5.63 dB
Unwanted Emissions, conducted	±1.5 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.12 dB (150 kHz to 30 MHz)

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 897218,the FCC Designation No. : CN1220.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062D.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode. 57 hopping channels are provided:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	915.8	16	918.8	31	921.8	46	924.8
2	916	17	919	32	922	47	925
3	916.2	18	919.2	33	922.2	48	925.2
4	916.4	19	919.4	34	922.4	49	925.4
5	916.6	20	919.6	35	922.6	50	925.6
6	916.8	21	919.8	36	922.8	51	925.8
7	917	22	920	37	923	52	926
8	917.2	23	920.2	38	923.2	53	926.2
9	917.4	24	920.4	39	923.4	54	926.4
10	917.6	25	920.6	40	923.6	55	926.6
11	917.8	26	920.8	41	923.8	56	926.8
12	918	27	921	42	924	57	927
13	918.2	28	921.2	43	924.2	/	/
14	918.4	29	921.4	44	924.4	/	/
15	918.6	30	921.6	45	924.6	/	/

Channel 1, 29, 57 were selected to test.

EUT Exercise Software

No software was used in test, the device was configured to engineer mode by manufacturer.


Equipment Modifications

No modification was made to the EUT.

Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From	To
DC Power Cable	No	No	2.0	Adapter	EUT

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i) & §1.1310 & §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(1)	20 dB Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(i)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(i)	Quantity of hopping channel Test	Compliance
§15.247(b)(2)	Peak Output Power Measurement	Compliance
§15.247(d)	Band Edges	Compliance

FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE

Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$
 ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Measurement Result

The maximum peak conducted power including tolerance is 19.5 dBm(89.13mW).

The device employs 57 hopping channels, each channel hopping 38 times(each time 1.86ms) in 20s period.

The duty cycle calculated as below:

Duty Cycle= $T_{\text{on}}/T_{\text{on+Off}} = (0.00186 \times 38 \times 57)/20 = 20.14\%$

Conducted time-Average Power = $89.13 \times 20.14\% = 17.95$ mW

The minimum distance from the antenna to body distance(body-worn use condition with the clip) is 17mm, please refer to the EUT photo.

$[(\text{max. power of channel, mW})/(\text{min. test separation distance, mm})][\sqrt{f(\text{GHz})}]$
 $= 17.95/17 \cdot (\sqrt{0.927}) = 1.0 < 3.0$

So the stand-alone SAR evaluation is not necessary.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one internal antenna arrangement, and the antenna gain is 0 dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207(a)

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to the main LISN with a 120 V/60 Hz AC power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

Herein,

V_C : corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN or ISN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCS 30	830245/006	2017-12-11	2018-12-11
R&S	Two-line V-network	ENV 216	101614	2017-12-08	2018-12-08
R&S	L.I.S.N	ESH2-Z5	892107/021	2017-09-25	2018-09-25
Unknown	Coaxial Cable	C-NJNJ-50	C-0200-01	2017-09-05	2018-09-05
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data


Environmental Conditions

Temperature:	30.2 °C
Relative Humidity:	57 %
ATM Pressure:	101.3 kPa

The testing was performed by Sider Huang on 2018-06-22.

Test Mode: Transmitting


AC120V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.157346	44.1	9.000	L1	11.1	21.5	65.6	Compliance
0.266226	36.6	9.000	L1	10.3	24.6	61.2	Compliance
0.281497	35.0	9.000	L1	10.2	25.8	60.8	Compliance
0.360371	37.6	9.000	L1	10.0	21.1	58.7	Compliance
0.436318	28.3	9.000	L1	9.9	28.8	57.1	Compliance
0.549741	24.1	9.000	L1	9.9	31.9	56.0	Compliance

Frequency (MHz)	Average (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.166371	27.9	9.000	L1	11.0	27.2	55.1	Compliance
0.351859	27.0	9.000	L1	10.0	21.9	48.9	Compliance
0.422630	20.2	9.000	L1	10.0	27.2	47.4	Compliance
0.446873	20.4	9.000	L1	9.9	26.5	46.9	Compliance
1.190776	22.9	9.000	L1	9.8	23.1	46.0	Compliance
1.289541	19.9	9.000	L1	9.8	26.1	46.0	Compliance

AC120V, 60 Hz, Neutral:



Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.158604	41.9	9.000	N	11.1	23.6	65.5	Compliance
0.279263	34.5	9.000	N	10.2	26.3	60.8	Compliance
0.304845	35.3	9.000	N	10.1	24.8	60.1	Compliance
0.366160	34.5	9.000	N	10.0	24.1	58.6	Compliance
0.399703	31.7	9.000	N	10.0	26.2	57.9	Compliance
0.532496	26.5	9.000	N	9.9	29.5	56.0	Compliance

Frequency (MHz)	Average (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.156097	28.3	9.000	N	11.1	27.4	55.7	Compliance
0.354674	29.4	9.000	N	10.0	19.5	48.9	Compliance
0.443327	20.9	9.000	N	9.9	26.1	47.0	Compliance
1.190776	25.2	9.000	N	9.8	20.8	46.0	Compliance
1.289541	21.4	9.000	N	9.8	24.6	46.0	Compliance
3.049107	17.6	9.000	N	9.8	28.4	46.0	Compliance


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission Below 1GHz tests were performed in the 3 meters chamber A, above 1GHz tests were performed in the 3 meters chamber B, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 10 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	AV

Note: If the maximized peak measured value complies with the limit, then it is unnecessary to perform an QP measurement

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz - 1 GHz, peak and average detection modes for frequencies above 1 GHz.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2017-12-11	2018-12-11
Sunol Sciences	Antenna	JB3	A060611-1	2017-11-10	2020-11-10
Agilent	Spectrum Analyzer	E4440A	SG43360054	2018-01-04	2019-01-04
ETS-Lindgren	Horn Antenna	3115	000 527 35	2016-01-05	2019-01-04
MITEQ	Amplifier	AFS42-00101800-25-S-42	2001271	2017-09-05	2018-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-01	2017-09-05	2018-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0075-01	2017-09-05	2018-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-1000-01	2017-09-05	2018-09-05
Unknown	Coaxial Cable	C-SJSJ-50	C-0800-01	2017-09-05	2018-09-05
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Data

Environmental Conditions


Temperature:	26.9~28.6°C
Relative Humidity:	37~44 %
ATM Pressure:	101.3~101.7 kPa

* The testing was performed by Tyler Pan and Sunny Cen on 2018-06-22~2018-06-27.

Test Mode: Transmitting


1) 30MHz-1GHz(Low channel was the worst)

Horizontal:



Frequency (MHz)	Receiver Reading (dBμV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
30.0000	3.33	QP	27.87	31.20	40.00	8.80
124.0900	8.90	QP	15.30	24.20	43.50	19.30
152.2200	10.33	QP	13.87	24.20	43.50	19.30
187.1400	11.21	QP	12.39	23.60	43.50	19.90
324.8800	10.06	QP	16.14	26.20	46.00	19.80
361.7400	12.17	QP	17.03	29.20	46.00	16.80

Vertical:




Frequency (MHz)	Receiver Reading (dBμV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
30.0000	3.03	QP	27.87	30.90	40.00	9.1
116.3300	9.84	QP	14.76	24.60	43.50	18.90
161.9200	11.53	QP	13.67	25.20	43.50	18.30
284.1400	9.42	QP	15.28	24.70	46.00	21.30
314.2100	10.69	QP	15.91	26.60	46.00	19.40
438.3700	9.16	QP	19.24	28.40	46.00	17.60


2) 1GHz-10 GHz

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Measurement	Polar (H/V)	Factor (dB/m)					
Low Channel: 915.8 MHz									
915.80	73.30	QP	H	22.40	4.22	0.00	99.92	N/A	N/A
915.80	74.00	QP	V	22.40	4.22	0.00	100.62	N/A	N/A
902.00	11.60	QP	V	22.34	4.29	0.00	38.23	46.00	7.77
1831.60	52.35	PK	V	26.59	1.66	35.95	44.65	74.00	29.35
1831.60	46.81	AV	V	26.59	1.66	35.95	39.11	54.00	14.89
2747.40	50.25	PK	V	29.19	1.91	36.51	44.84	74.00	29.16
2747.40	44.91	AV	V	29.19	1.91	36.51	39.50	54.00	14.50
3663.20	49.56	PK	V	31.66	2.51	37.06	46.67	74.00	27.33
3663.20	42.89	AV	V	31.66	2.51	37.06	40.00	54.00	14.00
4579.00	48.53	PK	V	32.46	3.08	37.13	46.94	74.00	27.06
4579.00	41.89	AV	V	32.46	3.08	37.13	40.30	54.00	13.70
5494.80	55.32	PK	V	34.09	3.54	37.34	55.61	74.00	18.39
5494.80	49.35	AV	V	34.09	3.54	37.34	49.64	54.00	4.36
Middle Channel: 921.4 MHz									
921.40	71.30	QP	H	22.43	4.30	0.00	98.03	N/A	N/A
921.40	73.50	QP	V	22.43	4.30	0.00	100.23	N/A	N/A
1842.80	52.66	PK	V	26.64	1.66	35.97	44.99	74.00	29.01
1842.80	46.26	AV	V	26.64	1.66	35.97	38.59	54.00	15.41
2764.20	51.28	PK	V	29.25	1.92	36.53	45.92	74.00	28.08
2764.20	45.34	AV	V	29.25	1.92	36.53	39.98	54.00	14.02
3685.60	50.73	PK	V	31.71	2.55	37.03	47.96	74.00	26.04
3685.60	44.61	AV	V	31.71	2.55	37.03	41.84	54.00	12.16
4607.00	50.12	PK	V	32.51	3.10	37.13	48.60	74.00	25.40
4607.00	44.37	AV	V	32.51	3.10	37.13	42.85	54.00	11.15
5528.40	54.18	PK	V	34.11	3.55	37.41	54.43	74.00	19.57
5528.40	48.42	AV	V	34.11	3.55	37.41	48.67	54.00	5.33
High Channel: 927 MHz									
927.00	67.20	QP	H	22.54	4.35	0.00	94.09	N/A	N/A
927.00	68.00	QP	V	22.54	4.35	0.00	94.89	N/A	N/A
928.00	11.20	QP	V	22.56	4.34	0.00	38.10	46.00	7.90
1854.00	52.20	PK	V	26.69	1.66	35.99	44.56	74.00	29.44
1854.00	47.65	AV	V	26.69	1.66	35.99	40.01	54.00	13.99
2781.00	52.60	PK	V	29.31	1.93	36.55	47.29	74.00	26.71
2781.00	46.73	AV	V	29.31	1.93	36.55	41.42	54.00	12.58
3708.00	50.26	PK	V	31.76	2.57	37.02	47.57	74.00	26.43
3708.00	44.74	AV	V	31.76	2.57	37.02	42.05	54.00	11.95
4635.00	51.39	PK	V	32.57	3.08	37.11	49.93	74.00	24.07
4635.00	45.14	AV	V	32.57	3.08	37.11	43.68	54.00	10.32
5562.00	54.38	PK	V	34.12	3.56	37.49	54.57	74.00	19.43
5562.00	48.57	AV	V	34.12	3.56	37.49	48.76	54.00	5.24

Worst plots(Low channel)
Horizontal



Vertical



FCC §15.247(a) (1) – CHANNEL SEPARATION TEST

Applicable Standard

(1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	831929/005	2017-08-31	2018-08-31
Unknown	Coaxial Cable	C-SJ00-0010	C0010/04	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

1. Set the EUT in transmitting mode, spectrum Bandwidth was set at 3 kHz, maxhold the channel.
2. Set the adjacent channel of the EUT maxhold another trace.
3. Measure the channel separation.

Test Data

Environmental Conditions

Temperature:	28.8°C
Relative Humidity:	56 %
ATM Pressure:	101.1 kPa

* The testing was performed by Swim Lv on 2018-07-10.


Test Result: Compliance.

Please refer to following tables and plots


Test Mode: Transmitting

Channel	Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)
Low	915.8	0.199	0.144
Middle	921.4	0.200	0.145
High	927	0.200	0.144


Low Channel



Middle Channel



High Channel



FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING

Applicable Standard

(i) For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	831929/005	2017-08-31	2018-08-31
Unknown	Coaxial Cable	C-SJ00-0010	C0010/04	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	27.6°C
Relative Humidity:	53 %
ATM Pressure:	101.8 kPa

* The testing was performed by Swim Lv on 2018-06-26.


Test Result: Compliance.

Please refer to following tables and plots


Test Mode: Transmitting

Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
Low	915.8	0.144
Middle	921.4	0.145
High	927	0.144


Low Channel



Middle Channel



High Channel



FCC §15.247(a) (1) (i) - QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

(i) For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the Max-Hold function record the Quantity of the channel.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	831929/005	2017-08-31	2018-08-31
Unknown	Coaxial Cable	C-SJ00-0010	C0010/04	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	28.8°C
Relative Humidity:	56 %
ATM Pressure:	101.1 kPa

* The testing was performed by Swim Lv on 2018-07-10.


Test Result: Compliance.

Please refer to following tables and plots

Test Mode: Transmitting

Frequency Range (MHz)	Number of Hopping Channel	Limit
902-928	57	50

Number of Hopping Channels



FCC §15.247(a) (1) (i) - TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard

(i) For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.

Test Procedure

The EUT was worked in channel hopping; the time of single pulses was tested.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	831929/005	2017-08-31	2018-08-31
Unknown	Coaxial Cable	C-SJ00-0010	C0010/04	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	28.8°C
Relative Humidity:	56 %
ATM Pressure:	101.1 kPa


* The testing was performed by Swim Lv on 2018-07-10.

Test Result: Compliance. Please refer to following tables and plots


Test Mode: Transmitting

Channel	Occupancy Time For Single Hop (ms)	Hops in Observed Period (20s)	Dwell time (s)	Limit (s)	Result
Middle	1.86	38	0.071	0.4	Compliance
Dwell time=Pulse time (ms) × hopping number per channel in Observed Period(19*2=38) Observed Period=20S					


2 Burst in 20s



19 pulse in one Burst



1.86ms for one pulse



FCC §15.247(b) (2) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (2) For frequency hopping systems operating in the 902-928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels, as permitted under paragraph (a)(1)(i) of this section.

Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	USB Wideband Power Sensor	U2022XA	MY5417006	2017-12-11	2018-12-11
Unknown	Coaxial Cable	C-SJ00-0010	C0010/04	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	27.6°C
Relative Humidity:	53 %
ATM Pressure:	101.8 kPa

* The testing was performed by Swim Lv on 2018-06-26.

Test Result: Compliance.

Test Mode: Transmitting

Channel	Frequency (MHz)	Peak Conducted Output power (dBm)	Limit (dBm)
Low	915.8	19.22	30
Middle	921.4	19.10	30
High	927	19.08	30

Note: The data above was tested in conducted mode.

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW/ VBW of spectrum analyzer to 100/300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	831929/005	2017-08-31	2018-08-31
Unknown	Coaxial Cable	C-SJ00-0010	C0010/04	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions


Temperature:	27.6~28.8°C
Relative Humidity:	53~56 %
ATM Pressure:	101.1~101.8 kPa

* The testing was performed by Swim Lv on 2018-06-26 & 2018-07-10.


Test Result: Compliance

Single Channel Mode,

Band Edge, Left Side




Band Edge, Right Side




Hopping Mode

Band Edge, Left Side



Band Edge, Right Side



***** END OF REPORT *****