

**OvisLink Corp.**  
**5F, No.6, Lane 130, Min-Chuan Rd., Hsin-Tien Dist.,**  
**New Taipei City 231 Taiwan**

Federal Communications Commission  
Authorization and Evaluation Division  
Equipment Authorization Branch  
7435 Oakland Mills Road  
Columbia, MD 21046

**Applicant's declaration concerning RF Radiation Exposure**

We hereby indicate that the product  
Product description: 5G High Throughput Outdoor CPE with PoE Pass through  
Model No: AirMax5X


The equipment complies with FCC RF radiation exposure limits set forth for an uncontrolled environment. The integral antennas used for this transmitter must not be co-located or operating in conjunction with any other antenna or transmitter within the host device.

A safety statement concerning minimum separation distances from enclosure of the Product : 5G High Throughput Outdoor CPE with PoE Pass through will be integrated in the user's manual to provide end-users with transmitter operating conditions for satisfying RF exposure compliance.

The appropriate information can be drawn from the test report no: W6D21409-14494-C-1-R and the accompanying calculations.

Company: OvisLink Corp.  
Address: 5F, No.6, Lane 130, Min-Chuan Rd., Hsin-Tien Dist., New Taipei City 231 Taiwan

Date: 2014-12-08

  
\_\_\_\_\_  
Signature

Name: Albert Yeh  
Title: Vice President



Registration number: W6D21409-14494-C-1-R

FCC ID: ODMAIRMAX5X

## 3.2 Equivalent isotropic radiated power

FCC Rule: 15.247(b)(3)

For systems using digital modulation in the 5725–5850 MHz bands: 1 Watt.

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Test equipment used: ETSTW-RE 055

## 3.3 RF Exposure Compliance Requirements

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.6 m normally can be maintained between the user and the device.

### 3.3.1 MPE Calculation Method

#### (A) Limits for Occupational/Controlled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm <sup>2</sup> ) | Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|---|---|
| 0.3-3.0               | 614                               | 1.63                              | (100)*                                  | 6   |
| 3.0-30                | 1842/f                            | 4.89/f                            | (900/f <sup>2</sup> )*                  | 6   |
| 30-300                | 61.4                              | 0.163                             | 1.0                                     | 6   |
| 300-1500              | --                                | --                                | f/300                                   | 6   |
| 1500-100,000          | --                                | --                                | 5                                       | 6   |

#### (B) Limits for General Population/Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm <sup>2</sup> ) | Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|---|---|
| 0.3-1.34              | 614                               | 1.63                              | (100)*                                  | 30  |
| 1.34-30               | 824/f                             | 2.19/f                            | (180/f <sup>2</sup> )*                  | 30  |
| 30-300                | 27.5                              | 0.073                             | 0.2                                     | 30  |
| 300-1500              | --                                | --                                | f/1500                                  | 30  |
| 1500-100,000          | --                                | --                                | 1.0                                     | 30  |

f = frequency in MHz

\*Plane-wave equivalent power density

$$E \text{ (V/m)} \cdot \frac{\sqrt{30 \times P \times G}}{d}$$

$$\text{Power Density: } Pd \text{ (W/m}^2\text{)} \cdot \frac{E^2}{377}$$



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D21409-14494-C-1-R  
FCC ID: ODMAIRMAX5X

E = Electric field (V/m) P = output power (W) G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd \cdot \frac{30 \times P \times G}{377 \times d^2}$$

| Frequency         | Max output power (W) | Antenna Gain | Power Density(S) (mW/cm <sup>2</sup> ) | Limit of Power Density (S) (mW/cm <sup>2</sup> ) | Test Result |
|-------------------|----------------------|--------------|--|--|-------------|
| 802.11 n<br>20MHz | 0.716                | 17.01        | 0.80                                   | 1.0  | Complies    |

From the peak EUT RF output power, the minimum mobile separation distance, d=0.6 m, as well as the gain of the used antenna, the RF power density can be obtained.