



## Adapter Specifications

---

<b>Supported Computers:</b>	486, Pentium
<b>Standard Compliant:</b>	IEEE 802.3 10BASE-T for 10 Mbps baseband CSMA/CD local area network IEEE 802.3u 100BASE-TX for 100 Mbps baseband CSMA/CD local area network
<b>Bus Type:</b>	32-bit PCI Bus Master
<b>WakeOnLAN mode:</b>	Support Magic Packet Wakeup
<b>ACPI mode:</b>	Supports : <b>PCI bus Power Management Interface Spec.(Rev 1.1).</b> <b>D0, D1, D2, D3hot, and D3cold, 5 different power states.</b> <b>PMEB (including LWAKE) can be generated form D1, D2, D3hot, and D3cold.</b> <b>Magic Packet wakeup.</b> <b>LinkUp wakeup.</b>

*Technical Specifications*

**Microsoft Wake Up frame.**

<b>Transmission Speed:</b>	IEEE 802.3u Auto-Negotiation for automatic speed selection. 10 Mbps (ordinary Ethernet), 20 Mbps (full-duplex Ethernet), 100 Mbps (ordinary Fast Ethernet), 200 Mbps (full-duplex Fast Ethernet)
<b>LED Indicator:</b>	FUDUP(Full-Duplex), Tx /Rx (Transmit/Receive) , 10/100(Mbps media selection) and PWR(Power)
<b>Boot ROM Size:</b>	8,16,32,64 and 128Kbyte
<b>Operating Temperature:</b>	32 ~ 131 degrees °F/ 0 ~ 55 degrees °C
<b>Storage Temperature:</b>	-4 ~ 176 degrees °F/ -20 ~ 80 degrees °C
<b>Humidity:</b>	10 ~ 90% RH non-condensing
<b>Dimension (L x W):</b>	12.0 x 6.5 cm
<b>Operating Voltage:</b>	+5V± 5% @ 300mA maximum