

Nemko Korea Co., Ltd.

165-51, Yurim-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, 17042, Republic of Korea
TEL:+82 31 330-1700 FAX:+82 31 322 2332

FCC & IC EVALUATION REPORT FOR CERTIFICATION

Project No. : NK-23-R-228	Dates of receipt : July 24, 2023
Applicant : i-SENS, Inc. 43, Banpo-daero 28-gil, Seocho-gu, Seoul 06646, Korea, Republic of	Dates of Issue : February 13, 2024 Test Site : Nemko Korea Co., Ltd.

FCC ID :	OELCGM-R-001
IC :	21003-CGMR001
Applicant :	i-SENS, Inc.
Brand Name :	CareSens

Model: CGM-R-001

Additional Model(s): CGM-R-002

EUT Type: CareSens Air Receiver

Classification: FCC Part 15 Digital Transmission System (DTS)

Date of Test: August 23, 2023 ~ September 7, 2023

Applied Standard: FCC 47 CFR Part 15.247
RSS-Gen Issue 5, RSS-247 Issue 3

The device bearing the brand name and model specified above has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013. The client should not use it to claim product endorsement by TAF or any government agencies. The test results in the report only apply to the tested sample.

I attest to the accuracy of data and all measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Tested By : Hyeonseung Lee
Test Engineer

Reviewed By : Hoonpyo Lee
Technical Manager

Revision History

Rev.	Issue Date	Revisions	Revised By
00	February 13, 2024	Initial issue	Hyeonseung Lee

TABLE OF CONTENTS

1. INTRODUCTION.....	4
1.1 Test facility	4
1.2 Accreditation and listing	4
2. EUT INFORMATION & TEST CONDITIONS	5
2.1 EUT Information	5
2.2 Operation During Test.....	6
2.3 Support Equipment	8
2.4 Setup Drawing.....	8
3. ANTENNA REQUIREMENTS	9
4. SUMMARY OF TEST RESULTS	10
5. TEST METHODOLOGY.....	11
6. DESCRIPTION OF TESTS.....	12
6.1 6 dB Bandwidth / Occupied Bandwidth	12
6.2 Peak Output Power	13
6.3 Power Spectral Density	14
6.4 Band Edge / Conducted Spurious Emissions	15
6.5 Radiated Emissions	16
6.7 AC Line Conducted Emissions.....	17
7. TEST DATA.....	18
7.1 6 dB Bandwidth / Occupied Bandwidth	18
7.2 Peak Output Power	21
7.3 Power Spectral Density	23
7.4 Band Edge / Conducted Spurious Emissions	25
7.5 Radiated Spurious Emissions	28
7.6 Radiated Band Edge	33
7.7 Radiated Emissions_Below 1GHz	35
7.8 AC Line Conducted	37
8. TEST EQUIPMENT.....	39
9. ACCURACY OF MEASUREMENT & DECISION RULE.....	40
9.1 Uncertainty Calculation	40
9.2 Decision rule.....	40







1. INTRODUCTION

1.1 Test facility

The measurement procedure described in American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz (ANSI C63.4-2014), the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2013) was used in determining radiated and conducted emissions emanating.

These measurement tests were conducted at **Nemko Korea Co., Ltd.**
The site address 165-51, Yurim-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, 17042, Rep. of Korea.

1.2 Accreditation and listing

	Accreditation type	Accreditation number
	CAB Accreditation for DOC	Designation No. KR0026
	KOLAS Accredited Lab. (Korea Laboratory Accreditation Scheme)	Registration No. KT155
	Canada IC Registered site	Site No. 29506
	VCCI registration site(RE/CE/Telecom CE)	Member No. 2118
	EMC CBTL	TL124
	KCC(RRL)Designated Lab.	Registration No. KR0026

2. EUT INFORMATION & TEST CONDITIONS

2.1 EUT Information

2.1.1 Specifications

EUT Type	CareSens Air Receiver
Model Name	CGM-R-001
Frequency of Operation	2 402 MHz ~ 2 480 MHz
Peak Output Power (Conducted)	-0.20 dBm
Number of Channels	40 CH
Modulations	GFSK
Antenna Gain (peak)	3.36 dBi
Antenna Setup	1TX / 1RX
EUT Rated Voltage	3.7 Vdc
EUT Test Voltage	3.7 Vdc
Remarks	-

2.2 Operation During Test

The EUT is the transceiver which is Bluetooth v5.2 supporting Bluetooth LE mode(Only 1 Mbps). The Laptop PC was used to control the EUT to transmit the wanted TX channel continuously (duty cycle < 98%) by the testing program (RF Tools) and testing command supported by manufacturer. The operating voltage of EUT was 3 Vdc supplied from jig board connected to USB port on Laptop PC.

The EUT was tested at the lowest, middle and the highest channels with the maximum output power in accordance with the manufacturer's specifications. The worst data were recorded in the report.

2.2.1 Table of Test power setting

Frequency	Mode	Modulation	Power setting Level
2 402 MHz ~ 2 480 MHz	BLE 1Mbps	GFSK	0

2.2.2 Table of Test frequency

Frequency band	Modulation	Test Channel (CH)	Frequency (MHz)
2.4 GHz	GFSK	0	2 402
		19	2 440
		39	2 480

2.2.3 Average Output Power

Mode	Frequency	Average Output Power (dBm)	Antenna Gain (dBi)	e.i.r.p (dBm)
Bluetooth LE 1Mbps	2 402	-0.39	3.36	2.97
	2 440	-0.36		3.00
	2 480	-0.42		2.94

2.2.4 Antenna Information

Frequency band	Modulation	Antenna TX mode	Support CDD	Support MIMO
2.4 GHz	GFSK	<input checked="" type="checkbox"/> 1TX, <input type="checkbox"/> 2TX	<input type="checkbox"/> Yes, <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes, <input checked="" type="checkbox"/> No

2.2.5 Additional Information Related to Testing

The cable and attenuator loss from 30 MHz to 26.5 GHz was reflected in spectrum analyzer with correction factor for all conducted testing.

2.2.6 Worst-case Configuration and Mode

Radiated emission below 1GHz was performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

Radiated emission above 1GHz was performed with the EUT set to transmit low/mid/high channels.

The emissions (Band-edge & spurious emissions) were investigated in three orthogonal orientations X, Y and Z.

Accordingly, the orientation was determined and tested as shown in the table below:

Test Items	X	Y	Z
Band-edge	-	-	O
Spurious emissions	-	-	O


2.2.7 Additional model covered by this report

The purpose of the marketing and the color of the product are different.

2.3 Support Equipment

EUT	i-SENS, Inc. Model : CGM-R-001	S/N: N/A Identical Proto-type
Laptop Computer	LG Model : 15Z90N-VP50ML	FCC DOC S/N : 003NZET038884
AC/DC Adapter	LG Model : WA-48B19FS	FCC DOC S/N : AKDS7648893016463

2.4 Setup Drawing



3. ANTENNA REQUIREMENTS

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission under FCC part 15 and RSS-Gen.

§15.203 of the FCC Rules part 15 Subpart C

: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

RSS-Gen Section 6.8

: The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below)

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

The transmitter has permanently attached Dielectric Chip antenna (Internal antenna) on board.

Used Antenna	
Model name	2 402 MHz ~ 2 480 MHz
	Max. peak gain (dBi)
IB24FE-Receiver (Embedded Antenna)	3.36

4. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specification:

Name of Test	FCC Paragraph No.	IC Paragraph No.	Test Limit	Test Condition	Result	Remark
6dB Bandwidth	15.247(a)(2)	RSS-247 (5.2)(a)	> 500 kHz	Conducted	Complies	-
Occupied Bandwidth	-	RSS-Gen (6.7)				
Peak Output Power	15.247(b)(3)	RSS-247 (5.4)(d)	< 1 Watt < 4 Watt(e.i.r.p.)		Complies	-
Power Spectral Density	15.247(e)	RSS-247 (5.2)(b)	< 8 dBm/3 kHz		Complies	-
Band Edge / Conducted Spurious Emission	15.247(d)	RSS-247 (5.5)	≥ 20 dBc		Complies	-
Radiated Spurious Emission	15.205, 15.209	RSS-Gen (8.9),(8.10)	< 74 dBμV/m (PK) < 54 dBμV/m (AV) Radiated limits detailed in 15.209	Radiated	Complies	-
AC Line Conducted Emission	15.207	RSS-Gen (8.8)	FCC 15.207 Limits	Line Conducted	Complies	-

5. TEST METHODOLOGY

1. FCC CFR 47 Part 2.
2. FCC CFR 47 Part 15.
3. KDB 558074 D01 15.247 Meas Guidance v05r02.
4. RSS-Gen Issue 5
5. RSS-247 Issue 3
6. ANSI C63.10-2013.

6. DESCRIPTION OF TESTS

6.1 6 dB Bandwidth / Occupied Bandwidth

Test Setup



Test Measurement Method

ANSI C63.10-2013, Section 11.8.2 Option 2
KDB 558074 D01 v05r02, Section 8.2
RSS-Gen section 6.7

Test Procedure

- 6 dB Bandwidth (DTS Chanel Bandwidth)

EUTs 6 dB bandwidth is measured at low, middle, high channels with a spectrum analyzer connected to the antenna terminal while the EUTs operating at its maximum power control level. The spectrum analyzer setting is as follows.

RBW = 100 kHz

VBW > 3 x RBW

Detector = Peak

Trace mode = max hold

Sweep = auto couple

Allow trace to fully stabilize.

The bandwidth measurement function on the spectrum analyzer is used to measure the 6 dB bandwidth.

- Occupied Bandwidth

EUTs occupied bandwidth is measured at low, middle, high channels with a spectrum analyzer connected to the antenna terminal while the EUTs operating at its maximum power control level. The spectrum analyzer setting is as follows.

Span = Set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.

Detector = Set to "Sample". However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or "Max Hold") may be necessary to determine the occupied / x dB bandwidth if the device is not transmitting continuously.

RBW = 1% to 5% of the actual occupied / x dB bandwidth

VBW > 3 x RBW, Video averaging is not permitted.

Note: It may be necessary to repeat the measurement a few times until the RBW and VBW are in compliance with the above requirement.

6.2 Peak Output Power

Test Setup



Test Measurement Method

ANSI C63.10-2013, Section 11.9.1.1
KDB 558074 D01 v05r02, Section 8.3.1.1

Test Procedure

EUTs Maximum Peak Conducted Output Power is measured at low, middle, high channels with a spectrum analyzer connected to the antenna terminal while the EUTs operating at its maximum power control level.

The spectrum analyzer setting is as follows.

RBW \geq DTS bandwidth

VBW \geq 3 x RBW

Span \geq 3 x RBW

Sweep time = auto couple

Detector = peak

Trace mode = max hold

Allow trace to fully stabilize.

Use peak marker function to determine the peak amplitude level.

6.3 Power Spectral Density

Test Setup



Test Measurement Method

ANSI C63.10-2013, Section 11.10.2 Method PKPSD
KDB 558074 D01 v05r02, Section 8.4

Test Procedure

EUTs Power Spectral Density is measured at low, middle, high channels with a spectrum analyzer connected to the antenna terminal while the EUTs operating at its maximum power control level.

The spectrum analyzer setting is as follows.

Center frequency = DTS channel center frequency

Span = 1.5 times the DTS channel bandwidth

RBW \geq 3 kHz

VBW \geq 3 x RBW

Detector = peak

Sweep time = auto couple

Trace mode = max hold

Allow the trace to stabilize.

The peak search function on the spectrum analyzer is used to determine the maximum amplitude level within the RBW.

6.4 Band Edge / Conducted Spurious Emissions

Test Setup



Test Measurement Method

ANSI C63.10-2013, Section 11.11.3

KDB 558074 D01 v05r02, Section 8.5, Section 8.7.2

Test Procedure

EUTs Conducted spurious emissions are measured at low, middle, high channels with a spectrum analyzer connected to the antenna terminal while the EUTs operating at its maximum power control level. The spectrum analyzer setting is as follows.

1) Reference Level

Center frequency = DTS channel center frequency

Span $\geq 1.5 \times$ DTS bandwidth

RBW = 100 kHz

VBW $\geq 3 \times$ RBW

Detector = peak

Sweep time = auto couple

Trace mode = max hold

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

2) Unwanted Emissions

Set the center frequency and span to encompass frequency range to be measured.

RBW = 100 kHz

VBW $\geq 3 \times$ RBW

Detector = peak

Sweep time = auto couple

Trace mode = max hold

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.

6.5 Radiated Emissions

Test Measurement Method

ANSI C63.10-2013, Section 6.6.4.3, Section 11.11, Section 11.12
KDB 558074 D01 v05r02, Section 8.6, Section 8.7

Test Procedure

The measurement was performed at the test site that is specified in accordance with ANSI C63.10-2013. The spurious emission was scanned from 9 kHz to 30 MHz using Loop Antenna and 30 to 1000 MHz using Trilog broadband test antenna. Above 1 GHz, Horn antenna was used.

For emissions testing at below 1GHz, The test equipment was placed on turntable with 0.8 m above ground. For emission measurements above 1 GHz, The test equipment was placed on turntable with 1.5 m above ground. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The EUT, cable, wire arrangement and mode of operation that has the highest amplitude relative to the limit was selected. Then, the turn table was rotated from 0° to 360° and an antenna mast was moved from 1 m to 4 m height to maximize the suspected highest amplitude signal. The final maximized level was recorded.

At frequencies below 1000 MHz, measurements performed using the CISPR quasi-peak detection. At frequencies above 1000 MHz, measurements performed using the peak and average measurement procedures described in ANSI 63.10-2013 section 11.12. Peak emission levels were measured by setting the analyzer RBW = 1 MHz, VBW = 3 MHz, Detector = Peak, Trace mode = max hold. Average emission levels were measured by setting the analyzer RBW = 1 MHz, VBW = 10 kHz, Detector = Peak, Trace mode = max hold. Allow max hold to run for at least 50 times (1/duty cycle) traces.

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009–0.490	2400/F(kHz)	300
0.490–1.705	24000/F(kHz)	30
1.705–30.0	30	30
30–88	100	3
88–216	150	3
216–960	200	3
Above 960	500	3

Radiated Emissions Limits per 47 CFR 15.209(a) & RSS-Gen (8.9)

6.7 AC Line Conducted Emissions

Test Measurement Method

ANSI C63.10-2013, Section 6.2

Test Procedure

The Line conducted emission test facility is located inside a 4 x 7 x 2.5 meter shielded enclosure. It is manufactured by EM engineering. The shielding effectiveness of the shielded room is in accordance with MIL-STD-285 or NSA 65-6. A 1 m x 1.5 m wooden table 0.8 m height is placed 0.4 m away from the vertical wall and 1.5 m away from the side of wall of the shielded room. Rohde & Schwarz (ENV216) of the 50 ohm/50 μ H Line Impedance Stabilization Network (LISN) are bonded to the shielded room. The EUT is powered from the Rohde & Schwarz LISN. Power to the LISNs are filtered by high-current high insertion loss Power line filters. The purpose of filter is to attenuate ambient signal interference and this filter is also bonded to shielded enclosure. All electrical cables are shielded by tinned copper zipper tubing with inner diameter of 1 / 2 ". If DC power device, power will be derived from the source power supply it normally will be powered from and this supply lines will be connected to the LISNs, All interconnecting cables more than 1 meter were shortened by non-inductive bundling (serpentine fashion) to a 1 meter length. Sufficient time for EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer to determine the frequency producing the maximum EME from the EUT. The spectrum was scanned from 150 kHz to 30 MHz with 200 msec sweep time. The frequency producing the maximum level was re-examined using the EMI test receiver. (Rohde & Schwarz ESCI). The detector functions were set to CISPR quasi-peak mode & average mode. The bandwidth of receiver was set to 9 kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each EME emission. Each emission was maximized by; switching power lines; varying the mode of operation or resolution; clock or data exchange speed; scrolling H pattern to the EUT and of support equipment, and powering the monitor from the floor mounted outlet box and computer aux AC outlet, if applicable; whichever determined the worst case emission.

Each EME reported was calibrated using the R&S signal generator.




Fig. 2. LISN Schematic Diagram

7. TEST DATA

7.1 6 dB Bandwidth / Occupied Bandwidth

FCC §15.247(a)(2)
RSS-247 (5.2)(a), RSS-Gen (6.7)

Test Mode : Set to Lowest channel, Middle channel and Highest channel

Result

- 6 dB Bandwidth


Bluetooth Mode & Data Rate	Channel No.	Frequency (MHz)	6 dB Bandwidth (kHz)	Minimum Bandwidth Limit (kHz)
LE 1Mbps	0	2 402	753.2	500
	19	2 440	737.4	500
	39	2 480	738.5	500

- Occupied Bandwidth


Bluetooth Mode & Data Rate	Channel No.	Frequency (MHz)	Occupied Bandwidth (MHz)	Limit (MHz)
LE 1Mbps	0	2 402	1.071	-
	19	2 440	1.065	-
	39	2 480	1.068	-

PLOTS OF EMISSIONS


LE 1Mbps, 6 dB Bandwidth, Lowest Channel (2 402 MHz)




LE 1Mbps, 6 dB Bandwidth, Middle Channel (2 440 MHz)




LE 1Mbps, 6 dB Bandwidth, Highest Channel (2 480 MHz)




LE 1Mbps, Occupied Bandwidth, Lowest Channel (2 402 MHz)



LE 1Mbps, Occupied Bandwidth, Middle Channel (2 440 MHz)



LE 1Mbps, Occupied Bandwidth, Highest Channel (2 480 MHz)



7.2 Peak Output Power

FCC §15.247(b)(3)
RSS-247(5.4)(d)

Test Mode : Set to Lowest channel, Middle channel and Highest channel

Result


Bluetooth Mode & Data Rate	Frequency (MHz)	Peak Output Power (dBm)	Limit (dBm)	Antenna Gain (dBi)	e.i.r.p. (dBm)	Limit (dBm)
LE 1Mbps	2 402	-0.20	30.00	3.36	3.16	36.00
	2 440	-0.22	30.00		3.14	36.00
	2 480	-0.24	30.00		3.12	36.00

Notes:


- The following equation was used for spectrum offset:
Spectrum offset (dB) = Attenuator (dB) + Cable Loss (dB) + SMA Type Connector Loss (dB)
- The following equation was used for e.i.r.p. calculation:
e.i.r.p. (dBm) = Peak output power (dBm) + Antenna gain (dBi)

PLOTS OF EMISSIONS


LE 1Mbps, Peak Output Power, Lowest Channel (2 402 MHz)



LE 1Mbps, Peak Output Power, Middle Channel (2 440 MHz)



LE 1Mbps, Peak Output Power, Highest Channel (2 480 MHz)



7.3 Power Spectral Density

FCC §15.247(e)
RSS-247(5.2)(b)

Test Mode : Set to Lowest channel, Middle channel and Highest channel

Result

Bluetooth Mode & Data Rate	Channel No.	Frequency (MHz)	Measured PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Margin (dB)
LE 1Mbps	0	2 402	-15.58	8.00	-23.58
	19	2 440	-15.61	8.00	-23.61
	39	2 480	-15.59	8.00	-23.59

Notes:

1. The following equation was used for spectrum offset:


$$\text{Spectrum offset (dB)} = \text{Attenuator (dB)} + \text{Cable Loss (dB)} + \text{SMA Type Connector Loss (dB)}$$

PLOTS OF EMISSIONS


LE 1Mbps, Power Spectral Density, Lowest Channel (2 402 MHz)



LE 1Mbps, Power Spectral Density, Middle Channel (2 440 MHz)



LE 1Mbps, Power Spectral Density, Highest Channel (2 480 MHz)



7.4 Band Edge / Conducted Spurious Emissions

FCC §15.247(d)
RSS-247(5.5)

Test Mode : Set to Lowest channel, Middle channel and Highest channel

Result


Bluetooth Mode & Data Rate	Channel No.	Frequency (MHz)	Conducted Spurious Emissions (dBc)	Limit (dBc)
LE 1Mbps	0	2 402	More than 20 dBc	20
	19	2 440	More than 20 dBc	20
	39	2 480	More than 20 dBc	20

Notes:


The cable and attenuator loss from 30 MHz to 26.5 GHz was reflected in spectrum analyzer with correction factor for the spurious emissions test.

PLOTS OF EMISSIONS (Band Edge)


LE 1Mbps, Band Edge, Lowest Channel (2 402 MHz)



LE 1Mbps, Reference Level, Middle Channel (2 440 MHz)




LE 1Mbps, Band Edge, Highest Channel (2 480 MHz)




PLOTS OF EMISSIONS (Conducted Spurious Emissions)


LE 1Mbps, Conducted Spurious Emissions, Lowest Channel (2 402 MHz)



LE 1Mbps, Conducted Spurious Emissions, Middle Channel (2 440 MHz)



LE 1Mbps, Conducted Spurious Emissions, Highest Channel (2 480 MHz)



7.5 Radiated Spurious Emissions

FCC §15.205, §15.209, §15.247(d)
RSS-Gen (8.9),(8.10)

Test Mode : Set to Lowest channel, Middle channel and Highest channel

Result

LE 1Mbps_Lowest channel (2 402 MHz)

Frequency (MHz)	Reading (dBµV)	Pol* (H/V)	Mode*	AF+CL+Amp (dB)**	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)
4 803.75	50.92	H	PK	1.7	52.62	74.00	21.38
4 803.75	46.72	H	AV	1.7	48.42	54.00	5.58
7 688.75	40.61	H	PK	7.6	48.21	74.00	25.79

LE 1Mbps_Middle channel (2 440 MHz)

Frequency (MHz)	Reading (dBµV)	Pol* (H/V)	Mode*	AF+CL+Amp (dB)**	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)
4 879.38	47.10	H	PK	2.2	49.30	74.00	24.70
4 880.00	43.80	H	AV	2.2	46.00	54.00	8.00
7 320.00	38.98	V	PK	6.2	45.18	74.00	28.82

LE 1Mbps_Highest channel (2 480 MHz)

Frequency (MHz)	Reading (dBµV)	Pol* (H/V)	Mode*	AF+CL+Amp (dB)**	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)
4 960.00	47.36	H	PK	2.4	49.76	74.00	24.24
4 959.38	42.18	H	AV	2.4	44.58	54.00	9.42
7 671.25	40.75	H	PK	7.4	48.15	74.00	25.85


Notes:

1. *Pol. : H = Horizontal, V = Vertical, Mode : PK = Peak, AV = Average
2. **AF + CL + Amp. = Antenna Factor + Cable Loss + Amplifier.
3. Average measurement was not performed when peak-detected emission complies with the average limit.
4. Other spurious was under 20 dB below Fundamental.
5. Bluetooth 1Mbps, Middle channel (2 402 MHz) was the worst condition.
6. The radiated emissions testing were made by rotating EUT through three orthogonal axes and rotating the receive antenna with horizontal, Vertical polarization.
7. Peak emissions were measured using RBW = 1 MHz, VBW = 3 MHz, Detector = Peak.
8. Average emissions were measured using RBW = 1 MHz, VBW = 10 kHz, Detector = Peak.
9. The spectrum was measured from 1 GHz to 10th harmonic and the worst-case emissions were reported.


PLOTS OF EMISSIONS

Worst Case


BLE 1Mbps, Lowest Channel (2 402 MHz) : 1 GHz to 8 GHz_Peak




BLE 1Mbps Lowest Channel (2 402 MHz) : 8 GHz to 18 GHz_Peak




BLE 1Mbps Lowest Channel (2 402 MHz) : 18 GHz to 26.5 GHz_Peak



BLE 1Mbps, Lowest Channel (2 402 MHz) : 1 GHz to 8 GHz_Average



BLE 1Mbps, Lowest Channel (2 402 MHz) : 8 GHz to 18 GHz_Average



7.6 Radiated Band Edge

FCC §15.205, §15.209
RSS-Gen (8.9),(8.10)

Test Mode : Set to Lowest channel and Highest channel

Result

BLE 1Mbps, Lowest Channel (2 402 MHz)

Frequency (MHz)	Reading (dBμV)	Pol* (H/V)	Mode*	AF+CL+Amp (dB)**	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2 389.65	52.69	V	PK	-7.5	45.19	74.00	28.81

BLE 1Mbps, Highest Channel (2 480 MHz)


Frequency (MHz)	Reading (dBμV)	Pol* (H/V)	Mode*	AF+CL+Amp (dB)**	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2 484.09	55.40	V	PK	-7.1	48.30	74.00	25.70

Notes:


- *Pol. : H = Horizontal, V = Vertical, Mode : PK = Peak, AV = Average
- **AF + CL + Amp. = Antenna Factor + Cable Loss + Amplifier.
- Average measurement was not performed when peak-detected emission complies with the average limit.
- Other spurious was under 20 dB below Fundamental.
- The radiated emissions testing were made by rotating EUT through three orthogonal axes and rotating the receive antenna with horizontal, Vertical polarization.
- Peak emissions were measured using RBW = 1 MHz, VBW = 3 MHz, Detector = Peak.

PLOTS OF EMISSIONS

BLE 1Mbps, Lowest Channel (2 402 MHz)_Peak



BLE 1Mbps, Highest Channel (2 480 MHz)_Peak



7.7 Radiated Emissions_Below 1GHz

FCC §15.209
RSS-Gen (8.9),(8.10)

Result

BLE 1Mbps, Lowest Channel (2 402 MHz)

Frequency (MHz)	Reading (dBµV)	Pol* (H/V)	Mode*	AF+CL+Amp (dB)**	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)
34.10	54.60	V	QP	-23.6	31.00	40.00	9.00
77.05	51.24	H	QP	-28.9	22.34	40.00	17.66
180.35	53.80	H	QP	-26.5	27.30	43.50	16.20
197.16	43.82	V	QP	-24.5	19.32	43.50	24.18
360.02	49.32	H	QP	-19.1	30.22	46.00	15.78
600.20	36.02	V	QP	-13.4	22.62	46.00	23.38

Radiated Measurements at 3meters


Notes:

1. The worst-case emission was reported.
2. *Pol. : H = Horizontal, V = Vertical, Mode : PK = Peak, QP = Qusi-Peak
3. **AF + CL + Amp. = Antenna Factor + Cable Loss + Amplifier.
4. Measurements using CISPR quasi-peak mode below 1 GHz.
5. The radiated emissions testing were made by rotating EUT through three orthogonal axes and rotating the receive antenna with horizontal, Vertical polarization. The worst data was recorded.
6. No emission found between lowest internal used/generated frequency to 30MHz (9kHz~30MHz). Per FCC part 15.31(o), test results were not reported.
Although these tests were performed other than open field test site, adequate comparison measurements were confirmed against 30 m open are test site.
Therefore, sufficient tests were made to demonstrate that the alternative site produces results that correlate with the one of tests made in an open field based on KDB 414788.
7. The limit is on the FCC §15.209.

PLOTS OF EMISSIONS

Worst Case

Radiated emission below 1GHz, LE 1Mbps, Lowest Channel (2 402 MHz)



7.8 AC Line Conducted

FCC §15.207
RSS-Gen(8.8)

Result :

BLE 1Mbps, Highest Channel (2 480 MHz)

Final Result

Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.164925	---	32.69	54.71	22.02	9.000	N	ON	9.9
0.164925	45.77	---	64.71	18.94	9.000	N	ON	9.9
0.169900	---	32.42	54.48	22.06	9.000	N	ON	10.0
0.169900	45.13	---	64.48	19.34	9.000	N	ON	10.0
0.182338	---	32.71	53.92	21.22	9.000	N	ON	9.9
0.182338	43.41	---	63.92	20.52	9.000	N	ON	9.9
0.383825	---	38.23	48.08	9.85	9.000	L1	ON	9.8
0.383825	45.37	---	58.08	12.71	9.000	L1	ON	9.8
0.388800	45.66	---	57.98	12.32	9.000	L1	ON	9.8
0.388800	---	39.11	47.98	8.87	9.000	L1	ON	9.8
2.368850	25.57	---	56.00	30.43	9.000	L1	ON	9.7
2.368850	---	18.10	46.00	27.90	9.000	L1	ON	9.7
3.077788	---	21.53	46.00	24.47	9.000	L1	ON	9.7
3.077788	28.93	---	56.00	27.07	9.000	L1	ON	9.7
4.174775	---	18.25	46.00	27.75	9.000	L1	ON	9.7
4.174775	25.16	---	56.00	30.84	9.000	L1	ON	9.7

Line Conducted Emissions Tabulated Data


Notes:

1. Measurements using CISPR quasi-peak mode & average mode.
2. The worst channel was investigated and the worst -case emission are reported. See attached Plots.
3. Lowest channel (2 402MHz) is the worst case.
4. *) Factor = LISN + Cable Loss
5. **) LINE : L = Line , N = Neutral
6. The limit is on the FCC §15.207(a) & RSS-Gen(8.8)

PLOTS OF EMISSIONS

Worst Case

AC Lice Conducted emission, BLE 1Mbps, Lowest Channel (2 402 MHz)



8. TEST EQUIPMENT

No.	Instrument	Manufacture	Model	Serial No.	Calibration Date	Next Calibration Date
1	DIGITAL MULTIMETER	EZ DIGITAL	DM-334	2111395	2022-10-13	2023-10-13
2	Humidity Temperature Recorder	Lutron	MHB-382SD	AK.26553	2022-10-17	2023-10-17
3	Signal Generator	R&S	SMB100A	175861	2023-04-13	2024-04-13
4	10 dB Attenuator	API technologies corp	40A2W-10	1917	2023-01-09	2024-01-09
5	Signal & Spectrum Analyzer	KEYSIGHT	N9030B	MY57144327	2023-03-31	2024-03-31
6	EMI TEST RECEIVER	R&S	ESW44	103091	2023-03-29	2024-03-29
7	TRILOG Broadband Test Antenna	Schwarzbeck	VULB 9163	01431	2022-11-16	2024-11-16
8	DOUBLE RIDGED HORN ANTENNA	R&S	HF907	100197	2023-01-13	2024-01-13
9	Horn Antenna	Q-par Angus	QMS-00225	17637	2023-09-07	2024-09-07
10	Signal Conditioning Unit	R&S	SCU 01	10029	2023-03-29	2024-03-29
11	Signal Conditioning Unit	R&S	SCU 18	10065	2023-03-29	2024-03-29
12	Signal Conditioning Unit	R&S	SCU-26D	1984522	2023-04-03	2024-04-03
13	OPEN SWITCH AND CONTROL UNIT	R&S	OSP120	101766	N/A	N/A
14	SWICH AND EXTENSION UNIT CAN-BUS	R&S	OSP150	100929	N/A	N/A
15	WiFi Filter Bank	R&S	U082	-	N/A	N/A
16	TWO-LINE V-NETWORK	R&S	ENV216	102829	2023-07-04	2024-07-04
17	EMI TEST RECEIVER	R&S	ESR3	102930	2023-07-03	2024-07-03
18	LOOP ANTENNA	R&S	HFH2-Z2	100279	2023-03-21	2024-03-21

9. ACCURACY OF MEASUREMENT & DECISION RULE

9.1 Uncertainty Calculation

The Measurement Uncertainties stated were calculated in accordance with the requirements of measurement uncertainty contained in CISPR 16-4-2 with the confidence level of 95%

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	2.44 dB
Radiated Disturbance, 30 MHz to 1 GHz	5.68 dB
Radiated Disturbance, Above 1 GHz	5.06 dB

9.2 Decision rule

The choice of whether or not to include the measurement uncertainty of the measuring system used in the test in the conformance determination.:

- Application of internal procedures used in type testing where traceability of measurement uncertainty is established.
- Applying the decision that the standard used for type testing does not require it.

END REPORT