

## RF Exposure Evaluation Statement

**Product Name:** TLSR8266DG32D

**Model No.:** TLSR8266DG32D

**FCC ID:** OEOTLSR8266DG32D

## 1.1 RF Exposure Compliance Requirement

### 1.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

## Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

### 1.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot$$
$$[\sqrt{f}(\text{GHz})] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

- ☐  $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- ☐ Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>
- ☐ The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion

### 1.1.3 EUT RF Exposure

| Operational Mode: BLE ( worst case )                    |                                           |                        |                       |      |                  |                     |
|---------------------------------------------------------|-------------------------------------------|------------------------|-----------------------|------|------------------|---------------------|
| Channel                                                 | Maximum Peak Conducted Output Power (dBm) | Tune up tolerance (dB) | Maximum tune-up Power |      | Calculated value | Exclusion threshold |
|                                                         |                                           |                        | (dBm)                 | (mW) |                  |                     |
| 2402                                                    | 8.08                                      | ±1                     | 9.08                  | 8.09 | 2.51             | 3.0                 |
| 2442                                                    | 7.81                                      | ±1                     | 8.81                  | 7.60 | 2.38             |                     |
| 2480                                                    | 7.62                                      | ±1                     | 8.62                  | 7.28 | 2.29             |                     |
| Conclusion: the calculated value ≤3.0, SAR is exempted. |                                           |                        |                       |      |                  |                     |