



---

**AT&T Wireless Services**

Wireless Local Technologies Group

PO Box 97059

Redmond, WA 98073-9759

# FCC R3 Type Acceptance Report

11576

**Revision 1.0**

**8/2/00**

© 1995-2000 AT&T Wireless Services  
All rights reserved.

For additional copies of this document, please contact:

**AT&T Wireless Services**  
**PO Box 97059**  
**Redmond, WA 98073-9759**  
**Telephone: 425-702-2767**  
**Facsimile: 425-702-3941**  
**Ask for FCC R3 Type Acceptance Report or 11576.**

# Contents

Contents .....	iii
List of Figures .....	ix
List of Tables .....	xvii
<b>Chapter 1 Attestation Statements</b>	
<b>Chapter 2 Block Diagrams</b>	
2.1 Block Diagrams .....	2-2
<b>Chapter 3 Cover Letters</b>	
<b>Chapter 4 External Photographs</b>	
4.1 Photographs of the R3 Indoor Unit .....	4-2
4.2 Photographs of the R3 Outdoor Unit .....	4-7
<b>Chapter 5 ID Label/Location Information</b>	
5.1 ID Label .....	5-2
5.2 Location Information .....	5-3
<b>Chapter 6 Internal Photographs</b>	
6.1 Internal Photographs of the R3 Outdoor Unit .....	6-2

**6.2 Internal Photographs of the R3 Indoor Unit** ..... 6-9

## **Chapter 7 Operational Description**

**7.1 System Overview** ..... 7-2

7.1.1 PWAN General Description ..... 7-2

7.1.2 PWAN Network Element Overview ..... 7-2

7.1.3 Wireless Network Element Deployment ..... 7-4

7.1.4 PWAN Airlink Profile ..... 7-5

7.1.5 PWAN Telephony Functions ..... 7-6

7.1.6 PWAN FAX/Modem VF Traffic Functions ..... 7-9

7.1.7 PWAN High-Speed Data Functions ..... 7-9

7.1.8 HSD Medium Access ..... 7-10

**7.2 Airlink Overview** ..... 7-11

7.2.1 PWAN Physical Layer Overview ..... 7-11

7.2.1.1 Services Provided by the Physical Layer ..... 7-13

7.2.2 PWAN Airlink Overview ..... 7-13

7.2.2.1 PWAN Implementation of OFDM ..... 7-15

7.2.3 PWAN Airlink Resource Allocation ..... 7-18

7.2.4 PWAN Network Access Channel (NAC) Functional Description 7-19

7.2.4.1 BC Definition ..... 7-19

7.2.4.2 CLC Definition ..... 7-19

7.2.4.3 UCAC Definition ..... 7-20

7.2.4.4 SCAC Definition ..... 7-20

7.2.5 PWAN Voice Traffic Channel (VTch) Functional Description ... 7-21

7.2.5.1 Associated Control Channel Functional Description . 7-21

7.2.6 PWAN High-Speed Data Services ..... 7-21

7.2.6.1 Basic Data Service Allocation Definition ..... 7-21

7.2.6.2 PWAN Data Traffic Channel (DTch) Definition ..... 7-22

7.2.6.3 High-Speed Data Medium Access Control ..... 7-23

7.2.7 Network Synchronization ..... 7-23

## **Chapter 8 Parts List/Tune Up Information**

**8.1 Parts List** ..... 8-2

8.1.1 R3 Outdoor Unit PCB ..... 8-2

8.1.2 R3 Indoor Unit PCB ..... 8-5

8.1.3 R3 Indoor Unit 2-line Expansion PCB ..... 8-8

8.1.4 R3 Indoor Unit Lucent AC-DC Power Supply ..... 8-9

8.1.5 R3 Indoor Unit Panasonic AC-DC Power Supply ..... 8-11

8.1.6	R3 Outdoor Unit Lucent DC-DC Power Module . . . . .	8-12
<b>8.2</b>	<b>Output Power Tuning Procedures . . . . .</b>	<b>8-13</b>
8.2.1	Hardware Output Power Limiting Circuit . . . . .	8-13
8.2.2	Software Output Power Control . . . . .	8-15
8.2.3	Manufacturing Calibration . . . . .	8-16
8.2.4	Hardware Frequency vs Temperature Results . . . . .	8-16

## Chapter 9 RF Exposure

<b>9.1</b>	<b>RF Human Exposure - FDTD Analysis and SAR Testing . . . . .</b>	<b>9-2</b>
9.1.1	Applicable FCC Rules . . . . .	9-2
9.1.2	Test Configuration . . . . .	9-2
9.1.2.1	Modelling . . . . .	9-2
9.1.2.2	SAR Testing . . . . .	9-2
9.1.3	Test Results . . . . .	9-3
<b>9.2</b>	<b>Summary and Conclusions . . . . .</b>	<b>9-3</b>
<b>9.3</b>	<b>Computer Hardware and Software Used for Performing Calculations</b>	<b>9-4</b>
9.3.1	Computer Hardware . . . . .	9-4
9.3.2	Computer Software . . . . .	9-5
<b>9.4</b>	<b>2 FDTD Models . . . . .</b>	<b>9-5</b>
9.4.1	Antenna Model . . . . .	9-5
9.4.2	Kuster Homogeneous Head Model . . . . .	9-6
9.4.2.1	Nose of Model Centered Over Geometric Center of Patch Array . . . . .	9-7
9.4.2.2	Nose of Model Centered Over Geometric Center of Lower Right and Left Patches . . . . .	9-7
9.4.3	Orientation with Tip of Nose in Contact with Radome and in Center of Four Patch Array . . . . .	9-10
<b>9.5</b>	<b>Calculation of SAR in Kuster Head and Shoulders Homogeneous Model</b>	<b>9-12</b>
9.5.1	Orientation with Tip of Nose in Contact with Radome at Center of Four Patch Array . . . . .	9-12
9.5.2	Orientation with Tip of Nose in Contact with Radome and Centered over Lower Right Patch . . . . .	9-13
9.5.3	Orientation with Tip of Nose in Contact with Radome and Centered over Lower left Patch . . . . .	9-15
<b>9.6</b>	<b>FDTD Calculation of SAR in REMCOM Head and Shoulders Inhomogeneous Model . . . . .</b>	<b>9-16</b>

## Chapter 10 Schematics

10.1	R3 Outdoor Unit PCB	10-2
10.2	R3 Indoor Unit PCB	10-3
10.3	R3 Indoor Unit 2-line Expansion Card PCB	10-4
10.4	R3 Indoor Unit Lucent AC-DC Power Supply	10-5
10.5	R3 Indoor Unit Panasonic AC-DC Power Supply	10-6
10.6	R3 Outdoor Unit Lucent DC-DC Power Module	10-7

## Chapter 11 Test Report

11.1	Test Methodology	11-2
11.1.1	Introduction	11-2
11.1.2	Equipment Classification	11-2
11.1.3	Remote Unit RF Frequency Stability vs. Temperature Test Methodology	11-3
11.1.3.1	Applicable FCC Rules Parts	11-3
11.1.3.2	Overview	11-3
11.1.3.3	Test Methodology	11-4
11.1.4	R3 Frequency Stability vs. Input Voltage Test Methodology	11-6
11.1.4.1	Applicable FCC Rule Parts	11-6
11.1.4.2	Overview	11-6
11.1.4.3	Test Methodology	11-7
11.1.5	R3 Occupied Bandwidth Test Methodology	11-9
11.1.5.1	Applicable FCC Rule Parts	11-9
11.1.5.2	Overview	11-9
11.1.5.3	Test Methodology	11-9
11.1.6	Modulation Characterization Test Methodology	11-11
11.1.6.1	Applicable FCC Rules	11-11
11.1.6.2	Overview	11-11
11.1.6.3	Test Methodology	11-12
11.1.7	RF Output Power Test Methodology	11-14
11.1.7.1	Applicable FCC Rules	11-14
11.1.7.2	Overview	11-14
11.1.7.3	Test Methodology	11-15
11.1.8	Spurious Emissions at the Antenna Terminal Test Methodology	11-16
11.1.8.1	Applicable FCC Rules	11-16
11.1.8.2	Overview	11-17
11.1.8.3	Test Methodology	11-18
11.1.9	RF Human Exposure	11-20

11.1.9.1	Applicable FCC Rules	11-20
11.1.9.2	Overview	11-20
11.1.10	Radiated Emissions	11-21
11.1.10.1	Applicable FCC Rules	11-21
11.1.10.2	Overview	11-21
11.1.10.3	Test Methodology	11-22
11.1.10.4	Radiated Emissions Equipment Configuration 30-1000 MHz	11-22
11.1.10.5	Measure Parameters	11-24
11.1.10.6	Antenna Factors	11-25
11.1.10.7	Cable Factors	11-27
11.1.10.8	Radiated Emissions Equipment Configuration 1000-3500 MHz	11-27
11.1.10.9	Cable Factors	11-30
<b>11.2</b>	<b>RF Characterization Test Results</b>	11-31
11.2.1	Test Equipment List	11-31
11.2.2	Equipment Under Test List	11-33
11.2.3	R3 RF Frequency Stability vs. Temperature Test Results	11-33
11.2.3.1	Applicable FCC Rules Parts	11-33
11.2.3.2	Test Configuration	11-33
11.2.4	Results Summary	11-34
11.2.5	R3 Frequency Stability vs. Input Voltage Test Results	11-35
11.2.5.1	Applicable FCC Rule Parts	11-35
11.2.5.2	Test Configuration	11-36
11.2.5.3	Results Summary	11-36
11.2.6	R3 Occupied Bandwidth Test Results	11-37
11.2.6.1	Applicable FCC Rule Parts	11-37
11.2.6.2	Test Configuration	11-37
11.2.6.3	Results Summary	11-38
11.2.7	Modulation Characterization Test Results	11-39
11.2.7.1	Applicable FCC Rules	11-39
11.2.7.2	Test Configuration	11-39
11.2.7.3	Results Summary	11-39
11.2.8	RF Output Power Test Results	11-46
11.2.8.1	Applicable FCC Rules	11-46
11.2.8.2	Test Configuration	11-46
11.2.9	Spurious Emissions at the Antenna Terminal	11-49
11.2.9.1	Applicable FCC Rules	11-49
11.2.9.2	Test Configuration	11-49
11.2.9.3	Results Summary	11-50

- 11.3 Electromagnetic Compatibility Test Results** ..... 11-57
  - 11.3.1 Introduction ..... 11-57
  - 11.3.2 Equipment Lists ..... 11-58
  - 11.3.3 Equipment Under Test List ..... 11-60
  - 11.3.4 Test Results ..... 11-61
    - 11.3.4.1 Radiated Emissions ..... 11-61
    - 11.3.4.2 Conducted Emissions ..... 11-121
    - 11.3.4.3 Radiated to Conducted Spurious Emissions ..... 11-131
- 11.4 R3 Outdoor Unit Specifications** ..... 11-133
  - 11.4.1 Overview ..... 11-133
  - 11.4.2 Antenna Specification ..... 11-133
  - 11.4.3 Operational Temperature Ranges ..... 11-135
  - 11.4.4 R3 Outdoor Unit Pattern ..... 11-135

## **Chapter 12 Test Setup Photos**

- 12.1 Radiated Emissions Test Setup** ..... 12-2
- 12.2 Conducted Emission Test Setup** ..... 12-8
- 12.3 Testing Facility and Location** ..... 12-9

## **Chapter 13 User Manuals**



# List of Figures

Figure 2.1	RU Digital Board Comprehensive Block Diagram	.2-2
Figure 2.2	R3 Transmitter Baseband and IF Functional Block Diagram	.2-3
Figure 2.3	Transmitter Functional Block Diagram	.2-4
Figure 2.4	R3 Receiver RF Block Diagram	.2-5
Figure 2.5	Receiver IF and Baseband Functional Block Diagram	.2-6
Figure 2.6	Remote Unit RF Phase-Lock Loop Block Diagram	.2-7
Figure 2.7	R3 Control Logic and 32-MHz Oscillator Block Diagram	.2-8
Figure 4.1	Front of the R3 Indoor Unit	.4-2
Figure 4.2	Right-side view of the R3 Indoor Unit	.4-3
Figure 4.3	Side View of the R3 Indoor Unit	.4-4
Figure 4.4	Rear view of the R3 Indoor Unit	.4-5
Figure 4.5	R3 Surge Protector	.4-6
Figure 4.6	Front View of the R3 Outdoor Unit Antenna	.4-7
Figure 4.7	Rear View of the R3 Outdoor Unit	.4-8
Figure 4.8	Side View of the Outdoor Unit with Mounting Bracket	.4-9
Figure 5.1	FCC ID Label for the R3 Indoor Unit	.5-2
Figure 5.2	FCC ID Label for the R3 Outdoor Unit	.5-2
Figure 5.3	FCC ID Label Location on Antenna	.5-3
Figure 5.4	Close-up of Label on R3 Outdoor Unit	.5-4
Figure 5.5	FCC ID Label Location on the R3 Indoor Unit	.5-5

Figure 5.6 FCC Label Location on R3 Indoor Unit ..... 5-6

Figure 6.1 R3 Outdoor Unit - Radome Removed Revealing Back View of Antenna . 6-2

Figure 6.2 R3 Outdoor Unit Back - Radome Removed Revealing DC-DC Converter 6-3

Figure 6.3 Top View of the R3 Outdoor Unit RF Board ..... 6-4

Figure 6.4 R3 Outdoor Unit Backside of Radome and Frontside of Antenna ..... 6-5

Figure 6.5 Bottom View of the R3 Outdoor Unit - Patch Antenna Separated from the RF PCB ..... 6-6

Figure 6.6 Top View of the DC-DC Converter ..... 6-7

Figure 6.7 Bottom View of the DC-DC Converter ..... 6-8

Figure 6.8 R3 Indoor Unit Cover Removed with Lucent Power Supply ..... 6-9

Figure 6.9 R3 Indoor Unit with Cover Removed and Panasonic Power Supply .... 6-10

Figure 6.10 R3 Indoor Unit Chassis with Cover Removed ..... 6-11

Figure 6.11 Top View of the Main R3 Indoor Unit Digital PCB ..... 6-12

Figure 6.12 Bottom View of R3 Indoor Unit Main Digital PCB ..... 6-13

Figure 6.13 Top View of The Lucent Power Supply. .... 6-14

Figure 6.14 Bottom View of the Lucent Power Supply ..... 6-15

Figure 6.15 Top View of the Panasonic Power Supply ..... 6-16

Figure 6.16 Bottom View of the Panasonic Power Supply ..... 6-17

Figure 6.17 Top view of the R3 Indoor Unit Expansion Card ..... 6-18

Figure 6.18 Bottom View of the R3 Indoor Unit Expansion Card ..... 6-19

Figure 6.19 R3 Indoor Unit—View of Batteries and Terminal Cables ..... 6-20

Figure 7.1 PWAN Telephony Architecture ..... 7-3

Figure 7.2 PWAN Figure OSI Model ..... 7-6

Figure 7.3 PWAN Airlink Protocol Profile ..... 7-7

Figure 7.4 PWAN Telephony Processing ..... 7-8

Figure 7.5 PWAN HSD Architecture ..... 7-10

Figure 7.6 HSD Logical Channel Relationships ..... 7-11

Figure 7.7 PWAN OSI Model ..... 7-12

Figure 7.8 Illustration of OFDM Burst Parameters ..... 7-14

Figure 7.9 OFDM Time-Domain Waveform Generation ..... 7-15

Figure 7.10 PWAN Subband Allocation ..... 7-16

Figure 7.11 PWAN FDMA Structure ..... 7-16

Figure 7.12 PWAN TDMA Framing Structure ..... 7-17

Figure 7.13 PWAN Airlink Resource Matrix  
..... 7-18

Figure 7.14 NAC Logical Channel Timing Relationships ..... 7-20

Figure 7.15 Basic Data Service Allocation ..... 7-22

Figure 7.16 RSP Definitions ..... 7-24

Figure 8.1	Hardware Output Limiting Circuit . . . . .	8-15
Figure 9.1		9-6
Figure 9.2		9-6
Figure 9.3		9-8
Figure 9.4		9-8
Figure 9.5		9-8
Figure 9.6		9-10
Figure 9.7		9-12
Figure 9.8		9-13
Figure 9.9		9-13
Figure 9.10		9-14
Figure 9.11		9-14
Figure 9.12		9-15
Figure 9.13		9-15
Figure 9.14		9-16
Figure 9.15		9-16
Figure 9.16		9-17
Figure 9.17		9-17
Figure 9.18		9-18
Figure 11.1	Remote Unit Delay Compensation Pilot Frequency Relationships . . . . .	11-4
Figure 11.2	Remote Unit Frequency Stability vs. Temperature Test Configuration . . .	11-5
Figure 11.3	R3 Frequency Stability vs. Input Voltage Test Configuration . . . . .	11-8
Figure 11.4	R3 Occupied Bandwidth and Modulation Characterization Test Configuration 11-10	
Figure 11.5	R3 Output Power Test Configuration . . . . .	11-16
Figure 11.6	R3 Conducted Power Spectral Mask . . . . .	11-18
Figure 11.7	Spectral Purity Test Configuration . . . . .	11-19
Figure 11.8	Equipment Set Graph . . . . .	11-23
Figure 11.9	Equipment Set . . . . .	11-28
Figure 11.10	R3 Frequency Stability vs. Temperature, DCP Tone #7 . . . . .	11-35
Figure 11.11	R3 Frequency Stability vs. Input Voltage . . . . .	11-37
Figure 11.12	R3 99% Occupied Bandwidth During Delay Compensation Pilot Operation . 11-38	
Figure 11.13	Voice Channel Power vs. Frequency, 99.0% Occupied BW, and Time-Domain Average Burst Power . . . . .	11-40
Figure 11.14	Voice Channel CCDF . . . . .	11-40
Figure 11.15	HSD Channel Power vs. Frequency, 99% Occupied BW, and Time-Domain Average Burst Power . . . . .	11-41

Figure 11.16 HSD Channel CCDF ..... 11-42

Figure 11.17 Network Access Channel Power vs. Frequency, 99% Occupied Bandwidth, and Time-Domain Average Power ..... 11-43

Figure 11.18 Network Access Channel CCDF ..... 11-43

Figure 11.19 Delay Compensation Channel Power vs. Frequency, 99% Occupied BW, and Time-Domain Average Power ..... 11-44

Figure 11.20 Delay Compensation Channel CCDF ..... 11-45

Figure 11.21 Time-Domain Power Envelope, Average Power ..... 11-47

Figure 11.22 Time-Domain Power Envelope, Peak Power at £ 99.0% Occurrence ..... 11-47

Figure 11.23 Time-Domain Power Envelope, Peak/Average Ratio at £ 99.0% Occurrence ..... 11-48

Figure 11.24 R3 Conducted Power Spectral Mask ..... 11-50

Figure 11.25 1-MHz Band-Power Between 1865.5 and 1866.5 MHz ..... 11-50

Figure 11.26 1-MHz Band Power Between 1866.5 and 1867.5 MHz ..... 11-51

Figure 11.27 1 MHz Channel Power Between 1867.5 and 1868.5 MHz ..... 11-51

Figure 11.28 1 MHz Channel Power Between 1868.5 and 1869.5 MHz ..... 11-52

Figure 11.29 Maximum Lower Guard Band Spurious Power, Measured in a 12 kHz Resolution BW ..... 11-52

Figure 11.30 Maximum Upper Guard Band Spurious Power Measured in a 12 kHz Resolution BW ..... 11-53

Figure 11.31 Spectral Purity from 1859.5 MHz to 1866.5 MHz, with Spurious Power Between 1864.5 and 1865.5 MHz Measured in a 1 MHz Bandwidth .. 11-53

Figure 11.32 Spectral Purity from 1853 to 1860 MHz, with Spurious Power Measured in a 1 MHz Band-Power Marker Centered on 1859 MHz ..... 11-54

Figure 11.33 Spectral Purity from 1868.5 MHz to 1875.5 MHz with 1 MHz Band-Power Reference Between 1871 and 1872 MHz ..... 11-54

Figure 11.34 Spectral Purity from 1875 MHz to 1882 MHz with 1 MHz Band-Power Reference Centered at 1878 MHz ..... 11-55

Figure 11.35 Directional Coupler and Cable Sweep ..... 11-57

Figure 11.36 3-meter Chamber Ambient ..... 11-62

Figure 11.37 30 - 1000 MHz: Four Voice Calls with HSD ..... 11-64

Figure 11.38 1000 - 3500 MHz: Four Voice Calls ..... 11-66

Figure 11.39 R3 Fundamental Skirts ..... 11-68

Figure 11.40 3.5 - 18 GHz: Four Voice Calls With HSD, Horizontal Polarization, Full Scan 11-69

Figure 11.41 3.5 - 18 GHz: Four Voice Calls With HSD, Horizontal Polarization, Highest Signal, 7.46 GHz Peak ..... 11-70

Figure 11.42 3.5 - 18 GHz: Four Voice Calls With HSD, Horizontal Polarization, Highest Signal, 7.46 GHz Average ..... 11-71

Figure 11.43 3.5 - 18 GHz: Four Voice Calls With HSD, Horizontal Polarization, Second

	Highest Signal, 3.73 GHz Peak	11-72
Figure 11.44	3.5 - 18 GHz: Four Voice Calls With HSD, Horizontal Polarization, Second Highest Signal, 3.73 GHz Average	11-73
Figure 11.45	3.5 - 18 GHz: Four Voice Calls With HSD, Horizontal Polarization, Third Highest Signal, 9.33 GHz Peak	11-74
Figure 11.46	3.5 - 18 GHz: Four Voice Calls With HSD, Horizontal Polarization, Third Highest Signal, 9.33 GHz Average	11-75
Figure 11.47	3.5 - 18 GHz: Four Voice Calls With HSD, Vertical Polarization, Full Scan	11-76
Figure 11.48	3.5 - 18 GHz: Four Voice Calls With HSD, Vertical Polarization, Highest Signal, 3.73 GHz Peak	11-77
Figure 11.49	3.5 - 18 GHz: Four Voice Calls With HSD, Vertical Polarization, Highest Signal, 3.73 GHz Average	11-78
Figure 11.50	3.5 - 18 GHz: Four Voice Calls With HSD, Vertical Polarization, Second Highest Signal, 7.46 GHz Peak	11-79
Figure 11.51	3.5 - 18 GHz: Four Voice Calls With HSD, Vertical Polarization, Second Highest Signal, 7.46 GHz Average	11-80
Figure 11.52	18-26.5 GHz: Four Voice Calls With HSD, Horizontal Polarization, Full Scan	11-81
Figure 11.53	18-26.5 GHz: Four Voice Calls With HSD, Vertical Polarization, Full Scan	11-82
Figure 11.54	30-1000 MHz: Two Voice Calls with HSD	11-83
Figure 11.55	1-3.5 GHz: Two Voice Calls with HSD	11-85
Figure 11.56	R3 Fundamental Skirts	11-86
Figure 11.57	3.5 - 18 GHz: Two Voice Calls With HSD, Horizontal Polarization, Full Scan	11-87
Figure 11.58	3.5 - 18 GHz: Two Voice Calls With HSD, Horizontal Polarization, Highest Signal, 7.46 GHz Peak	11-88
Figure 11.59	3.5 - 18 GHz: Two Voice Calls With HSD, Horizontal Polarization, Highest Signal, 7.46 GHz Average	11-89
Figure 11.60	3.5 - 18 GHz: Two Voice Calls With HSD, Horizontal Polarization, Second Highest Signal, 3.73 GHz Peak	11-90
Figure 11.61	3.5 - 18 GHz: Two Voice Calls With HSD, Horizontal Polarization, Second Highest Signal, 3.73 GHz Average	11-91
Figure 11.62	3.5 - 18 GHz: Two Voice Calls With HSD, Horizontal Polarization, Third Highest Signal, 5.6 GHz Peak	11-92
Figure 11.63	3.5 - 18 GHz: Two Voice Calls With HSD, Horizontal Polarization, Third Highest Signal, 5.6 GHz Average	11-93
Figure 11.64	3.5 - 18 GHz: Two Voice Calls With HSD, Vertical Polarization, Full Scan	11-94
Figure 11.65	3.5 - 18 GHz: Two Voice Calls With HSD, Vertical Polarization, Highest Signal, 3.73 GHz Peak	11-95

Figure 11.66 3.5 - 18 GHz: Two Voice Calls With HSD, Vertical Polarization, Highest Signal, 3.73 GHz Average ..... 11-96

Figure 11.67 3.5 - 18 GHz: Two Voice Calls With HSD, Vertical Polarization, Second Highest Signal, 7.46 GHz Peak ..... 11-97

Figure 11.68 3.5 - 18 GHz: Two Voice Calls With HSD, Vertical Polarization, Second Highest Signal, 7.46 GHz Average ..... 11-98

Figure 11.69 3.5 - 18 GHz: Two Voice Calls With HSD, Vertical Polarization, Third Highest Signal, 9.33 GHz Peak ..... 11-99

Figure 11.70 3.5 - 18 GHz: Two Voice Calls With HSD, Vertical Polarization, Third Highest Signal, 9.33 GHz Average ..... 11-100

Figure 11.71 30-1000 MHz: Four Voice Calls with HSD ..... 11-101

Figure 11.72 1-3.5 GHz: Four Voice Calls with HSD ..... 11-103

Figure 11.73 R3 Fundamental Skirts ..... 11-105

Figure 11.74 3.5 - 18 GHz: Four Voice Calls With HSD, Horizontal Polarization, Full Scan 11-106

Figure 11.75 3.5-18 GHz: Four Voice Calls With HSD, Horizontal Polarization, Highest Signal, 3.73 GHz Peak ..... 11-107

Figure 11.76 3.5-18 GHz: Four Voice Calls With HSD, Horizontal Polarization, Highest Signal, 3.73 GHz Average ..... 11-108

Figure 11.77 3.5-18 GHz: Four Voice Calls With HSD, Vertical Polarization, Full Scan ... 11-109

Figure 11.78 3.5-18 GHz: Four Voice Calls With HSD, Vertical Polarization, Highest Signal, 3.73 GHz Peak ..... 11-110

Figure 11.79 3.5-18 GHz: Four Voice Calls With HSD, Vertical Polarization, Highest Signal, 3.73 GHz Average ..... 11-111

Figure 11.80 3.5-18 GHz: Four Voice Calls With HSD, Vertical Polarization, Second Highest Signal, 7.46 GHz Peak ..... 11-112

Figure 11.81 3.5-18 GHz: Four Voice Calls With HSD, Vertical Polarization, Second Highest Signal, 7.46 GHz Average ..... 11-113

Figure 11.82 18-26.5 GHz: Four Voice Calls With HSD, Horizontal Polarization, Full Scan 11-114

Figure 11.83 18-26.5 GHz: Four Voice Calls With HSD, Vertical Polarization, Full Scan ... 11-115

Figure 11.84 30-1000 MHz: Two Voice Calls and HSD ..... 11-116

Figure 11.85 1-3.5 GHz Two Voice Calls and HSD ..... 11-118

Figure 11.86 R3 Fundamental Skirts ..... 11-120

Figure 11.87 Notch Filter Characterization From 1 - 2 GHz ..... 11-121

Figure 11.88 Conducted Emission Setup ..... 11-123

Figure 11.89 Two Voice Calls with HSD and Lucent Power Supply: Line 1 ..... 11-124

Figure 11.90 Two Voice Calls with HSD and Lucent Power Supply: Line 2 ..... 11-125

Figure 11.91 Four Voice Calls with HSD and Lucent Power Supply: Line 1 ..... 11-126

Figure 11.92	Four Voice Calls with HSD and Lucent Power Supply: Line 2	11-127
Figure 11.93	Two Voice Calls with HSD and Panasonic Power Supply: Line 1	11-128
Figure 11.94	Two Voice Calls with HSD and Panasonic Power Supply: Line 2	11-129
Figure 11.95	Four Voice Calls with HSD and Panasonic Power Supply: Line 1	11-130
Figure 11.96	Four Voice Calls with HSD and Panasonic Power Supply: Line 2	11-131
Figure 11.97	Manufacturer's Antenna Pattern	11-135
Figure 11.98	AT&T R3 Outdoor Unit Pattern	11-136
Figure 12.1	Radiated Emissions Test Setup	12-3
Figure 12.2	HP 84300A E62 Microwave Intentional Radiator System	12-4
Figure 12.3	HP8546A EMI Receiver with K&L notch filter	12-5
Figure 12.4	HP8546A EMI Receiver, No Filter	12-6
Figure 12.5	Overall EUT Setup Picture	12-7
Figure 12.6	Overall Conducted Emissions Test Setup	12-8
Figure 12.7	EMCO 3825/2 Conducted Emissions LISN	12-9





# List of Tables

Table 7.1	PWAN Reference Architecture – Interface Definitions	7-4
Table 7.2	Basic PWAN OFDM Parameters	7-17
Table 7.3	NAC Logical Channel Summary	7-19
Table 8.1	R3 Outdoor Unit PCB	8-2
Table 8.2	R3 Indoor Unit PCB	8-5
Table 8.3	R3 2-line Expansion PCB	8-8
Table 8.4	Lucent AC-DC Power Supply	8-9
Table 8.5	Panasonic AC-DC Power Supply	8-11
Table 8.6	R3 Lucent DC-DC Power Module	8-12
Table 8.7	Results of Power vs Frequency vs Temperature (DAC_D Registry = 58 Hex)	8-17
Table 9.1	Summary and Comparison of Calculated and Measured Maximum SARs to FCC MPL for Various Tissue Models Exposed to AT&T RU Antenna.	9-3
Table 11.1	PWAN Interface Definitions	11-2
Table 11.2	Hewlett-Packard 89441A Occupied Bandwidth Test Parameters	11-10
Table 11.3	Hewlett-Packard 89441A Modulation Characterization Test Parameters	11-12
Table 11.4	Hewlett-Packard 89441A RF Power Test Parameters	11-14
Table 11.5	Hewlett-Packard 89441A Spectral Purity Test Configuration Parameters	11-17
Table 11.6	Antenna 1 (Bilog 1632) 3-m Correction Factors	11-25
Table 11.7	Cable 1 (Gore Cable) 53-ft. Correction Factors	11-27
Table 11.8	Antenna 1 (Emco 3115 Serial # 5515) Correction Factors	11-30
Table 11.9	Cable 1 (Gore Cable) 53-ft. Correction Factors	11-31
Table 11.10	Test Equipment	11-32
Table 11.11	EUT Equipment Under Test List	11-33

Table 11.12 R3 Transmit Frequency Stability vs. Temperature ..... 11-35

Table 11.13 Transmit Frequency Stability vs. Input Voltage ..... 11-37

Table 11.14 Occupied Bandwidth Test Result Summary ..... 11-38

Table 11.15 Channel Characterization Test Results ..... 11-45

Table 11.16 RF Output Power Characteristics ..... 11-48

Table 11.17 R3 In-Band and Out-Of-Band Power Summary ..... 11-55

Table 11.18 Emissions Test Equipment ..... 11-59

Table 11.19 EUT Equipment Under Test List ..... 11-60

Table 11.20 FCC Radiated Emissions Limits ..... 11-62

Table 11.21 Data for 30 MHz-1GHz; Lucent Four Voice/HSD ..... 11-65

Table 11.22 Data for 1-3.5 GHz; Lucent Four Voice/HSD ..... 11-67

Table 11.23 Data for 30 MHz-1GHz; Lucent Two Voice /HSD ..... 11-84

Table 11.24 Data for 1 GHz-3.5 GHz; Lucent Two Voice/HSD ..... 11-86

Table 11.25 Data for 30 MHz-1 GHz; Panasonic Four Voice/HSD ..... 11-102

Table 11.26 Data for 1 GHz-3.5 GHz; Panasonic Four Voice/HSD ..... 11-104

Table 11.27 Data for 30 MHz-1GHz; Panasonic Two Voice /HSD ..... 11-117

Table 11.28 Data for 1 GHz-3.5 GHz; Panasonic Two Voice/HSD ..... 11-119

Table 11.29 FCC Conducted Emission Limits ..... 11-122

Table 11.30 Part 24 Spurious Emission Limits ..... 11-133

Table 11.31 R3 Outdoor Unit Performance Specifications ..... 11-134